

Schinkels®

PERFORMANCE FIRST



Discover more about our products!

- PHARMACY & LABORATORY REFRIGERATORS
- BLOOD BANK REFRIGERATORS
- VACCINE REFRIGERATORS
- ULTRA-LOW TEMPERATURE FREEZERS

We are your expert in providing the right solutions for Medical Cold Storage

High performance product
Temperature Uniformity
Ensuring safety of storage

SBB-368L



SBB-588L



SBB-88L



CONTACT

US NOW



+6017-219 7148
sales@schinkelsgroup.com.my

www.schinkelsgroup.com.my



21-2 & 21-1, Jalan Nova K U5/K,
Subang Bestari, 40150 Shah Alam,
Selangor, Malaysia.



Intelligent Temperature Control

·Equipped with high-precision microcomputer temperature control system and 1 high-brightness digital temperature display with a display accuracy at 0.1°C.

·Equipped with access port for external data logger



Data Storage

Enhance your peace of mind with our cutting-edge accessory: the Online Monitoring Temperature Alarm System, meticulously integrated into our product. This state-of-the-art system acts as a vigilant 24/7 watchdog, continuously monitoring temperature levels and promptly alerting you to any deviations, ensuring optimal conditions are maintained at all times.



Power Management System

·Enhanced with a power management module, the system achieves optimized energy efficiency. It employs high-precision voltage control to stabilize both voltage and refrigerator performance.

Moreover, it effectively mitigates excessive heat generation, thereby eliminating any potential risks of overheating.



Refrigeration System with HCs Refrigerant

Equipped with a seal hermetic compressor with low noise level, high-efficiency air-cooled condenser and finned evaporator, ensuring optimum refrigeration and low energy consumption.



Human-oriented

·Equipped with 6 dip-coating shelves with label strips (Stainless steel pull-out racks are optional)
·9 dip-coating blood bag frames, can hold 90 blood bags in 450ml for each.

CONTACT

US NOW



+6017-219 7148 / 03-5885 3965



sales@schinkelsgroup.com.my



21-2 & 21-1, Jalan Nova K U5/K,
Subang Bestari, 40150 Shah
Alam, Selangor, Malaysia.

MODEL	SBB-88L	SBB-368L	SBB-588L
Cabinet Type	Upright		
Capacity (L)	Up to 170L	Up to 380L	Up to 630L
External Dimensions (mm)	654W x 774D x 1330H	806W x 723D x 1870H	812W x 912D x 1978H
Internal Dimensions (mm)	525W x 550D x 744H	677W x 493D x 1145H	685W x 690D x 1378H
Weight (kg)	106	163	179

PERFORMANCE

Temperature Range (°C)	3 to 5 / ±4°C		
Controller	High Precision Microprocessor (HPM)		
Display	Numeralite display (accuracy at 0.1°C)		

REFRIGERANT

Cooling Method	Active cooling		
Defrost Mode	Automatic		

ELECTRICAL

Power Supply (V/Hz)	220 -240V / 50 Hz *MS IEC 60364		
Power (W)	260	528	465
Rated Current (A)	1.7	2.4	3.13

ACCESSORIES

Online Monitoring Temperature Alarm System (OMTAS)	Available as accessories or build in. *Contact our sales personnel.		
--	---	--	--