



POWERED BY SALSIFY

[Americas PDS Database](#) > [K&W Instant Cooling System Stop Leak](#)



K&W Instant Cooling System Stop Leak

ATTRIBUTES

Item Number

1008134

Legacy Number

401214

Case Number

1006062

Product Description

Using nanotechnology, this product fills in cracks & crevices other products can't, making a stronger, more solid bond than competitors' products. Compatible with all types of anti-freeze.

Applications

Aluminum engine blocks, cooling systems, cylinder heads, engine blocks, freeze plugs, head gaskets, heaters cores, iron engine blocks, metal radiators, plastic radiators,

radiators, water pumps

Unit Package Description

16 Ounce Bottle

Brand

K&W

Net Fill

15 Fl Oz

Unit Dimensions

7.75H x 1.75W x 3.12D in

Units Per Case

1

UPC Code

78372012143

Case Dimensions

7.75H x 6.75W x 6.75D in

Appearance

Lumpy Copper Liquid

Base Type

Water Based

Flash point (F)

None

Flash point (C)

None

Flammability Class - CPSC

None

KB Value

N/A

Plastic Safe

Yes

Film Thickness

N/A

Evaporation Rate

Slow

Dielectric Strength

N/A

Timken Ok Load (lbs)

N/A

Propellant

None

Aerosol Flammability Level

N/A

DOT Proper Shipping Name

Not Regulated

4 Ball EP

N/A

4 Ball Wear

N/A

Drop Point

N/A

pH

11.3

NLGI Grade

N/A

Water Washout

N/A

Working Temp (F)

190°F

Working Temp (C)

88°C

VOC % (Consumer Product def)

0.1

VOC g/L (Consumer Product def)

1.08

VOC lbs/gal (Consumer Prod def)

Not Determined

VOC Category

Not Regulated

Removal (How To)

Remove with water.