


SSL切削刀具

螺纹车削刀具

螺纹铣削刀具

切槽(断)刀具



用心打造每一粒刀片

目录 Contents

螺纹车削刀具 ----- 01~65

THREADING TURNING TOOLS



螺纹车削刀具
THREADING TURNING TOOLS

螺纹铣削刀具 ----- 67~98

THREADING MILLING TOOLS



螺纹铣削刀具
THREADING MILLING TOOLS

切槽(断)刀具 ----- 100~136

GROOVING & PARTING-OFF TOOLS



切槽(断)刀具
GROOVING TOOLS

SSL




目录 Contents

螺纹车刀刀片型号说明 Threading Insert Identification System	02
应用资料 Application Data	03~04
刀片材质说明 Instruction for Insert Material	05
MTTR立装螺纹刀片 Partial Profile V-style Inserts	06
TT/TTX立装螺纹刀片 Partial Profile V-style Inserts	07
TKFT立装螺纹刀片 Partial Profile V-style Inserts	08
GE系列螺纹刀片 GE Threading Inserts	09
泛用型螺纹刀片 Partial Profile Inserts	10~13
ISO标准型螺纹刀片 ISO Metric	14~15
UN-60° 美制统一标准螺纹刀片 UN UNC UNF UNEF UNS	16~17
W-55° 英国惠氏螺纹刀片 55° Whitworth Full Profile	18~19
60° 美国标准锥管螺纹刀片 NPT	20~21
60° 美国干密封锥管螺纹刀片 NPTF	22~23
55° 英国标准锥管螺纹刀片 BSPT	24~25
30° 标准梯形螺纹刀片 Trapez DIN103	26~27
29° 美制梯形螺纹刀片 American ACME	28~29
29° 美制短齿梯形螺纹刀片 Stub ACME	30~31
30° RD圆螺纹刀片 DIN405	32
80° PG螺纹刀片 PG	33
ABUT美制锯齿形螺纹刀片 American Buttress	34
SAGE德标锯齿形螺纹刀片 DIN513	35
石油管螺纹刀片 Insert for API Oil Pipe	36~41
PCD/PCBN螺纹刀片 PCD/PCBN	42~43
螺纹刀车杆 Threading Toolholders	44~49
应用资料 Application Data	50~65

螺纹车削刀具

👉 螺纹车刀刀片型号说明 Threading Insert Identification System

1. 刀片尺寸 Insert Size	2. 刀片型式 Insert Style	3. 刀片类型 Type of Insert	4. 螺纹旋向 RHL/LH Insert
L(mm) D 06 5/32" 08 3/16" 11 1/4" 16 3/8" 22 1/2" 27 5/8" 	 U  V	E 外螺纹 External N 内螺纹 Internal  E N  图片为右手刀片 Right Insert(see picture)	R 右手刀片 Right Hand Insert L 左手刀片 Left Hand Insert  R L  图片为外螺纹刀片 External Insert(see picture)

16

1

2

E

3

R

4

1.5

5

ISO

6

7

8

5. 螺距 Pitch	6. 螺纹标准 Standard	7. 齿数(对齿齿形M) No. of Teeth(for Multitooth Style)
完全形 Full Profile Pitch Range mm TPI 0.5~6 48~4	60° —— 55° 通用型螺纹 Partial Profile 60° 55° —— 55° 通用型螺纹 Partial Profile 55° ISO —— ISO 标准型螺纹 ISO Metric UN —— 50° 美制统一标准型螺纹 American UN UNJ —— 50° 美制航空航天螺纹 Aviation thread W —— 55° 英制惠氏螺纹 Whitworth for BSW BSP NPT —— 50° 美国标准锥管螺纹 NPT NPTF —— 50° 美制干密封螺纹 NPTF BSPT —— 55° 英制标准锥管螺纹 British Standard Pipe Thread ACME —— 美制 29° 梯形螺纹 American ACME STACME —— 美制 29° 短齿梯形螺纹 American Stub ACME TR —— 30° 标准梯形螺纹 Trapeze DIN 103 ABUT —— 美制 55° 圆齿形螺纹 American Butress RD —— 消防食品机械圆螺纹 Round DIN 405 RD20400 —— 消防及食品机械圆螺纹 Round DIN 20400 APIRD —— API 圆螺纹 API Round Casing & Tubing BUT —— API 圆齿形螺纹 API Butress Casing	2 3 5 6 8
局部齿顶形 Partial Profile Pitch Range mm TPI A 0.5~1.5 48~16 AG 0.5~3.0 48~8 Q 1.75~3.0 14~8 H 3.5~5.0 7~5 Q 5.5~6.0 4.5~4 V 6.0~10 4~2.5		8. 梳齿的刀片型式 Insert Style of Multitooth  M

如何选择并正确使用螺纹刀具需进行以下5个步骤:

How to choose and use threading cutters?

首先需要了解: 加工外螺纹/内螺纹

You have to know firstly: machining internal & external threads

主轴旋转方向

turning direction of spindle

右旋螺纹/左旋螺纹

right hand & left hand

进给方向

feed direction

第一步: 选择旋转螺纹的加工方法和刀具式样 (详见37页)

Firstly choosing machining ways & cutter styles of turning thread (see page 37)

外螺纹(右旋螺纹) External (Right Hand)

铁屑向上排-刀杆正向安装

主轴正转(M03)


进给方向—向卡盘方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned forward-M03

Feed direction—feed towards chuck



铁屑向下排-刀杆反向安装

主轴正转(M03)


进给方向—向卡盘方向进给

Scrap iron displaced downward

—tool holders installed backward

Spindle turned forward-M03

Feed direction—feed towards chuck



外螺纹(左旋螺纹) External (Left Hand)

铁屑向上排-刀杆正向安装

主轴正转(M03)


进给方向—向顶尖方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned forward-M03

Feed direction—feed towards center



铁屑向上排-刀杆正向安装

主轴正转(M04)


进给方向—向卡盘方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned forward-M03

Feed direction—feed towards chuck



内螺纹(右旋螺纹) Internal (Right Hand)

铁屑向上排-刀杆正向安装

主轴正转(M03)


进给方向—向卡盘方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned forward-M03

Feed direction—feed towards chuck



铁屑向下排-刀杆反向安装

主轴反转(M03)


进给方向—向卡盘方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned backward-M04

Feed direction—feed towards chuck



内螺纹(左旋螺纹) Internal (Left Hand)

铁屑向上排-刀杆正向安装

主轴正转(M03)

进给方向—向顶尖方向进给


注: 建议更换成带角度的垫片, 改变刀具
径向倾角, 使其加工出的牙型角合格。

Scrap iron displaced upward

—tool holders installed forward

Spindle turned backward-M04

Feed direction—feed towards chuck

Note: it is good for machining perfect tooth by
using parallel with reasonable angle and
by changing the radial direction of cutters.

铁屑向上排-刀杆正向安装

主轴反转(M04)


进给方向—向卡盘方向进给

Scrap iron displaced upward

—tool holders installed forward

Spindle turned backward-M04

Feed direction—feed towards chuck



第二步:挑选适合应用的刀片 Secondly choosing applicable inserts

刀片尺寸 Insert Dimension	目录编号 Model No.		材质代号 Material Type			
			有色金属:DK110	钢:DP220	不锈钢:DM215	
11	11E...	11N...	●	●	●	
16	16E...	16N...	●	●	●	
22	22E...	22N...	●	●	●	
	MTTR43...		●	●	●	

第三步:选择材质与切削参数 Thirdly choosing suitable material and cutting parameter

DK110:适合加工有色金属, 推荐线速度 V_c : (100~300)m/min

DP220:适合加工各种钢件, 推荐线速度 V_c : (100~150)m/min

DM215:适合加工不锈钢, 推荐线速度 V_c : (60~120)m/min, 也可加工钢件, 推荐线速度 V_c : (100~180)m/min

DK110 is the top choice for cast iron and non-ferrous metals (e.g. aluminum alloy), recommended V_c : 100~300m/min

DP220 is the top choice for various steel, recommended V_c : 100~150m/min

DM215 is the top choice for stainless steels as well as steel, recommended V_c : 60~120m/min for stainless steel;
 V_c : 100~180m/min for steel

第四步:从样本选择适合的刀具 Fourthly choosing suitable cutters according to catalogue

所需资料:

1. 加工内螺纹还是外螺纹
2. 螺纹底孔直径 (加工内螺纹时)
3. 刀具样式 (详见第一步)
4. 刀片规格
5. 刀杆规格

Data required:

- 1 Internal or external thread you need machining.
- 2 Under part's diameter when you machining internal thread.
- 3 Cutter style (see the first step)
- 4 Inserts Specification
- 5 Tool holders Specification

第五步:选择适合的刀垫 Finally choosing applicable anvil

根据螺纹牙型大小, 螺距直径, 螺旋方法, 选择垫片。

Choosing applicable anvil according to thread tooth size, pitch diameter and screw ways.

刀片材质说明

Instruction for Insert Material

	Wear resistance ←			Toughness →	
	01	10	20	30	40
P 钢 steels			PM125 DP220 DM215		
M 不锈钢 stainless steel			PM125 DM215		
K 铸铁 cast iron			DM215	PM125	
N 有色金属 non-ferrous metals		DK110			



DP220



PM125



DM215



DK110

DP220(P30,M40)

Layer system:PVD TiN

DP220 钢件各种场合下的广泛应用，具有较好的韧性！推荐使用线速度 $V_c: 90 \sim 180 \text{ m/min}$ DP220 is good at all application with perfect toughness. Recommended parameter $V_c: 90 \sim 180 \text{ m/min}$

PM125(M25,P20)

Layer system:PVD TiAlN

PM125 钢件不锈钢通用材质，耐高温性能提升，适应更高转速的加工场合

加工不锈钢时推荐使用线速度 $V_c: 80 \sim 140 \text{ m/min}$ ，加工钢件时推荐使用线速度 $V_c: 120 \sim 180 \text{ m/min}$ PM125 apply to stainless steel and steel,thermostable,superior to high speed machining high speed. Recommended parameter $V_c: 80 \sim 140 \text{ m/min}$ for stainless steel; $V_c: 120 \sim 180 \text{ m/min}$ for steel

DM215(M25,P20)

Layer system:PVD TiAlN

DM215 不锈钢材质的首选，但是在钢件的中高速加工中也有比较优异的表现！也可以加工铸铁！



加工不锈钢时推荐使用线速度 $V_c: 60 \sim 120 \text{ m/min}$ ，加工钢件时推荐使用线速度 $V_c: 100 \sim 180 \text{ m/min}$ DM215 is the first choice in stainless steels, superior to other steels machining under medium and high speed. Recommended parameter $V_c: 60 \sim 120 \text{ m/min}$ for stainless steel; $V_c: 100 \sim 180 \text{ m/min}$ for steelDK110(K15) 颗粒度: Grain size: $0.6 \mu\text{m}$ 硬度: Hardness:HV1670DK110 铝合金等有色金属材质的首选！推荐使用线速度 $V_c: 100 \sim 300 \text{ m/min}$ DK110 is the top choice in cast iron and non-ferrous metals (e.g. aluminum alloy) machining. Recommended parameter $V_c: 100 \sim 300 \text{ m/min}$

SSL 公、英、美制螺纹刀具 THREADING TOOLS

60° 立装泛用型螺纹刀片 Partial Profile V-style Inserts



图片为右手刀片
(Right insert(see picture))




型号	材质	型号	材质	加工螺距范围	刀片尺寸	尺寸
Ordering Code	Material Code	Ordering Code	Material Code	Pitch	Insert Size	Dimensions (mm)
右手刀片 Right Hand	DP220 DM215	左手刀片 Left Hand	DP220 DM215	mm tpi	IC T L/inch	r X Y
MTTR 436001	○ ●	MTTL 436001	○	1.0~1.75 24-14		0.1 1.7 0.29
MTTR 436002	○ ●	MTTL 436002	○	2.0~2.5 13-10	1/2" 4.76 .87	0.2 1.7 0.29
MTTR 436003	○ ●	MTTL 436003	○	3.0~3.5 9-7		0.3 1.7 0.29
MTTR 436004	○ ●	MTTL 436004	○	4.0~4.5 6-5		0.4 1.7 0.29

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard
订货示例: MTTR 436002 DM215 10片 Ordering example: MTTR 436002 DM215 10pcs

55° 立装泛用型螺纹刀片 Partial Profile V-style Inserts



图片为右手刀片
(Right insert(see picture))





型号	材质	型号	材质	加工螺距范围	刀片尺寸	尺寸
Ordering Code	Material Code	Ordering Code	Material Code	Pitch	Insert Size	Dimensions (mm)
右旋螺纹 Right Hand	DP220 DM215	左旋螺纹 Left Hand	DP220 DM215	mm tpi	IC T L/inch	r X Y
MTTR 435501	○	MTTL 435501		1.0~1.75 24-14		0.1 1.7 0.29
MTTR 435502	○	MTTL 435502		2.0~2.5 13-10	1/2" 4.76 .87	0.2 1.7 0.29
MTTR 435503	○	MTTL 435503		3.0~3.5 9-7		0.3 1.7 0.29
MTTR 435504	○	MTTL 435504		4.0~4.5 6-5		0.4 1.7 0.29

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard
订货示例: MTTR 435502 DM215 10片 Ordering example: MTTR 435502 DM215 10pcs

 TTX 立装泛用型螺纹刀片 TTX Partial Profile V-style Inserts



图片为右手刀片
Right insert(see picture)




型号 Ordering Code	材质 Material Code		型号 Ordering Code	材质 Material Code		加工螺距范围 Pitch		尺寸 Dimensions (mm)						适用刀杆 tool holders 详见P45 SeeP45
右手刀片 Right Hand	DK110	PM125	左手刀片 Left Hand	DK110	PM125	mm	tpi	IC	L	T	S1	S2	r	
TTX32R60005	○	●	TTX32L60005	○	○	0.5~1.0	48~32	9.525	16	3.18	0.6	1.12	0.05	KTT...-16
TTX32R6001	○	●	TTX32L6001	○	○	1.0~2.0	28~14	9.525	16	3.18	1.1	1.62	0.1	
TTX32R5501	○	●	TTX32L5501	○	○	-	28~19	9.525	16	3.18	0.75	1.01	0.1	



●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: TTX32R6001 PM125 10片 Ordering example: TTX32R6001 PM125 10pcs

 TT 立装泛用型螺纹刀片 TT Partial Profile V-style Inserts



图片为右手刀片
Right insert(see picture)





型号 Ordering Code	材质 Material Code		型号 Ordering Code	材质 Material Code		加工螺距范围 Pitch		尺寸 Dimensions (mm)						适用刀杆 tool holders 详见P45 SeeP45
右手刀片 Right Hand	DK110	PM125	左手刀片 Left Hand	DK110	PM125	mm	tpi	IC	L	T	S1	S2	r	
TT32R6000	○	●	TT32L6000	○	○	0.5~1.0	48~32	9.525	16	3.18	0			KTT...-16
TT32R6001	○	●	TT32L6001	○	○	1.0~2.5	28~14	9.525	16	3.18	0.1			
TT32R6002	○	●	TT32L6002	○	○	1.5~2.5	16~10	9.525	16	3.18	0.2			
TT32R6003	○	●	TT32L6003	○	○	2.5	11~10	9.525	16	3.18	0.3			
TT32R5501	○	●	TT32L5501	○	○	-	28~10	9.525	16	3.18	0.1			
TT32R5502	○	●	TT32L5502	○	○	-	14~10	9.525	16	3.18	0.2			

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: TT32R6001 PM125 10片 Ordering example: TT32R6001 PM125 10pcs

SSL 公、英、美制螺纹刀具 THREADING TOOLS

👉 TKFT 立装泛用型螺纹刀片 TKFT Partial Profile V-style Inserts





图片为右手刀片
Right Insert (see picture)

型号 Ordering Code	材质 Material Code		型号 Ordering Code	材质 Material Code		加工螺距范围 Pitch		尺寸 Dimensions (mm)						通用刀杆 tool holders 详见P119 See P119
	DK110	PM125		DK110	PM125	mm	tpi	H	T	W	S1	S2	r	
右手刀片 Right Hand			左手刀片 Left Hand											
TKFT12RA80005	○	●	TKFT12LA80005	○	○	-	28~19	8.7	3.0	2.5	0.8	1.7	0.05	KTKFR...-12
TKFT12RB80005	○	●	TKFT12LB80005	○	○	0.5~1.0	48~32	8.7	3.0	2.5	1.7	0.8	0.05	
TKFT12RN8001	○	●	TKFT12LN8001	○	○	1.0~2.0	28~14	8.7	3.0	2.5	1.25	1.25	0.1	KTKFL...-12
TKFT12RA55005	○	●	TKFT12LA55005	○	○	-	28~19	8.7	3.0	2.5	0.8	1.7	0.05	
TKFT12RB55005	○	●	TKFT12LB55005	○	○	0.5~1.0	48~32	8.7	3.0	2.5	1.7	0.8	0.05	

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: TKFT12RN8001 PM125 10片 Ordering example: TKFT12RN8001 PM125 10pcs

👉 GE 螺纹刀片 GE Threading Insert



图片为右手刀片
Right Insert(see picture)

型号 Ordering Code	材质 Material Code		型号 Ordering Code	材质 Material Code		加工螺距范围 Pitch		尺寸 Dimensions (mm)				适用刀杆 tool holders 详见P116 : SeeP116
	DK110	PM125		DK110	PM125	mm	in	A	L	T	r	
右手刀片 Right Hand			左手刀片 Left Hand									
GER6001-A	○	○	GEL6001-A	○	○	0.5~1.5	48~18	6.69	6.5	2.58	0.05	SIGE...A
GER5501-A	○	○	GEL5501-A	○	○	0.5~1.5	48~14	6.69	6.5	2.58	0.05	
GER6001-B	○	●	GEL6001-B	○	○	0.5~1.5	48~16	8.46	8.2	3.18	0.05	SIGE...B
GER6002-B	○	●	GEL6002-B	○	○	1.0~2.5	25~10	8.46	8.2	3.18	0.1	
GER5501-B	○	●	GEL5501-B	○	○	0.5~1.5	48~16	8.46	8.2	3.18	0.1	
GER2.0TR-B	○	○	GEL2.0TR-B	○	○	2.0	—	8.46	8.2	3.18	0.1	SIGE...B
GER3.0TR-B	○	○	GEL3.0TR-B	○	○	3.0	—	8.46	8.2	3.18	0.1	
★GER4.0TR-B	○	○	★GEL4.0TR-B	○	○	4.0	—	8.46	8.2	3.18	0.2	
GER3.0TR-C	○	○	GEL3.0TR-C	○	○	3.0	—	5.8	11.5	4.0	0.1	SIGE...C
GER4.0TR-C	○	○	GEL4.0TR-C	○	○	4.0	—	5.8	11.5	4.0	0.2	
GER4.0TR-D	○	○	GEL4.0TR-D	○	○	4.0	—	6.8	16.5	5.0	0.2	SIGE...D
GER5.0TR-D	○	○	GEL5.0TR-D	○	○	5.0	—	6.8	16.5	5.0	0.2	
GER6.0TR-D	○	○	GEL6.0TR-D	○	○	6.0	—	6.8	16.5	5.0	0.2	



●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: GER6001-APM125 10片 Ordering example: GER6001-APM125 10pcs

★ 建议该刀片只能用作精修螺形螺纹尺寸时使用

👉 60° 泛用型螺纹刀片 Partial Profile 60° Threading Insert

外螺纹 External



图片为右手刀片
Right Insert(see picture)

Right Hand/Left Hand														
型 号	材 质			型 号	材 质			加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110	DP220	DM215	左手刀片 Left Hand	DK110	DP220	DM215	mm	吋	IC	L/inch	T(max)	X (mm)	Y (mm)
11ERA60	●	●	●	11ELA60			○	0.5-1.5	48-16	1/4"	.43	0.07	.029	.035
16ERA60	●	●	●	16ELA60			○	0.5-1.5	48-16			0.07	.031	.035
16ERAG80	●	●	●	16ELAG80			○	0.5-3.0	48-8	3/8"	.63	0.07	.047	.067
16ERG80	●	●	●	16ELG80			○	1.75-3.0	18-8			0.25	.047	.067
22ERN60	●	●	●	22ELN60			○	3.5-6.0	7-5	1/2"	.87	0.4	.067	.088
27ERQ80	○	○	○	27ELQ80			○	5.5-8.0	4.5-4			0.68		
27VERN80	○	○	○	27VELV80			○	6.0-10	4-2.5	5/8"	1.06	0.68		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ERAG80 DM215 10片 Ordering example: 16ERAG80 DM215 10pcs

★ 27V***系列刀片为立尖型, 形状参考05页MTTR系列



★ 27V series is V-style, The shape of the 05 page MTTR series

 60° 泛用型螺纹刀片 Partial Profile 60° Threading Insert

内螺纹 Internal



图片为右手刀片
Right insert (see picture)



Right Insert (see picture)														
型 号	材 质			型 号	材 质			加工螺距范围		刀片尺寸		尺寸		
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110	DP220	DM215	左手刀片 Left Hand	DK110	DP220	DM215	mm	in	IC	Width	Feed	X mm	Y mm
06NRA60	○	○	○	06NLA60				0.5-1.5	48-16	5/32"	.271	0.07	.03	.031
08NRA60	●	○	●	08NLA60				0.5-1.5	48-16	3/16"	.325	0.07	.03	.031
11NRA60	●	●	●	11NLA60		○		0.5-1.5	48-16	1/4"	.43	0.07	.031	.035
16NRA60	●	●	●	16NLA60		○		0.5-1.5	48-16			0.07	.031	.035
16NRA60	●	●	●	16NLAG60		○		0.5-3.0	48-8	3/8"	.63	0.07	.047	.067
16NRO60	●	●	●	16NLO60		○		1.75-3.0	16-8			0.2	.047	.067
22NRA60	●	●	●	22NLA60		○		3.5-6.0	7-5	1/2"	.87	0.4	.067	.098
27NRO60	○	○	○	27ELO60		○		5.5-6.0	4.5-4	5/8"	1.06	0.61		
27VNRV60	○	○	○	27VELV60		○		6.0-10	4-2.5			0.61		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16NRA60 DM215 10片 Ordering example: 16NRA60 DM215 10pcs

★ 27V***系列刀片为立装型, 形状参考05页MTTR系列

★ 27V series is V-style, The shape of the 05 page MTTR series

 55° 泛用型螺纹刀片 Partial Profile 55° Threading Insert

外螺纹 External



图片为右手刀片
Right Insert(see picture)

Right insert (see previous)

型 号	材 质	型 号	材 质	加工螺距范围		刀片尺寸		尺寸		
Ordering Code	Material Code	Ordering Code	Material Code	Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm	in	IC	Linch	Time	X(mm)	Y(mm)
11ERA55	● ● ●	11ELA55	○	0.5-1.5	48-16	1/4"	.43	0.07	.031	.035
16ERA55	● ● ●	16ELA55	○	0.5-1.5	48-16			0.07	.031	.035
16ERAG55	● ● ●	16ELAG55	○	0.5-3.0	48-8	3/8"	.83	0.07	.047	.067
16ERG55	● ● ●	16ELG55	○	1.75-3.0	18-8			0.25	.047	.067
22ERN55	● ● ●	22ELN55	○	3.5-5.0	7-5	1/2"	.87	0.4	.067	.098
27ERQ55	● ● ●	27ELQ55	○	5.5-8.0	4.5-4			0.68		
27VERN55	● ● ●	27VELV55	○	6.0-8.0	4-2.5	5/8"	1.06	0.68		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16ERAG55 DM215 10片 Ordering example: 16ERAG55 DM215 10pcs

★27V***系列刀片为立装型, 形状参考05页MTTR系列

★27V series is V-style, The shape of the 05 page MTTR series

 55° 泛用型螺纹刀片 Partial Profile 55° Threading Insert

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

型 号 Ordering Code	材 质 Material Code			型 号 Ordering Code	材 质 Material Code			加工螺纹范围 Pitch		刀片尺寸 Insert Size		尺 寸 Dimensions		
	DK110	DP220	DM215		DK110	DP220	DM215	mm	tpi	IC	L/inch	Ymax	Xmax	Ymin
右手刀片 Right Hand				左手刀片 Left Hand										
06NRA55	○	○	○	06NLA55				0.5-1.5	48-16	5/32"	.271	0.06	.03	.035
06NRA55	●	○	●	06NLA55				0.5-1.5	48-16	3/16"	.325	0.06	.03	.035
11NRA55	●	●	●	11NLA55			○	0.5-1.5	48-16	1/4"	.43	0.06	.031	.035
16NRA55	●	●	●	16NLA55			○	0.5-1.5	48-16			0.06	.031	.035
16NRAG55	●	●	●	16NLAG55			○	0.5-3.0	48-8	3/8"	.83	0.06	.047	.067
16NRQ55	●	●	●	16NLQ55			○	1.75-3.0	16-8			0.2	.047	.067
22NRN55	●	●	●	22NLN55			○	3.5-5.0	7-5	1/2"	.87	0.4	.067	.098
27NRQ55	●	●	●	27NLQ55			○	5.5-8.0	4.5-4	5/8"	1.06	0.61		
27VNRV55	●	●	●	27VNLV55			○	6.0-8.0	4-2.5			0.61		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16NRAG55 DM215 10片 Ordering example: 16NRAG55 DM215 10pcs

★ 27V***系列刀片为立装型, 形状参考05页MTTR系列

★ 27V series is V-style, The shape of the 05 page MTTR series

ISO标准型螺纹刀片 ISO Metric

外螺纹 External



图片为右手刀片
Right Insert(see picture)

型号 Ordering Code	材质 Material Code			型号 Ordering Code	材质 Material Code			加工螺距范围 Pitch		刀片尺寸 Insert Size		尺寸 Dimensions		
右手刀片 Right Hand	DK110	DP220	DM215	左手刀片 Left Hand	DK110	DP220	M215	mm	tpi	IC	Linch	mm	X mm	Y mm
11ER0.50 ISO				11EL0.50 ISO				0.50				0.07	.024	.016
11ER0.75 ISO	●	●	●	11EL0.75 ISO			○	0.75				0.11	.024	.024
11ER1.00 ISO	●	●	●	11EL1.00 ISO			○	1.00				0.14	.027	.027
11ER1.25 ISO	●	●	●	11EL1.25 ISO			○	1.25		1/4"	.43	0.18	.031	.035
11ER1.50 ISO	●	●	●	11EL1.50 ISO			○	1.50				0.22	.031	.039
11ER1.75 ISO	●	●	●	11EL1.75 ISO			○	1.75				0.25	.035	.047
11ER2.00 ISO	●	●	●	11EL2.00 ISO			○	2.00				0.29	.039	.061
16ER0.50 ISO	○	○	●	16EL0.50 ISO				0.50				0.07	.024	.016
16ER0.75 ISO	●	●	●	16EL0.75 ISO			○	0.75				0.07	.024	.024
16ER1.00 ISO	●	●	●	16EL1.00 ISO			●	1.00				0.1	.027	.027
16ER1.25 ISO	●	●	●	16EL1.25 ISO			●	1.25				0.12	.031	.035
16ER1.50 ISO	●	●	●	16EL1.50 ISO			●	1.50		3/8"	.63	0.18	.031	.039
16ER1.75 ISO	●	●	●	16EL1.75 ISO			●	1.75				0.23	.036	.047
16ER2.00 ISO	●	●	●	16EL2.00 ISO			●	2.00				0.25	.039	.061
16ER2.50 ISO	●	●	●	16EL2.50 ISO			●	2.50				0.36	.043	.059
16ER3.00 ISO	●	●	●	16EL3.00 ISO			●	3.00				0.43	.047	.063
16ER3.50 ISO	○	○	●	16EL3.50 ISO				3.50				0.51	.047	.063
22ER3.00 ISO	○	○	●	22EL3.00 ISO				3.00				0.43	.047	.063
22ER3.50 ISO	○	●	●	22EL3.50 ISO			○	3.50				0.51	.063	.09
22ER4.00 ISO	○	●	●	22EL4.00 ISO			●	4.00				0.58	.063	.09
22ER4.50 ISO	○	●	●	22EL4.50 ISO			○	4.50		1/2"	.87	0.65	.067	.094
22ER5.00 ISO	○	●	●	22EL5.00 ISO			●	5.00				0.75	.067	.098
22ER5.50 ISO			●	22EL5.50 ISO				5.50				0.79	.067	.098
22ER6.00 ISO		●	●	22EL6.00 ISO				6.00				0.87	.067	.098
27ER5.50 ISO			○	27EL5.50 ISO				5.50				0.79		
27ER6.00 ISO		●	●	27EL6.00 ISO				6.00				0.87		
27VER6.00 ISO			○	27VEL6.00 ISO				6.00		5/8"	1.06	0.87		
27VER8.00 ISO		○	○	27VEL8.00 ISO				8.00						
27VER10.0 ISO			○	27VEL10.0 ISO				10.0						

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16ER1.50ISO DM215 10片 Ordering example: 16ER1.50ISO DM215 10pcs

★27V***系列刀片为立装型, 形状参考05页MTTR系列

★27V series is V-style, The shape of the 05 page MTTR series

ISO标准型螺纹刀片 ISO Metric

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



型 号	材 质	型 号	材 质	加工螺距范围	刀片尺寸	尺寸
Ordering Code	Material Code	Ordering Code	Material Code	Pitch	Insert Size	Dimensions
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 M215	mm	IC	mm
08NR0.5ISO		08NL0.5ISO		0.5		0.04 .024 .016
08NR0.75ISO		08NL0.75ISO		0.75		0.05 .024 .024
08NR1.0ISO		08NL1.0ISO		1.0	3/16"	0.07 .024 .027
08NR1.25ISO		08NL1.25ISO		1.25		0.09 .031 .035
08NR1.5ISO		08NL1.5ISO		1.5		0.11 .031 .039
11NR0.5ISO		11NL0.5ISO		0.50		0.04 .024 .016
11NR0.75ISO		11NL0.75ISO		0.75		0.05 .024 .024
11NR1.0ISO		11NL1.0ISO		1.00		0.07 .024 .027
11NR1.25ISO		11NL1.25ISO		1.25	1/4"	0.09 .031 .035
11NR1.5ISO		11NL1.5ISO		1.50		0.11 .031 .039
11NR1.75ISO		11NL1.75ISO		1.75		0.13 .035 .047
11NR2.0ISO		11NL2.0ISO		2.00		0.14 .039 .051
16NR0.5ISO		16NL0.5ISO		0.50		0.04 .024 .016
16NR0.75ISO		16NL0.75ISO		0.75		0.05 .024 .024
16NR1.0ISO		16NL1.0ISO		1.00		0.07 .024 .027
16NR1.25ISO		16NL1.25ISO		1.25		0.09 .031 .035
16NR1.5ISO		16NL1.5ISO		1.50		0.11 .031 .039
16NR1.75ISO		16NL1.75ISO		1.75	3/8"	0.13 .035 .047
16NR2.0ISO		16NL2.0ISO		2.00		0.14 .039 .051
16NR2.5ISO		16NL2.5ISO		2.50		0.18 .043 .059
16NR3.0ISO		16NL3.0ISO		3.00		0.22 .043 .069
16NR3.5ISO		16NL3.5ISO		3.50		0.25 .043 .069
22NR3.0ISO		22NL3.0ISO		3.00		0.22 .043 .069
22NR3.5ISO		22NL3.5ISO		3.50		0.25 .063 .09
22NR4.0ISO		22NL4.0ISO		4.00		0.29 .063 .09
22NR4.5ISO		22NL4.5ISO		4.50	1/2"	0.32 .063 .094
22NR5.0ISO		22NL5.0ISO		5.00		0.36 .063 .094
22NR5.5ISO		22NL5.5ISO		5.50		0.4 .063 .094
22NR6.0ISO		22NL6.0ISO		6.00		0.43 .063 .094
27NR5.5ISO		27NL5.5ISO		5.50		0.4
27NR6.0ISO		27NL6.0ISO		6.00		0.43
27VNR6.0ISO		27VNL6.0ISO		6.00	5/8"	1.06 0.43
27VNR8.0ISO		27VNL8.0ISO		8.00		
27VNR10.0ISO		27VNL10.0ISO		10.0		

● 常备库存(主推) Stock standard(main) ○ 一般库存 Stock standard

订货示例: 16NR1.50ISO DM215 10片 Ordering example: 16NR1.50ISO DM215 10pcs

UN-60° 美制统一标准型螺纹刀片 60° American UN NC NF NEF NS

外螺纹 External



图片为右手刀片
Right insert (see picture)

Right Hand/Left Hand															
型 号	材 质			型 号	材 质			加工螺距范围		刀片尺寸		尺 寸			
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions			
右手刀片 Right Hand	DK110	DP220	DN215	左手刀片 Left Hand	DK110	DP220	DN215	mm	in	IC	Length	Fmax	X max	Y max	
11ER32UN		○	○	11EL32UN				0.794	32			0.13	.024	.024	
11ER28UN	○	○	○	11EL28UN				0.907	28			0.13	.024	.027	
11ER24UN	○	○	●	11EL24UN			○	1.058	24			0.16	.027	.031	
11ER20UN	○	○	●	11EL20UN			○	1.270	20	1/4"	.43	0.18	.031	.035	
11ER18UN	○	○	●	11EL18UN			○	1.411	18			0.18	.035	.039	
11ER16UN	○	○	●	11EL16UN			○	1.588	16			0.23	.039	.043	
11ER14UN	○	○	●	11EL14UN			○	1.814	14			0.26	.043	.047	
11ER12UN	○	○	●	11EL12UN			○	2.117	12			0.3	.043	.055	
16ER32UN		○	○	16EL32UN				0.794	32			0.13	.024	.024	
16ER28UN	○	○	●	16EL28UN				0.907	28			0.13	.024	.027	
16ER24UN	○	○	●	16EL24UN			○	1.058	24			0.16	.027	.031	
16ER20UN	○	○	●	16EL20UN			○	1.270	20			0.18	.031	.035	
16ER18UN	○	○	●	16EL18UN			○	1.411	18			0.18	.035	.039	
16ER16UN	○	○	●	16EL16UN			○	1.588	16	3/8"	.53	0.23	.039	.043	
16ER14UN	○	○	●	16EL14UN			○	1.814	14			0.26	.043	.047	
16ER12UN	○	○	●	16EL12UN			○	2.117	12			0.3	.043	.055	
16ER11UN				16EL11UN				2.309	11			0.33	.043	.055	
16ER10UN	○	○	○	16EL10UN				2.540	10			0.38	.043	.059	
16ER9UN				16EL9UN				2.822	9			0.41	.047	.059	
16ER8UN	○	○	●	16EL8UN			○	3.175	8			0.46	.047	.063	
22ER7UN		○	●	22EL7UN			○	3.629	7			0.52	.047	.063	
22ER6UN		○	●	22EL6UN			○	4.233	6			0.61	.047	.063	
22ER5UN		○	●	22EL5UN			○	5.080	5	1/2"	.87	0.74	.057	.073	
22ER4.5UN		○	●	22EL4.5UN				5.844	4.5			0.83	.057	.073	
22ER4UN		○	●	22EL4UN				6.350	4			0.87	.057	.073	
27ER4.5UN		○	○	27EL4.5UN			○	5.844	4.5	5/8"	1.06				
27ER4UN		○	○	27EL4UN			○	6.350	4						
27VER4UN		○	○	27VEL4UN			○	6.360	4						
27VER3UN		○	○	27VEL3UN			○	8.466	3						

●:常备库存(主模) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER14UN DN215 10片 Ordering example: 16ER14UN DN215 10pcs

★27V***系列刀片为立装型, 形状参考05页MTTR系列



★27V series is V-style, The shape of the 05 page MTTR series

UN-60° 美制统一标准型螺纹刀片 60° American UN NC NF NEF NS

内螺纹 Internal



图片为右手刀片
Right insert(see picture)



Right Hand (see picture)																	
型 号 Ordering Code	材 质 Material Code			型 号 Ordering Code	材 质 Material Code			加工螺距范围 Pitch		刀片尺寸 Insert Size		尺 寸 Dimensions					
	右手刀片 Right Hand	DK110	DP220		DM215	左手刀片 Left Hand	DK110	DP220	DM215	mm	tpi	IC	Linch	X (mm)	Y (mm)		
11NR32UN		○	○	11NL32UN				○	0.794	32	1/4"	.43	0.07	.024	.024		
11NR28UN	○	○	○	11NL28UN				○	0.907	28			0.07	.024	.024		
11NR24UN	○	○	●	11NL24UN				○	1.058	24			0.08	.027	.031		
11NR20UN	○	○	●	11NL20UN				○	1.270	20			0.09	.031	.035		
11NR18UN	○	○	●	11NL18UN				○	1.411	18			0.1	.031	.038		
11NR16UN	○	○	●	11NL16UN				○	1.588	16			0.11	.035	.043		
11NR14UN	○	○	●	11NL14UN				○	1.814	14			0.13	.035	.047		
11NR12UN	○	○	●	11NL12UN				○	2.117	12			0.16	.043	.055		
16NR32UN				16NL32UN					0.794	32	3/8"	.63	0.07	.024	.024		
16NR28UN				16NL28UN					0.907	28			0.07	.024	.024		
16NR24UN				16NL24UN					1.058	24			0.08	.027	.031		
16NR20UN	○	○	●	16NL20UN			○	1.270	20	0.09			.031	.035			
16NR18UN	○	○	●	16NL18UN			○	1.411	18	0.1			.031	.038			
16NR16UN	○	○	●	16NL16UN			○	1.588	16	0.11			.035	.043			
16NR14UN	○	○	●	16NL14UN			○	1.814	14	0.13			.035	.047			
16NR12UN	○	○	●	16NL12UN			○	2.117	12	0.16			.043	.055			
16NR11UN				16NL11UN					2.309	11			0.16	.043	.055		
16NR10UN	○	○	●	16NL10UN				○	2.540	10			0.18	.043	.059		
16NR9UN				16NL9UN					2.822	9			0.2	.043	.059		
16NR8UN	○	○	●	16NL8UN				○	3.175	8			0.23	.043	.059		
22NR7UN		○	●	22NL7UN				○	3.529	7	1/2"	.87	0.23	.047	.065		
22NR6UN		○	●	22NL6UN				○	4.233	6			0.31	.047	.065		
22NR5UN		○	●	22NL5UN				○	5.080	5			0.37	.057	.072		
22NR4.5UN		○	●	22NL4.5UN					5.844	4.5			0.42	.057	.072		
22NR4UN		○	●	22NL4UN					6.350	4			0.43	.057	.072		
27NR4.5UN		○	○	27NL4.5UN					5.844	4.5	5/8"	1.06					
27NR4UN		○	○	27NL4UN					6.350	4							
27VNR4UN		○	○	27VNL4UN					6.350	4							
27VNR3UN		○	○	27VNL3UN					8.466	3							

●: 常备库存(主选) Stock standard(main) ○: 一般库存 Stock standard



订货示例: 16NR14UN DM215 10片 Ordering example: 16NR14UN DM215 10pcs

★ 27V***系列刀片为立装型, 形状参考05页MTTR系列

★ 27V series is V-style, The shape of the 05 page MTTR series

👉 W-55° 英国惠氏螺纹刀片 55° Whitworth Full Profile

外螺纹 External



图片为右手刀片
Right Insert(see picture)

型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸			
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions			
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	in	IC	Length	Width	X (mm)	Y (mm)	
11ER28W		○ ●	11EL28W			0.907	28			0.1	.024	.027	
11ER26W			11EL26W			0.977	26			0.1	.024	.027	
11ER24W		○ ●	11EL24W			1.058	24			0.1	.024	.027	
11ER20W		○ ●	11EL20W			1.27	20	1/4"	.43	0.17	.031	.035	
11ER19W		○ ●	11EL19W			1.337	19			0.18	.031	.039	
11ER18W		○ ●	11EL18W			1.411	18			0.19	.031	.039	
11ER16W		○ ●	11EL16W			1.588	16			0.22	.035	.043	
11ER14W		○ ●	11EL14W			1.814	14			0.25	.039	.047	
16ER28W		○ ○	16EL28W			0.907	13			0.1	.024	.027	
16ER26W			16EL26W			0.977	26			0.1	.024	.027	
16ER24W		○ ○	16EL24W			1.058	24			0.1	.024	.027	
16ER20W		○ ●	16EL20W			1.27	20			0.17	.031	.035	
16ER19W		○ ●	16EL19W		○	1.337	19			0.18	.031	.039	
16ER18W		○ ●	16EL18W			1.411	18			0.19	.031	.039	
16ER16W		○ ●	16EL16W			1.588	16	3/8"	.63	0.22	.035	.043	
16ER14W		○ ●	16EL14W		○	1.814	14			0.25	.039	.047	
16ER12W		○ ●	16EL12W			2.117	12			0.29	.043	.055	
16ER11W		○ ●	16EL11W		○	2.309	11			0.32	.043	.059	
16ER10W		○ ●	16EL10W			2.54	10			0.35	.043	.059	
16ER9W		○ ●	16EL9W		○	2.822	9			0.39	.047	.067	
16ER8W		○ ●	16EL8W			3.175	8			0.44	.047	.069	
16ER7W		○ ●	16EL7W			3.629	7			0.5	.047	.069	
22ER7W		○ ○	22EL7W			3.629	7			0.5	.063	.088	
22ER6W		○ ○	22EL6W			4.233	6			0.56	.063	.088	
22ER5W		○ ○	22EL5W			5.08	5	1/2"	.87	0.7	.063	.088	
22ER4.5W		○ ○	22EL4.5W			5.644	4.5			0.77	.071	.091	
22ER4W		○ ○	22EL4W			6.35	4			0.87	.071	.091	
27ER4.5W		○ ○	27EL4.5W			5.644	4.5			0.77			
27ER4W		○ ○	27EL4W			6.350	4	5/8"	1.06	0.87			
27VER4W		○ ○	27VEL4W			6.350	4						
27VER3W		○ ○	27VEL3W			8.466	3						
27VER2.5W		○ ○	27VEL2.5W			10.16	2.5						

●:常备库存(主槽) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16ER14W DM215 10片 Ordering example: 16ER14W DM215 10pcs

★27V***系列刀片为立装型, 形状参考05页MTTR系列

★27V series is V-style, The shape of the 05 page MTTR series

👉 W-55° 英国惠氏螺纹刀片 55° Whitworth Full Profile

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

图号 Ordering Code	材质 Material Code			图号 Ordering Code	材质 Material Code			加工螺距范围 Pitch		刀片尺寸 Insert Size		尺寸 Dimensions		
	DK110	DP220	DM215		DK110	DP220	DM215	mm	tpi	IC	L/inch	Fmax	X(max)	Y(max)
右手刀片 Right Hand				左手刀片 Left Hand										
11NR28W		○	●	11NL28W				0.907	28			0.1	.031	.035
11NR26W				11NL26W				0.977	26			0.1	.031	.035
11NR24W		○	○	11NL24W				1.058	24			0.1	.031	.035
11NR20W		○	○	11NL20W				1.27	20	1/4"	.43	0.17	.031	.035
11NR19W		○	●	11NL19W			○	1.337	19			0.18	.031	.035
11NR18W		○	○	11NL18W				1.411	18			0.19	.031	.035
11NR16W		○	○	11NL16W				1.588	16			0.22	.035	.039
11NR14W		○	●	11NL14W			○	1.814	14			0.25	.035	.039
16NR28W			○	16NL28W				0.907	13			0.1	.031	.035
16NR26W				16NL26W				0.977	26			0.1	.031	.035
16NR24W			○	16NL24W				1.058	24			0.1	.031	.035
16NR20W		○	●	16NL20W				1.27	20			0.17	.031	.035
16NR19W		○	●	16NL19W			○	1.337	19			0.18	.031	.035
16NR18W				16NL18W				1.411	18			0.19	.031	.035
16NR16W		○	●	16NL16W				1.588	16	3/8"	.63	0.22	.035	.039
16NR14W		○	●	16NL14W			○	1.814	14			0.25	.035	.039
16NR12W		○	●	16NL12W				2.117	12			0.29	.039	.047
16NR11W		○	●	16NL11W			○	2.309	11			0.32	.039	.055
16NR10W		○	●	16NL10W				2.54	10			0.35	.043	.059
16NR9W		○	●	16NL9W			○	2.822	9			0.39	.043	.059
16NR8W		○	●	16NL8W				3.175	8			0.44	.047	.059
16NR7W		○	●	16NL7W				3.629	7			0.5	.047	.059
22NR7W		○	○	22NL7W				3.629	7			0.5	.063	.088
22NR6W		○	○	22NL6W				4.233	6			0.58	.063	.088
22NR5W		○	○	22NL5W				5.08	5	1/2"	.87	0.7	.063	.088
22NR4.5W		○	○	22NL4.5W				5.644	4.5			0.77	.072	.091
22NR4W		○	○	22NL4W				6.35	4			0.87	.072	.091
27NR4.5W		○	○	27NL4.5W				5.644	4.5			0.77		
27NR4W		○	○	27NL4W				6.350	4			0.87		
27VNR4W		○	○	27VNL4W				6.350	4	5/8"	1.08			
27VNR3W		○	○	27VNL3W				8.466	3					
27VNR2.5W		○	○	27VNL2.5W				10.16	2.5					

● 常备库存(主接) Stock standard(main) ○ 一般库存 Stock standard

订货示例: 16NR14W DM215 10片 Ordering example: 16NR14W DM215 10pcs



★ 27V***系列刀片为立装型, 形状参考05页MTTR系列

★ 27V series is V-style, The shape of the 05 page MTTR series

SSL 公、英、美制螺纹刀具 THREADING TOOLS

👉 60° NPT 美国标准锥管螺纹刀片 NPT

外螺纹 External



图片为右手刀片
Right insert(see picture)

Right Insert (see picture)

型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	Linch	W inch	X inch	Y inch
11ER27NPT		○ ●	11EL27NPT			0.941	27				.031	.027
11ER18NPT		○ ●	11EL18NPT			1.411	18	1/4"	.43	0.03	.036	.031
11ER14NPT		○ ●	11EL14NPT			1.814	14			0.04	.047	.035
16ER27NPT		○ ●	16EL27NPT		○	0.941	27				.031	.027
16ER18NPT		○ ●	16EL18NPT		○	1.411	18			0.03	.036	.031
16ER14NPT		○ ●	16EL14NPT		○	1.814	14	3/8"	.63	0.04	.047	.035
16ER11.5NPT		○ ●	16EL11.5NPT		○	2.209	11.5			0.05	.059	.043
16ER8NPT		○ ●	16EL8NPT		○	3.175	8			0.07	.071	.051

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16ER14NPT DM215 10片 Ordering example: 16ER14NPT DM215 10pcs

👉 60° NPT 美国标准锥管螺纹刀片 NPT

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



Right Hand (see picture)												
型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	吋	IC	L/inch	T/吋	X/吋	Y/吋
11NR27NPT		○ ●	11NL27NPT		○	0.941	27				.039	.031
11NR18NPT		○ ●	11NL18NPT		○	1.411	18	1/4"	.43	0.03	.039	.031
11NR14NPT		○ ●	11NL14NPT		○	1.814	14			0.04	.039	.031
16NR27NPT		○ ●	16NL27NPT			0.941	27				.039	.031
16NR18NPT		○ ●	16NL18NPT			1.411	18			0.03	.039	.031
16NR14NPT		○ ●	16NL14NPT		○	1.814	14	3/8"	.63	0.04	.039	.031
16NR11.5NPT		○ ●	16NL11.5NPT		○	2.209	11.5			0.05	.052	.049
16NR8NPT		○ ●	16NL8NPT		○	3.175	8			0.07	.071	.051



●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16NR14NPT DM215 10片 Ordering example: 16NR14NPT DM215 10pcs

SSL 公、英、美制螺纹刀具 THREADING TOOLS

👉 60° NPTF 美国干密封圆锥管螺纹刀片 NPTF

外螺纹 External



图片为右手刀片
Right Insert(see picture)



图号 Ordering Code	材质 Material Code	图号 Ordering Code	材质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size	尺寸 Dimensions
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm tpi	IC L/inch	F/inch X mm Y mm
11ER27NPTF	○ ○	11EL27NPTF		0.941 27		.039 .031
11ER18NPTF	○ ○	11EL18NPTF		1.411 18	1/4"	.039 .031
11ER14NPTF	○ ○	11EL14NPTF		1.814 14		.039 .031
16ER27NPTF	○ ○	16EL27NPTF		0.941 27		.039 .031
16ER18NPTF	○ ○	16EL18NPTF		1.411 18		.039 .031
16ER14NPTF	○ ○	16EL14NPTF		1.814 14	3/8"	.039 .031
18ER11.5NPTF	○ ○	18EL11.5NPTF		2.209 11.5		.062 .049
18ER8NPTF	○ ○	18EL8NPTF		3.175 8		.071 .051

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER14NPTF DM215 10片 Ordering example: 16ER14NPTF DM215 10pcs

👉 60° NPTF 美国干密封圆锥管螺纹刀片 NPTF

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

Right Hand (see picture)														
型 号	材 质			型 号	材 质			加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215			左手刀片 Left Hand	DK110 DP220 DM215			mm	in	IC	L(inch)	F(in)	X(in)	Y(in)
11NR27NPTF		○		11NL27NPTF				0.941	27				.039	.031
11NR18NPTF		○		11NL18NPTF				1.411	18	1/4"	.43		.039	.031
11NR14NPTF		○	○	11NL14NPTF				1.814	14				.039	.031
16NR27NPTF		○	○	16NL27NPTF				0.941	27				.039	.031
16NR18NPTF		○	○	16NL18NPTF				1.411	18				.039	.031
16NR14NPTF		○	○	16NL14NPTF				1.814	14	3/8"	.63		.039	.031
16NR11.5NPTF		○	○	16NL11.5NPTF				2.209	11.5				.052	.049
16NR8NPTF		○	○	16NL8NPTF				3.175	8				.071	.051



●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16NR14NPTF DM215 10片 Ordering example: 16NR14NPTF DM215 10pcs

SSL 公、英、美制螺纹刀具 THREADING TOOLS

👉 BSPT-55° 英国标准锥管螺纹刀片 BSPT

外螺纹 External



图片为右手刀片
Right Insert(see picture)

Right Hand (see picture)



型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	吋	IC	Length	mm	Inch	mm
11ER28SPT	○	●	11EL28SPT			0.907	28			0.1	.031	.035
11ER19SPT	○	●	11EL19SPT			1.337	19	1/4"	.43	0.16	.037	.039
11ER14SPT	○	●	11EL14SPT			1.814	14			0.22	.047	.039
16ER28SPT	○	●	16EL28SPT			0.907	28			0.1	.031	.035
16ER19SPT	○	●	16EL19SPT		○	1.337	19	3/8"	.63	0.16	.037	.039
16ER14SPT	○	●	16EL14SPT		○	1.814	14			0.22	.047	.039
16ER11SPT	○	●	16EL11SPT		○	2.309	11			0.29	.056	.041

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER14BSPT DM215 10片 Ordering example: 16ER14BSPT DM215 10pcs

👉 BSPT-55° 英国标准锥管螺纹刀片 BSPT

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



型 号 Ordering Code	材 质 Material Code	型 号 Ordering Code	材 质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size			
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm	吋	IC	L/inch	
11NR28BSPT	○ ●	11NL28BSPT	○	0.907	28			0.1 .031 .035
11NR19BSPT	○ ●	11NL19BSPT	○	1.337	19	1/4"	.43	0.16 .037 .039
11NR14BSPT	○ ●	11NL14BSPT	○	1.814	14			0.22 .047 .039
16NR28BSPT		16NL28BSPT		0.907	28			0.1 .031 .035
16NR19BSPT	○ ●	16NL19BSPT		1.337	19	3/8"	.63	0.16 .037 .039
16NR14BSPT	○ ●	16NL14BSPT	○	1.814	14			0.22 .047 .039
16NR11BSPT	○ ●	16NL11BSPT	○	2.309	11			0.29 .069 .041

●:常备库存(主选) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16NR14BSPT DM215 10片 Ordering example: 16NR14BSPT DM215 10pcs

👉 TR-30° 梯形螺纹 Trapez DIN 103

外螺纹 External



图片为右手刀片
Right Insert(see picture)



型号	材质			型号	材质			加工螺距范围		刀片尺寸		尺寸		
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110	DP220	DM215	左手刀片 Left Hand	DK110	DP220	DM215	mm	吋	IC	L/inch	Front	X/Inch	Y/mm
16ER1.5TR		○	●	16EL1.5TR			○	1.50				0.1	.041	.038
16ER2.0TR		○	●	16EL2.0TR			○	2.00		3/8"	.63	0.1	.051	.043
16ER3.0TR		○	●	16EL3.0TR			○	3.00				0.1	.059	.051
22ER4.0TR		○	●	22EL4.0TR			○	4.00				0.1	.075	.067
22ER5.0TR		○	●	22EL5.0TR			○	5.00				0.1	.098	.083
22ER6.0TR		○	●	22EL6.0TR			○	6.00		1/2"	.87	0.1	.101	.089
22UER7.0TR		○	○	22UEL7.0TR				7.00				0.1	.085	.54
27ER6.0TR		○	○	27EL6.0TR			○	6.00				0.1		
27ER7.0TR		○	○	27EL7.0TR				7.00				0.1		
27VER6.0TR		○	●	27VEL6.0TR			○	6.00				0.1		
27VER7.0TR		○	●	27VEL7.0TR			○	7.00				0.15		
27VER8.0TR		○	●	27VEL8.0TR			○	8.00		5/8"	1.06	0.2		
27VER9.0TR		○	○	27VEL9.0TR				9.00				0.2		
27VER10TR		○	●	27VEL10TR			○	10.0				0.2		
27VER12TR				27VEL12TR				12.0				0.3		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER3.0TR DM215 10片 Ordering example: 16ER3.0TR DM215 10pcs

👉 TR-30° 梯形螺纹 Trapez DIN 103

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

Right Insert (see picture)



型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸			
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions			
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	in	IC	Length	Width	X (mm)	Y (mm)	
11NR1.5TR		○ ●	11NL1.5TR		○	1.50			.43		0.1	.041	.039
11NR2.0TR		○ ●	11NL2.0TR		○	2.00					0.1	.051	.043
16NR1.5TR		○ ●	16NL1.5TR		○	1.50					0.1	.041	.039
16NR2.0TR		○ ●	16NL2.0TR		○	2.00		3/8"	.63		0.1	.051	.043
16NR3.0TR		○ ●	16NL3.0TR		○	3.00					0.1	.069	.061
22NR4.0TR		○ ●	22NL4.0TR		○	4.00					0.1	.075	.067
22NR5.0TR		○ ●	22NL5.0TR		○	5.00		1/2"	.87		0.1	.090	.083
22NR6.0TR		○ ●	22NL6.0TR		○	6.00					0.1	.101	.090
22LNR7.0TR		○ ○	22LNL7.0TR			7.00					0.1	.085	.54
27NR6.0TR		○ ○	27NL6.0TR		○	6.00					0.1		
27NR7.0TR		○ ○	27NL7.0TR			7.00					0.1		
27VNR6.0TR		○ ●	27VNL6.0TR		○	6.00					0.1		
27VNR7.0TR		○ ●	27VNL7.0TR		○	7.00		5/8"	1.06		0.15		
27VNR8.0TR		○ ●	27VNL8.0TR		○	8.00					0.2		
27VNR9.0TR		○ ○	27VNL9.0TR			9.00					0.2		
27VNR10TR		○ ●	27VNL10TR		○	10.0					0.2		
27VNR12TR			27VNL12TR			12.0					0.3		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16NR3.0TR DM215 10片 Ordering example: 16NR3.0TR DM215 10pcs

👉 ACME-29° 美制ACME梯形螺纹刀片 American ACME

外螺纹 External



图片为右手刀片
Right Insert(see picture)

型 号 Ordering Code	材 质 Material Code	型 号 Ordering Code	材 质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size	尺寸 Dimensions
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm tpi	IC L/inch	F/inch X/mm Y/mm
16ER16ACME	○ ●	16EL16ACME		1.588 16		0.06 .043 .039
16ER14ACME	○ ●	16EL14ACME		1.814 14		0.08 .043 .039
16ER12ACME	○ ●	16EL12ACME		2.117 12	3/8" .63	0.01 .047 .043
16ER10ACME	○ ●	16EL10ACME	○	2.540 10		0.12 .065 .061
16ER8ACME	○ ●	16EL8ACME	○	3.175 8		0.18 .069 .065
22ER6ACME	○ ●	22EL6ACME	○	4.233 6		0.2 .083 .071
22ER5ACME	○ ●	22EL5ACME		5.080 5	1/2" .87	0.25 .09 .079
22ER4ACME	○ ●	22EL4ACME		6.350 4		0.3 .112 .082
27ER4ACME	○ ○	27EL4ACME		6.350 4	5/8" 1.06	0.3
27VER3ACME	○ ○	27VEL3ACME		8.466 3		0.3

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER12ACME DM215 10片 Ordering example: 16ER12ACME DM215 10pcs

★ 27V***系列刀片为立装型, 形状参考05页MTTR系列



★ 27V series is V-style, The shape of the 05 page MTTR series

👉 ACME-29° 美制ACME梯形螺纹刀片 American ACME

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



Right Insert (see primary)

型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110	DP220 DM215	左手刀片 Left Hand	DK110	DP220 DM215	mm	in	IC	Linch	T(max)	X(max)	Y(max)
11NR16ACME		○ ●	11NL16ACME			1.588	16	1/4"	.43	0.06	.043	.039
11NR14ACME		○ ●	11NL14ACME			1.814	14			0.08	.043	.039
16NR16ACME		○ ●	16NL16ACME			1.588	16			0.06	.043	.039
16NR14ACME		○ ●	16NL14ACME			1.814	14			0.08	.043	.039
16NR12ACME		○ ●	16NL12ACME		○	2.117	12	3/8"	.63	0.01	.047	.043
16NR10ACME		○ ●	16NL10ACME		○	2.540	10			0.12	.055	.051
16NR8ACME		○ ●	16NL8ACME		○	3.175	8			0.18	.059	.055
22NR6ACME		○ ●	22NL6ACME		○	4.233	6			0.2	.063	.071
22NR5ACME		○ ●	22NL5ACME			5.080	5	1/2"	.87	0.25	.09	.079
22NR4ACME		○ ●	22NL4ACME			6.350	4			0.3	.112	.092
27NR4ACME		○ ○	27NL4ACME			6.350	4	5/8"	1.06	0.3		
27VNR3ACME		○ ○	27VNL3ACME			8.466	3			0.3		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16NR12ACME DM215 10片 Ordering example: 16NR12ACME DM215 10pcs

★27V***系列刀片为立装型。形状参考05页MTTR系列

★27V series is V-style, The shape of the 05 page MTTR series

👉 STACME-29° 美制短齿梯形螺纹刀片 Stub ACME

外螺纹 External



图片为右手刀片
(Right Insert/see picture)

Right Insert(see picture)

型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	F/inch	X (mm)	Y (mm)
16ER16STACME		○ ○	16EL16STACME			1.588	16			0.06	.039	.039
16ER14STACME		○ ○	16EL14STACME			1.814	14			0.08	.039	.039
16ER12STACME		○ ○	16EL12STACME			2.117	12	3/8"	.63	0.01	.051	.047
16ER10STACME		○ ○	16EL10STACME			2.540	10			0.12	.051	.047
16ER8STACME		○ ●	16EL8STACME			3.175	8			0.18	.059	.055
16ER6STACME		○ ●	16EL6STACME			4.233	6			0.2	.059	.055
22ER6STACME		○ ○	22EL6STACME			4.233	6			0.2	.059	.055
22ER5STACME		○ ●	22EL5STACME			5.080	5	1/2"	.87	0.25	.090	.083
22ER4STACME		○ ●	22EL4STACME			6.350	4			0.3	.099	.087
27ER4STACME		○ ●	27EL4STACME			6.350	4	5/8"	1.06	0.3		
27VER3STACME		○ ○	27VEL3STACME			8.466	3			0.3		

●:常备库存(主槽) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER12STACME DM215 10片 Ordering example: 16ER12STACME DM215 10pcs

★27V***系列刀片为立装型, 形状参考05页MTTR系列



★27V series is V-style, The shape of the 05 page MTTR series

👉 STACME-29° 美制短齿梯形螺纹刀片 Stub ACME

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



Right Insert(see picture)

型 号	材 质			型 号	材 质			加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code			Ordering Code	Material Code			Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110	DP220	DM215	左手刀片 Left Hand	DK110	DP220	DM215	mm	in	IC	L/inch	Y/mm	X/mm	Y/mm
11NR18STACME		○	○	11NL18STACME				1.588	16	1/4"	.43	0.06	.039	.039
11NR14STACME		○	○	11NL14STACME				1.814	14			0.08	.039	.039
16NR18STACME		○	○	16NL18STACME				1.588	16			0.06	.039	.039
16NR14STACME		○	○	16NL14STACME				1.814	14			0.08	.039	.039
16NR12STACME		○	○	16NL12STACME				2.117	12	3/8"	.83	0.01	.051	.047
16NR10STACME		○	○	16NL10STACME				2.540	10			0.12	.051	.047
16NR8STACME		○	●	16NL8STACME				3.175	8			0.18	.059	.055
16NR6STACME		○	●	16NL6STACME				4.233	6			0.2	.059	.055
22NR6STACME		○	○	22NL6STACME				4.233	6			0.2	.059	.055
22NR5STACME		○	●	22NL5STACME				5.080	5	1/2"	.87	0.25	.090	.083
22NR4STACME		○	●	22NL4STACME				6.350	4			0.3	.099	.087
27NR4STACME		○	●	27NL4STACME				6.350	4	5/8"	1.06	0.3		
27VNR3STACME		○	○	27VNL3STACME				8.466	3			0.3		

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16NR12STACME DM215 10片 Ordering example: 16NR12STACME DM215 10pcs

★ 27V***系列刀片为立装型, 形状参考05页MTTR系列

★ 27V series is V-style, The shape of the 05 page MTTR series

👉 RD圆螺纹 30° DIN405

外螺纹 External





图片为右手刀片
Right Insert(see picture)

Right Insert (see previous)												
型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	Tmax	X/mm	Y/mm
16ER10RD		○ ●	16EL10RD			2.54	10			0.81	.051	.055
16ER 8RD		○ ●	16EL 8RD			3.175	8	3/8"	.83	0.78	.059	.063
16ER 6RD		○ ●	16EL 6RD			4.23	6			1.01	.067	.059
22ER 6RD		○ ●	22EL 6RD			4.23	6			1.01	.067	.059
22ER 5RD		○ ○	22EL 5RD			5.08	5	2 1/4"	.87	1.21	.078	.066
22ER 4RD		○ ●	22EL 4RD			6.35	4			1.51	.082	.087

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER8RD DM215 10片 Ordering example: 16ER8RD DM215 10pcs

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	Tmax	X/mm	Y/mm
16NR10RD		○ ●	16NL10RD			2.54	10			0.58	.051	.055
16NR 8RD		○ ●	16NL 8RD			3.175	8	3/8"	.83	0.7	.059	.063
16NR 6RD		○ ●	16NL 6RD			4.23	6			0.94	.067	.059
22NR 6RD		○ ●	22NL 6RD			4.23	6			0.94	.067	.059
22NR 5RD		○ ○	22NL 5RD			5.08	5	2 1/4"	.87	1.12	.078	.066
22NR 4RD		○ ●	22NL 4RD			6.35	4			1.4	.082	.087

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 16NR8RD DM215 10片 Ordering example: 16NR8RD DM215 10pcs

Pg 钢导管螺纹刀片 Pg DIN40430

外螺纹 External



图片为右手刀片
Right Insert(see picture)



Right Insert (see previous)											
型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺寸	
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions (inch)	
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	r	X Y
11ER20Pg		○ ●	11EL20Pg			1.27	20				.031 .035
11ER18Pg		○ ●	11EL18Pg			1.41	18	1/4"	.43		.031 .039
11ER16Pg		○ ●	11EL16Pg			1.59	16				.035 .043
16ER20Pg		○ ●	16EL20Pg			1.27	20				.031 .035
16ER18Pg		○ ●	16EL18Pg			1.41	18	3/8"	.63		.031 .039
16ER16Pg		○ ●	16EL16Pg			1.59	16				.035 .043



●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例:16ER18Pg DM215 10片 Ordering example:16ER18Pg DM215 10pcs

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



型 号		材 质		型 号		材 质		加工螺距范围		刀片尺寸		尺寸		
Ordering Code		Material Code		Ordering Code		Material Code		Pitch		Insert Size		Dimensions (inch)		
右手刀片 Right Hand		DK110 DP220 DM215		左手刀片 Left Hand		DK110 DP220 DM215		mm	tpi	IC	Length	r	X	Y
11NR20Pg			○ ●	11NL20Pg				1.27	20				.030	.034
11NR18Pg			○ ●	11NL18Pg				1.41	18	1/4"	.43		.030	.038
11NR16Pg			○ ●	11NL16Pg				1.59	16				.033	.041
16NR20Pg			○ ●	16NL20Pg				1.27	20				.031	.035
16NR18Pg			○ ●	16NL18Pg				1.41	18	3/8"	.63		.031	.039
16NR16Pg			○ ●	16NL16Pg				1.59	16				.035	.043

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例:16NR18Pg DM215 10片 Ordering example:16NR18Pg DM215 10pcs

👉 ABUT美制锯齿形螺纹刀片 American Buttress

外螺纹 External



图片为右手刀片
Right Insert(see picture)





型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions (inch)		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	r	X	Y
11ER20ABUT		○ ○	11EL20ABUT			1.270	20	1/4"	.43	.003	.031	.035
11ER16ABUT		○ ○	11EL16ABUT			1.588	16			.003	.031	.034
16ER20ABUT		○ ○	16EL20ABUT			1.270	20	3/8"	.63	.004	.031	.034
16ER16ABUT		○ ○	16EL16ABUT			1.588	16			.005	.031	.034
16ER12ABUT		○ ○	16EL12ABUT			2.117	12			.007	.039	.041
16ER10ABUT		○ ○	16EL10ABUT			2.540	10			.008	.043	.047
22ER8ABUT		○ ○	22EL8ABUT			3.175	8	1/2"	.87	.010	.047	.052
22ER6ABUT		○ ○	22EL6ABUT			4.233	6			.012	.063	.068

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard
订货示例: 16ER12ABUT DM215 10片 Ordering example: 16ER12ABUT DM215 10pcs

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



型 号	材 质		型 号	材 质		加工螺距范围		刀片尺寸		尺 寸		
Ordering Code	Material Code		Ordering Code	Material Code		Pitch		Insert Size		Dimensions (inch)		
右手刀片 Right Hand	DK110 DP220 DM215		左手刀片 Left Hand	DK110 DP220 DM215		mm	tpi	IC	L/inch	r	X	Y
11NR20ABUT		○ ○	11NL20ABUT			1.270	20	1/4"	.43	.003	.031	.035
11NR16ABUT		○ ○	11NL16ABUT			1.588	16			.003	.031	.034
16NR20ABUT			16NL20ABUT			1.270	20			.004	.031	.034
16NR16ABUT		○ ○	16NL16ABUT			1.588	16	3/8"	.63	.005	.031	.034
16NR12ABUT		○ ○	16NL12ABUT			2.117	12			.007	.039	.041
16NR10ABUT		○ ○	16NL10ABUT			2.540	10			.008	.043	.047
22NR8ABUT		○ ○	22NL8ABUT			3.175	8	1/2"	.87	.010	.047	.052
22NR6ABUT		○ ○	22NL6ABUT			4.233	6			.012	.063	.069


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard
订货示例: 16NR12ABUT DM215 10片 Ordering example: 16NR12ABUT DM215 10pcs

SAGE德标锯齿螺纹 DIN513


外螺纹 External



图片为右手刀片
Right Insert (see picture)



DIN513
GB/T 13576



型 号	材 质	型 号	材 质	加工螺距范围	刀片尺寸	尺寸
Ordering Code	Material Code	Ordering Code	Material Code	Pitch	Insert Size	Dimensions (inch)
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm	IC Linch	r X Y
16ER2.0SAGE	○ ○	16EL2.0SAGE		2.0	3/8" .63	0.059 0.086
22ER3.0SAGE	○ ○	22EL3.0SAGE		3.0		0.065 0.114
22ER4.0SAGE	○ ○	22EL4.0SAGE		4.0	1/2" .87	0.083 0.125
* 22UER5.0SAGE	○ ○	* 22UEL5.0SAGE		5.0		
* 22UER6.0SAGE	○ ○	* 22UEL6.0SAGE		6.0		
27ER5.0SAGE	○ ○	27EL5.0SAGE		5.0	7/8" 1.06	
27ER6.0SAGE	○ ○	27EL6.0SAGE		6.0		

●常备库存(主推) Stock standard(main) ○:一般库存 Stock standard


订货示例 22ER3.0SAGE DM215 10片 Ordering example: 22ER3.0SAGE DM215 10pcs

*代表刀片为U型结构 The insert is U-style


内螺纹 Internal



图片为右手刀片
Right Insert (see picture)



DIN513
GB/T 13576



型 号	材 质	型 号	材 质	加工螺距范围	刀片尺寸	尺寸
Ordering Code	Material Code	Ordering Code	Material Code	Pitch	Insert Size	Dimensions (inch)
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm	IC Linch	r X Y
16NR2.0SAGE	○ ○	16NL2.0SAGE		2.0	3/8" .63	0.059 0.086
22NR3.0SAGE	○ ○	22NL3.0SAGE		3.0		0.065 0.114
22NR4.0SAGE	○ ○	22NL4.0SAGE		4.0	1/2" .87	0.083 0.125
* 22UNR5.0SAGE	○ ○	* 22UNL5.0SAGE		5.0		
* 22UNR6.0SAGE	○ ○	* 22UNL6.0SAGE		6.0		
27NR5.0SAGE	○ ○	27NL5.0SAGE		5.0	7/8" 1.06	
27NR6.0SAGE	○ ○	27NL6.0SAGE		6.0		

●常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例 22ER3.0SAGE DM215 10片 Ordering example: 22ER3.0SAGE DM215 10pcs


*代表刀片为U型结构 The insert is U-style

👉 美制API螺纹刀片 API

外螺纹 External



图片为右手刀片
Right Insert(see picture)



美制API Spec 7-1985
国标GB/T 9253.1-1999

$$\alpha = \arctan(IPF/24)$$




外螺纹刀片

刀片尺寸 Insert size		螺距 Thread	锥度 Taper	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Len	tpi	IPF	III	DK110	DP220	DM215		hmin	X	Y
1/2"	22	4	V-0.038R	1:6	22ER4API382	●	○	NC23-NC50	3.09	2.1	2.8
		4	V-0.038R	1:4	22ER4API383	●	○	NC56-NC77	3.08	2.1	2.8
		4	V-0.050	1:6	22ER4API502	●	○	6-5/8"REG	3.75	2.0	2.9
		4	V-0.050	1:4	22ER4API503	●	○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.0	2.9
		5	V-0.040	1:4	22ER5API403	●	○	2-3/8"-4-1/2"REG	2.99	1.8	2.6
		6	V-0.055	1:8	22ER6API551	●	○	NC10-NC16	1.41	2.6	2.0
5/8"	27	4	V-0.038R	1:6	27ER4API382	●	○	NC23-NC50	3.09	2.1	2.8
		4	V-0.038R	1:4	27ER4API383	●	○	NC56-NC77	3.08	2.1	2.8
		4	V-0.050	1:6	27ER4API502	●	○	6-5/8"REG	3.75	2.1	3.1
		4	V-0.050	1:4	27ER4API503	●	○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.1	3.1
		5	V-0.040	1:4	27ER5API403	●	○	2-3/8"-4-1/2"REG	2.99	1.9	2.7

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



美制API Spec 7-1985
国标GB/T 9253.1-1999

$$\alpha = \arctan(IPF/24)$$




内螺纹刀片


刀片尺寸 Insert size		螺距 Thread	锥度 Taper	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Len	tpi	IPF	III	DK110	DP220	DM215		hmin	X	Y
1/2"	22	4	V-0.038R	1:6	22NR4API382	●	○	NC23-NC50	3.09	2.1	2.8
		4	V-0.038R	1:4	22NR4API383	●	○	NC56-NC77	3.08	2.1	2.8
		4	V-0.050	1:6	22NR4API502	●	○	6-5/8"REG	3.75	2.0	2.9
		4	V-0.050	1:4	22NR4API503	●	○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.0	2.9
		5	V-0.040	1:4	22NR5API403	●	○	2-3/8"-4-1/2"REG	2.99	1.8	2.6
		6	V-0.055	1:8	22NR6API551	●	○	NC10-NC16	1.41	2.6	2.0
5/8"	27	4	V-0.038R	1:6	27NR4API382	●	○	NC23-NC50	3.09	2.1	2.8
		4	V-0.038R	1:4	27NR4API383	●	○	NC56-NC77	3.08	2.1	2.8
		4	V-0.050	1:6	27NR4API502	●	○	6-5/8"REG	3.75	2.1	3.1
		4	V-0.050	1:4	27NR4API503	●	○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.1	3.1
		5	V-0.040	1:4	27NR5API403	●	○	2-3/8"-4-1/2"REG	2.99	1.9	2.7

美制API螺纹刀片 API

外螺纹 External

图片为右手刀片
Right Insert (see picture)美标API Spec 7-1985
图例08/T-1 9253.1-1999

$$\alpha = \arctan(IPF/24)$$




外螺纹刀片

刀片尺寸 Insert size	螺距 Thread	锥度 Taper	刀片型号 Ordering Code	材质 Material Code	螺纹尺寸 Size	尺寸规格 Dimension(mm)		
						hmin	X	Y
1/2" 22	4 V-0.038R	1:6	22ER4API382A	● ○	NC23-NC50	3.09	2.1	2.8
	4 V-0.038R	1:4	22ER4API383A	● ○	NC56-NC77	3.08	2.1	2.8
	4 V-0.050	1:6	22ER4API502A	● ○	6-5/8"REG	3.75	2.0	2.9
	4 V-0.050	1:4	22ER4API503A	● ○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.0	2.9
	5 V-0.040	1:4	22ER5API403A	● ○	2-3/8"~4-1/2"REG	2.99	1.8	2.6
	6 V-0.055	1:8	22ER6API551A	● ○	NC10-NC16	1.41	2.6	2.0
5/8" 27	4 V-0.038R	1:6	27ER4API382A	● ○	NC23-NC50	3.09	2.1	2.8
	4 V-0.038R	1:4	27ER4API383A	● ○	NC56-NC77	3.08	2.1	2.8
	4 V-0.050	1:6	27ER4API502A	● ○	6-5/8"REG	3.75	2.1	3.1
	4 V-0.050	1:4	27ER4API503A	● ○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.1	3.1
	5 V-0.040	1:6	27ER5API403A	● ○	2-3/8"~4-1/2"REG	2.99	1.9	2.7

内螺纹 Internal

图片为右手刀片
Right Insert (see picture)美标API Spec 7-1985
图例08/T-1 9253.1-1999

$$\alpha = \arctan(IPF/24)$$



内螺纹刀片


刀片尺寸 Insert size	螺距 Thread	锥度 Taper	刀片型号 Ordering Code	材质 Material Code	螺纹尺寸 Size	尺寸规格 Dimension(mm)		
						hmin	X	Y
1/2" 22	4 V-0.038R	1:6	22NR4API382A	● ○	NC23-NC50	3.09	2.1	2.8
	4 V-0.038R	1:4	22NR4API383A	● ○	NC56-NC77	3.08	2.1	2.8
	4 V-0.050	1:6	22NR4API502A	● ○	6-5/8"REG	3.75	2.0	2.9
	4 V-0.050	1:4	22NR4API503A	● ○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.0	2.9
	5 V-0.040	1:4	22NR5API403A	● ○	2-3/8"~4-1/2"REG	2.99	1.8	2.6
	6 V-0.055	1:8	22NR6API551A	● ○	NC10-NC16	1.41	2.6	2.0
5/8" 27	4 V-0.038R	1:6	27NR4API382A	● ○	NC23-NC50	3.09	2.1	2.8
	4 V-0.038R	1:4	27NR4API383A	● ○	NC56-NC77	3.08	2.1	2.8
	4 V-0.050	1:6	27NR4API502A	● ○	6-5/8"REG	3.75	2.1	3.1
	4 V-0.050	1:4	27NR4API503A	● ○	5-1/2", 7-5/8", 8-5/8"REG	3.74	2.1	3.1
	5 V-0.040	1:6	27NR5API403A	● ○	2-3/8"~4-1/2"REG	2.99	1.9	2.7

60° -API石油管用螺纹刀片 Insert for API Oil Pipe

外螺纹 External




图片为右手刀片
Right Insert(see picture)



标准 美制API螺纹 SPEC. 7:1990
公差等级标准 美制API螺纹

$$\alpha = \arctg(IPF/24)$$



外螺纹刀片

型 号 Ordering Code	材 质 Material Code	型 号 Ordering Code	材 质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size	尺寸 Dimensions (inch)
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm in	IC L/inch	r X Y
16ER10APIRD	○ ●	16EL10APIRD		2.540 10	3/8" .63	.004 .043 .059
16ER08APIRD	○ ●	16EL08APIRD		3.175 8		.005 .047 .063


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER10APIRD DM215 10片 Ordering example: 16ER10APIRD DM215 10pcs

内螺纹 Internal




图片为右手刀片
Right Insert(see picture)



标准 美制API螺纹 SPEC. 7:1990
公差等级标准 美制API螺纹

$$\alpha = \arctg(IPF/24)$$



内螺纹刀片

型 号 Ordering Code	材 质 Material Code	型 号 Ordering Code	材 质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size	尺寸 Dimensions (inch)
右手刀片 Right Hand	DK110 DP220 DM215	左手刀片 Left Hand	DK110 DP220 DM215	mm in	IC L/inch	r X Y
16NR10APIRD	○ ●	16NL10APIRD		2.540 10	3/8" .63	.004 .043 .059
16NR08APIRD	○ ●	16NL08APIRD		3.175 8		.005 .047 .063

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16NR10APIRD DM215 10片 Ordering example: 16NR10APIRD DM215 10pcs

美制VAM螺纹刀片 VAM


外螺纹 External



图片为右手刀片
Right Insert(see picture)



$\alpha = \arctg (IPF/24)$
标准 STD. 5B:1979



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
3/8	16	8	0.75	16ER8VAM		○	○	2-3/8", 2-7/8"	0.97	1.7	1.8
1/2	22	6	0.75	22ER6VAM		○	○	3-1/2"	0.97	2.4	2.4
		5	0.75	22ER5VAM		○	○	5"-9-5/8"	1.54	2.4	2.7

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 16ER8VAM DM215 10片 Ordering example: 16ER8VAM DM215 10pcs


内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



$\alpha = \arctg (IPF/24)$
标准 STD. 5B:1979



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
3/8	16	8	0.75	16NR8VAM		○	○	2-3/8", 2-7/8"	0.97	1.7	1.8
1/2	22	6	0.75	22NR6VAM		○	○	3-1/2"	0.97	2.4	2.4
		5	0.75	22NR5VAM		○	○	5"-9-5/8"	1.54	2.4	2.7

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard


订货示例: 16NR8VAM DM215 10片 Ordering example: 16NR8VAM DM215 10pcs

👉 美制EL石油套管螺纹刀片 EL

外螺纹 External




图片为右手刀片
Right insert(see picture)



标准 美制API螺纹 STD. 5B:1979

$$\alpha = \arctg (1/FF/24)$$



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
1/2	22	6	1.5	22ER6EL		○	○	5°~7-5/8"	1.39	1.8	1.9
		5	1.25	22ER5EL		○	○	8-5/8"~10-3/4"	1.91	2.2	2.4


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 22ER6EL DM215 10片 Ordering example: 22ER6EL DM215 10pcs

内螺纹 Internal



图片为右手刀片
Right insert(see picture)



标准 美制API螺纹 STD. 5B:1979

$$\alpha = \arctg (1/FF/24)$$



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
1/2	22	6	1.5	22NR6EL		○	○	5°~7-5/8"	1.39	1.8	1.9
		5	1.25	22NR5EL		○	○	8-5/8"~10-3/4"	1.91	2.2	2.4

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 22NR6EL DM215 10片 Ordering example: 22NR6EL DM215 10pcs

API锯齿套螺纹刀片

外螺纹 External



图片为右手刀片
Right Insert(see picture)



标准 STD. 58:1979

$$\alpha = \arctg (1/fz/24)$$



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
1/2"	22	5	0.75	22ER5BUT75		○	○	4-1/2"~13-3/8"	1.55	3.1	1.9
		5	1	22ER5BUT1		○	○	16"~20"	1.55	3.1	1.9


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: 22ER5BUT1 DM215 10片 Ordering example: 22ER5BUT75 DM215 10pcs

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)



标准 STD. 58:1979

$$\alpha = \arctg (1/fz/24)$$



刀片尺寸 Insert size		螺距 tpi	锥度 IPF	刀片型号 Ordering Code	材质 Material Code			螺纹尺寸 Size	尺寸规格 Dimension(mm)		
IC	Lmm			RH	DK110	DP220	DM215		hmin	X	Y
1/2"	22	5	0.75	22NR5BUT75		○	○	4-1/2"~13-3/8"	1.55	3.1	1.9
		5	1	22NR5BUT1		○	○	16"~20"	1.55	3.1	1.9

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard



订货示例: 22NR5BUT1 DM215 10片 Ordering example: 22NR5BUT75 DM215 10pcs

PCD/PCBN螺纹刀片 PCD/PCBN

外螺纹 External



图片为右手刀片
Right Insert(see picture)



型 号 Ordering Code	材质 Material Code	型 号 Ordering Code	材质 Material Code	加工螺距范围 Pitch	刀片尺寸 Insert Size	尺寸 Dimensions (inch)
右手刀片 Right Hand	CB20 PC20	左手刀片 Left Hand	CB20 PC20	mm in	IC L/inch	I X Y
11ERA60F		11ELA60F		0.5-1.5 48-16	1/4" .43	.003 .031 .035
11ERA55F		11ELA55F		0.5-1.5 48-16		.003 .031 .035
16ERA60F	●	16ELA60F	●	1.0-2.5 24-10	3/8" .63	.004 .047 .067
16ERA55F	●	16ELA55F	●	1.0-2.5 24-10		.004 .047 .067
22ERN60F	○	22ELN60F	○	3.0-5.0 8-5	1/2" .87	.021 .067 .098
22ERN55F	○	22ELN55F	○	3.0-5.0 8-5		.021 .067 .098

★CB20为立方氮化硼刀片 (PCBN), 适用于精加工高硬度钢



CB20: Polycrystalline Cubic Boron Nitride (PCBN) Inserts, application of High hardness steel for finishing

★PC20为金刚石刀片 (PCD), 适用于精加工有色金属

PC20: Polycrystalline diamond (PCD) Inserts, application of Non-ferrous metals for finishing

PCD/PCBN螺纹刀片 PCD/PCBN

内螺纹 Internal



图片为右手刀片
Right Insert(see picture)

型 号 Ordering Code	材 质 Material Code		型 号 Ordering Code	材 质 Material Code		加工螺距范围 Pitch		刀片尺寸 Insert Size		尺寸 Dimensions (inch)		
	CB20	PC20		CB20	PC20	mm	tpi	IC	L/inch	I	X	Y
11NRA60F			11NLA60F			0.5-1.5	48-16	1/8"	.43	.003	.031	.035
11NRA55F			11NLA55F			0.5-1.5	48-16	1/8"	.43	.003	.031	.035
16NRA60F	●	●	16NLA60F	●	●	0.5-3.0	48-8	3/8"	.63	.004	.047	.067
16NRA55F	●	●	16NLA55F	●	●	0.5-3.0	48-8	3/8"	.63	.004	.047	.067
22NRA60F	○	○	22NLA60F	○	○	3.5-6.0	7-5	1/2"	.87	.021	.067	.098
22NRA55F	○	○	22NLA55F	○	○	3.5-6.0	7-5	1/2"	.87	.021	.067	.098




★CB20为立方氮化硼刀片 (PCBN), 适用于精加工高硬度钢

CB20: Polycrystalline Cubic Boron Nitride (PCBN) Inserts, application of High hardness steel for finishing

★PC20为金刚石刀片 (PCD), 适用于精加工有色金属

PC20: Polycrystalline diamond (PCD) Inserts, application of Non-ferrous metals for finishing

👉 外螺纹车刀杆 (偏头) Threading Tool Holders



图片为右手刀具
Right Cutting Tools (see picture)

注意: 右手刀具 (R) 配右手刀片 (R), 左手刀具 (L) 配左手刀片 (L)
Note: right tools match with right inserts; left tools match with left inserts.

型号 Ordering Code		尺寸 Dimensions (mm)					刀片 Insert		刀片螺钉	扳手	刀垫	侧面螺钉	扳手
右刀 Right Hand	左刀 Left Hand	h	b	H	F	L	右 Right	左 Left	Insert Screw	Tool Key	Anvil	Anvil Screw	Hex Wrench
SER1212F16	SEL1212F16	12	12	12	16	80	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER1616H16	SEL1616H16	16	16	16	20	100	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER2020K16	SEL2020K16	20	20	20	25	125	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER2525M16	SEL2525M16	25	25	25	32	150	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER3225P16	SEL3225P16	32	25	32	32	170	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER3232P16	SEL3232P16	32	32	32	40	170	16ER	16EL	L60M3.5x12	T-15	EGM-16	MQ030080	T10
SER2020K22	SEL2020K22	20	20	20	27	125	22ER	22EL	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER2525M22	SEL2525M22	25	25	25	32	150	22ER	22EL	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER3225P22	SEL3225P22	32	25	32	32	170	22ER	22EL	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER3232P22	SEL3232P22	32	32	32	40	170	22ER	22EL	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER4040R22	SEL4040R22	40	40	40	50	200	22ER	22EL	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER2525M27	SEL2525M27	25	25	25	32	150	27ER	27EL	L60M6x16	T-20	EGM-27	MQ040080	S2.5
SER3232P27	SEL3232P27	32	32	32	32	170	27ER	27EL	L60M6x16	T-20	EGM-27	MQ040080	S2.5
SER4040R27	SEL4040R27	40	40	40	40	200	27ER	27EL	L60M6x16	T-20	EGM-27	MQ040080	S2.5
SER5050S27	SEL5050S27	50	50	50	50	250	27ER	27EL	L60M6x16	T-20	EGM-27	MQ040080	S2.5

订货示例: SER2020K16 1件 Ordering example: SER2020K16 1pc

👉 梯形螺纹专用刀垫 (外螺纹用)

Anvil for trapezoidal threading inserts (External)



订货型号 EGM-22T

Ordering code: EGM-22T


★ 梯形螺纹刀垫 EGM-22T 适用于 22ER6.0TR、22ER5.0TR、22ER4ACME、22ER4STACME

The anvil EGM-22T apply to 22ER6.0TR, 22ER5.0TR, 22ER4ACME, 22ER4STACME



★ 刀垫需单独订购

Anvil EGM-22T must be ordered separately

👉 外螺纹车刀杆（直头） Threading Tool Holders (b=F)



图片为右手刀具
Right Cutting Tools(see picture)



注意：右手刀具(R)配右手刀片(R)，左手刀具(L)配左手刀片(L)
Note:right tools match with right inserts;left tools match with left inserts.

型号Ordering Code		尺寸Dimensions(mm)					刀片Insert		刀片螺钉	扳手	刀垫	侧压螺钉	扳手
右刀Right Hand	左刀Left Hand	h	b	H	F	L	右Right	左Left	Insert Screw	Turn Key	Anvil	Anvil Screw	Hex Wrench
SER1010K11-A	SEL1010K11-A	10	10	10	10	125	11ER.	11EL.	L60M2.5x6	T-08	-	-	-
SER1212K11-A	SEL1212K11-A	12	12	12	12	125	11ER.	11EL.	L60M2.5x6	T-08	-	-	-
SER1616K11-A	SEL1616K11-A	16	16	16	16	125	11ER.	11EL.	L60M2.5x6	T-08	-	-	-
SER1616H16-A	SEL1616H16-A	16	16	16	16	100	16ER.	16EL.	L80M3.5x12	T-15	EGM-16	MQ030080	T10
SER2020K16-A	SEL2020K16-A	20	20	20	20	125	16ER.	16EL.	L80M3.5x12	T-15	EGM-16	MQ030080	T10
SER2525M16-A	SEL2525M16-A	25	25	25	25	150	16ER.	16EL.	L80M3.5x12	T-15	EGM-16	MQ030080	T10
SER3225P16-A	SEL3225P16-A	32	25	32	25	170	16ER.	16EL.	L80M3.5x12	T-15	EGM-16	MQ030080	T10
SER3232P16-A	SEL3232P16-A	32	32	32	32	170	16ER.	16EL.	L80M3.5x12	T-15	EGM-16	MQ030080	T10
SER2525M22-A	SEL2525M22-A	25	25	25	25	150	22ER.	22EL.	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER3225P22-A	SEL3225P22-A	32	25	32	25	170	22ER.	22EL.	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER3232P22-A	SEL3232P22-A	32	32	32	32	170	22ER.	22EL.	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5
SER4040R22-A	SEL4040R22-A	40	40	40	40	200	22ER.	22EL.	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5

订货示例：SER2020K16-A 1件 Ordering example: SER2020K16-A 1pc

👉 梯形螺纹专用刀垫（外螺纹用）

Anvil for trapezoidal threading inserts (External)



订货型号EGM-22T

Ordering code: EGM-22T


★ 梯形螺纹刀垫EGM-22T适用于22ER6.0TR、22ER5.0TR、22ER4ACME、22ER4STACME

The anvil EGM-22T apply to 22ER6.0TR, 22ER5.0TR, 22ER4ACME, 22ER4STACME

★ 刀垫需单独订购

Anvil EGM-22T must be ordered separately

内螺纹车刀杆 Threading Tool Holders



图片为右手刀具
Right Cutting Tools(see picture)

注意：右手刀具(R)配右手刀片(R)，左手刀具(L)配左手刀片(L)
Note:right tools match with right inserts;left tools match with left inserts.

型号 Ordering Code		尺寸 Dimensions(mm)							刀片 Insert		刀片螺钉	扳手	刀垫	侧压螺钉	扳手
右刀 Right Hand	左刀 Left Hand	d1	d	F	L	h	h1	Dmin	右 Right	左 Left	Insert Screw	Torx Key	Anvil	Anvil Screw	Hex Wrench
SNR001H08	SNL001H08	7	8	5	100	7.4	15	8.5	18NR..	18NL..	L60M2x6	T-08	-	-	-
SNR001H11	SNL001H11	10	10	7.4	100	9	12	12	11NR..	11NL..	L80M2.5x6	T-08	-	-	-
SNR0012K11	SNL0012K11	12	12	8.4	125	11	15	15	11NR..	11NL..	L80M2.5x6	T-08	-	-	-
SNR0013M11	SNL0013M11	13	16	8.9	150	15	25	15	11NR..	11NL..	L80M2.5x6	T-08	-	-	-
SNR0013M16	SNL0013M16	13	16	10.2	150	15	25	16	16NR..	16NL..	L80M3.5x8	T-15	-	-	-
SNR0016M16	SNL0016M16	15	16	11.7	150	15	25	19	16NR..	16NL..	L80M3.5x8	T-15	-	-	-
SNR0020Q16	SNL0020Q16	19	20	13.7	180	18	24	24	16NR..	16NL..	L80M3.5x12	T-15	NGM-16	MQ030080	T10
SNR0025R16	SNL0025R16	24	25	16.2	200	23	29	29	16NR..	16NL..	L80M3.5x12	T-15	NGM-16	MQ030080	T10
SNR0032S16	SNL0032S16	31	32	19.7	250	30	38	38	16NR..	16NL..	L80M3.5x12	T-15	NGM-16	MQ030080	T10
SNR0040T16	SNL0040T16	38	40	23.7	300	37	44	44	16NR..	16NL..	L80M3.5x12	T-15	NGM-16	MQ030080	T10
SNR0050U16	SNL0050U16	47	50	28.7	350	46	54	54	16NR..	16NL..	L80M3.5x12	T-15	NGM-16	MQ030080	T10
SNR0020Q22	SNL0020Q22	19	20	15.6	180	18	24	24	22NR..	22NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0025R22	SNL0025R22	24	25	18.1	200	23	29	29	22NR..	22NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0032S22	SNL0032S22	31	32	21.8	250	30	38	38	22NR..	22NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0040T22	SNL0040T22	38	40	25.8	300	37	46	46	22NR..	22NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0050U22	SNL0050U22	47	50	30.6	350	46	56	56	22NR..	22NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0032T27	SNL0032T27	30	32	21.8	250	30	65	37	27NR..	27NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5
SNR0040U27	SNL0040U27	38	40	26.6	300	38	70	46	27NR..	27NL..	L80M4.5x14	T-20	NGM-22	MQ040080	S2.5

订货示例：SNR0020Q16 1件 Ordering example: 'SNR0020Q16' 1pc

梯形螺纹专用刀垫（内螺纹用）

Anvil for trapezoidal threading inserts (Internal)



订货型号NGM-22T

Ordering code: NGM-22T

★ 梯形螺纹刀垫NGM-22T适用于22NR6.0TR、22NR5.0TR、22NR4ACME、22NR4STACME

The anvil NGM-22T apply to 22NR6.0TR, 22NR5.0TR, 22NR4ACME, 22NR4STACME


★ 刀垫需单独订购

Anvil NGM-22T must be ordered separately


外螺纹车刀杆(立装型) Threading Tool Holders (V-Style)



图片为右手刀具
Right Cutting Tools(see picture)



形式 I
Type I



注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手
Note:right tools match with right inserts;left tools match with left inserts.


型号Ordering Code		尺寸Dimensions(mm)							刀片Insert	刀片螺钉	扳手	压板	压板螺钉	扳手
右刀Right Hand	左刀Left Hand	h	b	H	F	L	Ht			Insert Screw	Torx Key	Clamp	Clamp Screw	Hex Wrench
SVER3232P27-6	SVEL3232P27-6	32	32	32	36	170	-			L60M6x16	T-20	HL1814	ML0620	L3
SVER3232P27-8	SVEL3232P27-8	32	32	32	36	170	-			L60M6x16	T-20	HL1814	ML0620	L3
SVER3232P27-10	SVEL3232P27-10	32	32	32	36	170	-	27VER**	27VEL**	L60M6x16	T-20	HL1814	ML0620	L3
SVER4040R27-6	SVEL4040R27-6	40	40	40	45	200	-			L60M6x16	T-20	HL1814	ML0620	L3
SVER4040R27-8	SVEL4040R27-8	40	40	40	45	200	-			L60M6x16	T-20	HL1814	ML0620	L3
SVER4040R27-10	SVEL4040R27-10	40	40	40	45	200	-			L60M6x16	T-20	DLM4	MS0625	L3

订货示例: SVER3232P27-6 1件 Ordering example: SVER3232P27-6 1pc


外螺纹车刀杆(MTHR型) Threading Tool Holders (V-Style)




图片为右手刀具
Right Cutting Tools(see picture)



形式 I
Type I



形式 II
Type II




注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手刀片(L)
Note:right tools match with right inserts;left tools match with left inserts.

型号Ordering Code		尺寸Dimensions(mm)							刀片Insert	形式	刀片螺钉	扳手	压板	压板螺钉	扳手
右刀Right Hand	左刀Left Hand	h	b	H	F	L	Ht	右Right	左Left	Type	Insert Screw	Torx Key	Clamp	Clamp Screw	Hex Wrench
MTHR1616H43	MTHL1616H43	16	16	16	20	100	3	MTTR43..	MTTL43..		L60M4.5x12	T-20	HL1814	ML0620	L3
MTHR2020K43	MTHL2020K43	20	20	20	25	125	-	MTTR43..	MTTL43..		L60M4.5x12	T-20	HL1814	ML0620	L3
MTHR2525M43	MTHL2525M43	25	25	25	32	150	-	MTTR43..	MTTL43..	I	L60M4.5x12	T-20	HL1814	ML0620	L3
MTHR3225P43	MTHL3225P43	32	25	32	32	170	-	MTTR43..	MTTL43..		L60M4.5x12	T-20	HL1814	ML0620	L3
MTHR3232P43	MTHL3232P43	32	32	32	40	170	-	MTTR43..	MTTL43..		L60M4.5x12	T-20	HL1814	ML0625	L3
WTHR2020K43	WTHL2020K43	20	20	20	25	125	-	MTTR43..	MTTL43..	II	L60M4.5x12	T-20	DLM4	MS0625	L3
WTHR2525M43	WTHL2525M43	25	25	25	32	150	-	MTTR43..	MTTL43..		L60M4.5x12	T-20	DLM4	MS0625	L3

订货示例: MTHR2020K43 1件 Ordering example: MTHR2020K43 1pc

内螺纹车刀杆(立装型) Threading Tool holders(V-Style)




图片为右手刀具
Right Cutting Tools(see picture)

型号Ordering Code	尺寸Dimensions(mm)						刀片Insert	刀片螺钉	扳手	压板	压板螺钉	扳手
右刀Right Hand	h	ll	d	F	L	Drin		Insert Screw	Torx Key	Clamp	Clamp Screw	Hex Wrench
SVNR0025R-T43	23	20	25	17.5	220	32	MTTL43.	L80M4.5x12	T-20	-	-	-
SVNR0032S-T43	30	30	30	22.5	250	41	MTTL43.	L80M4.5x12	T-20	-	-	-
SVNR0040S-T43	38	38	40	25	250	48	MTTL43.	L80M4.5x12	T-20	-	-	-
SVNR0032S27-6	30	32	32	22.5	250	41	27VNR **	L80M6x16	T-20	-	-	-
SVNR0040T27-6	38	40	40	28.5	300	50	27VNR **	L80M6x16	T-20	-	-	-
SVNR0040T27-8	38	40	40	28.5	300	50	27VNR **	L80M6x20	T-20	-	-	-
SVNR0040U27-10	38	40	40	28.5	350	50	27VNR **	L80M6x20	T-20	-	-	-
SVNR0050U27-8	48	50	50	33.5	350	60	27VNR **	L80M6x20	T-20	-	-	-
SVNR0050U27-10	48	50	50	33.5	400	60	27VNR **	L80M6x20	T-20	-	-	-

订货示例: SVNR3232P27-61件 Ordering example: SVNR3232P27-6 1pc

外螺纹刀杆(排刀型) Threading Tool Holders




图片为左手刀具
Right Cutting Tools(see picture)

型号Ordering Code	尺寸Dimensions(mm)						刀片Insert	刀片螺钉	扳手	刀垫	侧压螺钉	扳手
左刀杆 Left Hand	h	b	H	F	L	右Right		Insert Screw	Torx Key	Awil	Awil Screw	Hex Wrench
SEL1010K16-A90	10	10	10		125	11ER****	L80M2.5x8	T-06	-	-	-	-
SEL1212K11-A90	12	12	12		125	11ER****	L80M2.5x8	T-06	-	-	-	-
SEL1616K11-A90	16	16	16	20	125	11ER****	L80M2.5x8	T-06	-	-	-	-
SEL1616H16-A90	16	16	16	24	100	16ER****	L80M3.5x12	T-15	EGM-16	MQ030080	T10	
SEL2020K16-A90	20	20	20	28	125	16ER****	L80M3.5x12	T-15	EGM-16	MQ030080	T10	
SEL2525M16-A90	25	25	25		150	16ER****	L80M3.5x12	T-15	EGM-16	MQ030080	T10	
SEL3225P16-A90	32	25	32		170	16ER****	L80M3.5x12	T-15	EGM-16	MQ030080	T10	
SEL3232P16-A90	32	32	32		170	16ER****	L80M3.5x12	T-15	EGM-16	MQ030080	T10	
SEL2525M22-A90	25	25	25		150	22ER****	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5	
SEL3232P22-A90	32	32	32		170	22ER****	L80M4.5x14	T-20	EGM-22	MQ040080	S2.5	

订货示例: SEL2020K16-A 1件 Ordering example: SEL2020K16-A 1pc

 TT/TTX型螺纹刀杆 Threading Tool Holders




图片为右手刀具
Right Cutting Tools(see picture)

注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手刀片(L)
Note: right tools match with right inserts; left tools match with left inserts.

右刀杆	左刀杆	尺寸Dimensions(mm)						形式	刀片	刀片螺钉	扳手
Right Hand	Left Hand	h	b	L	L1	F	Type	Insert	Insert Screw	Torx Key	
KTTR1010K-16F	KTTL1010K-16F	10	10	125	20	10	I	TT ****	L60M4X8	T-15	
KTTR1212K-16F	KTTL1212K-16F	12	12	125	25	12			L60M4X8	T-15	
KTTR1616M-16F	KTTL1616M-16F	16	16	150	30	16			L60M4X8	T-15	
KTTR2020K-16	KTTL2020K-16	20	20	125	20	20	II	TTX ****	L60M4X8	T-15	
KTTR2525M-16	KTTL2525M-16	25	25	150	30	25			L60M4X8	T-15	

 TT型螺纹刀杆(排刀型) Threading Tool Holders






图片为左手刀具
Right Cutting Tools(see picture)

左刀杆	尺寸Dimensions(mm)						刀片	刀片螺钉	扳手
Left Hand	H	h	b	L	F	h	Insert	Insert Screw	Torx Key
KTTL1010H-16-A90	10	10	10	100	18	4.8	TT32R****	L60M4X8	T-15
KTTL1212H-16-A90	12	12	12	100	20	6.2		L60M4X8	T-15
KTTL1616K-16-A90	16	16	16	125	24	7		L60M4X8	T-15
KTTL2020K-16-A90	20	20	20	125	28	8.5	TTX32R****	L60M4X8	T-15




应用资料 Application Data

螺纹车削加工方案对照表
Comparison Table of Threading Cutting Machining



外螺纹——右旋螺纹 External-Right Hand




外螺纹——左旋螺纹 External-Left Hand



内螺纹——右旋螺纹 Internal-Right Hand



内螺纹——左旋螺纹 Internal-Left Hand



应用资料 Application Data

横向进刀角度

径向对中 (0°) 进刀齿侧 30° 进刀

优点:

刀片全部刀刃对螺纹牙形两侧同时切削, 防止刀刃崩刀。

缺点:

排屑困难。在切削高强度材料时容易崩刀。产生毛刺的可能性增大。由于在精车螺纹时整个切削刃全部切入, 容易引起振刀。



优点:

利用刀片侧刃进给切削, 使切屑容易排出切削区域。这就减少刀片后角形成毛刺的问题。为了避免由于刀刃后角摩擦而降低表面光洁度、磨刀或齿侧面过度的磨损, 横向进刀的角度应小于螺纹齿形角 $3^\circ \sim 5^\circ$ 。这是一种齿侧面修正类型。

缺点:

刀片可能有堵塞或摩擦的现象而使刃口崩刃。在切削软而粘性的金属, 如低碳钢、铝和不锈钢时, 会破坏表面光洁度。

较好的进刀方法

修正齿侧进刀

齿侧交替进刀



优点:

刀片同时切削螺纹牙形两侧, 防止像 0° 进刀时容易发生的崩刃。虽然也会形成排屑沟槽, 但是由于切削厚度不均匀有利于排屑, 犹如齿侧进刀。这是比较好的进刀方法, 尤其是使用有断屑槽的刀片时。

缺点:

和径向对进刀的缺点相同, 但是在降低切削力方面比较明显, 同时排屑的问题也得到解决。



优点:

由于两侧切削刃平均使用, 提高了刀片的寿命。
注: 采用这种进刀方法对一些机床可能需要特殊的编程技术。

缺点:

在传统机床上加工困难。

应用资料 Application Data

■ 机床编程

现代CNC控制的刀片在横向进刀角度 $28^{\circ} \sim 29.5^{\circ}$ 时性能最好,当然也可使用 $20^{\circ} \sim 30^{\circ}$ 的进刀角度。同时,重要的是要保持每一刀的最小切削深度为0.005英寸(0.13mm)。为了更稳定的控制切屑,建议进刀深度保持在0.005~0.010英寸(0.13~0.25 mm)之间的一个恒定的数值。

横向进刀角度

建议的横向进刀角度

$28^{\circ} \sim 29.5^{\circ}$




修正齿侧进刀

■ 最后一刀


某些CNC控制的机床要求最后一刀为 0° 的进刀速度。切削大部分碳钢和合金钢工件时,最后一刀的切削深度可以为0.005英寸(0.13 mm),以形成合格的表面光洁度。对某些材料可采用进刀深度为0.001~0.003英寸(0.02~0.25 mm)的来回式走刀以提高表面光洁度。

全牙形刀片



全牙形和泛螺距牙形比较

泛螺距刀片



-螺紋尺寸是按照已制定的螺紋标准确定。

-由于螺紋外径和底径同时加工,因此可以得到同心度的螺紋。

-由于最后一刀加工出准确的螺紋牙形,减少额外的操作或去毛刺操作,因此降低加工成本。

-同一刀片可以加工规定范围内的不同螺距的螺紋。

-对非标螺紋的加工有较大的柔性。

应用资料 Application Data

走刀次数和进刀量

走刀次数和进刀量对于螺纹切削工序具有决定性影响。在大多数现代机床上，应在螺纹切削周期中给定总螺纹深度和第一次或最后一次切深。


为了提高螺纹切削质量，应使用下面推荐的进刀量。对于多齿刀片，坚持使用进刀量推荐值是极为重要的。可作为初始值的推荐值。合适的走刀次数必须通过实验来决定。

- 为优化刀具寿命，工件直径应不超过螺纹的最大直径0.14mm
- 应避免进刀量低于0.05mm
- 对于奥氏体不锈钢，进刀量应避免低于0.08mm

两种进一步提高切削质量的方法

① 连续递减 - 可获得不变的切屑面积


这包括相对较大的初始值（0.2-0.35mm），并且与螺纹牙形的具体深度有关。此值会逐渐降低且以0.02-0.09mm的进给进行精加工。最后一次走刀可以是不进刀的空走刀，这是用于消除切削过程中的反弹。这种走刀方式是现代CNC机床上最常用的方法。



切屑面积 + 跳跃走刀

② 恒定的进刀量 - 可获得最佳的切屑控制和长的刀具寿命。

在新型机床上正变得越来越通用的加工方法。通过固定螺纹切削周期中的某一个参数，而使切屑厚度恒定，进而可以形成最佳切屑。初始值大约为0.18-0.12mm，实际值应由上一次走刀（至少应为0.08mm）的具体值确定。



恒定的走刀量

用于部分牙形刀片（V形 55° 和 60°）的切削参数

使用部分牙形刀片进行螺纹切削时，可使用推荐的走刀次数。但是，当使用具有小螺距的刀片时，每次走刀量不能超过最大推荐值。

注意！

当螺纹要求小公差时，最后一次走刀可先进刀（空走刀）。对于硬材料，则需要相应增加走刀次数。当螺纹切削加工淬硬材料（例如奥氏体不锈钢）时，进刀量应不得超过0.08mm。

应用资料 Application Data

进刀方式的选择

共有三种不同类型的进刀方式

- (1) 径向进刀
- (2) 改进式侧向进刀
- (3) 交替式进刀

■ 径向进刀


许多机床上最常用也只能使用的方法。可获得较新的屑和使刀片磨损更均匀。适合于小螺距。当用于螺距距时具有振动风险和较差的切屑控制。加工硬化材料（例如奥氏体不锈钢）的首选。



推荐使用表中给定的径向进给。

■ 改进式侧向进刀

对于60°牙形角的螺纹切削，轴向进刀量可以简单地按 $0.5 \times$ 径向进刀量来计算。对于55°的牙形角，则应以 $0.42 \times$ 径向进刀量进行计算。这便可得到一个比螺纹的牙形角小5°的进刀角。



■ 交替式进刀

主要用于切削大牙形时。此方法可获得均匀的刀片磨损和长刀具寿命。



需要在 CNC 机床上进行特定编程。

■ 如何控制切屑

当排屑通畅时，可获得良好的表面质量。当排屑不通畅和发生振动时，适合于粗牙螺纹和内螺纹。为避免表面粗糙度或由于后角的摩擦而导致过度的后刀面磨损，应使进刀角保持为3-5°，且比螺旋角要小。

实际上，由机床、工件材料、刀片槽型和螺距共同决定了进刀方式的选择。

应用资料 Application Data

■ 公式

按公式以连续递减方式计算每次走刀量

$$\Delta_{apx} = \frac{a_p}{\sqrt{nap-1}} \times \sqrt{\eta}$$

Δ_{ap} 轴向进给
 $\times$ 实际走刀 (从 1 到 nap 的系列值)
 a_p 螺纹总深度
 nap 走刀次数
 η 第一次走刀 = 0.3
 第二次走刀 = 1
 第三次及更多走刀 = X-1

示例:

工况:

外螺纹切削
 螺距: 1.5mm
 a_p : 0.94mm
 nap : 6次走刀

计算:

$$\Delta_{ap1} = \frac{0.94}{\sqrt{5}} \times \sqrt{0.3} = 0.23$$

$$\Delta_{ap2} = \frac{0.94}{\sqrt{5}} \times \sqrt{1} = 0.42$$

$$\Delta_{ap3} = \frac{0.94}{\sqrt{5}} \times \sqrt{2} = 0.59$$

$$\Delta_{ap4} = \frac{0.94}{\sqrt{5}} \times \sqrt{3} = 0.73$$

$$\Delta_{ap5} = \frac{0.94}{\sqrt{5}} \times \sqrt{4} = 0.84$$

$$\Delta_{ap6} = \frac{0.94}{\sqrt{5}} \times \sqrt{5} = 0.94$$

结果:

第一次走刀, 进刀量
=0.23mm

第二次走刀, 进刀量
0.42-0.23=0.19mm

第三次走刀, 进刀量
0.59-0.42=0.17mm





第四次走刀, 进刀量
0.73-0.59=0.14mm

第五次走刀, 进刀量
0.84-0.73=0.11mm

第六次走刀, 进刀量
0.94-0.84=0.1mm

应用资料 Application Data

疑难解析 FAQ

问题 Questions	原因 Reasons	措施 Solutions
 前刀面磨损过快 Quick-wearing flank	切削速度太高 Cutting speed is fast 横切深度太小 Transverse cutting depth is too small 材料不耐磨 Material is not wear-resistant 冷却液供给不足 Coolant is not enough for demand 错误的倾斜刀垫 The slope of anvil is wrong 错误的车削直径 The cutting diameter is wrong 刀片在中心线以上 The insert is above the center line	减小主轴转速 To decrease spindle speed 增大横切深度 To enlarge transverse cutting depth 更改侧向进给 To change the lateral feeding 应用涂层类 To make applicable coating 增加冷却液供给 To increase the supply of coolant 重新选择刀垫 To choose a new anvil 调整车削直径 To adjust cutting diameter 调整中心高度 To adjust center height
 刃边剥落 Cutting edge peeling off	切削速度太高 Cutting speed is fast 横切深度太小 Transverse cutting depth is too small 牌号选择错误 Coating grade is wrong 切削控制不良 Control of cutting is not good 冷却液供给不足 Coolant is not enough for demand 中心高度不正确 The center height is not correct	减小主轴转速 To decrease spindle speed 减小切削深度 To decrease cutting depth 应用涂层类牌号 To choose applicable coating grade 应用高韧性类牌号 To use high-toughness coating grade 更改侧向进给 To change the lateral feeding 增加冷却液供给 To increase the supply of coolant 调整中心高度 To adjust center height
 塑性变形 Plastic deformation	塑性变形切削区温度过高 The temperature in plastic deformation cutting area is too high 牌号选择错误 Coating grade is wrong 冷却液供给不足 Coolant is not enough for demand	减小主轴转速 To decrease spindle speed 减小切削深度 To decrease cutting depth 调整车削直径 To adjust cutting diameter 应用涂层类牌号 To choose applicable coating grade 应用硬性牌号 To use hardness coating grade 增加冷却液供给 To increase the supply of coolant
 切削瘤 Cutting tumor	切削温度过低 Cutting temperature is too low 牌号选择错误 Coating grade is wrong 冷却液供给不足 Coolant is not enough for demand	增加主轴转速 To increase spindle speed 增加切削深度 To increase cutting depth 应用涂层类牌号 To choose applicable coating grade 增加冷却液供给 To increase the supply of coolant
 刀片碎裂 Insert broken	切削刃温度过低 The temperature of cutting edge is too low 切深太大 Cutting depth is too large 牌号选择错误 Coating grade is wrong 错误的车削直径 Cutting diameter is wrong 中心高度不正确 Center height is wrong 横切深度太小 Transverse cutting depth is too small 错误的倾斜刀垫 The slope of anvil is wrong 刀具悬伸太长 The overhang of cutter is too long	增加主轴转速 To increase spindle speed 降低切深 To decrease cutting depth 增加进刀次数 To increase feed times 应用韧性牌号 To choose roughness coating grade 调整车削直径 To adjust cutting diameter 调整中心高度 To adjust center height 更改侧向进给 To change lateral feeding 重新选择刀垫 To choose a new anvil 减少刀具悬伸 To shorten overhang of cutter
 表面质量差 Bad quality of surface	错误的切削速度 Cutting speed is wrong 切削区温度过高 Temperature in cutting area is too high 切削控制不良 Control of cutting is not good 冷却液供给不足 Coolant is not enough for demand 错误的倾斜刀垫 The slope of anvil is wrong 刀具悬伸太长 The overhang of cutter is too long 中心高度不正确 The center height is not correct	增加主轴转速 To increase spindle speed 降低切削速度 To decrease cutting speed 减小切削深度 To decrease cutting depth 更改侧向进给 To change the lateral feeding 增加冷却液供给 To increase the supply of coolant 重新选择刀垫 To choose a new anvil 减少刀具悬伸 To shorten overhang of cutter 调整中心高度 To adjust center height
 切削控制不良 Bad control of cutting	切削区温度过高 Temperature in cutting area is too high 牌号选择错误 Coating grade is wrong 冷却液供给不足 Coolant is not enough for demand 错误的车削直径 Cutting diameter is wrong	减小主轴转速 To decrease spindle speed 减小切削深度 To decrease cutting speed 调整车削直径 To adjust cutting diameter 应用涂层类牌号 To choose applicable coating grade 调整车削直径 To adjust cutting diameter 应用 M 型刀片 To use M-style inserts 增加冷却液供给 To increase the supply of coolant 调整车削直径 To adjust cutting diameter

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

ISO公制细丝60°-外螺纹 60° ISO Metric Full Profile-External

螺距 (mm) Pitch	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
0.5	0.31	0.1	0.08	0.07	0.06												16ER0.50ISO
0.75	0.46	0.16	0.14	0.13	0.08												16ER0.75ISO
1.0	0.61	0.18	0.16	0.12	0.10	0.06											16ER1.00ISO
1.25	0.77	0.19	0.17	0.14	0.11	0.10	0.06										16ER1.25ISO
1.5	0.92	0.22	0.21	0.17	0.14	0.12	0.06										16ER1.50ISO
1.75	1.07	0.22	0.21	0.16	0.13	0.11	0.09	0.09	0.06								16ER1.75ISO
2.0	1.23	0.24	0.23	0.17	0.16	0.14	0.12	0.11	0.06								16ER2.00ISO
2.5	1.53	0.26	0.23	0.19	0.17	0.15	0.13	0.12	0.11	0.11	0.06						16ER2.50ISO
3.0	1.84	0.27	0.25	0.20	0.18	0.16	0.14	0.13	0.12	0.12	0.11	0.10	0.06				16ER3.00ISO
3.5	2.15	0.33	0.30	0.24	0.21	0.18	0.17	0.15	0.14	0.14	0.12	0.11	0.06				22ER3.50ISO
4.0	2.45	0.34	0.31	0.24	0.22	0.19	0.17	0.16	0.14	0.14	0.13	0.12	0.12	0.11	0.06		22ER4.00ISO
4.5	2.76	0.38	0.34	0.28	0.24	0.22	0.20	0.18	0.16	0.16	0.15	0.14	0.13	0.12	0.06		22ER4.50ISO
5.0	3.07	0.42	0.39	0.32	0.27	0.24	0.22	0.20	0.18	0.18	0.17	0.16	0.15	0.12	0.06		22ER5.00ISO

UN 细丝60°-外螺纹 UN 60° Full Profile-External

螺距 (牙数/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
32	0.49	0.17	0.15	0.11	0.09												16ER32UN
28	0.58	0.17	0.14	0.10	0.09	0.06											16ER28UN
24	0.65	0.18	0.16	0.14	0.11	0.06											16ER24UN
20	0.78	0.20	0.18	0.13	0.11	0.10	0.06										16ER20UN
18	0.87	0.22	0.20	0.15	0.13	0.11	0.06										16ER18UN
16	0.97	0.22	0.20	0.15	0.12	0.11	0.11	0.06									16ER16UN
14	1.11	0.23	0.21	0.16	0.13	0.11	0.11	0.10	0.06								16ER14UN
13	1.20	0.25	0.22	0.17	0.14	0.13	0.12	0.11	0.06								16ER13UN
12	1.30	0.26	0.23	0.18	0.16	0.14	0.13	0.12	0.06								16ER12UN
11	1.42	0.28	0.23	0.19	0.16	0.14	0.13	0.12	0.11	0.06							16ER11UN
10	1.56	0.29	0.24	0.19	0.16	0.14	0.13	0.12	0.11	0.06							16ER10UN
9	1.73	0.34	0.29	0.22	0.17	0.15	0.14	0.13	0.12	0.11	0.06						16ER9UN
8	1.95	0.35	0.30	0.24	0.19	0.16	0.15	0.14	0.13	0.12	0.11	0.06					16ER8UN
7	2.22	0.37	0.33	0.26	0.24	0.20	0.17	0.16	0.15	0.14	0.12	0.06					22ER7UN
6	2.60	0.42	0.35	0.29	0.25	0.21	0.16	0.17	0.16	0.15	0.15	0.12	0.11	0.06			22ER6UN
5	3.12	0.43	0.36	0.31	0.27	0.24	0.22	0.20	0.19	0.19	0.19	0.17	0.15	0.12	0.06		22ER5UN

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

惠氏螺纹 55°-外螺纹 Whitworth 55° Full Profile-External

螺距 (牙距英寸) Pitch (Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全牙廓制型 Full Profile Cutting Style	
28	0.58	0.17	0.14	0.11	0.10	0.08											16ER28W	
26	0.63	0.18	0.15	0.13	0.11	0.08											16ER26W	
20	0.81	0.20	0.16	0.14	0.12	0.11	0.06										16ER20W	
19	0.86	0.21	0.19	0.15	0.13	0.12	0.06										16ER19W	
18	0.90	0.25	0.19	0.15	0.13	0.12	0.06										16ER18W	
16	1.02	0.21	0.16	0.15	0.13	0.11	0.06	0.09	0.06								16ER16W	
14	1.16	0.23	0.21	0.17	0.14	0.12	0.12	0.11	0.06								16ER14W	
12	1.36	0.27	0.25	0.20	0.16	0.15	0.14	0.13	0.06								16ER12W	
11	1.46	0.27	0.24	0.20	0.17	0.15	0.14	0.13	0.12	0.06							16ER11W	
10	1.63	0.27	0.25	0.20	0.17	0.16	0.15	0.13	0.13	0.12	0.06						16ER10W	
9	1.81	0.28	0.26	0.21	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.06					16ER9W	
8	2.03	0.30	0.27	0.22	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.12	0.06				16ER8W	
7	2.32	0.34	0.32	0.26	0.22	0.20	0.18	0.17	0.16	0.15	0.14	0.12	0.06				22ER7W	
6	2.71	0.36	0.33	0.27	0.23	0.21	0.20	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.06		22ER6W	
5	3.25	0.42	0.40	0.35	0.29	0.26	0.24	0.22	0.20	0.19	0.18	0.17	0.15	0.12	0.06		22ER5W	

英制BSPT55°-外螺纹 BSPT55°-External

螺距 (牙距英寸) Pitch (Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全牙廓制型 Full Profile Cutting Style	
28	0.58	0.17	0.14	0.11	0.10	0.06											16ER28BSPT	
19	0.86	0.22	0.19	0.15	0.12	0.12	0.06										16ER19BSPT	
14	1.16	0.24	0.20	0.17	0.14	0.12	0.12	0.11	0.06								16ER14BSPT	
11	1.46	0.25	0.23	0.21	0.18	0.16	0.14	0.13	0.12	0.06							16ER11BSPT	

圆形DIN405 30°-外螺纹 Round DIN405 30°-External

螺距 (牙距英寸) Pitch (Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全牙廓制型 Full Profile Cutting Style	
10	1.27	0.02	0.21	0.20	0.19	0.16	0.12	0.10	0.06								16ER10RD	
8	1.59	0.23	0.21	0.20	0.19	0.18	0.16	0.14	0.12	0.10	0.06						16ER8RD	
6	2.12	0.26	0.25	0.24	0.22	0.21	0.19	0.17	0.16	0.14	0.12	0.10	0.06				16ER6RD	
4	3.16	0.34	0.33	0.32	0.30	0.18	0.26	0.24	0.22	0.20	0.18	0.17	0.15	0.12	0.06		22ER4RD	

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

ISO梯形90°-外螺纹 ISO TR-90°-External

螺距 (mm)	总切削深度	加工步数 Cutting Steps															适用刀片 Applicable Inserts
Pitch	Cutting Depth	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style
1.5	0.90	0.23	0.21	0.19	0.13	0.11	0.06										16ER1.5TR
2	1.25	0.29	0.26	0.21	0.17	0.14	0.12	0.06									16ER2.0TR
3	1.75	0.32	0.31	0.24	0.19	0.18	0.17	0.15	0.13	0.06							16ER3.0TR
4	2.25	0.33	0.32	0.24	0.22	0.21	0.17	0.16	0.15	0.14	0.13	0.12	0.16				22ER4.0TR
5	2.75	0.35	0.32	0.26	0.24	0.22	0.21	0.19	0.19	0.17	0.15	0.14	0.13	0.12	0.06		22ER5.0TR

ACME梯形29°-外螺纹 ACME 29°-External

螺距 (牙距英寸)	总切削深度	加工步数 Cutting Steps															适用刀片 Applicable Inserts
Pitch (Tooth/Inch)	Cutting Depth	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style
12	1.19	0.27	0.23	0.20	0.17	0.14	0.12	0.06	0.06								16ER12ACME
10	1.52	0.29	0.25	0.21	0.18	0.16	0.14	0.12	0.11	0.06							16ER10ACME
8	1.84	0.30	0.26	0.22	0.19	0.16	0.15	0.14	0.13	0.12	0.11	0.06					16ER8ACME
6	2.37	0.34	0.30	0.27	0.24	0.21	0.19	0.16	0.14	0.12	0.12	0.11	0.11	0.06			22ER6ACME
5	2.79	0.36	0.33	0.30	0.26	0.23	0.20	0.18	0.17	0.16	0.15	0.14	0.13	0.12	0.06		22ER5ACME

UNJ60° 美制航空航天螺纹-外螺纹 UNJ 60°-External

螺距 (牙距英寸)	总切削深度	加工步数 Cutting Steps															适用刀片 Applicable Inserts
Pitch (Tooth/Inch)	Cutting Depth	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style
32	0.46	0.16	0.14	0.10	0.06												16ER32UNJ
28	0.52	0.16	0.12	0.09	0.09	0.06											16ER28UNJ
24	0.61	0.17	0.14	0.14	0.14	0.09											16ER24UNJ
20	0.73	0.19	0.16	0.13	0.13	0.09	0.06										16ER20UNJ
18	0.81	0.23	0.18	0.14	0.14	0.10	0.06										16ER18UNJ
16	0.92	0.26	0.21	0.14	0.14	0.10	0.06										16ER16UNJ
14	1.06	0.26	0.23	0.17	0.17	0.11	0.10	0.06									16ER14UNJ
12	1.22	0.28	0.27	0.20	0.20	0.13	0.11	0.06									16ER12UNJ
10	1.47	0.30	0.29	0.21	0.21	0.13	0.12	0.11	0.10	0.06							16ER10UNJ
8	1.83	0.31	0.30	0.23	0.23	0.15	0.14	0.13	0.12	0.11	0.10	0.06					16ER8UNJ

API锯齿形-外螺纹 API Buttress-External

螺距 (牙距英寸)	总切削深度	加工步数 Cutting Steps															适用刀片 Applicable Inserts
Pitch (Tooth/Inch)	Cutting Depth	1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style
5	1.55	0.25	0.23	0.17	0.15	0.13	0.12	0.12	0.11	0.11	0.10	0.06					22ER5APBU

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

API圆形90°-外螺纹 API Round 90° -External

螺距 (牙数/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
10	1.41	0.25	0.23	0.18	0.14	0.12	0.12	0.12	0.11	0.10	0.08						16ER10APRD
8	1.81	0.25	0.24	0.19	0.16	0.14	0.14	0.13	0.13	0.13	0.13	0.11	0.08				16ER8APRD

美制NPT90°-外螺纹 NPT90° -External

螺距 (牙数/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
27	0.86	0.15	0.13	0.12	0.11	0.09	0.08										16ER27NPT
18	1.01	0.20	0.16	0.14	0.13	0.12	0.11	0.09	0.08								16ER18NPT
14	1.33	0.23	0.19	0.18	0.14	0.13	0.12	0.11	0.10	0.08	0.06						16ER14NPT
11.5	1.64	0.24	0.19	0.17	0.15	0.15	0.13	0.13	0.12	0.11	0.10	0.09	0.06				16ER11.5NPT
8	2.42	0.30	0.28	0.23	0.20	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.11	0.11	0.10	0.08	16ER8NPT

美制NPTF90°-外螺纹 NPTF90° -External

螺距 (牙数/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
27	0.84	0.16	0.14	0.11	0.09	0.08	0.06										16ER27NPTF
18	1.00	0.19	0.16	0.14	0.13	0.12	0.11	0.09	0.08								16ER18NPTF
14	1.35	0.23	0.21	0.21	0.14	0.13	0.12	0.11	0.10	0.08	0.06						16ER14NPTF
11.5	1.63	0.24	0.23	0.23	0.15	0.13	0.11	0.11	0.11	0.10	0.10	0.10	0.06				16ER11.5NPTF
8	2.38	0.32	0.27	0.27	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.12	0.11	0.11	0.10	0.08	16ER8NPTF

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

ISO公制螺纹60° -内螺纹 60° ISO Metric Full Profile-Internal

螺距 (mm) Pitch	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style	
0.5	0.29	0.09	0.07	0.07	0.06												11NR0.50ISO	16NR0.50ISO
0.75	0.43	0.15	0.13	0.08	0.06												11NR0.75ISO	16NR0.75ISO
1.0	0.58	0.17	0.15	0.11	0.08	0.06											11NR1.00ISO	16NR1.00ISO
1.25	0.72	0.18	0.16	0.12	0.11	0.09	0.06										11NR1.25ISO	16NR1.25ISO
1.5	0.87	0.21	0.20	0.16	0.13	0.11	0.06										11NR1.50ISO	16NR1.50ISO
1.75	1.01	0.21	0.20	0.15	0.12	0.10	0.09	0.08	0.06								11NR1.75ISO	16NR1.75ISO
2.0	1.15	0.24	0.22	0.16	0.14	0.12	0.10	0.09	0.06								11NR2.00ISO	16NR2.00ISO
2.5	1.44	0.26	0.24	0.21	0.15	0.13	0.12	0.10	0.09	0.09	0.06							16NR2.50ISO
3.0	1.73	0.28	0.25	0.22	0.17	0.14	0.13	0.12	0.11	0.10	0.09	0.08	0.06					16NR3.00ISO
3.5	2.02	0.32	0.30	0.23	0.19	0.17	0.15	0.14	0.13	0.12	0.11	0.10	0.06					22NR3.50ISO
4.0	2.31	0.33	0.31	0.24	0.22	0.18	0.15	0.14	0.13	0.12	0.12	0.11	0.10	0.10	0.06			22NR4.00ISO
4.5	2.60	0.36	0.33	0.26	0.24	0.21	0.19	0.16	0.15	0.14	0.13	0.12	0.12	0.11	0.06			22NR4.50ISO
5.0	2.89	0.41	0.38	0.32	0.27	0.24	0.21	0.18	0.16	0.15	0.14	0.13	0.13	0.12	0.06			22NR5.00ISO

UN 螺纹60° -内螺纹 UN 60° Full Profile-Internal

螺距 (牙数/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style	
32	0.46	0.16	0.14	0.10	0.08												11NR32UN	16NR32UN
28	0.52	0.16	0.13	0.09	0.08	0.06											11NR28UN	16NR28UN
24	0.61	0.17	0.15	0.13	0.10	0.06											11NR24UN	16NR24UN
20	0.73	0.16	0.15	0.13	0.11	0.10	0.06										11NR20UN	16NR20UN
18	0.81	0.20	0.18	0.14	0.12	0.11	0.06										11NR18UN	16NR18UN
16	0.92	0.20	0.18	0.15	0.12	0.11	0.10	0.06									11NR16UN	16NR16UN
14	1.05	0.21	0.18	0.15	0.13	0.11	0.11	0.10	0.06								11NR14UN	16NR14UN
13	1.13	0.22	0.19	0.16	0.14	0.13	0.12	0.11	0.06									16NR13UN
12	1.22	0.24	0.22	0.16	0.16	0.13	0.12	0.11	0.06									16NR12UN
11	1.33	0.24	0.22	0.20	0.15	0.12	0.12	0.11	0.11	0.06								16NR11UN
10	1.47	0.25	0.22	0.21	0.14	0.13	0.12	0.12	0.11	0.11	0.06							16NR10UN
9	1.63	0.31	0.23	0.21	0.17	0.15	0.14	0.13	0.12	0.11	0.06							16NR9UN
8	1.83	0.31	0.26	0.21	0.18	0.15	0.15	0.14	0.13	0.12	0.11	0.06						16NR8UN
7	2.09	0.36	0.30	0.24	0.21	0.18	0.17	0.16	0.15	0.14	0.12	0.06						22NR7UN
6	2.44	0.40	0.33	0.25	0.23	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.11	0.06				22NR6UN
5	2.93	0.41	0.35	0.31	0.26	0.23	0.21	0.20	0.19	0.17	0.15	0.14	0.13	0.12	0.06			22NR5UN

应用资料 Application Data

螺纹刀片进刀量推荐值

Treading Insert Cutting Times within Definite Depth for Reference

惠氏螺纹55°-内螺纹 Whitworth 55° Full Profile-Internal

螺距 (牙距/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style	
28	0.58	0.17	0.14	0.11	0.10	0.06												16NR28W
26	0.63	0.18	0.15	0.13	0.11	0.06												16NR26W
20	0.81	0.20	0.18	0.14	0.12	0.11	0.08											16NR20W
19	0.86	0.21	0.19	0.15	0.13	0.12	0.08										11NR19W	16NR19W
18	0.90	0.25	0.19	0.15	0.13	0.12	0.08											16NR18W
16	1.02	0.21	0.18	0.15	0.13	0.11	0.09	0.08	0.06									16NR16W
14	1.16	0.23	0.21	0.17	0.14	0.12	0.12	0.11	0.06								11NR14W	16NR14W
12	1.36	0.27	0.25	0.20	0.18	0.15	0.14	0.13	0.06									16NR12W
11	1.48	0.27	0.24	0.20	0.17	0.15	0.14	0.13	0.12	0.06								16NR11W
10	1.63	0.27	0.25	0.20	0.17	0.15	0.15	0.13	0.13	0.12	0.06							16NR10W
9	1.81	0.28	0.26	0.21	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.06						16NR9W
8	2.03	0.30	0.27	0.22	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.12	0.06					16NR8W
7	2.32	0.34	0.32	0.26	0.22	0.20	0.18	0.17	0.16	0.15	0.14	0.12	0.06					22NR7W
6	2.71	0.35	0.33	0.27	0.23	0.21	0.20	0.19	0.17	0.16	0.15	0.14	0.13	0.12	0.06			22NR6W
5	3.25	0.42	0.40	0.35	0.29	0.26	0.24	0.22	0.20	0.19	0.18	0.17	0.15	0.12	0.06			22NR5W

英制BSP75°-内螺纹 BSP75°-Internal

螺距 (牙距/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style	
19	0.86	0.22	0.19	0.15	0.12	0.12	0.06										11NR19BSP	16NR19BSP
14	1.16	0.24	0.20	0.17	0.14	0.12	0.12	0.11	0.06								11NR14BSP	16NR14BSP
11	1.48	0.25	0.23	0.21	0.18	0.16	0.14	0.13	0.12	0.06								16NR11BSP

圆形DIN405 30°-内螺纹 Round DIN405 30°-Internal

螺距 (牙距/英寸) Pitch (Tooth/Inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable Inserts	
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	全面磨削型 Full Profile Cutting Style	
10	1.27	0.02	0.21	0.20	0.19	0.18	0.12	0.10	0.06								16NR10RD	
8	1.58	0.23	0.21	0.20	0.19	0.18	0.16	0.14	0.12	0.10	0.06						16NR8RD	
6	2.12	0.26	0.25	0.24	0.22	0.21	0.19	0.17	0.16	0.14	0.12	0.10	0.06				16NR6RD	
4	3.18	0.34	0.33	0.32	0.30	0.18	0.26	0.24	0.22	0.20	0.19	0.17	0.15	0.12	0.06		22NR4RD	

应用资料 Application Data

螺纹刀片进刀量推荐值

Threading Insert Cutting Times within Definite Depth for Reference

ISO梯形30°-内螺纹 ISO TR-30°-Internal

螺距 (mm) Pitch	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable inserts 全齿廓削型 Full Profile Cutting Style
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
1.5	0.90	0.23	0.21	0.16	0.13	0.11	0.08										16NR1.5TR
2	1.25	0.29	0.26	0.21	0.17	0.14	0.12	0.08									16NR2.0TR
3	1.75	0.32	0.31	0.24	0.19	0.16	0.17	0.15	0.13	0.08							16NR3.0TR
4	2.25	0.33	0.32	0.24	0.22	0.21	0.17	0.16	0.15	0.14	0.13	0.12	0.10				22NR4.0TR
5	2.75	0.35	0.32	0.26	0.24	0.22	0.21	0.19	0.19	0.17	0.15	0.14	0.13	0.12	0.08		22NR5.0TR

ACME梯形29°-内螺纹 ACME 29°-Internal

螺距 (牙数/英寸) Pitch(Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable inserts 全齿廓削型 Full Profile Cutting Style
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
12	1.19	0.27	0.23	0.20	0.17	0.14	0.12	0.08	0.06								16NR12ACME
10	1.52	0.29	0.25	0.21	0.18	0.16	0.14	0.12	0.11	0.08							16NR10ACME
8	1.84	0.30	0.26	0.22	0.19	0.16	0.15	0.14	0.13	0.12	0.11	0.08					16NR8ACME
6	2.37	0.34	0.30	0.27	0.24	0.21	0.19	0.16	0.14	0.12	0.12	0.11	0.11	0.08			22NR6ACME
5	2.79	0.36	0.33	0.30	0.26	0.23	0.20	0.18	0.17	0.16	0.15	0.14	0.13	0.12	0.08		22NR5ACME

API锯齿形-内螺纹 API Buttress-Internal

螺距 (牙数/英寸) Pitch(Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable inserts 全齿廓削型 Full Profile Cutting Style
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
5	1.55	0.25	0.23	0.17	0.15	0.13	0.12	0.12	0.11	0.11	0.10	0.08					22NR5APBU

API圆角60°-内螺纹 API Round 60°-Internal

螺距 (牙数/英寸) Pitch(Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable inserts 全齿廓削型 Full Profile Cutting Style
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
10	1.41	0.25	0.23	0.16	0.14	0.12	0.12	0.12	0.11	0.10	0.08						16NR10APRD
8	1.61	0.25	0.24	0.19	0.16	0.14	0.14	0.13	0.13	0.13	0.13	0.11	0.08				16NR8APRD

美制NPT60°-内螺纹 NPT 60°-Internal

螺距 (牙数/英寸) Pitch(Tooth/inch)	总切削深度 Cutting Depth	加工步数 Cutting Steps															适用刀片 Applicable inserts 全齿廓削型 Full Profile Cutting Style
		1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	
27	0.68	0.15	0.13	0.12	0.11	0.09	0.08										16NR27NPT
18	1.01	0.20	0.16	0.14	0.13	0.12	0.11	0.08	0.06								16NR18NPT
14	1.33	0.23	0.19	0.16	0.14	0.13	0.12	0.11	0.10	0.09	0.06						16NR14NPT
11.5	1.64	0.24	0.19	0.17	0.15	0.15	0.13	0.13	0.12	0.11	0.10	0.09	0.06				16NR11.5NPT
8	2.42	0.33	0.28	0.23	0.20	0.18	0.16	0.15	0.14	0.13	0.12	0.12	0.11	0.11	0.10	0.06	16NR8NPT


螺纹识别表 Thread Identification Table

特征代号 Code	名称 Description	牙型 (牙型角或牙型角、锥度) Thread Angle	标记示例 Example of marking	适用刀片 Insert	国家、地区及标准编号 Example of marking
Acme	爱克司螺纹	牙型角29°；锥度为0	1 ³ / ₄ -4Acme-2G	22ER4ACME	澳大利亚 AS B202-1992
					英国 BS1104:1957
					新西兰 NZS 1342:1958
					美国 ASME B1.5-1997
STUB Acme	短牙爱克司螺纹	牙型角29°；锥度为0	0.500-16STUB; ACME	16ER16STACME	美国 ASME B1.5-1977
API Sucker Rod	美国石油学会 抽油杆螺纹	牙型角60°；锥度为0	3/4 API Sucker Rod	16ER10API RD	罗马尼亚 STAS 329-80
					美国 API Spec 11B-1988
B.S.F.	惠氏细牙螺纹	牙型角55°；锥度为0	1/2h-16 B.S.F.	16ER16W	澳大利亚 AS 3501-1987
					英国 BS84-1956
					马来西亚 MS 218:1974
B.S.W.	惠氏粗牙螺纹	牙型角55°；锥度为0	1/4h-20 B.S.W.	16ER20W	澳大利亚 AS 3501-1987
					英国 BS84-1956
					马来西亚 MS 218:1974
Butt	锯齿螺纹	牙型角为7°、45°； 锥度为0	2.5-8 Butt-2A	16ER8ABUT	美国 ANSI B1.9-1973
Buttress			2.0 BS Buttress; Thread 8 psi medium class		澳大利亚 AS B192-1981
					英国 BS 1657:1980
					新西兰 NZS 955:1951
G	55°非密封 管螺纹	牙型角55°；锥度为0	G 1 ¹ / ₂ ; G 1 ¹ / ₂ a; G 1 ¹ / ₂ b	16ER11W	国际 ISO 228-1:2000
					中国 GB/T 7307-2001
					德国 DIN ISO 228-1:2001
					法国 pr NF EN ISO 228-1:2002
					英国 BS 2779:1986
					俄罗斯 GOST 6357-81
					日本 JIS B 0203-1996
					澳大利亚 AS 1722:Part 2-1975
					巴西 NBR 6414/83
					意大利 UNI ISO 228-1
NPT	一般密封圆 锥管螺纹	牙型角60°；锥度为1:16	NPT 3/8; 3/8-18 NPT	16ER18NPT	中国 GB/T 12716-2002
					厄瓜多尔 NEN 117
					法国 NF E03-801, NF E29-684
					俄罗斯 GOST 6111
					美国 ASME B1.20.1-1983
NPTF	干密封圆锥 管螺纹	牙型角60°；锥度为1:16	1/8-27 NPTF-1	11ER27NPTF	瑞典 SMS1704, SMS1706, SMS1707
Tr	ISO米制 梯形螺纹	牙型角30°；锥度为0	Tr 40x7	27ER7, CTR	美国 ANSI B1.20.3-1978
					国际 ISO 2901, ISO 2903-1983, ISO 2902, ISO 2904-1977
					中国 GB/T 5796.1/5796.4-2005, BT/T 12399-2008
					德国 DIN 103 T1-T6, DIN 283 T1-T2, DIN 8341
					法国 NF ISO 2901-2903-1987
					英国 NF B55348-1975
					日本 JIS B 0216-0218
					俄罗斯 GOST 9404, GOST 8602, GOST 3475, GOST 2478, GOST 2479-1981
					意大利 UNI ISO 2901-2904
					荷兰 NEN 2780-2784
					印度 IS 7500 (Part I - IV)-1973
					芬兰 SFS 4409-4502

螺纹识别表 Thread Identification Table

特征代号 Code	名称 Description	牙型 (牙型角或牙数, 锥度) Thread Angle	标记示例 Example of marking	适用刀片 Insert	国家、地区及标准编号 Example of marking
UN	统一细牙	牙型角60° ; 锥度为0	2 1/2-16 UN-2B	16ER16UN	国际ISO 68-2:1996, ISO 263:1973, ISO 725:1976, ISO 5864:1989
					澳大利亚AS B133; Part1~2
					中国GB/T 20667-20670-2006
					丹麦DS/ISO 263:08/ISO 725
					英国BS ISO 68-2:1996, BS 1580-1-1580-3
					新西兰 NZS 1227
					瑞典 SMS 1713
					美国 ASME B1.1-1989
W	惠氏细牙	牙型角55° ; 锥度为0	W 3/16	16ER24W	阿根廷 IRAM 5030, IRAM 5035
					瑞士 SNV 24490, SNV 219504
					德国 DIN 477 T1, DIN 4666, DIN 49301
					意大利 UNI 2706-2709
					瑞典 SMS 3 B
Rc	55° 密封圆锥内螺纹	牙型角55° ; 锥度1:16	Rc 1 1/4	16NR11BSPT	国际ISO 7-1:1994
					中国 GB/T 7306.2-2000
					法国 NF E03-004
					英国 BS 21:1966
					印度 IS:554-1975
					意大利 UNI ISO 7-1
					日本 JIS B 0203-1999
					俄罗斯 GOST 6211-81
					瑞典 SS ISO 7-1
API	石油钻杆接头螺纹	牙型角60° 锥度1:4, 1:6, 1:8	API NC26(2-3/8 F) API IF TUB API 3-1/2 FH API 4-1/2 REG	22ER4API***	中国GB/T 9253, 1-1999
					美国API Spec7-1985
SAGE	锯齿螺纹	牙型角5° /30° 锥度为0	84036-6C	27WR6, OSAGE	中国GB/T 9253, 1-1999 美国API Spec7-1985
RD	圆弧螺纹	牙型角30° 锥度为0	RD40-1/6	16NR6, CRD	德国 DIN 405
Pg	铜导管螺纹	牙型角30° 锥度为0	Pg16	16NR16Pg	德国 DIN 40430

SSL





目录 Contents

sSL

螺纹铣削刀具

标准型螺纹铣刀 Threading Milling Tools	67~72
TM型螺纹铣刀 TM-Style Threading Milling Tools	73~84
深孔螺纹铣刀 Threading Milling Tools for Deep Hole	85~88
旋风螺纹铣刀 Thread Whirling Tools	89
SMT单刃螺纹铣刀 SMT Threading Milling Toolholders	90
整体硬质合金铣刀 Carbide Thread milling tool	91~94
应用资料 Application Data	95~98

👉 ISO标准型螺纹刀片 ISO





双面使用
Two cutting edge

H		6	7.5	12	16	20
T		2.38	3.1	4.7	5.5	6.3
加工螺距 Pitch		尺寸 Dimensions (mm)-A				
mm		12	14	21	30	40
0.5	外 Ext.					
0.5	内 Int.	*12N0.5 ISO	14N0.5 ISO			
0.75	外 Ext.		14E0.75 ISO			
0.75	内 Int.	*12N0.75 ISO	14N0.75 ISO			
1.0	外 Ext.		14E1.0 ISO	21E1.0 ISO		
1.0	内 Int.	*12N1.0 ISO	14N1.0 ISO	21N1.0 ISO		
1.25	外 Ext.		14E1.25 ISO			
1.25	内 Int.	*12N1.25 ISO	14N1.25 ISO			
1.5	外 Ext.		14E1.5 ISO	21E1.5 ISO	30E1.5 ISO	40E1.5 ISO
1.5	内 Int.	*12N1.5 ISO	14N1.5 ISO	21N1.5 ISO	30N1.5 ISO	40N1.5 ISO
1.75	外 Ext.		14E1.75 ISO			
1.75	内 Int.		14N1.75 ISO	21N1.75 ISO		
2.0	外 Ext.		14E2.0 ISO	21E2.0 ISO	30E2.0 ISO	40E2.0 ISO
2.0	内 Int.		14N2.0 ISO	21N2.0 ISO	30N2.0 ISO	40N2.0 ISO
2.5	外 Ext.		14E2.5 ISO	21E2.5 ISO		
2.5	内 Int.		14N2.5 ISO	21N2.5 ISO		
3.0	外 Ext.			21E3.0 ISO	30E3.0 ISO	40E3.0 ISO
3.0	内 Int.			21N3.0 ISO	30N3.0 ISO	40N3.0 ISO
3.5	外 Ext.				30E3.5 ISO	
3.5	内 Int.			21N3.5 ISO	30N3.5 ISO	40N3.5 ISO
4.0	外 Ext.				30E4.0 ISO	40E4.0 ISO
4.0	内 Int.				30N4.0 ISO	40N4.0 ISO
4.5	外 Ext.					
4.5	内 Int.				30N4.5 ISO	40N4.5 ISO
5.0	外 Ext.					40E5.0 ISO
5.0	内 Int.				30N5.0 ISO	40N5.0 ISO
5.5	外 Ext.					
5.5	内 Int.					40N5.5 ISO
6.0	外 Ext.					40E6.0 ISO
6.0	内 Int.					

订货示例: 14E2.5 ISO BR215 10片 Ordering example: 14E2.5 ISO BR215 10pcs

*代表刀片只能单面使用 * Inserts with a single cutting edge

👉 UN-60° 美制统一标准性螺纹刀片 UN,UNC,UNF,UNEF,UNS





双面使用
Two cutting edge

11	6	7.5	12	16	20
T	2.38	3.1	4.7	5.5	6.3
加工螺距 Pitch 尺寸 Dimensions (mm)=A					
tpi	12	14	21	30	40
32 外Ext.		14 E 32 UN			
32 内Int.	*12N32 UN	14 N 32 UN			
28 外Ext.		14 E 28 UN			
28 内Int.	*12N28 UN	14 N 28 UN			
27 外Ext.					
27 内Int.		14 N 27 UN			
24 外Ext.		14 E 24 UN	21 E 24 UN		
24 内Int.	*12N24 UN	14 N 24 UN	21 N 24 UN		
20 外Ext.		14 E 20 UN	21 E 20 UN	30 E 20 UN	
20 内Int.	*12N20 UN	14 N 20 UN	21 N 20 UN	30 N 20 UN	
18 外Ext.		14 E 18 UN	21 E 18 UN	30 E 18 UN	
18 内Int.	*12N18 UN	14 N 18 UN	21 N 18 UN	30 N 18 UN	
16 外Ext.		14 E 16 UN	21 E 16 UN	30 E 16 UN	40 E 16 UN
16 内Int.	*12N16 UN	14 N 16 UN	21 N 16 UN	30 N 16 UN	40 N 16 UN
14 外Ext.		14 E 14 UN	21 E 14 UN	30 E 14 UN	40 E 14 UN
14 内Int.		14 N 14 UN	21 N 14 UN	30 N 14 UN	40 N 14 UN
12 外Ext.		14 E 12 UN	21 E 12 UN	30 E 12 UN	40 E 12 UN
12 内Int.		14 N 12 UN	21 N 12 UN	30 N 12 UN	40 N 12 UN
11 外Ext.					
11 内Int.		14 N 11 UN			
10 外Ext.			21 E 10 UN	30 E 10 UN	40 E 10 UN
10 内Int.		14 N 10 UN	21 N 10 UN	30 N 10 UN	40 N 10 UN
8 外Ext.				30 E 8 UN	40 E 8 UN
8 内Int.			21 N 8 UN	30 N 8 UN	40 N 8 UN
7 外Ext.					
7 内Int.			21 N 7 UN		
6 外Ext.				30 E 6 UN	40 E 6 UN
6 内Int.				30 N 6 UN	40 N 6 UN
5 外Ext.					
5 内Int.				30 N 5 UN	
4.5 外Ext.					
4.5 内Int.					40 N 4.5UN
4 外Ext.					
4 内Int.					40 N 4 UN

订货示例: 14E10UN BR215 10片 Ordering sample: 14E10UN BR215 10pcs

*代表刀片只能单面使用 * Inserts with a single cutting edge

👉 W-55° 英国惠氏螺纹刀片 BSW,BSF,BSP






双面使用
Two cutting edge

H	6	7.5	12	16	20
T	2.35	3.1	4.7	5.5	6.3
加工螺距	尺寸 Dimensions (mm)=A				
tpi	12	14	21	30	40
24		14-24 W			
20		14-20 W	21-20 W		
19	• 12-19 W	14-19 W	21-19 W		
16		14-16 W	21-16 W	30-16 W	
14		14-14 W	21-14 W	30-14 W	
11		14-11 W	21-11 W	30-11 W	40-11 W
8					40- 8 W

订货示例: 14-19W BR215 10片 Ordering example: 14-19W BR215 10pcs

★代表刀片只能单面使用 ★ Inserts with a single cutting edge

👉 BSPT-55° 英国标准锥管螺纹刀片 BSPT





单面使用
One cutting edge

H	6	7.5	12	16	20
T	2.35	3.1	4.7	5.5	6.3
加工螺距	尺寸 Dimensions (mm)=A				
tpi	12	14	21	30	40
19	12-19 BSPT	14-19 BSPT			
14		14-14 BSPT	21-14 BSPT		
11			21-11 BSPT	30-11 BSPT	40-11 BSPT

订货示例: 14-19BSPT BR215 10片 Ordering example: 14-19BSPT BR215 10pcs



👉 NPT-60° 美国标准锥管螺纹刀片 NPT



H	6	7.5	12	16	20
T	2.38	3.1	4.7	5.5	6.5
加工螺距	尺寸 Dimensions (mm)=A				
tpi	12	14	21	30	40
18	12-18 NPT	14-18 NPT			
14		14-14 NPT	21-14 NPT		
11.5			21-11.5 NPT	30-11.5 NPT	40-11.5 NPT
8				30-8 NPT	40-8 NPT

订货示例: 14-18BSPT BR215 10片 Ordering example: 14-18BSPT BR215 10pcs


👉 Pg螺纹刀片 Pg-DIN 40430



H	7.5	12	16
T	3.1	4.7	5.5
加工螺距	尺寸 Dimensions (mm)=A		
tpi	14	21	30
18	14-18 PG (PG 9, 11, 13.5, 16)	21-18 PG (PG 16)	
16		21-16 PG (PG 21, 29, 36, 42, 48)	30-16 PG (PG 36, 42, 48)

订货示例: 14-18PG BR215 10片 Ordering example: 14-18PG BR215 10pcs

单刃螺纹铣刀杆 single insert toolholders




*带内冷孔的刀杆，需要订制

型号 Ordering Code	尺寸 Dimensions (mm)						刀片 Insert	螺钉 Insert Screw	扳手 Torx Key
SR0010H12	12	9.5	16	7.8	85	29	12****	L60M2.5X7	T8
SR0012F14	14	12.0	20	8.9	80	30	14****	L60M3X8	T10
SR0014H14	14	14.5	20	11.2	85	33	14****	L60M3X8	T10
SR0017H14	14	17.0	20	13.4	85	35	14****	L60M3X8	T10
★ SR0018H21	21	18.0	20	13.8	85	35	21****	L60M3.5X8	T15
SR0021H21	21	21.0	20	15.5	94	44	21****	L60M3.5X10	T15
SR0029J30	30	29.0	25	22	110	52	30****	L60M4X0.5X11.5D	T15
SR0048M40	40	48.0	40	35.0	153	83	40****	L60M5X0.8X14D	T20

★ 此刀杆不能装配：21E/M3.5ISO、21E/M7UN、21E/M8UN、21-11BSPT、21-11.5NPT、21-11.5NPTF


单刃螺纹铣刀杆（加长型） single insert toolholders (long shank)



*带内冷孔的刀杆，需要订制

型号 Ordering Code	尺寸 Dimensions (mm)				刀片 Insert	螺钉 Insert Screw	扳手 Torx Key
SR0025K21	21	25	20	125	21****	L60M3.5X10	T15
SR0031M30	30	31	25	150	30****	L60M4X0.5X11.5D	T15
SR0038M30	30	38	32	150	30****	L60M4X0.5X11.5D	T15
SR0038Q40	40	38	32	180	40****	L60M5X0.8X14D	T20
SR0048R40	40	48	40	210	40****	L60M5X0.8X14D	T20


双刃螺纹铣刀杆 Twin Insert Toolholders



*带内冷孔的刀杆，需要订制

型号 Ordering Code	尺寸 Dimensions (mm)						刀片 Insert	刃数 No. of Insert	螺钉 Insert Screw	扳手 Torx Key
	A	D	D1	D2	L	L1				
SR0020G14-2	14	20	20	16	93	37	14****	2	L60M3X7	T10
SR0020J14-2	14	20	20	16	113	57	14****	2	L60M3X7	T10
SR0030J21-2	21	30	25	24	113	52	21****	2	L60M3.5X10	T15
SR0030L21-2	21	30	25	24	140	80	21****	2	L60M3.5X10	T15
SR0040L30-2	30	40	32	30	135	70	30****	2	L60M4X0.5X11.5D	T15
SR0040P30-2	30	40	32	30	170	103	30****	2	L60M4X0.5X11.5D	T15
SR0050M40-2	40	50	40	38	153	80	40****	2	L60M5X0.8X14D	T20



螺纹铣刀盘（多刃） multi Insert Toolholders



*带内冷孔的刀杆，需要订制

型号 Ordering Code	尺寸 Dimensions (mm)				刀片 Insert	刃数 No. of Insert	螺钉 Insert Screw	扳手 Torx Key
	A	D	D1	L				
SR0063C21-5	21	63	22	50	21****	5	L60M3.5X10	T15
SR0063C30-4	30	63	22	50	30****	4	L60M4X0.5X10D	T15
SR0080D30-4	30	80	27	55	30****	4	L60M4X0.5X10D	T15
SR0100D30-4	30	100	32	60	30****	4	L60M4X0.5X10D	T15
SR0080D40-4	40	80	27	65	40****	4	L60M5X0.8X14D	T20
SR0100E40-4	40	100	32	70	40****	4	L60M5X0.8X14D	T20

ISO标准型螺纹铣刀片 ISO Metric Full Profile





双面使用

TM标准型

加工螺距 Pitch		尺寸 Dimensions (mm)					
mm		L=10.4mm D=6.0mm	L=11mm D=1/4"	L=16mm D=3/8"	L=22mm D=3/4"	L=27mm D=5/8"	L=38.5mm D=1 1/4"
0.5	外Ext						
	内Int	TM6.0N0.5 ISO	TM2N0.5 ISO	TM3N0.5 ISO			
0.75	外Ext		TM2E0.75 ISO	TM3E0.75 ISO			
	内Int	TM6.0N0.75 ISO	TM2N0.75 ISO	TM3N0.75 ISO			
1.0	外Ext		TM2E1.0 ISO	TM3E1.0 ISO	TM3BE1.0 ISO	TM5E1.0 ISO	
	内Int	TM6.0N1.0 ISO	TM2N1.0 ISO	TM3N1.0 ISO	TM3BN1.0 ISO	TM5N1.0 ISO	
1.25	外Ext		TM2E1.25 ISO	TM3E1.25 ISO	TM3BE1.25 ISO	TM5E1.25 ISO	
	内Int	TM6.0N1.25 ISO	TM2N1.25 ISO	TM3N1.25 ISO	TM3BN1.25 ISO	TM5N1.25 ISO	
1.5	外Ext		TM2E1.5 ISO	TM3E1.5 ISO	TM3BE1.5 ISO	TM5E1.5 ISO	TM6BE1.5 ISO
	内Int	TM6.0N1.5 ISO	TM2N1.5 ISO	TM3N1.5 ISO	TM3BN1.5 ISO	TM5N1.5 ISO	TM6BN1.5 ISO
1.75	外Ext			TM3E1.75 ISO	TM3BE1.75 ISO	TM5E1.75 ISO	
	内Int			TM3N1.75 ISO	TM3BN1.75 ISO	TM5N1.75 ISO	
2.0	外Ext			TM3E2.0 ISO	TM3BE2.0 ISO	TM5E2.0 ISO	TM6BE2.0 ISO
	内Int			TM3N2.0 ISO	TM3BN2.0 ISO	TM5N2.0 ISO	TM6BN2.0 ISO
2.5	外Ext					TM5E2.5 ISO	TM6BE2.5 ISO
	内Int					TM5N2.5 ISO	TM6BN2.5 ISO
3.0	外Ext					TM5E3.0 ISO	TM6BE3.0 ISO
	内Int					TM5N3.0 ISO	TM6BN3.0 ISO
3.5	外Ext					TM5E3.5 ISO	
	内Int					TM5N3.5 ISO	
4.0	外Ext					TM5E4.0 ISO	TM6BE4.0 ISO
	内Int					TM5N4.0 ISO	TM6BN4.0 ISO
4.5	外Ext					TM5E4.5 ISO	TM6BE4.5 ISO
	内Int					TM5N4.5 ISO	TM6BN4.5 ISO
5.0	外Ext						TM6BE5.0 ISO
	内Int						TM6BN5.0 ISO
5.5	外Ext						TM6BE5.5 ISO
	内Int						TM6BN5.5 ISO
6.0	外Ext						TM6BE6.0 ISO
	内Int						TM6BN6.0 ISO

订货示例: TM5E4.0 ISO BR215 10片 Ordering example: TM5E4.0 ISO BR215 10pcs

UN-60° 美制统一标准螺纹铣刀片 UN-60° American UN Full Profile



加工螺距 Pitch		尺寸 Dimensions (mm)					
TPI		L=10.4mm D=6.0mm	L=11mm D=1/4"	L=16mm D=3/8"	L=22mm D=3/8"	L=27mm D=5/8"	L=38.5mm D=3/4"
48	外Ext						
	内Int		TM2N48 UN				
40	外Ext						
	内Int		TM2N40 UN	TM3N40 UN			
32	外Ext						
	内Int	TM6.0N32 UN	TM2N32 UN	TM3N32 UN			
28	外Ext						
	内Int	TM6.0N28 UN	TM2N28 UN	TM3N28 UN			
27	外Ext						
	内Int		TM2N27 UN	TM3N27 UN			
26	外Ext						
	内Int			TM3N26 UN			
24	外Ext						
	内Int	TM6.0N24 UN	TM2N24 UN	TM3N24 UN	TM3BE24 UN	TM5E24 UN	
20	外Ext						
	内Int	TM6.0N20 UN	TM2N20 UN	TM3N20 UN	TM3BN20 UN	TM5N20 UN	
18	外Ext						
	内Int	TM6.0N18 UN	TM2N18 UN	TM3N18 UN	TM3BN18 UN	TM5N18 UN	
16	外Ext						
	内Int	TM6.0N16 UN	TM2N16 UN	TM3N16 UN	TM3BN16 UN	TM5N16 UN	
14	外Ext						
	内Int		TM2N14 UN	TM3N14 UN	TM3BN14 UN	TM5N14 UN	
13	外Ext						
	内Int			TM3N13 UN	TM3BN13 UN	TM5N13 UN	
12	外Ext						
	内Int			TM3N12 UN	TM3BN12 UN	TM5N12 UN	
11.5	外Ext						
	内Int			TM3N11.5 UN		TM5N11.5 UN	



订货示例: TM3E12UN BR215 10片 Ordering example: TM3E12UN BR215 10pcs

 UN-60° 美制统一标准螺纹铣刀片 UN-60° American UN Full Profile

加工螺距 Pitch		尺寸 Dimensions (mm)					
TPI		L=10.4mm D=6.0mm	L=11mm D=1/4"	L=16mm D=3/8"	L=22mm D=3/8"	L=27mm D=5/8"	L=38.5mm D=3/4"
11	外Ext					TM5E11 UN	
	内Int					TM5N11 UN	
10	外Ext					TM5E10 UN	
	内Int					TM5N10 UN	
9	外Ext					TM5E9 UN	
	内Int					TM5N9 UN	
8	外Ext					TM5E8 UN	
	内Int					TM5N8 UN	
7	外Ext					TM5E7 UN	
	内Int					TM5N7 UN	
6	外Ext					TM5E6 UN	TM6E6 UN
	内Int					TM5N6 UN	TM6N6 UN
5	外Ext						TM6E5 UN
	内Int						TM6N5 UN
4.5	外Ext						TM6E4.5 UN
	内Int						TM6N4.5 UN
4	外Ext						TM6E4 UN
	内Int						TM6N4 UN

订货示例: TM5E6UN BR215 10片 Ordering example: TM5E6UN BR215 10pcs



 NPTF 美制干密封螺纹铣刀片 NPTF (Dry seal)



加工螺距 Pitch		尺寸 Dimensions (mm)			
TPI		L=16mm D=3/8"	L=22mm D=3/8"	L=27mm D=5/8"	L=38.5mm D=3/4"
14		TM3-14 NPTF	TM3B-14 NPTF		
11.5		TM3-11.5 NPTF	TM3B-11.5 NPTF	TM5-11.5 NPTF	TM6B-11.5 NPTF
8				TM5-8 NPTF	TM6B-8 NPTF

订货示例: TM3-14NPTF BR215 10片 Ordering example: TM3-14NPTF BR215 10pcs

UNJ 美制航空航天机械螺纹铣刀片 UNJ Aviation Thread





双面使用

TM标准型

加工螺距 Pitch		尺寸 Dimensions (mm)			
TPI		L=10.4mm D=6.0mm	L=11mm D=1/4"	L=16mm D=3/8"	L=27mm D=5/8"
24	外Ext		TM2E24 UNJ	TM3E24 UNJ	
	内Int	TM6.0N24 UNJ	TM2N24 UNJ	TM3N24 UNJ	
20	外Ext		TM2E20 UNJ	TM3E20 UNJ	
	内Int	TM6.0N20 UNJ	TM2N20 UNJ	TM3N20 UNJ	
18	外Ext			TM3E18 UNJ	
	内Int	TM6.0N18 UNJ	TM2N18 UNJ	TM3N18 UNJ	
16	外Ext		TM2E16 UNJ	TM3E16 UNJ	TM5E16 UNJ
	内Int	TM6.0N16 UNJ	TM2N16 UNJ	TM3N16 UNJ	TM5N16 UNJ
14	外Ext		TM2E14 UNJ	TM3E14 UNJ	
	内Int		TM2N14 UNJ	TM3N14 UNJ	
13	外Ext			TM3E13 UNJ	
	内Int			TM3N13 UNJ	
12	外Ext			TM3E12 UNJ	TM5E12 UNJ
	内Int			TM3N12 UNJ	TM5N12 UNJ
11	外Ext			TM3E11 UNJ	TM5E11 UNJ
	内Int			TM3N11 UNJ	TM5N11 UNJ

订货示例: TM3E13UNJ BR215 10片 Ordering example: TM3E13UNJ BR215 10pcs

W-55° 英制惠氏螺纹铣刀片 W-55° Whitworth Full Profile





双面使用

TM标准型

加工螺距 Pitch		尺寸 Dimensions (mm)					
TPI		L=10.4mm D=6.0mm	L=11mm D=1/4"	L=16mm D=3/8"	L=22mm D=3/8"	L=27mm D=5/8"	L=38.5mm D=3/4"
28	外Ext	TM6.0E28 W	TM2E28 W				
	内Int	TM6.0N28 W	TM2N28 W				
26	外Ext	TM6.0E26 W	TM2E26 W	TM3E26 W			
	内Int	TM6.0N26 W	TM2N26 W	TM3N26 W			
24	外Ext	TM6.0E24 W	TM2E24 W	TM3E24 W	TM38E24 W		
	内Int	TM6.0N24 W	TM2N24 W	TM3N24 W	TM38N24 W		
20	外Ext	TM6.0E20 W	TM2E20 W	TM3E20 W	TM38E20 W		
	内Int	TM6.0N20 W	TM2N20 W	TM3N20 W	TM38N20 W		
19	外Ext	TM6.0E19 W	TM2E19 W	TM3E19 W	TM38E19 W		
	内Int	TM6.0N19 W	TM2N19 W	TM3N19 W	TM38N19 W		
18	外Ext			TM3E18 W	TM38E18 W		
	内Int			TM3N18 W	TM38N18 W		
16	外Ext			TM3E16 W	TM38E16 W	TM5E16 W	
	内Int			TM3N16 W	TM38N16 W	TM5N16 W	
14	外Ext		TM2E14 W	TM3E14 W	TM38E14 W	TM5E14 W	
	内Int		TM2N14 W	TM3N14 W	TM38N14 W	TM5N14 W	
12	外Ext			TM3E12 W	TM38E12 W	TM5E12 W	
	内Int			TM3N12 W	TM38N12 W	TM5N12 W	
11	外Ext			TM3E11 W	TM38E11 W	TM5E11 W	68E11 W
	内Int			TM3N11 W	TM38N11 W	TM5N11 W	68N11 W
10	外Ext					TM5E10 W	
	内Int					TM5N10 W	
9	外Ext					TM5E9 W	
	内Int					TM5N9 W	
8	外Ext					TM5E8 W	
	内Int					TM5N8 W	
7	外Ext					TM5E7 W	
	内Int					TM5N7 W	
6	外Ext					TM5E6 W	TM68E6 W
	内Int					TM5N6 W	TM68N6 W
5	外Ext						TM68E5 W
	内Int						TM68N5 W
4.5	外Ext						TM68E4.5 W
	内Int						TM68N4.5 W

订货示例: TM3E11W BR15 10片 Ordering example: TM3E11W BR215 10pcs



👉 NPT 美国标准锥管螺纹铣刀片 NPT-60° National Pipe Threads



加工螺距 Pitch	尺寸 Dimensions (mm)			
TPI	L=16mm D=3/8"	L=22mm D=3/8"	L=27mm D=3/8"	L=38.5mm D=3/4"
18	TM3E18 NPT			
14	TM3-14 NPT	TM3B-14 NPT		
11.5	TM3-11.5 NPT	TM3B-11.5 NPT	TM5-11.5 NPT	TM6B-11.5 NPT
8			TM5-8 NPT	TM6B-8 NPT

订货示例: TM3E14NPT BR215 10片 Ordering example: TM3E14NPT BR215 10pcs


👉 BSPT 英国标准锥管螺纹铣刀片 BSPT-55°



加工螺距 Pitch	尺寸 Dimensions (mm)		
TPI	L=11mm D=1/4"	L=15mm D=3/8"	L=27mm D=3/8"
19	TM2-19 BSPT		
14		TM3-14 BSPT	
11		TM3-11 BSPT	TM5-11 BSPT


订货示例: TM3-14BSPT BR15 10片 Ordering example: TM3-14BSPT BR215 10pcs

 螺纹铣刀杆 Threading Milling Tool Holders




型号	尺寸Dimensions(mm)					适用刀片	刀片螺钉	扳手
Ordering Code	L	L1	D	D1	D2	Insert	Insert Screw	Hex Key
STM6.0-C12	69	12	12	6.8	9	6.0****	M2.2X5	T7
STM6.0-C20	84	17	20	6.8	9	6.0****	M2.2X5	T7
STM2-C12	70	12	12	8.9	11.5	2****	M3X7	T8
STM2-C20	85	20	20	8.9	11.5	2****	M3X7	T8
STM3-C16	90	22	16	13.6	17	3****	M3.5X8	T15
STM3-C20	95	43	20	16.6	20	3****	M3.5X8	T15
SBTM3B-C16	79.5	29	16	13.5	17	3B****	M3.5X8	T15
SBTM3B-C20	81.5	29	20	15.5	19	3B****	M3.5X8	T15
SBTM3B-C25	92.3	30	25	15.5	19	3B****	M3.5X8	T15
SBTMW3B-C25	90.8	30	25	16.5	22	3B****	M3.5X8	T15
STM5-C25	110	52	25	24	30	5****	M5X14	T20
STM5-C25LH	110	52	25	24	30	5****	M5X14	T20
STM5-C32	120	58	32	31	37	5****	M5X14	T20
STM6B-C32	115	53	32	27	35	6B****	M7X15	T25
STM6B-C40	138	63	40	38	46	6B****	M7X15	T25

👉 螺纹铣刀杆 Threading Milling Tool Holders




型号	尺寸Dimensions(mm)					适用刀片	刀片螺钉	扳手
Ordering Code	L	L1	D	D1	D2	Insert	Insert Screw	Torx Key
STML2-C25	125	17	25	8.9	11.5	2****	M3X7	T8
STML3-C25	125	25	25	18.6	22	3****	M3.5X8	T15
SBTML3-C25	125	63.6	25	18.6	22	3****	M3.5X8	T15
SBTML3B-C20	98.5	44	20	15.5	19	3B****	M3.5X8	T15
SBTML3B-C25	125	63.6	25	18.6	22	3B****	M3.5X15	T15
STML5-C25	150	92	25	24	30	5****	M5X14	T20
STML5-C32	180	98	32	31	37	5****	M5X14	T20
STML8B-C40	185	93	40	38	46	6B****	M7X15	T25

 螺纹铣刀杆 Threading Milling Tool Holders




型号	尺寸Dimensions(mm)					适用刀片	刀片螺钉	扳手
Ordering Code	L	L1	D	D1	D2	Insert	Insert Screw	Tool Key
STM0.0-C20 124/003	85	15	20	6.7	9	5.0****	M2.2X5	T7
STM2-C20 124/005	77	15.5	20	7.4	10	5.0****	M2.2X5	T7
STM2-C20 124/006	77	15.5	20	8	12	2****	M3X7	T8
STM2-C20 124/009	77	15.5	20	7.4	10	2****	M3X7	T8
STM3-C18 124/001	91	20.5	16	12.2	15.5	3****	M3.5X8	T15
STM4-C25 124/002	98	30	25	13.4	18	3****	M3.5X8	T15
STM4-C25 124/007	98	40	25	16	20	3B****	M3.5X8	T16
STM5-C25 124/004	98	40	25	19	25	3B****	M3.5X8	T16
STM5-C25 124/006	98	40	25	16.4	22	3B****	M3.5X8	T16

👉 螺纹铣刀杆 Threading Milling Tool Holders




右刀杆	左刀杆	尺寸Dimensions(mm)					适用刀片	刀片螺钉	扳手
Right Hand	Left Hand	L	L1	D	D1	D2	Insert	Insert Screw	Torx Key
STMN3-C16	STMN3-C16 LH	125	17	25	8.9	11.5	2****	M3X7	T8
STMN3-C20	STMN3-C20 LH	125	25	25	18.6	22	3****	M3.5X8	T16
SBTMN3N-C16	SBTMN3N-C16 LH	125	63.5	25	18.6	22	3****	M3.5X8	T16
SBTMN3B-C20	SBTMN3B-C20 LH	98.5	44	20	16.5	19	3B****	M3.5X8	T16
SBTMN5-C32	SBTMN5-C32 LH	125	83.5	25	18.6	22	3B****	M3.5X8	T16

 螺纹铣刀杆 Twin insert ToolHolders




型号	尺寸Dimensions(mm)					适用刀片	刀片螺钉	扳手
Ordering Code	L	L1	D	D1	D2	Insert	Insert Screw	Tool Key
2STM2-C20	85	20	20	14.4	17	6.0****	M2.2X5	T7
2STM3-C25	100	43	25	22.5	26	6.0****	M2.2X5	T7
2SBTM3B-C25	104.2	46	25	22.5	26	2****	M3X7	T8
2STM5-C32	120	45	32	36	42	2****	M3X7	T8
2STM8B-C40	137.2	65	40	44	52	3****	M3.5X8	T15

👉 螺纹铣刀盘 Multi Insert Toolholder



型号	刀片数量	尺寸Dimensions(mm)			适用刀片	刀片螺钉	扳手
Ordering Code	NO. of Insert	D2	d(H7)	H	Insert	Insert Screw	Torx Key
SHTM2-D38-16	6	38	16	40	2****	M3X7	T8
SHTM2-D50-22	8	50	22	40	2****	M3X7	T8
SHTM3-D50-22	6	50	22	40	3****	M3.5X8	T16
SHTM3B-D63-22	6	63	22	40	3B****	M3.5X8	T16
SHTM5-D63-22	4	63	22	45	5****	M5X14	T20
SHTM6B-D63-22	4	63	22	50	6B****	M7X15	T25
SHTM5-D80-27	6	80	27	50	5****	M5X14	T20
SHTM6B-D80-27	5	80	27	50	6B****	M7X15	T25
SHTM5-D100-32	7	100	32	55	5****	M5X14	T20
SHTM6B-D100-32	6	100	32	55	6B****	M7X15	T25
SHTM5-D125-40	9	125	40	63	5****	M5X14	T20
SHTM6B-D125-40	8	125	40	63	6B****	M7X15	T25

60° 深孔加工螺纹铣刀片 Thread Mill for Deep Holes




U型




A型

型号 Ordering Code	材质 Material Code	加工螺距范围 mm	加工螺距范围 tpi	尺寸 Dimensions (mm)			刀杆 toolholder
11UIDA60	○ ●	0.5-1.5	48-16			0.05	
11UIDB60	○ ●	1.5-2.0	16-12			0.06	
11UIDD60	○ ●	2.0-2.5	9-12	1/4"	11	0.11	SMT**-**11U**-**
11UIDM60	○ ○	2.5	10			0.11	
11UIDC60	○ ●	2.5-4.0	10-6			0.14	
16UIDB60	○ ●	1.5-2.0	16-12			0.06	
16UIDE60	○ ●	2.5-3.5	10-7	3/8"	16	0.14	SMT**-**16U**-**
16UIDH60	○ ●	4.0-6.0	6-4			0.25	
22UIDK60	○ ○	6.0-8.0	4-3	1/2"	22	0.30	SMT**-**22U**-**
11AIDP60	○ ●	1.5-3.0	16-8	1/4"	11	0.06	SMT**-**11A**-**
16AIDT60	○ ●	2.0-4.0	12-6	3/8"	16	0.08	SMT**-**16A**-**




U型适用于大螺距
for large pitches



A型适用于小螺距以及退刀槽较短的情况
for short pitches

55° 深孔加工螺纹铣刀片 Thread Mill for Deep Holes




U型



A型


型号 Ordering Code	材料 Material Code	加工螺距范围 mm	加工螺距范围 tpi	尺寸 Dimensions(mm)			刀杆 tool holder
11UIDA55	○ ●	0.5-1.5	48-16			0.11	
11UIDB55	○ ●	1.5-2.0	16-12	1/4"	11	0.08	SMT**--**11U--**
11UIDL55	○ ●	2.5-3.5	11-7			0.24	
16UIDB55	○ ●	1.5-2.0	16-12			0.08	
16UIDL55	○ ●	2.5-3.5	11-7	3/8"	16	0.24	SMT**--**16U--**
16UIDH55	○ ○	4.0-6.0	6-4			0.27	
22UIDK55	○ ○	6.0-8.5	4-3	1/2"	22	0.50	SMT**--**22U--**

深孔加工螺纹铣刀具(U型) Thread Milling holder for Deep Holes



型号 Ordering Code	尺寸 Dimensions(mm)						刃数 NO. of Insert	适用刀片 Insert	刀片螺钉 Insert Screw	扳手 Torx Key
SMT15-16H11U-1	100	40		16	11	14.75	1			
SMT21-25K11U-2	125	60		25	16	20.65	2			
SMT23-25L11U-2	140	70	5.4	25	17.7	23	2	11UID***	L63M2.5X6	T8
SMT26-25M11U-3	150	80		25	20.4	26	3			
SMT26-25P11U-3	170	110		25	20.4	26	3			
SMT31-32P11U-4	170	95		32	25.7	31	4			
SMT36-32P16U-3	170	95		32	29	36.5	3			
SMT42-40R16U-4	200	120	8.0	40	34.2	42	4	16UID***	L63M3.5X10	T15
SMT42-40S16U-4	250	160		40	34.2	42	4			

 深孔加工螺纹铣刀具(A型) Thread Milling holder for Deep Holes



型号	尺寸 Dimensions (mm)				刃数 NO. of Insert	适用刀片 Insert	刀片螺钉 Insert Screw	扳手 Torx Key
Ordering Code	L	L2	D	D _{min}				
SMT26-20J11A-3	110	3.0	20	26	3	11A10***	L60M2.5x6	T8
SMT35-28M16A-3	150	4.0	28	35	3	16A10***	L60M3.0x8	T15



深孔加工螺纹铣刀型号说明

Thread Mill insert for Deep Holes

刀片 Insert

11	U	I	DC	60	DM215
刀片尺寸 Insert Size	刀片形式 Insert Style	刀片类型 Type of Insert	螺距 PITCH	牙型角度 Standard	材料代号 Carbide Grade
11-1C1/4" 16-1C3/8" 22-1C1/2"	U- A-	I-内螺纹 I-Internal	mm	60-50° 55-55°	DM215 适合不锈钢和钢 DM215 apply to stainless steel and steel DK110 适合铝合金等有色金属 DK110 apply to aluminium alloy and non-ferrous
			DA 0.5-1.5 48-18 DB 1.5-2.0 16-12 DC 2.5-4.0 10-6 DD 2.0-2.5 9-12 DE 2.5-3.6 10-7 DH 4.0-6.0 6-4 DK 8.0-8.0 4-3 DL - 11-7 DM 2.5 10 DN 1.0-2.0 24-11 DP 1.5-3.0 16-8 DR - 28-14 DT 2.0-4.0 12-6		




刀杆 Tool Holders

S	MT	26 - 25	M	11	U	3
锁紧形式 Clamping System	加工方式 System	刀具回转直径 Cutting Dia.	柄部直径 Shank Dia.	长度 Toolholder Length	刀片尺寸 Insert Size	刀片形式 Insert Style
S-螺钉锁紧 S-Screw Clamping	MT-铣削加工 MT-Thread Milling	15-14.75mm 21-20.65mm 23-23mm 26-26mm 31-31mm 36-36.5mm 42-42mm		6-100mm K-125mm L-140mm B-150mm P-170mm Z-200mm S-250mm	11-1C1/4" 16-1C3/8" 22-1C1/2"	U- A-
						刃数 (刀片数) No. of Flutes
						3



旋风铣螺纹刀片

Partial Profile Thread Milling Inserts



型号 Ordering Code	材质 Material Code			名称 Name	尺寸 Dimensions (mm)		
	DK110	DP220	DM215		H	L	T
SV601906			○	60° 通用螺纹刀片 Partial Profile 60°	19	12.7	6.35
SV601604			○	60° 通用螺纹刀片 Partial Profile 60°	16	9.53	4.65
SV601103			○	60° 通用螺纹刀片 Partial Profile 60°	11	6.35	3.18
SV600802			○	60° 通用螺纹刀片 Partial Profile 60°	08	4.76	2.38
SV551906			○	55° 通用螺纹刀片 Partial Profile 55°	19	12.7	6.35
SV551604			○	55° 通用螺纹刀片 Partial Profile 55°	16	9.53	4.65
SV551103			○	55° 通用螺纹刀片 Partial Profile 55°	11	6.35	3.18
SV550802			○	55° 通用螺纹刀片 Partial Profile 55°	08	4.76	2.38


●:常备库存(主推) Stock standard(main) ○:一般库存

订货示例: SV1604 DM215 10片 Ordering example: SV1604 DM215 10pcs


单刃螺纹铣刀 Indexable Threading Mills



形式一
Type one



形式二
Type two



型号 Model No.	齿数 Zt	尺寸Dimension(mm)				刀片 Insert	螺钉 Screw	扳手 Torx-key
		Dmin	qd	L1	L			
SMT12-12F11	1	12	12	25	80	11NR***	L60M2. 5X6	T-08
SMT18-20K16	1	18	20	35	125	16NR***	L60M3. 5X8	T-15
SMT25-25M16	1	25	25	65	150	16NR***	L60M3. 5X8	T-15
SMT35-32S22	1	35	32	110	250	22NR***	L60M4. 5X12	T-20
SMT46-40S22-3	3	46	40	130	225	22NR***	L60M4. 5X12	T-20

● 订货示例 : 1 件 SMT18-20K16
Ordering example : 1pc. SMT18-20K16

刀片使用 : 加工外螺纹 : 16NR ****
加工内螺纹 : 16NR ****

Insert information: External threading inserts : 16NR ****
Internal threading inserts : 16NR ****


外螺纹铣削方法 Milling Ways for External Thread

右旋螺纹 -R Right Hand-R	左旋螺纹 -L Left Hand-L	右旋螺纹 -R Right Hand-R	左旋螺纹 -L Left Hand-L
顺时针进给, 顺铣 CW Feed and Milling	逆时针进给, 逆铣 CCW Feed and Milling	顺时针进给, 逆铣 CW Feed and CCW Milling	逆时针进给, 顺铣 CCW Feed and CW Milling
刀片Insert: 16NR ****	刀片Insert: 16NR ****	刀片Insert: 16NR ****	刀片Insert: 16NR ****

内螺纹铣削方法 Milling Ways Internal Thread

右旋螺纹 -R Right Hand-R	左旋螺纹 -L Left Hand-L	右旋螺纹 -R Right Hand-R	左旋螺纹 -L Right Hand-R
顺时针进给, 顺铣 CW Feed and Milling	逆时针进给, 逆铣 CCW Feed and Milling	顺时针进给, 逆铣 CW Feed and CCW Milling	逆时针进给, 顺铣 CCW Feed and CW Milling
刀片Insert: 16NR ****	刀片Insert: 16NR ****	刀片Insert: 16NR ****	刀片Insert: 16NR ****

ISO-60° 整体硬质合金螺纹铣刀 ISO-60° Carbide thread milling tool




型号	规格	材质 Material Code	螺距	沟槽数	尺寸 Dimensions (mm)
Ordering Code	Description	DK105 BR205	Pitch	No. of Flutes	D d *L1 *L
HMT06022C5-0.5ISO	ø2.2x0.5x5.3xD6xL53-3T	○ ●	0.5	3	6 2.2 5.3 53
HMT06038C10-0.5ISO	ø3.8x0.5x10.3xD6xL53-3T	○ ●	0.5	3	6 3.8 10.3 53
HMT06031C7-0.7ISO	ø3.1x0.7x7.4xD6xL53-3T	○ ●	0.7	3	6 3.1 7.4 53
HMT06045C10-0.75ISO	ø4.5x0.75x10.1xD6xL53-3T	○ ●	0.75	3	6 4.5 10.1 53
HMT06036C9-0.8ISO	ø3.6x0.8x9.2xD6xL53-3T	○ ●	0.8	3	6 3.6 9.2 53
HMT06040C10-1.0ISO	ø4.0x1.0x10.5xD6xL53-3T	○ ●	1.0	3	6 4.0 10.5 53
HMT06040C14-1.0ISO	ø4.0x1.0x14.5xD6xL53-3T	○ ●	1.0	3	6 4.0 14.5 53
HMT06060D12-1.0ISO	ø6.0x1.0x12.5xD6xL53-4T	○ ●	1.0	4	6 5.95 12.5 53
HMT0808D16-1.0ISO	ø8.0x1.0x16.5xD8xL64-4T	○ ●	1.0	4	8 7.95 16.5 64
HMT0605C14-1.25ISO	ø5.0x1.25x14.4xD6xL53-3T	○ ●	1.25	3	6 5.0 14.4 53
HMT0605C19-1.25ISO	ø5.0x1.25x19.4xD6xL53-3T	○ ●	1.25	3	6 5.0 19.4 53
HMT0807D17-1.5ISO	ø7.0x1.5x17.3xD8xL64-4T	○ ●	1.5	4	8 7.0 17.3 64
HMT0807D24-1.5ISO	ø7.0x1.5x24.8xD8xL64-4T	○ ●	1.5	4	8 7.0 24.8 64
HMT1010D21-1.5ISO	ø10.0x1.5x21.8xD10xL76-4T	○ ●	1.5	4	10 9.95 21.8 76
HMT1616F33-1.5ISO	ø16.0x1.5x33.8xD16xL108-6T	○ ●	1.5	6	16 15.95 33.8 108
HMT0808D20-1.75ISO	ø8.0x1.75x20.1xD8xL64-4T	○ ●	1.75	4	8 7.95 20.1 64
HMT0808D28-1.75ISO	ø8.0x1.75x28.9xD8xL64-4T	○ ●	1.75	4	8 7.95 28.9 64
HMT1010D27-2.0ISO	ø10.0x2.0x27xD10xL76-4T	○ ●	2.0	4	10 9.95 27 76
HMT1010D39-2.0ISO	ø10.0x2.0x39xD10xL76-4T	○ ●	2.0	4	10 9.95 29 76
HMT1212D27-2.0ISO	ø12x2.0x27xD12xL81-4T	○ ●	2.0	4	12 11.95 27 81

订货示例: HMT0807D17-1.5ISO BR205 1支 Ordering example: HMT0807D17-1.5ISO BR205 1PCS

★该尺寸可以根据需求定制 ★"L" & "L1" can be customized according to the actual demand

ISO-60° 整体硬质合金螺纹铣刀 ISO-60° Carbide thread milling tool




型号	规格	材质	Material Code	螺距	沟槽数	尺寸 Dimensions (mm)			
Ordering Code	Description	DK105	BR205	Pitch	No. of Flutes	D	d	*L1	*L
DMT08041C19-1.00ISO	ø4.1x1.0x19xD08xL64-3	○	●	1.0	3	8	4.1	19	64
DMT10058C26-1.25ISO	ø5.8x1.25x26xD10xL76-3	○	●	1.25	3	10	5.8	26	76
DMT10077C32-1.50ISO	ø7.7x1.5x32xD10xL76-3	○	●	1.5	3	10	7.7	32	76
DMT12094D38-1.75ISO	ø9.4x1.5x38xD12xL81-4	○	●	1.5	4	12	9.4	38	81
DMT12087D38-1.75ISO	ø8.7x1.75x38xD12xL81-4	○	●	1.75	4	12	8.7	38	81
DMT16102D44-2.00ISO	ø10.2x2.0x44xD16xL92-4	○	●	2.0	4	16	10.2	44	92
DMT16122D50-2.00ISO	ø12.2x2.0x50xD16xL100-4	○	●	2.0	4	16	12.2	50	100
DMT16129E57-2.50ISO	ø12.9x2.5x57xD18xL108-5	○	●	2.5	5	16	12.9	57	108
DMT16148E63-2.50ISO	ø14.8x2.5x63xD18xL114-5	○	●	1.0	5	18	14.8	63	114

订货示例: DMT08041C19-1.00ISO BR205 1支 Ordering example: DMT08041C19-1.00ISO BR205 1PCS

★该尺寸可以根据需求定制 ★ "L" & "L1" can be customized according to the actual demand

ISO-60° 整体硬质合金螺纹铣刀 ISO-60° Carbide thread milling tool



型号	规格	材质 Material Code		螺距	沟槽数	尺寸 Dimensions (mm)			
Ordering Code	Description	DK105	BR205	Pitch	No. of Flutes	D	d	*L1	*L
D3MT03012C034-0.35ISO	ø1.2x0.35x3.4xD3xL30-3	○	●	0.35	3	6	1.2	3.4	30
D3MT06015C042-0.4ISO	ø1.55x0.4x4.2xD6xL57-3	○	●	0.4	3	6	1.55	4.2	57
D3MT06016C046-0.45ISO	ø1.65x0.45x4.6xD6xL57-3	○	●	0.45	3	6	1.65	4.6	57
D3MT06019C052-0.45ISO	ø1.95x0.45x5.2xD6xL57-3	○	●	0.45	3	6	1.95	5.2	57
D3MT06024C062-0.5ISO	ø2.4x0.5x6.2xD6xL57-3	○	●	0.5	3	6	2.4	6.2	57
D3MT06027C073-0.6ISO	ø2.75x0.6x7.3xD6xL57-3	○	●	0.6	3	6	2.75	7.3	57
D3MT06031C083-0.7ISO	ø3.15x0.7x8.3xD6xL57-3	○	●	0.7	3	6	3.15	8.3	57
D3MT06040C104-0.8ISO	ø4.05x0.8x10.4xD6xL57-3	○	●	0.8	3	6	4.05	10.4	57
D3MT06048C125-1.0ISO	ø4.8x1.0x12.5xD6xL57-3	○	●	1.0	3	6	4.8	12.5	57
D3MT08065C166-1.25ISO	ø6.5x1.25x16.6xD8xL63-3	○	●	1.25	3	8	6.5	16.6	63
D3MT10082C208-1.5ISO	ø8.2x1.5x20.8xD10xL73-3	○	●	1.5	3	10	8.2	20.8	73
D3MT10099C250-1.75ISO	ø9.9x1.75x25xD10xL73-3	○	●	1.75	3	10	9.9	25	73
D3MT12119C330-2.0ISO	ø11.9x2.0x33xD12xL83-3	○	●	2.0	3	12	11.9	33	83
D3MT16159C413-2.5ISO	ø15.9x2.5x41.3xD16xL92-3	○	●	2.5	3	16	15.9	41.3	92

订货示例: D3MT06024C062-0.5ISO BR205 1支 Ordering example: D3MT06024C062-0.5ISO BR205 1PCS

★该尺寸可以根据需求定制 ★“L” & “L1” can be customized according to the actual demand

整体螺纹铣刀型号说明

Thread Mill insert for Deep Holes

H	E	MT	B	06	022	C	5	-0.5	ISO	-LH	BR205
1	2	3	4	5	6	7	8	9	10	11	12

1-产品类型 Line	2-刀具类型 Type of tools	3-加工方式 System	4-内冲 Cooling	5-柄径 Shank Dia.	6-刃径 Cutting Dia.	7-沟槽数 NO. of Flutes
H-螺旋槽 H-Helical	E-外槽 E-External	MT-铣削加工 MT-Thread Milling	B-内喷水 B-coolant	06-6mm 08-8mm 10-10mm 12-12mm 16-16mm	022-2.2mm " " "	C-3 D-4 E-5 F-6
S-直槽 S-Straight Flutes	N-内槽 (省略) N-Internal					
D-深孔用小槽铣刀 D-Deep Threading or Mini Thread Milling insert D-单齿 One tooth D3-三齿 Three teeth						
8-有效刃长 Tool Cutting Length	9-螺距 Pitch	10-螺纹标准 Standard	11-沟槽方向 Flute Direction	12-材质代号 Arbide Grade		
5-5.3mm " "	0.5-0.5mm " "	ISO-公制ISO螺纹 UN-美制UN螺纹 T-美制惠氏螺纹 NPT-美制NPT直锥管螺纹 BSPT-美制BSPT直锥管螺纹 " "	RH-右旋 (默认省略) RH-Right hand LH-左旋 LH-Left hand	BR205 适合不锈钢和钢 BR205 apply to stainless steel and steel DK105 适合铝合金等有色金属 DK105 apply to aluminum alloy and non-ferrous		

应用资料 Application Data

关于螺纹铣削

为了实现螺纹的铣削，机床必须具备三轴联动的功能。而螺旋插补是CNC机床的功能，由机床控制刀具实现螺旋轨迹，螺旋插补由平面圆弧插补和垂直于该平面的线性运动联动形成。例如：从A点到B点（图A）的螺旋轨迹是由X-Y的平面圆弧插补运动和Z轴的线性直线运动联动而成。

对于大多数CNC系统，可以通过如下两种不同的指令实现该功能。

G02:顺时针圆弧插补指令

G03:逆时针圆弧插补指令




图1




图2


螺纹铣削运动（图2）显示是由刀具的自身旋转和机床的螺旋插补运动形成。在一个圆周的插补过程中，利用刀具的几何形式，并结合刀具沿Z轴方向移动一个螺距的运动，加工出所需要的螺纹。螺纹铣削可以采用以下三种切入方法。

- 1 圆弧切入法
- 2 径向切入法
- 3 切向切入法

应用资料 Application Data

1 圆弧切入法

采用该方法刀具切入，切出平稳，不留切削痕迹，不产生振动，即使是加工硬材料时也是如此。该方法的程序编制比径向切入法复杂一些，建议在加工精密螺纹时推荐使用该方法。




- 1-2：快速定位
- 2-3：刀具沿圆弧进给切向切入，同时沿Z轴插补进给
- 3-4：360°整圆做螺旋插补运动，轴向移动一个导程
- 4-5：刀具沿圆弧进给切向切出，同时沿Z轴做插补运动
- 5-6：快速退回。

2 径向切入法

采用该方法最简单，但有时会出现以下两种状况：

- 一、在切入和切出点会留下很小的垂直痕迹，但不会影响螺纹的质量
- 二、在加工非常硬的材料时，当切入接近全牙型时，由于刀具与工件接触面积增大，有可能产生振刀现象。为了避免当切入接近全牙型时的振动，进给量应尽量降低到螺旋插补进给的1/3




- 1-2：快速定位
- 2-3：360°整圆做螺旋插补运动，轴向移动一个导程
- 3-4：径向退回。

应用资料 Application Data

3 切向切入法

该方法非常简单，并具有圆弧切入法的优点，不过它仅适用于外螺纹的铣削加工。




螺纹铣削数据计算

1 计算刀具的进给速度和进给量

$$n = \frac{1000 \times V_c}{\pi \times D_2}$$

$$F1 = f_x n_z$$

V_c -切削线速度 (m/min)
 n -刀具转速 (R.P.M)
 D -刀具切削直径 (mm)
 $F1$ -刀具切削刃进给速度 (mm)
 Z -刀具切削刃数量
 f -每转每齿进给量 (mm/rev)



螺纹铣削数据计算示例

1. 主轴转速(n)的计算

$$V_c = (\pi \times D \times n) / 1000$$

V_c : 线速度(m/min) π : 圆周率(3.14159) D : 刀具直径(mm) n : 转速(rpm)

示例: 使用Φ25的铣刀 V_c 为(m/min)100 求 $n=?$ rpm

$$V_c = \pi d n / 1000$$

$$100 = \pi \times 25 \times n / 1000$$

$$n = 1000 \times 100 / \pi \times 25$$

$$n = 1280 \text{ rpm}$$

2. 进给量(F值)的计算

$$F1 = n \times Z \times f$$

$F1$: 进给量(mm/min) n : 转速(rpm) Z : 刃数 f : (实际每刃进给)



示例—标准2刃立铣刀以2000rpm速度切削工件，求进给量(F值)为多少? ($F_z=0.25$ mm)

$$F1 = n \times f \times z$$

$$F1 = 2000 \times 2 \times 0.25$$

$$F1 = 1000 \text{ (mm/min)}$$

2 计算刀具中心进给量



大多数CNC机床，在编程时要求采用刀具中心进给编程。刀具的进给速度是由刀具中心进给速度的大小决定的，而刀具中心的进给速度没有直接给出，但可由刀具进给速度与刀具中心进给速度的关系方程式计算求得。

用于CNC程序的“G”代码（ISO）

代码	功能	代码	功能
%	识别代码（ISO或者EIA），+磁带结束	H	刀具长度补偿号
G00	快速移动指令	D	刀具半径补偿号
G01	直线插补指令	X	X轴坐标
G02	顺时针圆弧/螺旋插补指令CW	Y	Y轴坐标
G03	逆时针圆弧/螺旋插补指令CCW	Z	Z轴坐标
G40	刀具半径补偿取消指令	R	圆弧插补半径
G41	左偏刀具半径补偿指令	I	圆弧起点相对圆心的X轴的增量尺寸
G42	右偏刀具半径补偿指令	J	圆弧起点相对于圆心的Y轴的增量尺寸
G43	刀具长度补偿指令	M3	主轴正转
G49	刀具长度补偿取消指令	M5	主轴停止
G57	工作坐标系选择	M30	主程序结束/复位
G90	绝对坐标-相对工件坐标系的原点给出	O	程序号
G91	增量坐标-相对于刀具位置给出	N	程序段号
F	进给量mm/min	(	注释开始
S	主轴转速RPM	)	注释结束

SSL



目录 Contents

SSL


切槽(断)刀具

TGP32切槽刀具	TGP32 Grooving Tools	100~104
DBA43切槽刀具	DBA43 Grooving Tools	105~107
T11N/T16N切槽刀具	T11N/T16N Grooving Tools	108~111
GE切槽刀具	GE Grooving Tools	112~116
TKF切槽(断)刀具	TKF Parting-Off Tools	117~119
TKFB背车刀具	TKFB Back Turning Tools	120~121
THC42切槽(断)刀具	THC42 Parting-Off Tools	122~125
MGMN切槽(断)刀具	MGMN Parting-Off Tools	126~129
TD切槽(断)刀具	TD Parting-Off Tools	130~134
DQ切槽(断)刀具	DQ Parting-Off Tools	135~136

 TGF32切槽刀片 TGF32 Grooving Insert (Deep Cut)



图片为右手刀片
Right Insert(see picture)



说明:带“*”尺寸可以根据用户需求定制
* The dimension can be customized

型 号 Ordering Code	材 质 Material code	型 号 Ordering Code	材 质 Material code	尺 寸 Dimensions (mm)					
				IC±0.02	T±0.02	d	*S±0.02	*L	*R
右手刀片 Right Hand	DK310 PM125	左手刀片 Left Hand	DK310 PM125						
TGF32R033	●	TGF32L033					0.33	0.8	0.03
TGF32R045	○	TGF32L045	●				0.45		
TGF32R050	○	TGF32L050	●				0.50	1.0	
TGF32R060	○	TGF32L060	●				0.60		0.05
TGF32R065	○	TGF32L065	●				0.65	1.4	
TGF32R070	○	TGF32L070	●				0.70		
TGF32R075	○	TGF32L075	●				0.75		
TGF32R080	○	TGF32L080	●				0.80		
TGF32R085	○	TGF32L085	●				0.85	2.0	
TGF32R090	○	TGF32L090	●				0.90		
TGF32R095	○	TGF32L095	●				0.95		
TGF32R100	○	TGF32L100	●				1.00		
TGF32R110	○	TGF32L110	●				1.10		
TGF32R115	○	TGF32L115	●				1.15		
TGF32R120	○	TGF32L120	●				1.20		
TGF32R125	○	TGF32L125	●				1.25	2.2	
TGF32R130	○	TGF32L130	●				1.30		
TGF32R135	○	TGF32L135	●	9.525	3.18	4.5	1.35		
TGF32R140	○	TGF32L140	●				1.40		
TGF32R145	○	TGF32L145	●				1.45	0.1	
TGF32R150	○	TGF32L150	●				1.50		
TGF32R155	○	TGF32L155	●				1.55		
TGF32R160	○	TGF32L160	●				1.60		
TGF32R165	○	TGF32L165	●				1.65		
TGF32R170	○	TGF32L170	●				1.70	2.4	
TGF32R175	○	TGF32L175	●				1.75		
TGF32R180	○	TGF32L180	●				1.80		
TGF32R185	○	TGF32L185	●				1.85		
TGF32R190	○	TGF32L190	●				1.90		
TGF32R200	○	TGF32L200	●				2.00		
TGF32R210	○	TGF32L210	●				2.10		
TGF32R215	○	TGF32L215	●				2.15	2.7	0.15
TGF32R220	○	TGF32L220	●				2.20		
TGF32R225	○	TGF32L225	●				2.25		

转下页

接上页

型 号	材 质	型 号	材 质	尺 寸				
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)				
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	*S±0.02	*L *R
TGF32R230	○ ●	TGF32L230	●				2.30	2.7
TGF32R240	○ ●	TGF32L240	●				2.40	
TGF32R250	○ ●	TGF32L250	●				2.50	
TGF32R260	○ ●	TGF32L260	●				2.60	0.15
TGF32R265	○ ●	TGF32L265	●	9.525	3.18	4.5	2.65	
TGF32R270	○ ●	TGF32L270	●				2.70	
TGF32R275	○ ●	TGF32L275	●				2.75	3.0
TGF32R280	○ ●	TGF32L280	●				2.80	
TGF32R300	○ ●	TGF32L300	●				3.00	
TGF32R320	○ ●	TGF32L320	●				3.20	0.2


订货示例: TGF32R200-R1.0 PM125 10件

Ordering example: TGF32R200-R1.0 PM125 10pc

 TGF32切槽刀片(球头型) TGF32 Grooving Insert(Round Head)



图片为右手刀片
Right Insert(see picture)



型 号	材 质	型 号	材 质	尺 寸				
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)				
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	S±0.02	L R
TGF32R100-R0.5	○ ●	TGF32L100-R0.5	●				1.0	2.2 0.50
TGF32R120-R0.6	○ ●	TGF32L120-R0.6	○				1.2	2.2 0.60
TGF32R150-R0.75	○ ●	TGF32L150-R0.75	●				1.5	2.2 0.75
TGF32R180-R0.9	○ ●	TGF32L180-R0.9	●	9.525	3.18	4.5	1.8	2.2 0.90
TGF32R200-R1.0	○ ●	TGF32L200-R1.0	●				2.0	2.7 1.00
TGF32R250-R1.25	○ ●	TGF32L250-R1.25	●				2.5	3.0 1.25
TGF32R300-R1.5	○ ●	TGF32L300-R1.5	●				3.0	3.2 1.50


订货示例: TGF32R200-R1.0 PM125 10件

Ordering example: TGF32R200-R1.0 PM125 10pc

👉 TGF32切槽刀片(大切深) TGF32 Grooving Insert



图片为右手刀片
Right Insert(see picture)



型 号	材 质	型 号	材 质	尺 寸				
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)				
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	S±0.02	*L R
TGF32R050L220		TGF32L050L220					0.50	2.20 0.05
TGF32R100L330	○ ●	TGF32L100L330	○ ●				1.00	3.30
TGF32R150L380	○ ●	TGF32L150L380	●	9.525	3.18	4.5	1.50	3.80 0.1
TGF32R200L400	○ ●	TGF32L200L400	●				2.00	4.00
TGF32R250L400	○ ●	TGF32L250L400	●				2.50	4.00


订货示例: TGF32R200L400 PM125 10件

Ordering example: TGF32R200L400 PM125 10pc


说明: 该刀片实际最大切削深度“L”与被加工直径相关, 当直径比较大时, 实际切削深度都会小于“L”值。

Note: insert's maximum depth of cut "L" is related to the workpiece's diameter, as the larger diameter, the smaller "L" will be.

👉 TGF32切槽刀片(斜刃型) TGF32 Parting-off Insert



图片为右手刀片
Right Insert(see picture)



导程角“15°”显示为刀片安装在刀杆上后的角度

Note: Relative to the toolholder, 15° is the insert's angle after installation.

型 号	材 质	型 号	材 质	尺 寸				
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)				
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	S±0.02	*L R
TGF32R075A15	●	TGF32L075A15	●				0.75	2.30 0.05
TGF32R100A15	●	TGF32L100A15	●				1.00	3.10
TGF32R125A15	●	TGF32L125A15	●	9.525	3.18	4.5	1.25	3.60 0.1
TGF32R150A15	●	TGF32L150A15	●				1.50	3.80
TGF32R200A15	●	TGF32L200A15	●				2.00	4.00
TGF32R250A15	●	TGF32L250A15	●				2.50	4.00


订货示例: TGF32R200A12 PM125 10件

Ordering example: TGF32R200A12 PM125 10pc

切槽刀具 GROOVING TOOLS

SSL

TKGFR/L刀杆 Grooving Tools



图示为右手刀具
Right Cutting Tools(see picture)

注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手刀片(L)
Note: Right tools match with right inserts; left tools match with left inserts.


型号Ordering Code		尺寸Dimensions(mm)								型式 Type	适用刀片Insert		刀片螺钉 Insert Screw	扳手 Torx Key
右刀Right Hand	左刀Left Hand	h	b	H	F	L	H2	H1			右Right	左Left		
TKGFR1010K-16F	TKGFL1010K-16F	10	10	10	10	125	2.5	2		I				
TKGFR1212K-16F	TKGFL1212K-16F	12	12	12	12	125	2.5	-			TGF32R	TGF32L	L60M4x10	T-15
TKGFR1212M-16F	TKGFL1212M-16F	12	12	12	12	150	2.5	-						
TKGFR1616M-16F	TKGFL1616M-16F	16	16	16	16	150	2.5	-						
TKGFR1212H-16	TKGFL1212H-16	12	12	12	12	100	2.5	2		II				
TKGFR1616H-16	TKGFL1616H-16	16	16	16	20	100	2.5	-			TGF32R	TGF32L	L60M4x10	T-15
TKGFR2020K-16	TKGFL2020K-16	20	20	20	25	125	2.5	-						
TKGFR2525M-16	TKGFL2525M-16	25	25	25	32	150	2.5	-						

订货示例: TKGFR1212M-16F 1件

Ordering example: TKGFR1212M-16F 1pc

切槽(断)刀具
GROOVING TOOLS

👉 TGF、DBA型内切槽刀杆 Internal Grooving Tools



图示为右手刀具
Right Cutting Tools(see picture)

注意：右手刀具(R)配TGF32L系列刀片
Note: Right tools match with left inserts

右刀杆	尺寸Dimensions(mm)						适用刀片	刀片螺钉	扳手
Right Hand	d1	d	L	D	T	ØDmin	Insert	Insert Screw	Torx Key
S16K-SRTGF3219	16	16	125	15	2	19	TGF32L***	L60M4X10	T-15
S20M-SRTGF3223	20	20	150	19	2	23		L60M4X10	T-15
S25Q-SRTGF3227	25	25	180	23	2.5	27		L60M4X10	T-15
S25R-SRDBA4329	25	25	200	23	3.5	29	DBA43L***	L60M5X11	T-20
S32S-SRDBA4335	32	32	250	30	3.3	35		L60M5X11	T-20

订货示例: S20M-SRTGF3219 1件


Ordering example: S20M-SRTGF3219 1pc

刀具切深说明:
explanation of tool's cutting depth:

当 "T" 值小于标准刀片切深时, 切深参考 "T" 值
When the "T" value is less than the standard blade cutting depth, reference to "T" value

当 "T" 值大于标准刀片切深时, 切深参考刀片切深
When the "T" value is higher than the standard blade cutting depth, reference to blade cutting depth

👉 TGF32切槽刀杆(排刀型) Gang-type Grooving Tools



图示为左手刀具
Right Cutting Tools(see picture)

注意：左手刀具(R)配TGF32R系列刀片
Note: Left tools match with right inserts

型号Ordering Code	尺寸Dimensions(mm)								适用刀片Insert	刀片螺钉	扳手
左刀Left Hand	h	b	H	F	L	H2	H1	L1	右Right Hand	Insert Screw	Torx Key
TKGFL1010F-16-A90	10	10	10	12	85	2.5	2	16	TGF32R****	L60M4x10	T-15
TKGFL1212H-16-A90	12	12	12	16	100	2.5	-	20			
TKGFL1616H-16-A90	16	16	16	20	100	2.5	-	24			
TKGFL2020K-16-A90	20	20	20	25	125	2.5	-	30			
TKGFL2525M-16-A90	25	25	25	32	150	2.5	-	35			

订货示例: TKGFL1212H-16-A90 1件

Ordering example: TKGFL1212M-16-A90 1pc

切槽刀具 GROOVING TOOLS


SSL

接上页




DBA43切槽刀片

DBA43 Grooving Insert



图片为右手刀片
Right Insert (see picture)



型 号	材 质	型 号	材 质	尺 寸					
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)					
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	*S±0.02	*L	*R
DBA43R075	●	DBA43L075					0.75		
DBA43R100	●	DBA43L100					1.00	2.5	
DBA43R120	●	DBA43L120					1.20		
DBA43R130	●	DBA43L130					1.30		
DBA43R140	●	DBA43L140					1.40	2.7	0.1
DBA43R145	●	DBA43L145					1.45		
DBA43R150	●	DBA43L150					1.50	3.0	
DBA43R160	●	DBA43L160					1.60		
DBA43R170	○	DBA43L170					1.70		
DBA43R175	○	DBA43L175					1.75		
DBA43R180	○	DBA43L180					1.80	3.3	
DBA43R185	●	DBA43L185					1.85		
DBA43R195		DBA43L195					1.95		
DBA43R200	●	DBA43L200	●				2.00		0.2
DBA43R210	○	DBA43L210					2.10		
DBA43R220	○	DBA43L220	○				2.20	3.5	
DBA43R225	○	DBA43L225	●				2.25		
DBA43R230	○	DBA43L230	●				2.30		
DBA43R240	○	DBA43L240	●				2.40		
DBA43R250	●	DBA43L250		12.7	4.76	5.4	2.50		
DBA43R265	○	DBA43L265	●				2.65	4.2	
DBA43R270	●	DBA43L270					2.70		
DBA43R280	○	DBA43L280	●				2.80		
DBA43R300	●	DBA43L300	○				3.00	4.6	
DBA43R320	○	DBA43L320	○				3.20		
DBA43R325	○	DBA43L325	○				3.25		
DBA43R330	○	DBA43L330	○				3.30		
DBA43R350	○	DBA43L350	●				3.50		
DBA43R360	○	DBA43L360	○				3.60	4.8	0.3
DBA43R380	●	DBA43L380					3.80		
DBA43R400	○	DBA43L400	●				4.00		
DBA43R420	○	DBA43L420	○				4.20		
DBA43R450	○	DBA43L450	○				4.50		
DBA43R460	○	DBA43L460	○				4.60	5.0	
DBA43R470	○	DBA43L470	○				4.70		
DBA43R480	○	DBA43L480	○		4.90		4.80		
DBA43R200-R0.5	○	DBA43L200-R0.5	○	12.7	4.76	5.4	2.00	3.5	0.5
DBA43R250-R0.5	○	DBA43L250-R0.5	○				2.50	4.2	

转下页

切槽(断)刀具
GROOVING TOOLS

DBA43R300-R0.5	○	●	DBA43L300-R0.5	○					3.00	3.0	
DBA43R350-R0.5	○	●	DBA43L350-R0.5	○		12.7	4.76	5.4	3.50	3.5	0.5
DBA43R400-R0.5	○	●	DBA43L250-R0.5	○					4.00	4.0	


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: DBA43R330 PM125 10片 Ordering example: DBA43R330 PM125 10pcs

DBA43切槽刀片(球头型) DBA43 Grooving Insert



图片为右手刀片
Right insert(see picture)



型 号	材质	型 号	材质	尺寸						
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)						
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	IC±0.02	T±0.02	d	*S±0.02	*L	*R	
DBA43R200-R1.0	○ ●	DBA43L200-R1.0	○ ○				2.00	3.5	1.0	
DBA43R250-R1.25	○ ○	DBA43L250-R1.25	○ ○	12.7	4.76	5.4	2.50	4.6	1.25	
DBA43R300-R1.5	○ ●	DBA43L300-R1.5	○ ○				3.00	4.6	1.5	
DBA43R400-R2.0	○ ●	DBA43L400-R2.0	○ ○				4.00	5.0	2.0	


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: DBA43R300-R1.5 PM125 10片 Ordering example: DBA43R300-R1.5 PM125 10pcs

切槽刀具 GROOVING TOOLS

SSL

DBA43切槽刀杆 Grooving Tools



图示为右手刀具
Right Cutting Tools(see picture)

注意：右手刀具 (R) 配右手刀片 (R)，左手刀具 (L) 配左手刀片 (L)
Note: Right tools match with right inserts; left tools match with left inserts.


型号Ordering Code		尺寸Dimensions(mm)								适用刀片Insert		刀片螺钉	扳手	压板	夹头螺栓	扳手
右刀Right Hand	左刀Left Hand	h	b	H	F	L	HL	T		右Right	左Left	Insert Screw	Torx Key	Clamp	Clamp Screw	Hex wrench
TKGBAR2020K22-35	TKGBAL2020K22-35	20	20	20	25	125		4.2		DBA43R075~320	DBA43L075~320					
TKGBAR2525M22-35	TKGBAL2525K22-35	25	25	25	32	150										
TKGBAR2020K22-52	TKGBAL2020K22-52	20	20	20	25	125	4					L60M5x11	T-20	HI1814	MI0625	S2.5
TKGBAR2525M22-52	TKGBAL2525M22-52	25	25	25	32	150		5.2		DBA43R320~480	DBA43L320~480					
TKGBAR3232P22-52	TKGBAL3232P22-52	32	32	32	40	170										

订货示例：TKGBAR2020K22-35 1件 Ordering example: TKGBAR2020K22-35 1pc

 T11/T16平装切槽刀片 T11/T16 Circlip Grooving Insert



图片为内切槽刀片
Internal Grooving Insert(see picture)



当“S”值较小时，刀杆上的垫片有可能发生干涉，用户需根据实际情况把发生干涉的部位磨掉。

型 号 Ordering Code 内切槽刀片 Internal grooving insert	材质 Material code DK110 PM125	型 号 Ordering Code 外切槽刀片 External grooving insert	材质 Material code DK110 PM125	尺寸 Dimensions (mm)			
				T	S±0.02	L	R
T11N040	●	T11E040			0.40	1.00	
T11N050	●	T11E050			0.50	1.00	
T11N060	●	T11E060			0.60	1.00	
T11N070	●	T11E070			0.70	1.20	0.05
T11N080	●	T11E080			0.80	1.20	
T11N090	●	T11E090			0.90	1.20	
T11N100	○ ●	T11E100	○ ●	3.18	1.00	1.50	
T11N110	●	T11E110			1.10	1.50	
T11N120	○ ●	T11E120	○ ○		1.20	1.50	
T11N130	○ ●	T11E130			1.30	1.50	
T11N140	○ ●	T11E140	○ ●		1.40	1.50	0.1
T11N150	○ ●	T11E150	○ ●		1.50	1.50	
T11N160	○ ●	T11E160			1.60	1.40	
T11N170	○ ●	T11E170			1.70	1.40	
T11N180	●	T11E180			1.80	1.30	
T11N200	○ ●	T11E200	○ ●		2.00	1.20	
T16N033	●	T16E033			0.33		
T16N040	●	T16E040			0.40		
T16N050	●	T16E050			0.50		
T16N060	●	T16E060			0.60	1.6	0.05
T16N070	●	T16E070			0.70		
T16N075	●	T16E075			0.75		
T16N080	○ ●	T16E080	○ ●		0.80		
T16N095	○ ●	T16E095	○ ○		0.95		
T16N100	○ ●	T16E100	○ ●		1.00		
T16N110	○ ●	T16E110	○ ○		1.10		
T16N115	○ ●	T16E115	○ ○		1.15		
T16N120	○ ●	T16E120	○ ●		1.20		
T16N125	○ ●	T16E125	○ ○		1.25		
T16N130	○ ●	T16E130			1.30		
T16N140	○ ●	T16E140	○ ●	3.65	1.40	1.8	0.1
T16N145	○ ●	T16E145	○ ○		1.45		
T16N150	○ ●	T16E150	○ ●		1.50		
T16N160	○ ●	T16E160	○ ●		1.60		
T16N175	○ ●	T16E175	○ ○		1.75		
T16N180	○ ●	T16E180	○ ●		1.80		
T16N200	○ ●	T16E200	○ ●		2.00		

切槽刀具 GROOVING TOOLS

SSL

接上页


型 号 Ordering Code 内切槽刀片 Internal grooving insert	材 质 Material code DK110 PM125	型 号 Ordering Code 外切槽刀片 External grooving insert	材 质 Material code DK110 PM125	尺 寸 Dimensions (mm) T 5±0.02 L R
T16N215	○ ●	T16E215	○ ●	2.15
T16N225	○ ○	T16E225	○ ○	2.25
T16N230	○ ●	T16E230	○ ●	2.30
T16N250	○ ●	T16E250	○ ●	2.50
T16N265	○ ●	T16E265	○ ●	2.65
T16N300	○ ●	T16E300	○ ●	3.00

●:常备库存(主槽) Stock standard(main) ○:一般库存 Stock standard

订货示例: T16N200 PM125 10片 Ordering example: T16N200 PM125 10pcs

T11/T16切槽刀具 T11/T16 Grooving Tools

内孔槽刀具 Internal



图片为右手刀具 (SNR00**系列内切槽刀杆)
Right Cutting Tools(see picture)

注:右手刀具配T16N、T11N系列刀片,左手刀具配T16E、T11E系列刀片
Note:right tools match with T16N、T11N inserts;left tools match with T16E、T11E inserts.

型号Ordering Code	尺寸Dimensions(mm)	刀片Insert	刀片螺钉	扳手	刀垫	侧面螺钉	扳手
右刀Right Hand左刀Left Hand	d1 d F L h L1 Dmin	右刀 Right 左刀 Left	Insert Screw	Torx Key	Anvil	Anvil Screw	Hex Wrench
SNR0010H11 SNL0010H11	10 10 7.4 100 9 12 12	T11N. T11E.	L80M2.5x8	T-08	-	-	-
SNR0012K11 SNL0012K11	12 12 8.4 125 11 15 15	T11N. T11E.	L80M2.5x8	T-08	-	-	-
SNR0013M11 SNL0013M11	13 16 8.9 150 15 25 15	T11N. T11E.	L80M2.5x8	T-08	-	-	-
SNR0013M16 SNL0013M16	13 16 10.2 150 15 25 16	T16N. T16E.	L60M3.5x8	T-15	-	-	-
SNR0016M16 SNL0016M16	15 16 11.7 150 15 25 19	T16N. T16E.	L60M3.5x8	T-15	-	-	-
SNR0020Q16 SNL0020Q16	19 20 13.7 180 18 24 24	T16N. T16E.	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SNR0025R16 SNL0025R16	24 25 16.2 200 23 29 29	T16N. T16E.	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SNR0032S16 SNL0032S16	31 32 19.7 250 30 36 36	T16N. T16E.	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SNR0040T16 SNL0040T16	38 40 23.7 300 37 44 44	T16N. T16E.	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SNR0050U16 SNL0050U16	47 50 28.7 350 46 54 54	T16N. T16E.	L60M3.5x12	T-15	GM-16	MQ040080	S2.5



订货示例: SNR0020M16 1件

Ordering example: SER2020K16 1pc

切槽(断)刀具
GROOVING TOOLS

T11/T16切槽刀具 T11/T16 Grooving Tools

外圆槽刀具 External



注:右平刀具配T16E, T11E系列刀片,左平刀具配T16N, T11N系列刀片
Note:right tools match with T16E, T11E inserts;left tools match with T16N, T11N inserts.

型号Ordering Code		尺寸Dimensions(mm)					刀片Insert		刀片螺钉	扳手	刀垫	侧面螺钉	扳手
右刀Right Hand	左刀Left Hand	h	b	H	F	L	右刀Right	左刀Left	Insert Screw	Torx Key	Anvil	Anvil Screw	Hex Wren
SER1212F16	SEL1212F16	12	12	12	16	80	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SER1616H16	SEL1616H16	16	16	16	20	100	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SER2020K16	SEL2020K16	20	20	20	25	125	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SER2525M16	SEL2525M16	25	25	25	32	150	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SER3225P16	SEL3225P16	32	25	32	32	170	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5
SER3232P16	SEL3232P16	32	32	32	40	170	T16N	T16E	L60M3.5x12	T-15	GM-16	MQ040080	S2.5

订货示例: SER2020K16 1件

Ordering example: SER2020K16 1pc




切槽刀具 GROOVING TOOLS

SSL

T16N/T22N端面切槽刀片 T16N/T22N Circlip Grooving Insert



图片为内切槽刀片
Internal Grooving Insert(see picture)



注意：该刀片配合螺纹车刀杆使用。
Note: The insert should be fitted in threading

型 号 Ordering Code	材质 Material code		适用刀杆 The Cutter Bar	所在 页码	端面尺寸 Dmin~Dmax	尺寸 Dimensions (mm)					
	DK110	PM125				IC	d	T	S±0.02	L	R
T16N150DM10	○	●							1.50	1.8	
T16N200DM10	○	●	SEL***-16		10~∞	9.525	4	3.65	2.00	2.2	
T16N250DM10	○	●							2.50	2.2	
T22N200DM15	○	●							2.00	3.0	0.1
T22N250DM15	○	●	SEL***-22		15~∞	12.7	5	4.76	2.50	3.0	
T22N300DM15	○	●		40					3.00	3.0	
T16N150DM10R075	○	●	SEL***-16	41	10~∞	9.525	4	3.5	1.50	2.0	0.75
T16N200DM10R100	○	●							2.00	2.2	1.0
T22N200DM15R100	○	●	SEL***-22						2.00	3.0	1.0
T22N250DM15R125	○	●			15~∞	12.7	5	4.76	2.50	3.0	1.25


●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: T16N200DM10 PM125 10片 Ordering example: T16N200DM10 PM125 10pcs

T16N/T22N 端面切槽刀具 T16N/T22N Circlip Grooving Tools



图片为左手刀具
Right Cutting Tools(see picture)



型号Ordering Code	尺寸Dimensions(mm)					刀片Insert	刀片螺钉 Insert Screw	扳手 Torx Key	刀垫 Anvil	侧压螺钉 Anvil Screw	扳手 Hex Wren
左刀Left Hand	h	b	H	F	L						
SEL1212F16	12	12	12	16	80	T16N.	L60M3.5x12	T-15	GM-16	MQ030080	T10
SEL1616H16	16	16	16	20	100	T16N.	L60M3.5x12	T-15	GM-16	MQ030080	T10
SEL2020K16	20	20	20	25	125	T16N.	L60M3.5x12	T-15	GM-16	MQ030080	T10
SEL2525M16	25	25	25	32	150	T16N.	L60M3.5x12	T-15	GM-16	MQ030080	T10
SEL2525M22	25	25	25	32	150	T22N.	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SEL3225P22	32	25	32	32	170	T22N.	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5
SEL3232P22	32	32	32	40	170	T22N.	L60M4.5x14	T-20	EGM-22	MQ040080	S2.5

订货示例: SER2020K161件




Ordering example: SER2020K16 1pc

切槽(断)刀具
GROOVING TOOLS

GE切槽刀片 GE Grooving Insert



型号	A	L	H	Φd
GERL...A	6.69	6.5	2.58	2.5
GERL...AR				
GERL...B	8.46	8.2	3.18	2.7
GERL...BR				

形状 Shape	右刀片 Right Hand	左刀片 Left Hand	材质 Material Code		刀片尺寸 Dimensions (mm)			适用刀杆 Toolholders	
			DK110	PM125	W	B	r		
 	GER050-A	GEL050-A	○	●	0.50	1.2	0.05	SIGER/L...A	
	GER060-A	GEL060-A	○	●	0.60				
	GER070-A	GEL070-A	○	●	0.70				
	GER080-A	GEL080-A	○	●	0.80				
	GER100-A	GEL100-A	○	●	1.00	1.5	0.1		SIGER/L...B
	GER120-A	GEL120-A	○	●	1.20				
	GER125-A	GEL125-A	○	●	1.25				
	GER140-A	GEL140-A	○	●	1.40				
	GER150-A	GEL150-A	○	●	1.50	2.2	0.1	SIGER/L...B	
	GER180-A	GEL180-A	○	●	1.80				
	GER200-A	GEL200-A	○	●	2.00				
	GER080-B	GEL080-B	○	●	0.80	1.8	0.05		
	GER100-B	GEL100-B	○	●	1.00				
	GER120-B	GEL120-B	○	●	1.20				
	GER125-B	GEL125-B	○	●	1.25				
	GER130-B	GEL130-B	○	●	1.30	2.2	0.1		
	GER145-B	GEL145-B	○	●	1.45				
	GER150-B	GEL150-B	○	●	1.50				
	GER180-B	GEL180-B	○	●	1.80	3.0	0.2		
	GER200-B	GEL200-B	○	●	2.00				
	GER225-B	GEL225-B	○	●	2.25				
	GER250-B	GEL250-B	○	●	2.50				
GER280-B	GEL280-B	○	●	2.80	2.5	1.25		SIGER/L...B	
GER300-B	GEL300-B	○	●	3.00					
 	GER100-050AR	GEL100-050AR	○	●	1.00	1.5	0.75	SIGER/L...A	
	GER150-075AR	GEL150-075AR	○	●	1.50				
	GER200-100AR	GEL200-100AR	○	●	2.00	2.2	1.0	SIGER/L...B	
	GER100-050BR	GEL100-050BR	○	●	1.00				
	GER150-075BR	GEL150-075BR	○	●	1.50	2.5	0.05	SIGER/L...C	
	GER200-100BR	GEL200-100BR	○	●	2.00				
	GER250-125BR	GEL250-125BR	○	●	2.50	2.5	0.1		
	GER300-150BR	GEL300-150BR	○	●	3.00				
 	GER100-C	GEL100-C	○	●	1.00	2.5	0.05	SIGER/L...C	
	GER120-C	GEL120-C	○	●	1.20				
	GER125-C	GEL125-C	○	●	1.25	2.5	0.1	SIGER/L...C	
	GER140-C	GEL140-C	○	●	1.40				
	GER145-C	GEL145-C	○	●	1.45	2.5	0.1	SIGER/L...C	



切槽刀具 GROOVING TOOLS

SSL

GE切槽刀片 GE Grooving Insert

型号	A	L	H	Φd
GER/L...C	5.8	11.48	4.05	2.8
GER/L...CR	5.8	11.48	4.05	2.8
GER/L...D	6.8	16.44	5.05	3.4
GER/L...DR	6.8	16.44	5.05	3.4
GER/L...E	9.54	21.68	5.55	4.4




形状 Shape	右刀片 Right Hand	左刀片 Left Hand	材质 Material Code		刀片尺寸 Dimensions (mm)			适用刀杆 Toolholders
			DK110	PM125	W	B	f	
 	GER150-C	GEL150-C	○	●	1.50			SIGER/L...C
	GER160-C	GEL160-C	○	●	1.70			
	GER170-C	GEL170-C	○	●	1.85			
	GER185-C	GEL185-C	○	●	1.85		0.1	
	GER195-C	GEL195-C	○	●	1.95			
	GER200-C	GEL200-C	○	●	2.00			
	GER225-C	GEL225-C	○	●	2.25			
	GER250-C	GEL250-C	○	●	2.50	2.5		
	GER275-C	GEL275-C	○	●	2.75			
	GER280-C	GEL280-C	○	●	2.80		0.2	
	GER300-C	GEL300-C	○	●	3.00			
	GER320-C	GEL320-C	○	●	3.20			
	GER350-C	GEL350-C	○	●	3.50			
 	GER100-D	GEL100-D	○	●	1.00			SIGER/L...D
	GER120-D	GEL120-D	○	●	1.20			
	GER125-D	GEL125-D	○	●	1.25	2.25	0.05	
	GER140-D	GEL140-D	○	●	1.40			
	GER145-D	GEL145-D	○	●	1.45			
	GER160-D	GEL160-D	○	●	1.60			
	GER170-D	GEL170-D	○	●	1.70			
	GER185-D	GEL185-D	○	●	1.85		0.1	
	GER195-D	GEL195-D	○	●	1.95			
	GER200-D	GEL200-D	○	●	2.00			
	GER225-D	GEL225-D	○	●	2.25			
	GER230-D	GEL230-D	○	●	2.30	3.8		
	GER250-D	GEL250-D	○	●	2.50			
	GER275-D	GEL275-D	○	●	2.75			
	GER280-D	GEL280-D	○	●	2.80			
	GER300-D	GEL300-D	○	●	3.00		0.2	
	GER320-D	GEL320-D	○	●	3.20			
	GER330-D	GEL330-D	○	●	3.30	4.5		
GER350-D	GEL350-D	○	●	3.50				
GER400-D	GEL400-D	○	●	4.00				
 	GER100-050CR	GEL100-050CR	○	●	1.00		0.5	SIGER/L...C
	GER150-075CR	GEL150-075CR	○	●	1.50		0.75	
	GER200-100CR	GEL200-100CR	○	●	2.00	2.5	1.0	
	GER250-125CR	GEL250-125CR	○	●	2.50		1.25	
	GER300-150CR	GEL300-150CR	○	●	3.00		1.5	

切槽(断)刀具
GROOVING TOOLS

GE切槽刀片 Grooving Insert

型号	A	L	H	Φd
GERL-C	5.8	11.48	4.05	2.8
GERL-CR				
GERL-D	6.8	16.44	5.05	3.4
GERL-DR				
GERL-E	9.54	21.66	5.55	4.4



形状 Shape	右刀片 Right Hand	左刀片 Left Hand	材质 Material Code		刀片尺寸 Dimensions (mm)			适用刀杆 Toolholders
								Toolholders
			DK110	PM125	W	B	r	
	GER150-075DR	GEL150-075DR	○	●	1.50	3.2	0.75	SIGER/L...D
	GER200-100DR	GEL200-100DR	○	●	2.00	3.2	1.0	
	GER250-125DR	GEL250-125DR	○	●	2.50	4.5	1.25	
	GER300-150DR	GEL300-150DR	○	●	3.00	4.5	1.5	
	GER100-E	GEL100-E		●	1.00	2.5	0.05	SIGER/L...E
	GER150-E	GEL150-E		●	1.50			
	GER170-E	GEL170-E	○		1.70	3.0		
	GER185-E	GEL185-E	○		1.85		0.1	
	GER195-E	GEL195-E	○		1.95			
	GER200-E	GEL200-E		●	2.00			
	GER225-E	GEL225-E	○		2.25	3.2		
	GER230-E	GEL230-E	○		2.30			
	GER250-E	GEL250-E		●	2.50			
	GER275-E	GEL275-E	○		2.75			
	GER280-E	GEL280-E	○		2.80	4.5		
	GER300-E	GEL300-E		●	3.00			
	GER330-E	GEL330-E	○		3.30		0.2	
	GER350-E	GEL350-E		●	3.50			
	GER400-E	GEL400-E		●	4.00	5.5		
	GER430-E	GEL430-E	○		4.30			
	GER450-E	GEL450-E		●	4.50			
	GER460-E	GEL460-E	○		4.60	6.5		
	GER500-E	GEL500-E		●	5.00			
	GER250-125ER	GEL250-125ER		○	2.50		1.25	SIGER/L...E
	GER300-150ER	GEL300-150ER		○	3.00	5.5	1.5	
	GER350-175ER	GEL350-175ER		○	3.50		1.75	
	GER400-200ER	GEL400-200ER		○	4.00		2.0	
	GER450-225ER	GEL450-225ER		○	4.50	6.5	2.25	
	GER500-250ER	GEL500-250ER		○	5.00		2.5	


订货示例: GER200-E PM125 10片 Ordering example: GER200-E PM125 10pcs

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

切槽刀具 GROOVING TOOLS

SSL

☞ SIGE型刀杆 SIGE Type Excellent Bar



图为右手刀具
Right Cutting Tools(see picture)

注意：右手刀具(R)配右手刀片(R)，左手刀具(L)配左手刀片(L)
Note: Right tools match with right inserts; left tools match with left inserts.

右刀杆	左刀杆	尺寸Dimensions(mm)							最小加工直径	适用刀片	刀片螺钉	扳手
Right Hand	Left Hand	d1	d	F	L	h	T	Dmin		Insert	Insert Screw	Torx Key
SIGER0808A	SIGEL0808A	8	7.2	100	20	4.8	1.5	8		GER/L100-A~200-A	L80M2.2X5	T6
★ SIGER0808A-WH	SIGEL0808A-WH	8	7.2	100	20	4.8	1.5	8		GER100-050AR~200-100AR		
SIGER1010B	SIGEL1010B	10	9	125	25	6.2	2.2	10		GER/L100-B~300-B		
★ SIGER1010B-WH	SIGEL1010B-WH	10	9	125	25	6.2	2.2	10		GER100-050BR~200-100BR	L80M2.5X8	T8
SIGER1210B	SIGEL1210B	10	9	125	30	7	2.2	12				
SIGER1412C	SIGEL1412C	12	11.4	150	33	8	2.5	14		GER/L100-C~350-C		
SIGER1612C	SIGEL1612C	12	11.4	150	20	8.5	2.5	16			L80M2.5X8	T8
SIGER1616C	SIGEL1616C	16	15	160	36	9	2.5	16		GER200-100CR~300-150CR		
SIGER2020D	SIGEL2020D	20	19	180	40	12.1	4.5	20		GER/L100-D~400-D	L80M3.0X8.0	T10
SIGER2525D	SIGEL2525D	25	24	200	45	12.3	4.2	25		GER200-100DR~300-150DR		
SIGER2525E	SIGEL2525E	25	24	200	48	15.6	6.5	25				
SIGER3232E	SIGEL3232E	32	30.4	220	55	19	6.5	32		GER/L100-E~500-E	L80M4.0X8.5	T15
SIGER4032E	SIGEL4032E	32	30.4	250	45	23	6.5	40				

订货示例: SIGER2020D 1支 Ordering example: SIGER2020D 1pcs

★ 为硬质合金加强抗震型刀杆



★ reinforced shock-resistant cemented carbide holder

切槽(断)刀具
GROOVING TOOLS

GER 端面切槽刀片 GER Circlip Grooving Insert



图片为内切槽刀片
Internal Grooving Insert(see picture)



型 号 Ordering Code	材质 Material code		适用刀杆 The Cutter Bar	端面圆尺寸 Dmin~Dmax	尺寸 Dimensions (mm)			
	DK110	PM125			S±0.02	B	R	
GER100DM06-D	○	●	SEGEL1010F-D	6~∞	1.00	2.5	0.05	
GER150DM10-D	○	●		10~∞	1.50	2.8	0.1	
GER200DM10-D	○	●			2.00	3.5		
GER250DM15-D	○	●	SEGEL1212H-D	15~∞	2.50	4.5	0.2	
GER300DM15-D	○	●	SEGEL1616H-D		3.00	4.5		
GER400DM15-D	○	●			4.00	4.5		
★ GER150DM10R075-D	○	●	SEGEL2020K-D	10~∞	1.50	2.5	0.75	
★ GER200DM10R100-D	○	●			2.00	3.5	1.0	
★ GER250DM15R125-D	○	●		SEGEL2525M-D	15~∞	2.50	4.5	1.25
★ GER300DM15R150-D	○	●	3.00			4.5	1.5	
★ GER400DM15R200-D	○	●	4.00			4.5	2.0	

●常备库存(主槽) Stock standard(main) ○一般库存 Stock standard


订货示例: GER200DM15-D PM125 10片 Ordering example: GER200DM15-D PM125 10pcs

★ 刃口为圆弧刃口 ★ Circular arc cutting edge

SEGE刀杆 Grooving Tools



图为左手刀具
Right Cutting Tools(see picture)



注意: 左手刀具配GER系列刀片, 右手刀具配GEL系列刀片
Note: Left tools match with right inserts, Right tools match with left inserts.

左刀杆 Left Hand	尺寸Dimensions (mm)						适用刀片 Right	刀片螺钉 Insert Screw	扳手 Torx Key
	h	b	L	F	H	Dmin			
SEGEL1010K-D	10	10	125	10	10	10	GER***-D	L60M3.6X8.0	T8
SEGEL1212K-D	12	12	125	12	12	12			
SEGEL1616H-D	16	16	100	20	16	16			
SEGEL2020K-D	20	20	125	25	20	20	GER***DM15-D		
SEGEL2525M-D	25	25	150	32	25	25			

★ 当配GER***-D系列刀片时, 可切外槽

★ It can be used for external grooving, when matched with GER-D series insert

★ 当配GER***DM15-D系列刀片时, 可切端面槽

★ It can be used for face grooving, when matched with GER-DM15-D series insert

TKF12系列切断刀片 TKF12 Parting-off Insert




S槽型刀片
S-Chipbreaker



NB槽型刀片
Without Chipbreaker




无导程角
Without Lead Angle




注：导程角“A”显示为刀片安装在刀杆上面后的角度
Note: Relative to the toolholder, A is the insert's angle after installation.



导程角
Lead Angle




无导程角
Without Lead Angle



注：导程角“A”显示为刀片安装在刀杆上面后的角度
Note: Relative to the toolholder, A is the insert's angle after installation.



导程角
Lead Angle



型 号 Ordering Code	材质 Material code	型 号 Ordering Code	材质 Material code	导程角 Lead Angle	尺寸 Dimensions (mm)					
右平刀片 Right Hand	DC110 PM125	左手刀片 Left Hand	DC110 PM125		IC±0.02	T±0.02	d	*S±0.03	*D	*R
TKF12R050-S	○ ●	TKF12L050-S						0.5	5	
TKF12R070-S	○ ●	TKF12L070-S						0.7	8	
TKF12R100-S	○ ●	TKF12L100-S	●	0°	8.7	3	5	1.0		0.03
TKF12R150-S	○ ●	TKF12L150-S	●					1.5	12	
TKF12R200-S	○ ●	TKF12L200-S	●					2.0		
TKF12R050-S16R	○ ●	TKF12L050-S16R						0.5	5	
TKF12R070-S16R	○ ●	TKF12L070-S16R						0.7	8	
TKF12R100-S16R	○ ●	TKF12L100-S16R	○	16°	8.7	3	5	1.0		0.05
TKF12R150-S16R	○ ●	TKF12L150-S16R	○					1.5	12	
TKF12R200-S16R	○ ●	TKF12L200-S16R	○					2.0		
TKF12R050-NB	○ ●	TKF12L050-NB	○					0.5	5	
TKF12R070-NB	○ ●	TKF12L070-NB	○					0.7	8	
TKF12R100-NB	○ ●	TKF12L100-NB	○	0°	8.7	3	5	1.0		0.03
TKF12R150-NB	○ ●	TKF12L150-NB	○					1.5	12	
TKF12R200-NB	○ ●	TKF12L200-NB	○					2.0		
TKF12R050-NB-20DR	○ ●	TKF12L050-NB-20DR	○					0.5	5	
TKF12R070-NB-20DR	○ ●	TKF12L070-NB-20DR	○					0.7	8	
TKF12R100-NB-20DR	○ ●	TKF12L100-NB-20DR	○	20°	8.7	3	5	1.0		0.05
TKF12R150-NB-20DR	○ ●	TKF12L150-NB-20DR	○					1.5	12	
TKF12R200-NB-20DR	○ ●	TKF12L200-NB-20DR	○					2.0		

●:常备库存(主挂) Stock standard(main) ○:一般库存 Stock standard

订货示例: TKF12R200-S PM125 10片 Ordering example: TKF12R200-S PM125 10pcs

★该尺寸可以根据需求定制 ★“L” & “L1” can be customized according to the actual demand

 TKF16系列切断刀片 TKF16 Parting-off Insert




S槽型刀片
S-Chipbreaker



NB槽型刀片
Without Chipbreaker




无导程角
Without Lead Angle




注：导程角“A”显示为刀片安装在刀杆上面后的角度
Note: Relative to the toolholder, A is the insert's angle after installation.



导程角
Lead Angle




无导程角
Without Lead Angle



注：导程角“A”显示为刀片安装在刀杆上面后的角度
Note: Relative to the toolholder, A is the insert's angle after installation.



导程角
Lead Angle




型 号 Ordering Code	材 质		型 号 Ordering Code	材 质		导程角 Lead Angle	尺 寸						
	Material code			Material code			Dimensions (mm)						
	DK110	PM125		左平刀片 Left Hand	DK110		PM125	IC±0.02	T±0.02	d	*S±0.03	*D	*R
TKF16R100-S	○	●	TKF16L100-S								1.0		
TKF16R150-S	○	●	TKF16L150-S		●						1.5		
TKF16R200-S	○	●	TKF16L200-S		●	0°	9.5	4	5		2.0	16	0.05
TKF16R250-S	○	●	TKF16L250-S		●						2.5		
TKF16R300-S	○	●	TKF16L300-S		●						3.0		
TKF16R100-S16R	○	●	TKF16L100-S16R								1.0		
TKF16R150-S16R	○	●	TKF16L150-S16R								1.5		
TKF16R200-S16R	○	●	TKF16L200-S16R		○	16°	9.5	4	5		2.0	16	0.05
TKF16R250-S16R	○	●	TKF16L250-S16R		○						2.5		
TKF16R300-S16R	○	●	TKF16L300-S16R		○						3.0		
TKF16R100-NB	○	●	TKF16L100-NB		○						1.0		
TKF16R150-NB	○	●	TKF16L150-NB		○						1.5		
TKF16R200-NB	○	●	TKF16L200-NB		○	0°	9.5	4	5		2.0	16	0.05
TKF16R250-NB	○	●	TKF16L250-NB		○						2.5		
TKF16R300-NB	○	●	TKF16L300-NB		○						3.0		
TKF16R100-NB-20DR	○	●	TKF16L100-NB-20DR		○						1.0		
TKF16R150-NB-20DR	○	●	TKF16L150-NB-20DR		○						1.5		
TKF16R200-NB-20DR	○	●	TKF16L200-NB-20DR		○	20°	9.5	4	5		2.0	16	0.05
TKF16R250-NB-20DR	○	●	TKF16L250-NB-20DR		○						2.5		
TKF16R300-NB-20DR	○	●	TKF16L300-NB-20DR		○						3.0		

●常备库存(主选) Stock standard(main) ○一般库存 Stock standard

订货示例: TKF12R200-S PM125 10片 Ordering example: TKF12R200-S PM125 10pcs

★该尺寸可以根据需求定制 ★“L” & “L1” can be customized according to the actual demand

👉 刀片型号表示方法 Representation method for blade type



刀杆	右手刀(R)	刀杆	左手刀(L)
刀片	右手刀(R)	刀片	左手刀(L)
导程角	右手刀(R)	导程角	右手刀(R)

👉 走芯机刀杆专用螺钉


Screw for CNC Precision Automatic Lathe tool holders



订货型号SP-M4X10

Ordering code: SP-M4X10

- ★ 走芯机刀杆专用螺钉 (M4X10)
Screw for CNC Precision Automatic Lathe tool holders (M4*10)
- ★ 从正面锁紧使用扳手T15, 从背面锁紧使用扳手T8
Front Side: Locking with T15 Wrench
Reverse Side: Locking with T8 Wrench
- ★ 需单独订购
Ordered Separately
- ★ 适配于TGF32、TKF12/16、TKFB、THC42系列刀具
Apply to: Tool Holders for inserts TGF32, TKF12/16, TKFB, THC42




螺钉可在刀杆
另一侧拧松,
方便拆换刀片

SSL 切槽刀具 GROOVING TOOLS

👉 TKFB背车加工刀片 TKFB Back Turning Insert



图片为右手刀片
Right Insert(see picture)



型 号 Ordering Code	材 质 Material code	适用刀杆 (详见P10) Application of a knife(see P10)	尺寸 Dimensions (mm)						
			3C	T	W	A	*L	d	*R
TKFB12R15005M	○ ●	KTKFR..12	8.7	3	1.5	0.25	2.6		<0.05
TKFB12R28005M	○ ●				2.8	0.3	4.6		<0.05
TKFB12R28010M	○ ●							5.0	<0.1
TKFB16R38005M	○ ●	KTKFR..16	9.5	4	3.8	0.3	6.3		<0.05
TKFB16R38010M	○ ●								<0.1

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard

订货示例: TKFB12R50005M PM125 10片 Ordering example: TKFB12R50005M PM125 10pcs


TKFB刀片命名规则:
TKFB Inser Identification chart:



切槽刀具 GROOVING TOOLS

SSL

切断(槽)刀杆 Parting-off Tools



图示为右手刀具

Right Cutting Tools(see picture)

注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手刀片(L)



Note: Right tools match with right inserts; left tools match with left inserts.

型号Ordering Code		尺寸Dimensions(mm)							适用刀片Insert		刀片螺钉	扳手
左刀Left Hand	右刀Right Hand	h	b	H	F	L	D	L1	右Right	左Left	Insert Screw	Torx Key
KTFL1010K-12	KTFR1010K-12	10	10	10	10	125		15				
KTFL1212K-12	KTFR1212K-12	12	12	12	12	85			TKF12R.	TKF12L.		
KTFL1212M-12	KTFR1212M-12	12	12	12	12		12		TKF12R.	TKF12L.	L60M4x10	T-15
KTFL1616M-12	KTFR1616M-12	16	16	16	16	150			TKF12R.	TKF12L.		
KTFL2020M-12	KTFR2020M-12	20	20	20	20							
KTFL1010K-16	KTFR1010K-16	10	10	10	10	125		20				
KTFL1212K-16	KTFR1212K-16	12	12	12	16	85			TKF16R.	TKF16L.		
KTFL1212M-16	KTFR1212M-16	12	12	12	12		16		TKF16R.	TKF16L.	L60M4x10	T-15
KTFL1616M-16	KTFR1616M-16	16	16	16	16	150			TKF16R.	TKF16L.		
KTFL2020M-16	KTFR2020M-16	20	20	20	20							

订货示例: KTFR1212M-12 1件

Ordering example: KTFR1212M-12 1pc

TKF切槽刀杆(排刀型) Parting-off Tools



图示为左手刀具

Right Cutting Tools(see picture)

型号Ordering Code		尺寸Dimensions(mm)							适用刀片Insert		刀片螺钉	扳手
左刀Right Hand	右刀Left Hand	h	b	H	F	L	D	L1	右Right	左Left	Insert Screw	Torx Key
KTFL1010F-12-A90	KTFR1010F-12-A90	10	10	10	10	80		16				
KTFL1212F-12-A90	KTFR1212F-12-A90	12	12	12	12	80		20	TKF12R.	TKF12L.		
KTFL1616H-12-A90	KTFR1616H-12-A90	16	16	16	16	100		24	TKF12R.	TKF12L.	L60M4x10	T-15
KTFL2020K-12-A90	KTFR2020K-12-A90	20	20	20	20	125		30	TKF12R.	TKF12L.		
KTFL1010K-16-A90	KTFR1010K-16-A90	10	10	10	10	80		20				
KTFL1212F-16-A90	KTFR1212F-16-A90	12	12	12	16	80		20	TKF16R.	TKF16L.		
KTFL1616H-16-A90	KTFR1616H-16-A90	16	16	16	16	100		24	TKF16R.	TKF16L.	L60M4x10	T-15
KTFL2020K-16-A90	KTFR2020K-16-A90	20	20	20	20	125		30	TKF16R.	TKF16L.		

订货示例: KTFR1212F-16-A90 1件


Ordering example: KTFR1212F-16-A90 1pc

切槽(断)刀具
GROOVING TOOLS

👉 THC42型双孔切断刀片 THC42 Double-hole Parting-off Insert




图片为右手刀片
Right Insert(see picture)



型 号	材 质	型 号	材 质	尺 寸				
Ordering Code	Material code	Ordering Code	Material code	Dimensions (mm)				
右手刀片 Right Hand	DK110 PM125	左手刀片 Left Hand	DK110 PM125	$B \pm 0.01$	$T \pm 0.01$	A	$*S \pm 0.01$	$*L *R$
THC42R100-CE	○ ●	THC42L100-CE	○ ○			0°	1.00	5 0.06
THC42R100-CE15R	○ ●	THC42L100-CE15L	○ ○			15°	1.00	5 0.06
THC42R150-CE	○ ●	THC42L150-CE	○ ○			0°	1.50	8.5 0.06
THC42R150-CE15R	○ ●	THC42L150-CE15L	○ ○			15°	1.50	8.5 0.06
THC42R200-CE	○ ●	THC42L200-CE	○ ○		3.07	0°	2.00	0.1
THC42R200-CE15R	○ ●	THC42L200-CE15L	○ ○			15°	2.00	0.1
THC42R250-CE	○ ●	THC42L250-CE	○ ○			0°	2.50	0.1
THC42R250-CE15R	○ ●	THC42L250-CE15L	○ ○			15°	2.50	0.1
THC42R300-CE	○ ●	THC42L300-CE	○ ○	7.94		0°	3.00	0.2
THC42R300-CE15R	○ ●	THC42L300-CE15L	○ ○			15°	3.00	11.5 0.2
THC42R340-CE	○ ●	THC42L340-CE	○ ○		3.47	0°	3.40	0.2
THC42R340-CE15R	○ ●	THC42L340-CE15L	○ ○			15°	3.40	0.2
THC42R200-CN	○ ●	THC42L200-CN	○ ○			0°	2.00	0.1
THC42R200-CU15R	○ ●	THC42L200-CU15L	○ ○			15°	2.00	0.1
THC42R250-CN	○ ●	THC42L250-CN	○ ○		3.07	0°	2.50	0.1
THC42R250-CU15R	○ ●	THC42L250-CU15L	○ ○			15°	2.50	0.1
THC42R300-CN	○ ●	THC42L300-CN	○ ○			0°	3.00	0.2
THC42R300-CU15R	○ ●	THC42L300-CU15L	○ ○			15°	3.00	0.2

●:常备库存(主推) Stock standard(main) ○:一般库存 Stock standard


订货示例: THC42R200-CE PM125 10片 Ordering example: THC42R200-CE PM125 10pcs



切槽刀具 GROOVING TOOLS

SSL

双孔切断(槽)刀杆 Double-hole parting-off Tools



图为右手刀具

Right Cutting Tools(see picture)

注意: 右手刀具(R)配右手刀片(R), 左手刀具(L)配左手刀片(L)

Note: Right tools match with right inserts; left tools match with left inserts.

型号 Ordering Code		尺寸 Dimensions(mm)						适用刀片 Insert		刀片螺钉	扳手
右刀 Right Hand	左刀 Left Hand	h	b	H	F	L	D	右 Right	左 Left	Insert Screw	Torx Key
THCR1010M42	THCL1010M42	10	10	10	10	110					
THCR1212M42	THCL1212M42	12	12	12	12	110					
THCR1616M42	THCL1616M42	12	16	16	16	110	21	THC42R	THC42L	L60M4x10	T15
THCR2020K42	THCL2020K42	16	20	20	20	125					
THCR2525M42	THCL2525M42	25	25	25	25	150					

订货示例: THCR2020K42 1件

Ordering example: THCR2020K42 1pc

双孔切断刀片命名规则:

Insert Identification Chart:




切槽(断)刀具
GROOVING TOOLS

👉 THC42型端面切槽刀片 THC42 Circlip Grooving Insert



图片为右手刀片
Right Insert(see picture)



型 号 Ordering Code	材 质 Material code	适用刀杆 The Cutter Bar	端面最小圆 Dmin	尺寸 Dimensions (mm)				
				$K \pm 0.01$	$T \pm 0.01$	$S \pm 0.01$	L	R
右手刀片 Right Hand	DKL10 PM125							
THC42L200DM10-CE	○ ●					2.00	9	0.06
THC42L250DM10-CE	○ ●					2.50	11.5	0.10
THC42L300DM10-CE	○ ●	THCL***42	10~∞	7.94	3.07	3.00	11.5	0.15
THC42L340DM10-CE	○ ●				3.47	3.40	11.5	0.15


● 常备库存(主推) Stock standard(main) ○ 一般库存 Stock standard

订货示例: THC42R200-CE PM125 10片 Ordering example: THC42R200-CE PM125 10pcs

切槽刀具 GROOVING TOOLS

SSL

THC系列端面切槽刀杆 Cutting Tools



图为左手刀具

Right Cutting Tools(see picture)

注意：左手刀具 (L) 配左手刀片 (L)






Note:left tools match with left inserts.

型号Ordering Code	尺寸Dimensions(mm)					适用刀片Insert	端面最小圆	刀片螺钉	扳手
左刀Left Hand	h	b	H	F	L		Dmin	Insert Screw	Torx Key
THCL1010J42	10	10	10	10	110	THC42L***DM10	10~∞	L60M4x10	T15
THCL1212J42	12	12	12	12	110				
THCL1616J42	12	16	16	16	110	THC42L***	10~∞	L60M4x10	T15
THCL2020K42	16	20	20	20	125				
THCL2525M42	25	25	25	25	150				

订货示例：THCL2020K42 1件

Ordering example: THCL2020K42 1pc

MGMN系列切槽刀片 GROOVING INSERT

刀片基本形状The basic shape of inserts		型号 Type		基本尺寸 Dimension (mm)					导程角 *A	材料推荐 Grade recommended		
				B	R	L	D	S		PM310	DP510	DN110
		MGMN	200-M	2	0.2	16	1.2	3.5	0	●	●	
			250-M	2.5	0.2	18.5	2	3.85	0	●	●	
			300-M	3	0.4	21	2.35	4.8	0	●	●	
			400-M	4	0.4	21	3.3	4.8	0	●	●	
			500-M	5	0.8	26	4.1	5.8	0	●	●	
		MGMN	150-G	1.5	0.15	16	1.2	3.5	0	●	●	
			200-G	2	0.2	16	1.6	3.5	0	●	●	
			300-G	3	0.4	21	2.35	4.8	0			
			400-G	4	0.4	21	3.3	4.8	0			
		MGMN	200-T	2	0.2	16	1.5	3.5	0			
			300-T	3	0.4	21	2.35	4.8	0			
			400-T	4	0.4	21	3.3	4.8	0			
			500-T	5	0.8	25.86	4.12	5.8	0			
		MGMN	200-M	2	1	16	1.5	3.5	0	●	●	
			300-M	3	1.5	21	2.35	4.8	0	●	●	
			400-M	4	2	21	3.3	4.8	0	●	●	
			500-M	5	2.5	25.86	4.12	5.8	0	●	●	
		MGMN	200-C	2	0.2	16	1.2	3.5	0	●	●	
			250-C	2.5	0.2	18.5	2	3.85	0	○	○	
			300-C	3	0.4	21	2.35	4.8	0	●	●	
			400-C	4	0.4	21	3.3	4.8	0	●	●	
			500-C	5	0.8	26	4.1	5.8	0	○	○	
		MGMN	150-LH	1.5	0.15	16	1.2	3.5	0	●		○
			200-LH	2	0.2	16	1.5	3.5	0	●		○
			250-LH	2.5	0.2	18.5	2	3.85	0	●		○
			300-LH	3	0.4	21	2.35	4.8	0	●		○
			400-LH	4	0.4	21	3.3	4.8	0	●		○
			500-LH	5	0.8	25.86	4.12	5.8	0	●		○
		MGMN	150-LH	1.5	0.15	16	1.2	3.5	0.6	●		○
			200-LH	2	0.2	16	1.5	3.5	0.6	●		○
			250-LH	2.5	0.2	18.5	2	3.85	0.6	●		○
			300-LH	3	0.4	21	2.35	4.8	0.6	●		○
			400-LH	4	0.4	21	3.3	4.8	0.6	●		○
			500-LH	5	0.8	25.86	4.12	5.8	0.6	●		○

★ LH槽型导程角可以定制 the leading angle of LH type could be customized as per customer's requirement.

PM310: 不锈钢和铜件通用材质, 耐高温性能提升, 适合加工不锈钢和软铜

PM310: Stainless steel and universal material, high temperature resistant performance, suitable for the processing of stainless steel and mild steel

DP510: 钢件用材质, 具有良好的韧性, 适合加工大部分钢件

DP510: Steel material, with good toughness, suitable for processing most of the steel parts

DK110: 铝用材质, 适合加工有色金属

DK110: Aluminum material, suitable for processing non-ferrous metals


切槽刀具 GROOVING TOOLS

SSL

MGMN系列切槽(断)刀杆 GROOVING TOOLS



图片为右手刀具
Right Insert(see picture)



型 号 Type		库存		适用刀片 Recommended insert 	适用条件 Application					配件 Parts	
		Stock item			外切槽、车削加工 External Grooving, Turning					 螺丝 Screw	 扳手 Wrench
		R	L		H-Φ	W	L	S	T(max)		
MGHRLL	1616-1.5	○		MGMN*** MOGN***	16	16	100	16.25	14.5	LTX0512	L2.0
	2020-1.5	○			20	20	125	20.25	14.5		
	2525-1.5	○			25	25	150	25.25	14.5		
	1212-2.0				12	12	100	14.25	14.5	BHA0816	L5.0
	1616-2.0	●	○	MGMN***	16	16	100	16.25	14.5		
	2020-2.0	●	○	MOGN***	20	20	125	20.25	14.5		
	2525-2.0	●	○		25	25	150	25.25	14.5	MHA0512	L4.0
	1616-2.5	●	○	MGMN*** MOGN***	16	16	100	16.3	16.5		
	2020-2.5	●	○		20	20	125	20.3	16.5		
	2525-2.5	●	○		25	25	150	25.3	16.5	BHA0616	L5.0
	1616-3.0	●	○		16	16	100	16.35	18.5		
	2020-3.0	●	○		20	20	125	20.4	18		
	2020-3.0-T10	○		MGMN*** MOGN***	20	20	125	20.4	10		
	2525-3.0	●	○		25	25	150	25.4	18		
	2525-3.0-T10	○			25	25	150	25.4	10		
	3232-3.0	●	○		32	32	170	32.4	18		
	3232-3.0-T10				32	32	170	32.4	10		
	2020-4.0	●	○		20	20	125	20.4	18		
	2020-4.0-T10	○			20	20	125	20.5	10		
	2525-4.0	●	○	MGMN***	25	25	150	25.4	18		
	2525-4.0-T10	○	○	MOGN***	25	25	150	25.4	10		
	3232-4.0	●	○		32	32	170	32.4	18		
	3232-4.0-T10				32	32	170	32.4	10		
	2020-5	○	○		20	20	150	20.5	23		
	2020-5-T15				20	20	150	20.5	15		
	2525-5	○	○	MGMN***	25	25	150	25.5	23		
	2525-5-T15			MOGN***	25	25	150	25.5	15		
	3232-5	○	○		32	32	170	32.5	23		
3232-5-T15				32	32	170	32.5	15			

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order

转下页

切槽(断)刀具
GROOVING TOOLS




MGMN系列切槽(断)刀杆

GROOVING TOOLS



图片为右手刀具
Right Insert(see picture)




型 号 Type		库存		通用刀片 Recommended Inserts 	适用条件 Application					配件 Parts	
		Stock Item			外切槽、车削加工 External Grooving, Turning					螺丝 Screw 	扳手 Wrench 
		R	L		H(h)	W	L	S	T(max)		
MGE-PAL	2020 -6	○	○		20	20	125	20.6	23		
	2020 -6-T15				20	20	125	20.6	15		
	2525 -6			MGMN800-M	25	25	150	25.6	23		
	2525 -6-T15			MRMN800-M	25	25	150	25.6	15		
	3232 -6				32	32	170	32.6	23		
	3232 -6-T15				32	32	170	32.6	15		

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order

切槽刀具 GROOVING TOOLS

SSL

切槽(断)刀杆 GROOVING TOOLS






型 号 Type		库存		适用刀片 Recommended inserts	适用条件 Application							配件 Parts		
		Stock Item			内槽加工, 车削加工 Internal Grooving, Turning							螺丝 Screw	扳手 Wrench	
		R	L		ΦD	Φd	L	L1	T(max)	H	S			
MGMRL	2016-1.5	○		MGMN150-G	20	16	125	35	4	15	11.3	MH30310	L2.5	
	2520-1.5	○			25	20	150	45	4	18	13.1	MHA2512	L4.0	
	2925-1.5				29	25	200	45	4	23	16.2			
	2016-2.0	○		MGMN200-G	20	16	125	35	5	15	12.4	MH30310	L2.5	
	2520-2.0	○			25	20	150	45	5	18	14	MHA2512	L4.0	
	2925-2.0	○			29	25	200	45	5	23	17.2			
	2016-2.5			MGMN250-G	20	16	125	35	6	15	12.5	MH30310	L2.5	
	2520-2.5	○			25	20	150	45	6	18	15.1	MHA2512	L4.0	
	2925-2.5	○			29	25	200	45	6	23	16.2			
	2520-3.0	●	●	MGMN300-M MRMN300-M	25	20	150	45	6	18	15.6	MHA2512	L4.0	
	3125-3.0	●	●		31	25	200	45	6	25	18.9			
	3732-3.0	●	●		37	32	250	65	6	30	21.5			
	2520-4.0	●	●	MGMN400-M MRMN400-M	25	20	150	45	6	18	15.6			
	3125-4.0	●			31	25	200	45	6	23	18.9			
	3732-4.0	●			37	32	250	65	6	30	21.5			
	3125-5	○		MGMN500-M MRMN500-M	31	25	200	45	8	25	19.5			
	3732-5	○			37	32	250	65	8	30	21.5			
	3125-6			MGMN600-M MRMN600-M	31	25	200	45	8	23	19.4			
3732-6			37		32	250	65	8	30	21.5				
3125-6A			MRGN800-A	31	25	200	45	8	23	19.4				
3732-6A				37	32	250	65	8	30	21.5				

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order

切槽(断)刀具
GROOVING TOOLS

👉 TD系列切槽刀片 GROOVING INSERT

刀片基本形状 The basic shape of insert	型号 Type	基本尺寸 Dimension (mm)					材质推荐 Grade recommended		
		B	R	L	D	S	PW310	DP510	DK110
 	TDJ2	2	0.2	20	1.7	3.9	●	●	
	TDJ3	3	0.2	20	2.4	4	●	●	
	TDJ4	4	0.3	19.76	3	4.05	●	●	
	TDJ5	5	0.3	25	4	4.89	●	●	
 	TDC2	2	0.2	20	1.7	3.84	●	●	
	TDC3	3	0.2	20	2.4	4	●	●	
	TDC4	4	0.3	20	3	4.03	●	●	
	TDC5	5	0.3	25	4	4.89	●	●	
 	TDT2	2	0.2	20	1.7	3.9			
	TDT3	3	0.2	20	2.4	4			
	TDT4	4	0.3	19.76	3	4.05			
	TDT5	5	0.3	25	4	4.89			
 	TDC2-LH	2	0.2	20	1.7	3.84	●	●	
	TDC3-LH	3	0.2	20	2.4	4	●	●	
	TDC4-LH	4	0.3	20	3	4.03	●	●	
	TDC5-LH	5	0.3	25	4	4.89	●	●	

PW310: 不锈钢和铜件通用材质, 耐高温性能提升, 适合加工不锈钢和软铜

PW310: Stainless steel and universal material, high temperature resistant performance, suitable for the processing of stainless steel and mild steel

DP510: 铜件用材质, 具有良好的韧性, 适合加工大部分铜件

DP510: Steel material, with good toughness, suitable for processing most of the steel parts

DK110: 铝用材质, 适合加工有色金属

DK110: Aluminum material, suitable for processing non-ferrous metals


切槽刀具 GROOVING TOOLS

SSL

🔑 TD系列切槽(断)刀杆 GROOVING TOOLS




图片为右手刀具
Right Insert(see picture)



型 号 Type		库存		适用刀片 Recommended Inserts	基本尺寸 Dimension (mm)					配件 Parts	
		Stock Item			H(H)	W	L	S	T(max)	螺丝 Screw	扳手 Wrench
		R	L								
TTER/L	1616-2.0	○		TD***2	16	16	110	15.1		M5X16	L4.0
	2020-2.0	○			20	20	125	18.1	14		
	2525-2.0	○			25	25	150	24.1			
	1616-3.0	○		16	16	110	14.8				
	2020-3.0	○		TD***3	20	20	125	18.8	18		
	2525-3.0	○		25	25	150	23.8				
	1616-4.0			16	16	110	14.5		M6X16	L5.0	
	2020-4.0	○		TD***4	20	20	125	18.5			18
	2525-4.0	○		25	25	150	23.5				
	2525-6.0	○		TD***5	25	25	150	23.1		M8X20	L6.0
	3232-6.0	○		32	32	170	28.1	23			

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order

👉 TD系列切槽(断)刀杆 GROOVING TOOLS




型 号 Type	库存		通用刀片 Recommended inserts 	适用条件 Application							配件 Parts	
	Stock Item			内槽加工、车削加工 Internal Grooving, Turning							 螺丝 Screw	 扳手 Wrench
	R	L		ΦD _{min}	Φd	L	L1	T(max)	H	S		
TTIR/L16-2C				25	16	125	—	8.5	7.5	18.5	M5X10	L4.0
TTIR/L20-2C			TDC/J2	25	20	160	40	6.0	9.0	15.8	M5X12	
TTIR/L25-2C				25	25	200	40	5.0	11.5	17.5	M5X16	
TTIR/L20-3C				25	20	160	40	6.0	9.0	15.8	M5X12	
TTIR/L25-3C			TDC/J3	25	25	200	40	5.1	11.5	17.5	M5X16	
TTIR/L32-3C				31	32	250	60	4.7	14.0	19.8	M5X16	
TTIR/L20-4C				25	20	160	40	6.0	9.0	15.8	M5X12	
TTIR/L25-4C			TDC/J4	25	25	200	40	5.2	11.5	17.5	M5X16	
TTIR/L32-4C				31	32	250	60	4.7	14.0	20.8	M5X16	L5.0
TTIR/L25-5C			TDC/J5	25	25	200	40	5.2	11.5	17.3	M6X16	
TTIR/L32-5C				31	32	250	60	4.7	14.0	20.8	M6X20	
TTIR/L25-3C-T8				32	25	200	40	8	11.5	21.5	M5X16	L4.0
TTIR/L32-3C-T10			TDC/J3	40	32	250	60	10	15	27	M5X20	
TTIR/L40-3C-T12				50	40	300	65	12	19	33	M5X25	
TTIR/L25-4C-T8				32	25	200	40	8	11.5	21.5	M5X16	
TTIR/L32-4C-T10			TDC/J4	40	32	250	60	10	15	27	M5X20	
TTIR/L40-4C-T12				50	40	300	65	12	19	33	M5X25	
TTIR/L50-4C-T14				60	50	350	70	14	23.5	40	M6X20	L5.0
TTIR/L32-5C-T10			TDC/J5	40	32	250	60	10	15	27	M6X25	
TTIR/L40-5C-T12				50	40	300	65	12	19	33	M6X20	
TTIR/L50-5C-T12				60	50	350	70	12	23.5	40	M6X25	

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order

刀板的命名规则 Identification chart:




TD系列切槽(断)刀板 PARTING & GROOVING BLADE



型 号 Type	刀座尺寸 Insert seat size	适用刀片 Recommended inserts 	适用条件 Application					配件 Parts	
			外切削槽、车削加工 External Grooving, Turning						刀板座 Block for parting & grooving blade
			B	L	H	A	φDmax		
TGB 26-2	2	TD***2	26	190		2.0	40	E96-338	TTB***-26
TGB 26-3	3	TD***3				2.4	50		
TGB 26-4	4	TD***4				3.2	80		
TGB 32-2	2	TD***2	32			2.0	50		TTB***-32
TGB 32-3	3	TD***3				2.4	100		
TGB 32-4	4	TD***4			24.9	3.2			
TGB 32-5	5	TD***5		4.0	120				
TGB 32-6	6	TD***6			5.2				



扳手需要单独订购
spanner need to be ordered separately

TD系列刀座 BLOCK FOR PARTING & GROOVING BLADE



型 号 Type	尺寸 Dimension (mm)									配件 Parts	
	H	W	H ₂	L	H ₁	H ₂	W ₁	B	M	扳手 Extractor	刀板 Parting & grooving blade
STGBU20-5	20	21.5	26	87	44	9	38	5.0	3-M6	L-N5	TGB 26-***
STGBU25-5	25	23	26	100	45	5	42	5.0	3-M6		
STGBU20-6	20	19	32	100	50	13	38	5.3	4-M6		
STGBU25-6	25	23	32	110	50	8	42	5.3	4-M6		TGB 32-***
STGBU32-6	32	29	32	110	54	5	48	5.3	4-M6		

 DQ系列切槽刀片 GROOVING INSERT

刀片基本形状 The basic shape of inserts		型号 Type	基本尺寸 Dimension (mm)			材质推荐 Grade recommended		
			B	R	L _{min}	PM310	DP510	DK110
		DQPED02502-MG	2.5	0.2	17	☐	☐	
		DQPF00302-MG	3	0.2	17	☐	☐	
		DQPG00402-MG	4	0.2	22	☐	☐	
		DQPH00503-MG	5	0.3	22	☐	☐	
		DQPK00604-MG	6	0.4	22	☐	☐	
		DQTED02503-MG	2.5	0.3	17	☐	☐	
		DQTFD0303-MG	3	0.3	17	☐	☐	
		DQTGD0404-MG	4	0.4	22	☐	☐	
		DQTHD0504-MG	5	0.4	22	☐	☐	
		DQTKD0608-MG	6	0.8	22	☐	☐	

注：可与株洲钻石刀片互换

PM310: 不锈钢和钢件通用材质，耐高温性能提升，适合加工不锈钢和碳钢

PM310: Stainless steel and universal material, high temperature resistant performance, suitable for the processing of stainless steel and mild steel

DP510: 钢件用材质，具有良好的韧性，适合加工大部分钢件

DP510: Steel material, with good toughness, suitable for processing most of the steel parts


DK110: 铝用材质，适合加工有色金属

DK110: Aluminum material, suitable for processing non-ferrous metals

DQ系列切槽(断)刀杆 GROOVING TOOLS




图片为右手刀具
Right Insert(see picture)



型 号 Type		库存		适用刀片 Recommended Inserts 	适用条件 Application					配件 Parts	
		Stock Item			外切槽、车削加工 External Grooving, Turning					 螺丝 Screw	 扳手 Wrench
					H(N)	W	L	S	T(max)		
DQEED	1616R/L10	○		DQ*ED025**	16	16	125	2.5	10	M5X20	L4.0
	1616R/L17	○			20	20	125	2.5	17		
	2020R/L10	○			25	25	125	2.5	10	M6X20	L5.0
	2020R/L17				12	12	125	2.5	17		
	2525R/L10	○	○		16	16	150	2.5	10		
	2525R/L17	○	○		20	20	150	2.5	17		
DQEFD	1616R/L10	○	○	DQ*FD03**	25	25	125	3	10	M5X20	L4.0
	1616R/L17	○	○		16	16	125	3	17		
	2020R/L10	○	○		20	20	125	3	10	M6X20	L5.0
	2020R/L17	○	○		25	25	125	3	17		
	2525R/L10	●	●		16	16	150	3	10		
	2525R/L17	●	●		20	20	150	3	17		
DQEGD	1616R/L13	●		DQ*GD04**	20	20	140	4	13	M6X20	L5.0
	1616R/L22	●	●		25	25	140	4	22		
	2020R/L13	●			25	25	150	4	13		
	2020R/L22	●	●		32	32	150	4	22		
	2525R/L13				32	32	170	4	13		
	2525R/L22	●	●		20	20	170	4	22		
DQEHD	2525R/L13	●		DQ*HD05**	20	20	150	5	13	M6X20	L5.0
	2525R/L22	●	●		25	25	150	5	22		
	3232R/L13	●	●		25	25	170	5	13		
	3232R/L22	●	●		32	32	170	5	22		
DQEKD	2525R/L13			DQ*KD06**	32	32	150	6	13	M6X20	L5.0
	2525R/L22	○	○		20	20	150	6	22		
	3232R/L13				20	20	170	6	13		
	3232R/L22	○	○		25	25	170	6	22		

●库存 stock item ○准库存 be preparing for stock 其余订货 the others can be made to order



——专注于螺纹刀具、切槽(断)刀具——
specialized in manufacturing the threading inserts, grooving and parting inserts

SSL