AGGREGATE & ROCK **Civil Engineering Testing Equipment**

www.nl-test.com

DIGIMATIC POINT LOAD TESTER APPARATUS (COMPACT VERSION) Standard: ASTM D5731

Strength Index

Used to determine the strength values of a rock specimen both in the field and in the laboratory. New rigid design load frame with hydraulic loading ram actuated by hand pump. A ruler attach on the frame allow for direct measuring specimen diameter. The apparatus applied high accuracy load cell & fine resolution reading control unit. The case come with easy compartment for storage of component parts.



Model Number	NL 1012 X / 008
Max. Capacity	50 kN x 0.01 kN Sensitivity
Max. Specimen Test	110 mm Dia.
Power	1.8 Ah Rechargeable with AC 220 V
Result Storage	999 Test Results
Accuracy & Repeatability	≤1.0 % F.S
Case Dimension (mm)	280(L) x 220(W) x 680(H) mm
Approx. Weight	40 kg

Unit Consists Of:

Model Number	Parts Description	Qty
NL 1012 X / 008 – P 003	Measuring Guide Plate	1no.
NL 1012 X / 008 – P 006	Conical Cone Set (Top & Bottom)	1set
NL 1012 X / 008 - P 007	Safety Cover	1 pc.
NL 1012 X / 008 - P 008	Power Charger	1 no.
NL CSNR	45 - 52 C Spanner	1 pc.

^{*1} Copy of Manual Instruction




Handle for easy Portability





Digital Readabout



Fully Close Set-up For Easy Storage



Under Compartment

Copyright 2016 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)