







Packing Assembly

AGGREGATE & ROCK **Civil Engineering Testing Equipment**

DIGIMATIC POINT LOAD TESTER APPARATUS (E-VERSION) Standard: ASTM D5731

Strength Index

Used to determine the strength values of a rock specimen both in the field and in the laboratory. New rigid design load frame with hydraulic loading ram actuated by hand pump. A ruler attach on the frame allow for direct measuring specimen diameter. The apparatus applied high accuracy load cell & fine resolution reading control unit.

Technical Specifications :

Model Number	NL 1012 X / 006N
Max. Capacity	50 kN x 0.01 kN Sensitivity
Max. Specimen Test	90 mm Dia.
Power	1.8 Ah Rechargeable with AC 220 V
Result Storage	50 Test Results
Accuracy & Repeatability	≤1.0 % F.S
Product Dimension	450(L) x 350(W) x 800(H) mm
Packing Dimension	500(L) x 420(W) x 860(H) mm
Approx. Weight	34 kg
Packing Weight	47 kg

Unit Consists Of :

Model Number	Parts Description	Qty
NL 1012 X / 006 – P 001	50 kN S Type Load Cell c/w Cable	lno.
NL DLD-200	Digital Load Display	1 unit
NL 1012 X / 006 – P 003	Measuring Guide Plate	lno.
NL 1012 X / 006 – P 006	Conical Cone Set (Top & Bottom)	1set.
NL 1012 X / 006 – P 007	Safety Cover	lpc.
NL 1012 X / 006 - P 008	Power Charger	lno.

*1 Copy of Manual Instruction

Copyright 2016 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)

ASIA LEADER MATERIAL TESTING EQUIPMENT