

FIGURE GATE & RUCKCivil Engineering Testing Equipment

www.nl-test.com



DIGIMATIC SAND EQUIVALENT SHAKER

Standard: EN 933-8, ASTM D2419, AASHTO T176, NF XP18-598, UNE 83131, UNI 8520-15, CNR N.27

Assessment of Fine

The digimatic sand equivalent shaker features consist of digimatic timer (can be set at required time) to increase accuracy and ease of operation compared to a spring-type timer. The unit provides adjustable oscillation speed to confirm with both ASTM & EN test procedure, also eliminating variations from on operator to the next. The unit provides a consistent and repeatable oscillation, eliminating variations from one operator to the next.

Technical Specifications:

Model Number	NL 1001 X / 004
Speed Of Strokes	175 - 180 strokes / min
Dimension	770 (L) x 350 (W) x 435 (H) mm
Packing Dimension	830 (L) x 490 (W) x 480 (H) mm
Approx. Weight	44 kg
Packing Weight	55 kg
Power	220 VAC, 50 / 60 Hz, 0.8 A, 1 ph,128 W

Optional Accessories:

Model Number	Parts Description
NL 1000 X / 002	Sand Equivalent Apparatus



Timer



Single Cylinder



NL 1000 X / 002

Copyright 2016 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)