BITUMEN & ASPHALT

Civil Engineering Testing Equipment

www.nl-test.com



DISTILLATION ASSEMBLY FOR RECOVERY OF ASPHALT

Standard: ASTM D1856, CNR No.133

Asphalt Binder Analysis

Used for recovering the asphalt from a solution of a previous extraction. The asphalt is recovered with properties substantially the same as those it possessed in the bituminous mixture and in quantities sufficient for further testing.

Technical Specifications :

·	
Model Number	NL 2011 X / 001
Approx. Weight	15 kg
Power	230 V, 50 / 60 Hz, 1 ph
Setup Dimension (mm)	770 (L) × 400 (W) × 620 (H)

Unit Consists Of :

Model Number	Parts Description	Qty
NL 2011 X / 001 – P 001	Flat Bottom Flasks 250 ml Cap	2nos.
NL 2011 X / 001 – P 002	Glass Tubing 'L' Shape	1no.
NL 2011 X / 001 – P 003	Inlet Aeration Tube	2nos.
NL 2011 X / 001 – P 004	Heating Mantle (Ø85 mm / for 250 ml Flask)	lno.
NL 2011 X / 001 – P 005	Water Jacketed Condenser	lno.
NL 2011 X / 001 – P 006	Glass Thermometer IP 5C (ASTM 7C) *Range (-2)°C to 300°C	lno.
NL 2011 X / 001 – P 007	Gas Flowmeter 1000 ml / min	lno.
NL 2011 X / 001 – P 008	Cork	lno.
NL 2011 X / 001 – P 009	Flexible Elastomeric Tubing	lno.
NL 7044 X / 001	Retort Stand	2nos.

^{*1} Copy of Manual Instruction

Copyright 2016 NL Scientific Instruments Sdn. Bhd. All Rights Reserved. Revision 3(All information in this catalogue only for customer's reference and not for quotation. Design and dimension maybe change without prior notice.)