

MOTORIZED SIEVES SHAKER (E-VERSION)

Standard: EN 932-5, AASHTO T 27

Sample Grading

NL Motorized Sieves Shaker (E - Version) has been developed and manufactured to combine low cost with the benefits of a well-designed and engineered shaker. This unit has a vertical sieving motion provided by a vibration motor. Used for sieving and grading test on soil, mineral aggregate. Reliable and long lasting, can hold up to 10 sieves.

FEATURES:-

- Easy removeable quick release knob clamping
- Triple motion action (vertical, lateral & rotational)
- Vibration Intensity

Technical Specifications :

Model Number	NL 1015 X / 015
Timer	1 - 60 minutes
Sieves Diameter	200 & 300 mm, 8" & 12" Diameter
Sieve Max Capacity	up to 10 nos.
Amplitude	Multi Level (Adjustable)
Product Dimension	440 (L) x 440 (W) x 830 (H) mm
Packing Dimension	480 (L) x 400 (W) x 300 (H) mm
Approx. Weight	39 kg
Packing Weight	50 kg
Power	220~240 V, 400 W, 1 Ph , 50 / 60 Hz

Unit Consists Of :

Model Number	Parts Description	Qty
NL 1015 X / 006 – P 001	Clamping Knobs (pair of 2)	1 pr.
NL 1015 X / 006 – P 002	Clamping Beam	1 no.
NL 1015 X / 006 – P 003	Threaded Rod c/w Extended Rod	2 nos.

*1 Copy of Manual Instruction

Optional Accessories :

Model Number	Parts Description
NL 1015 X / 012 - NCB	Noise Reduction Cabinet

