

Product Benefit Sheet

Revised: 2015/09/18 (version 1.0)



PETRONAS Urania 500 10W, 30, 40 & 50

Designed for wear protection and to control corrosion for older commercial vehicle diesel engines

Description and Applications

PETRONAS Urania 500 monograde series covers is a diesel engine oil which covers SAE 10W, 30, 40 & 50 viscosity grades. It is formulated for older commercial vehicle diesel engines to help control against wear and control corrosion.

PETRONAS Urania 500 monograde series is suitable for all types of older commercial vehicle diesel applications and high-revolution turbocharged diesel engines for both on-highway and off-highway. The SAE 10W and 30 are also suitable for used in transmission, differentials or final drives in equipment where API CD/ CAT TO-2 fluid are required.

Note: Always consult your owner's manual to check recommended viscosity grade and specifications for your particular vehicle

Features and Benefits

Delivers:

- Piston cleanliness & minimizing deposits build ups, protects engine from wear
- Helps dispersing soot, hence reduces soot induced oil thickening.
- Good TBN retention effectively neutralizing the acidic by-products from combustion.

Specifications and Approvals

PETRONAS Urania monograde series (SAE 10W, 30, 40 & 50) is a lubricant that meets and exceeds below performances:-

Meets or Exceeds the requirements of:

API CF/ SF	√
------------	---

* All technical data is provided for reference only.

Health, Safety and Environment

This product is unlikely to present any significant health and safety hazards when used in the recommended application. Avoid contact with skin. Wash immediately with soap and water after skin contact. Do not discharge into drains, soil or water.

For further detail regarding storage, safe handling, and disposal of product, please refers to product SDS or contact us at: www.pli-petronas.com

Important Note

The word PETRONAS, the PETRONAS logo and such other related trademarks and/or marks used herein are trademarks or registered trademarks of PETRONAS Lubricants International Sdn. Bhd. ("PLISB"), or its subsidiaries or related Holding Corporation under license unless indicated otherwise. The PLI Documents and the information contains herein is believed to be accurate as of the date of printing. PLISB makes no express or implied representation or warranties as to its accuracy or completeness or information in or any transaction performed. The PLI Documents information provided is based on standard tests under laboratory conditions and is given only as a guide. Users are advised to ensure that they refer to the latest version of these PLI Documents. It is the responsibility of the users to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations imposed by the respective local authorities.

Safety Data Sheets are available for all our products and should be only be consulted for appropriate information regarding storage, safe handling and disposal of the product. No responsibility shall be taken by either PLISB or its subsidiaries and related holding corporation for any loss or injury or any direct, indirect, special, exemplary, consequential damages or any damages whatsoever, whether in action of contract, negligence or other tortuous action, in connection or resulting from abnormal use of the materials and/or information, from any failure to adhere to recommendations, or from hazards inherent in the nature of the materials and/or information. All products, services and information supplied are under our standard conditions of sale. Please consult with any of our local representative in the event you require any further information.

Code: 72000882 (SAE 10W), 72000886 (SAE 30), 72000890 (SAE 40), 72000896 (SAE 50)