

# Perkunas


## LED PANEL LIGHT





*\*All pictures shown are for illustration purpose only*

Panel lights are used residentially and commercially and replace traditional fluorescent ceiling lights. Kitchens, bathrooms and living rooms are all popular choices for using panel lights but they can be used in any room around the home, even hallways.

SPECIFICATION:	12W ROUND / SQUARE	18W ROUND / SQUARE	24W ROUND / SQUARE
COLOUR	6500K/4000K/3000K	6500K/4000K/3000K	6500K/4000K/3000K
SIZE	140MM*28MM (4 INCHES)	180MM*30MM (6 INCHES)	220MM*32MM (8 INCHES)
DIFFUSOR MATERIAL	PS	PS	PS
DRIVER LIFETIME	25000HR	25000HR	25000HR
INPUT VOLTAGE	220V-50Hz	220V-50Hz	220V-50Hz
LAMP BEAD TYPE	2835 3V	2835 3V	2835 3V
LAMP BEAD QUANTITY TOTAL	110°	110°	110°
LUMINOUS FLUX	960LM	1440LM	1920LM
POWER FACTOR	0.5	0.5	0.5
BASE MATERIAL	FE	FE	FE
INPUT CURRENT	95MA	95MA	95MA
CRI	≥70	≥70	≥70
PCB MATERIAL	PC	PC	PC
IP RATE	IP20	IP20	IP20
PACKING	60/CTN	60/CTN	40/CTN



Diluluskan Oleh / Approved by:



12W Ø110MM  
18W Ø145MM  
24W Ø175MM

12W 110MM  
18W 145MM  
24W 175MM