











Perkunas **WER LED FLOODLIGHT**









*All pictures shown are for illustration purpose only


LED Flood Lights are wide angle lights designed to cover a large area or "flood" the area with light. Now powered by efficient LED technology, these lights are suitable for yard, parking lot, retail stores, warehouses and storage.




300W




400W




500W



600W



800W



1000W

Product Specification

Rated Power	Luminous Flux	Net Weight	Amount per Carton	Maximum Projected Area
300W	WW:28500LM/NW:30000LM/PW:31500LM	5.7KG	1PCS	0.179M²
400W	WW:38000LM/NW:40000LM/PW:42000LM	7.25KG	1PCS	0.236M ²
500W	WW:47500LM/NW:50000LM/PW:52500LM	9.2KG	1PCS	0.293M²
600W	WW:57000LM/NW:60000LM/PW:63000LM	11.65KG	1PCS	0.340M²
800W	WW:76000LM/NW:80000LM/PW:84000LM	15.4KG	1PCS	0.459M²
1000W	WW:95000LM/NW:100000LM/PW:105000LM	19.0KG	1PCS	0.567M ²

The Standard Parameter of Floodlight

ССТ	6500K	
CRI	Ra70	
Input voltage	220VAC	
Frequency	50Hz	
power Factor	≥0.9	
Ambient temperature	-30°C ~45°C	
Ambient humidity	5%~95%	
Storage Temperature	-40°C ~70°C	
beam angle	25°/60°/90°	
Service Life(h)	≥35000	
IP Grade	IP66	
Installation	Stand Style Installation	
Main material	Aluminum Alloy+PC+toughened glass	
Mounting height	3~50m	