



SUPER KING

Lead Acid Battery Charger



SK-128



SK-1213



SK- 2416



SK-4825

FEATURES

Rated supply voltage
> 220 ~ 240V AC 50Hz

Charging current
> Maximum range – 8A, 16A, 25A

Battery type
> 6V & 12V Lead Acid Battery

Battery arrangement [Above 2 units]
> Series connection only
> 12V Calcium & Calcium MF Battery

Casing
> High quality steel plate with epoxy powder coated finishing

Number of Batteries
> 6V Battery – 1 to 20pcs (Max.)
> 12V Battery – 1 to 10pcs (Max.)

Safety features
> Fast blow glass fuse
> MCB over current protection

Charging voltage
> Fixed range – 12V & 24V
> Multiple range – 6V ~ 48V
12V ~ 24V or 120V

List of chargeable Batteries

[Maintenance Free Battery & Lead Acid Battery]

Models :

NS60/L, 46B24R/L, NS40ZL, NS70Z/ZL, NX120-7/L, N100, N120, N150, N200, N250Z, DIN55, DIN66, DIN88, etc...

MODEL	CHARGING VOLTAGE (VDC)	CHARGING CURRENT (A)	DIMENSION (mm) H X W X D	WEIGHT (kg)
SK - 128	6V - 12V	8	152 x 246 x 169	4
SK - 1213	6V - 12V	13	152 x 246 x 169	5.5
SK - 2416	12V or 24V	16	160 x 246 x 237	9.5
SK - 4825	6V - 48V	25	295 x 355 x 305	25.45