

MARCH®



Technical Data TF-1000E

Technical Data TF-650E	
Power Input	2000W
Voltage	230V/50Hz
	110V/60Hz
RPM	Two Speeds High 500/220 Low 260/100
Core Drill	ø12mm - ø65mm
Max Cutting Depth	75mm
Twist Drill	up to ø25mm with Morse Taper
Tool Holder	MT3
Magnetic Adhesion	1800kg
Weight	27kg

Tooliilloal Bata II Toobe	
Power Input	2400W
Voltage	230V/50Hz
	110V/60Hz
RPM	Two Speeds High 450/200 Low 190/80
Core Drill	ø12mm - ø100mm
Max Cutting Depth	75mm
Twist Drill	up to ø32mm with Morse Taper
Tool Holder	MT3
Magnetic Adhesion	3200kg
Weight	34kg

Technical Data TF-1600E

Since 1980

Power Input	3600W
Voltage	230V/50Hz
	110V/60Hz
RPM	Two Speeds High 410/170 Low 150/70
Core Drill	ø12mm - ø160mm
Max Cutting Depth	110mm
Twist Drill	up to ø44mm with Morse Taper
Tool Holder	MT4
Magnetic Adhesion	3900kg
Weight	53kg

Ting Fong Electric & Machinery Co Ltd Tel: +886 2 85121509 Fax: +886 2 22782341 Email: march888@ms26.hinet.net