



# DULUX INSPIRE EXTERIOR & INTERIOR WALL SEALER

**A1290013 0015527 LINE (WATERBASED)**

## PRODUCT INFORMATION

<b>PRODUCT NAME</b>	Dulux Inspire Exterior & Interior Wall Sealer
<b>Product Code</b>	A1290013 0015527
<b>DESCRIPTION</b>	Dulux Inspire Exterior & Interior Wall Sealer is a good quality, water-based sealer.
<b>USAGE</b>	Suitable for interior masonry surface such as brickwork, plaster, cement and asbestos that is fully dry. It is suitable for use on both new and previously painted surfaces. In compliance to SIRIM Eco Label and Singapore GreenLabel.
<b>BENEFITS</b>	Provides good alkali and efflorescence resistance.
<b>PACK SIZE</b>	5 and 18 litres
<b>COLOR RANGE</b>	White only.

## PERFORMANCE GUIDE

<b>FILM PROPERTIES</b>	
Water Resistance	Will tolerate a slightly damp surface but is not suitable where the surface is saturated.
<b>THEORETICAL COVERAGE</b>	A guide to the theoretical coverage which can be achieved under normal conditions is 9 - 11 m <sup>2</sup> /litre

## PRODUCT DATA

<b>COMPOSITION (nominal)</b>	Pigment : Lightfast Non-Lead Pigments and Mineral Extenders. Binder : Acrylic Emulsion. Solvent : Water.
<b>VOLUME SOLIDS</b>	White 33% (nominal).

## APPLICATION

<b>THINNING</b>	
Brush or Roller	For sealing new or bare surfaces thin with up to 1 part of clean water to 10 parts of paint (10%). For normal use thinning is usually not necessary.
Conventional Spray	Add up to 1 part clean water to 10 parts of paint (10%).
Airless Spray	Ready for use.
<b>SPRAY RECOMMENDATIONS</b>	
Conventional Spray	Satisfactory through most equipment.
Airless Spray	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm <sup>2</sup> (2000 lb/sq in) with a spray tip size 0.43mm (17 thou) and a spray tip angle 65°.
<b>DRYING TIMES</b>	
Touch Dry	Single coat at standard thickness:
Recoat	Dependant on temperature and humidity. 2-3 hours.
<b>CLEANING UP</b>	Clean all equipment with clean water immediately after use.

## PRE-APPLICATION

<b>SURFACE PREPARATION</b>	Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be thoroughly rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate Primer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 17%. These wall should be left to dry further.	
<b>SYSTEM INFORMATION</b>	<b>PRIMER (1 COAT)</b>	<b>FINISH (2 COATS)*</b> Vibrant/ deep shade may require additional coats.
Powdery Surfaces	Dulux Weathershield Primer (A579-15222)	Dulux Inspire Interior
Alkaline and New Surfaces	Dulux Exterior & Interior Wall Sealer (A1290013 0015527)	or Dulux Inspire Exterior
Normal, Sound Surfaces	No Primer Required	

## PRECAUTION

<b>HEALTH, SAFETY AND ENVIRONMENT INFORMATION</b>	<ul style="list-style-type: none"> <li>• Keep out of the reach of children</li> <li>• Do not breathe vapour/ spray</li> <li>• Use only in well ventilated areas</li> <li>• Safety data sheet available for professional user on request.</li> <li>• Avoid contact with skin or eyes</li> <li>• If swallowed seek medical advice immediately and show this container or label.</li> <li>• Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet [sanding]/[flattening] should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used</li> <li>• Do not use empty container for storing food.</li> <li>• Remove as much paints as possible from brushes and rollers before cleaning.</li> <li>• Keep away from food, drinks and animal feed.</li> <li>• Store in a cool and shaded place.</li> <li>• Container must be in a secure, upright position and be tightly closed.</li> <li>• In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.</li> <li>• In case of contact with skin wash immediately with soap and water or a proprietary skin cleanser. Do not use solvents or thinners.</li> <li>• Wear eye/hand protection.</li> <li>• Avoid release to environment. Refer to special instructions/Safety data sheet.</li> <li>• Do not empty into water course.</li> <li>• Dispose of used container in compliance with local regulation.</li> <li>• Refer to Dulux Product Safety Data Sheet for further details.</li> <li>• In case of emergency, refer to Emergency Incident Response Hotline 1-800-80-6187</li> </ul>
---	---

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties.

### Akzo Nobel Paints (Malaysia) Sdn Bhd

(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:

Customer Care Department

Tel: 1-800-88-9338 Website: [www.dulux.com.my](http://www.dulux.com.my) Email: [customercare.my@akzonobel.com](mailto:customercare.my@akzonobel.com)