

TECHNICAL DATA SHEET

Tiger Brand Paint Remover 300

SOLVENT BASED PAINT REMOVER

DESCRIPTION:

Tiger Brand Paint Remover 300 is a single component heavy-duty paint removing agent.

TYPICAL USES:

Recommended for marine and industrial environment. Provide excellent paint removing function for most types of coating.

SUBSTRATES:

Recommended for application on steel and other metals surfaces.

ADVANTAGES:

- Provide strong and easy to apply properties.
- Product is ready for use.

TECHNICAL DATA @ 25°C:

Colour:	Translucent liquid
Finish:	NA
Volume Solids:	NA
Specific Gravity	0.95 (+/-) 0.05

DIRECTIONS FOR USE:

Surface Preparation

The preferred surface should be clean and dry, free from unnecessary grease and oil.

Application

Paint Remover 300 can be applied by roller or brush. Preferably, sufficient Paint Remover 300 must be applied to soak the coating. When the coating delaminates or when the adhesion is weakened, the paint remover together the coating must be removed for best results by hand held implements.

Allowing the paint remover to dry out, may not produce the best results as removing the coating may then become difficult.

Provide proper ventilation in confined areas to avoid inhalation of fumes.

Spreading Information

Recommended Wet film thickness: NA

Dry film thickness: NA

Spreading rate: NA

Thinning

No thinning is required.

Cleaning

All equipment and removed materials should be properly disposed off.

PACKAGING AND STORAGE:

The product comes in both 0.5/1.0/3.5/5.0/18.0 litres packing. Must be stored in cool well-ventilated area away from direct sunlight.

HEALTH AND SAFETY:

Do not inhale spray mist. Remove all contaminated clothing and wash skin with suitable proprietary cleaners or soap and water. In case of contact with eyes, flush immediately with water for at least 15 minutes. If persistent discomfort or irritation occurs after application please seek medical advice.

Disclaimer: The technical information provided is believed to be reliable based on the manufacturer's tests and experience. However as the product is often applied in varying field conditions beyond the manufacturer's control, our company cannot guarantee anything but the product itself. And the manufacturer reserves the right to amend the information without any notice.