

# AMANO

ELECTRONIC TIME RECORDER

# EX3500N

PRECISION HAS NEVER BEEN SO ECONOMICAL

High-quality dot matrix printer for clean, clear printing

Printing irregular work in red color

Programmable IN/OUT Printing position

6 column printing

## MAIN FEATURES

- Simple, clean design fits any business environment
- Simple and Easy Operation
- Large, easy-to-read analog clock face with quartz time base.
- Surface detection function for right side of time card
- Automatic adjustment of Daylight-Saving Time, short months, leap years
- Automatic card feeding, standard
- Auto IN/OUT shift
- Two color printing
- Time Signal



White

Black

No.	48		PAY ENDING		April, 20 03		
NAME	Jason Brown						
	HOURS	RATE	AMOUNT		DEDUCTIONS		
R.T.	186.5	\$6.00	\$1,119.00		INCOME TAX \$180.00		
O.T.	10	\$9.00	\$90.00		UNEMP. INS. \$20.00		
					HOSP.		
					BONDS		
					MISC.		
TOTAL EARNINGS			\$1,209.00				
TOTAL DEDUCTIONS			\$200.00				
BALANCE DUE			\$1,009.00		TOTAL \$200.00		
DATE	MORNING		AFTERNOON		OVERTIME		HRS.
	IN	OUT	IN	OUT	IN	OUT	
1	8:28	12:02	12:58	17:36			8
2	8:34	12:03	12:57	17:39	17:45	19:46	9.5
3	8:27	12:01	12:54	17:33			8
4	8:29	12:04	13:02	17:38			7.5
5	8:28	12:10					3.5
6							
7	8:28	12:01	12:58	15:00			5.5
8	8:28	12:03	12:58	17:36			8
9	8:29	11:55	12:59	17:31	18:00	20:03	9.5
10	8:24	12:04	12:59	17:37			8
11	8:29	12:01	12:58	17:37			8
12	8:27	12:03					3.5
13							
14	8:22	12:08	12:58	17:32			8
15	8:29	12:01	12:55	17:38			8

THE BALANCE SHOWN ABOVE IS CORRECT AND RECEIPT IS ACKNOWLEDGED.

SIGNATURE Jason Brown

AMANO FORM A-701

### Acceptable Pay Period

Pay period ending date can be set three ways.

- weekly
- bi-weekly
- monthly

### BASIC SPECIFICATIONS

Printing	Dot matrix printing
Power Supply	110/120VAC or 220/240VAC±10% 50/60Hz
Power Consumption	110-120VAC...Stand-by 70mA, Rated 400mA 220-240VAC...Stand-by 60mA, Rated 220mA
Operating Conditions	Temperature-10°C to 40°C Humidity 10% to 90% RH(without condensation)
Dimensions	190(W)×224(H)×127(D)mm (7.1/2")×(8.6/8")×(5")
Clock System	Quartz oscillation system, Accuracy ±3 seconds per week(25°C±5°C)(77°F±10°F)
Weight	2.3Kg(5.07Lbs.)
Memory holding function	Clock and programing data kept for 3 years without AC power

Specifications and descriptions contained in this catalog may be subject to change without notice.

Distributed by:

**AMANO Corporation**

275 MAMEDO-CHO, KOHOKU-KU, YOKOHAMA,  
JAPAN 222-8558  
TEL.+81-45-439-1508 FAX.+81-45-439-1151  
HOME PAGE : <http://www.amano.co.jp/english/>