

JP CONSULTANCY & ENGINEERING SDN. BHD. (884518-A)

NO. 41, Jalan Anggerik Mokara 31/64, Kawasan Industri Kota Kemuning, 40460 Shah Alam, Selangor D.E. Malaysia. Tel: +60351316514 Fax: +60351210964

Email: mnara@jpconsultancy.com.my / enquiry@jpconsultancy.com.my

Web: www.jpconsultancyandengineering.com

MATERIAL SAFETY DATA SHEET JP™ CORRO TEMP 700°C

1. PRODUCT AND COMPANY IDENTIFICATION

Product name : JP™ CORRO TEMP 700°C

Colour : Grey

Product Type : Solvent based composition – Flammable Company Address : JP CONSULTANCY & ENGINEERING SDN. BHD.

No. 41, Jalan Anggerik Mokara 31/64,

Kawasan Industri Kota Kemuning, 40460 Shah Alam,

Selangor D.E. Malaysia.

2. COMPOSITION/INFORMATION ON INGREDIENTS

Ingredient	CAS Number	%	Exposure Limits
Xylene	1330-20-7	10-20	not established
Butanol -n	71-36-3	10-20	not established
Modified Aluminium silicate		20-40	not established
Modified Magnesium silicate		10-20	not established
Additive (Proprietary)		5-10	not established

3. HAZARDS IDENTIFICATION

Emergency Overview : Flammable liquid. Causes moderate eye, skin, and digestive tract irritation.

Spray mist causes irritation to respiratory tract. Release into surface water is harmful to aquatic life. Combustible. Spills are slippery. Reacts with acids,

ammonium salts, reactive metals and some organics.

Eye contact : Causes moderate irritation to the eyes.
Skin contact : Causes moderate irritation to the skin.
Inhalation : Spray mist irritating to respiratory system.

Ingestion : May cause irritation to mouth, esophagus, and stomach. Chronic hazards : No known chronic hazards. Not listed as a carcinogen.

4. FIRST AID MEASURES

Eye : In case of contact, immediately flush eyes with plenty of water. Get medical

attention.

Skin : In case of contact flush skin with plenty of water. Remove contaminated

clothing and shoes. Inhalation: Remove to fresh air. Get medical attention.

Ingestion : If swallowed, DO NOT induce vomiting. Get medical attention immediately.



JP CONSULTANCY & ENGINEERING SDN. BHD. (884518-A)

NO. 41, Jalan Anggerik Mokara 31/64, Kawasan Industri Kota Kemuning, 40460 Shah Alam, Selangor D.E. Malaysia. Tel: +60351316514 Fax: +60351210964

Email: mnara@jpconsultancy.com.my / enquiry@jpconsultancy.com.my Web: www.jpconsultancyandengineering.com

5. FIRE FIGHTING MEASURES

THE PRODUCT IS FLAMMABLE

Suitable extinguishing media – Foam, Carbon dioxide.

6. ACCIDENTAL RELEASE MEASURES

- Avoid contact with skin and eyes.
- Spillages can cause slippery situations
- Collect as much as possible in a (clean) container or by absorbent material

7. HANDLING AND STORAGE

Handling : Avoid contact with the concentrated product. The product is sticky. Use

protective gloves and mask.

Storage : Keep packaging / storage vessel closed. Protect from freezing. Keep away from

sources of ignition.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering measures / system design : NA

Respiratory protection : prevent breathing of the spray Hand protection : wear chemical resistant gloves

Eye protection : wear suitable goggles

Skin protection : wear suitable protective clothing

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Thick liquid

Color : Grey

Odor : xylene, butanol.

PH : na

Specific gravity : 1.6 - 1.7 g/cc Solubility in water : not Miscible.

Flash point : 13°C

10. STABILITY AND REACTIVITY

Stability : This material is stable under all conditions of use and

storage.

Conditions to avoid : fire, ignition sources

Materials to avoid : water, oxidizing agent

Hazardous decomposition products : carbon dioxide



JP CONSULTANCY & ENGINEERING SDN. BHD. (884518-A)

NO. 41, Jalan Anggerik Mokara 31/64, Kawasan Industri Kota Kemuning, 40460 Shah Alam, Selangor D.E. Malaysia. Tel: +60351316514 Fax: +60351210964

Email: mnara@jpconsultancy.com.my / enquiry@jpconsultancy.com.my
Web: www.jpconsultancyandengineering.com

11. TOXICOLOGICAL INFORMATION

When tested for eye and skin irritation potential, a similar material caused moderate irritation to the eyes and moderate irritation to the skin. The acute oral toxicity of this product has not been tested.

12. ECOLOGICAL INFORMATION

This material is toxic to aquatic systems in high concentrations.

13. DISPOSAL CONSIDERATIONS

Do not dump in sewers, on the ground, into water bodies.

Recommended Method of Disposal: Dispose according to central and local governmental regulations.

14. TRANSPORTATION INFORMATION

Flammable liquid.

15 REGULATORY INFORMATION

Hazard Symbols : Flammable liquid

R-phrases : None S-phrases : None

16. OTHER INFORMATIONS

The product is meant for industrial use

The information on this material safety data sheet is believed to be accurate. This document is intended only as a guide to the appropriate precautions for handling a chemical by a person trained in chemical handling. JP Consultancy and Engineering Sdn. Bhd. makes no warranty with respect to such information or the product to which it relates, and we assume no liability resulting from the use or handling of the product to which this material safety data sheet relates. Users and handlers of this product should make their own investigations to determine the suitability of the information provided herein for their own purpose.