

ANGLE GRINDER



GWS 6/100(BOSCH)

DCA-PT-001
ASM03-100A
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
710
13,000
1.6



G15 SA2 (HITACHI)

DCA-PT-005
ASM02-125B
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(4/CTN)
Ø 125
Ø 22
1,200
11,800
3.0



DCA-PT-001C
ASM06-100
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
800
9,000
2.0



G18 SE2 (HITACHI)

DCA-PT-006
ASM180A
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(2/CTN)
Ø 180
Ø 22
2,020
8,300
5.0



DCA-PT-003
ASM05-100B
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
850
13,000
1.7



DCA-PT-006B
ASM180SH
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(2/CTN)
Ø 180
Ø 22
2,600
8,400
5.8



DCA-PT-001VS
ASM10-100
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
1,020
13,000
2.1



DCA-PT-006C
ASM05-180
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(2/CTN)
Ø 180
Ø 22
3,000
8,300
5.0



DCA-PT-003A
ASM 10-100S
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
1,020
13,000
2.1



Soft Start
G23 SC2 (HITACHI)

DCA-PT-006A
ASM230A
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(2/CTN)
Ø 230
Ø 22
2,020
6,600
5.0



DCA-PT-003B
ASM12-100
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(10/CTN)
Ø 100
Ø 16
850
13,000
1.8



DCA-PT-006D
ASM05-230
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(2/CTN)
Ø 230
Ø 22
3,000
6,600
5.0

STRAIGHT GRINDER



DCA-PT-007
ASS125B
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(4/CTN)
Ø 125
Ø 20
710
5,300
4.3



DCA-PT-007A
ASS150
Max. Wheel Diameter (mm)
Hole Diameter of Wheel (mm)
Rated Power Input (W)
Rated Speed (r/min)
Net Weight (kg)

(4/CTN)
Ø 150
Ø 20
1,020
5,000
4.7

GROOVE CUTTER



| | |
|-------------------------|----------------|
| DCA-PT-008GC | |
| AZR110 | (4/CTN) |
| Blade Diameter (mm) | Ø 110 |
| Rated Power Input (W) | 1,600 |
| No-Load Speed (r/min) | 10,800 |
| Max. Cutting Depth (mm) | 32 |
| Max. Cutting Width (mm) | 50 |
| Net Weight (kg) | 4.1 |



| | |
|-------------------------|----------------|
| DCA-PT-009A | |
| AZR02-150 | (1/CTN) |
| Blade Diameter (mm) | Ø 150 |
| Rated Power Input (W) | 1,400 |
| No-Load Speed (r/min) | 7,000 |
| Max. Cutting Depth (mm) | 30 |
| Max. Cutting Width (mm) | 32 |
| Net Weight (kg) | 6.3 |

MARBLE CUTTER



| | |
|----------------------------|----------------|
| DCA-PT-008 | |
| AZE110 | (4/CTN) |
| Blade Diameter (mm) | Ø 110 |
| Max. Cutting Capacity (mm) | 30 |
| Rated Power Input (W) | 1,200 |
| No-Load Speed (r/min) | 13,000 |
| Net Weight (kg) | 3.0 |



| | |
|----------------------------|----------------|
| DCA-PT-009 | |
| AZE180 | (2/CTN) |
| Blade Diameter (mm) | Ø 180 |
| Max. Cutting Capacity (mm) | 60 |
| Rated Power Input (W) | 1,520 |
| No-Load Speed (r/min) | 5,000 |
| Net Weight (kg) | 7.0 |



| | |
|----------------------------|----------------|
| DCA-PT-008A | |
| AZE05-110 | (4/CTN) |
| Blade Diameter (mm) | Ø 110 |
| Max. Cutting Capacity (mm) | 30 |
| Bevel Cutting Angle (°) | 0 - 45 |
| Rated Power Input (W) | 1,400 |
| No-Load Speed (r/min) | 12,000 |
| Net Weight (kg) | 3.2 |

WELD JOINT BEVELLER



| | |
|-----------------------|----------------|
| DCA-PT-015A | |
| AJB3 | (8/CTN) |
| Rated Power Input (W) | 800 |
| No-Load Speed (r/min) | 9,000 |
| Blade Size (mm) | Ø 9.5x3.5xØ4.2 |
| Net Weight (kg) | 2.5 |



| | |
|-----------------------|----------------|
| DCA-PT-015B | |
| ASN100 | (2/CTN) |
| Rated Power Input (W) | 1,400 |
| Rated Speed (r/min) | 690 - 3,800 |
| Wheel Size (mm) | 120 x 100 |
| Net Weight (kg) | 4.7 |

GRINDING POLISHER

DIE GRINDER



| | |
|-------------------------------|-----------------|
| DCA-PT-019CVS | |
| ASJ03-10 | (12/CTN) |
| Rated Power Input (W) | 105 |
| Rated Speed (r/min) | 14,000-30,000 |
| Max. Grinding Wheel Dia. (mm) | Ø 10 |
| Net Weight (kg) | 0.6 |



| | |
|-------------------------------|----------------|
| DCA-PT-019D | |
| ASJ04-25 | (8/CTN) |
| Rated Power Input (W) | 260 |
| Rated Speed (r/min) | 26,700 |
| Max. Grinding Wheel Dia. (mm) | Ø 25 |
| Net Weight (kg) | 1.3 |




| | |
|-------------------------------|----------------|
| DCA-PT-019 | |
| ASJ02-25 | (8/CTN) |
| Rated Power Input (W) | 400 |
| Rated Speed (r/min) | 27,000 |
| Max. Grinding Wheel Dia. (mm) | Ø 25 |
| Net Weight (kg) | 1.8 |




| | |
|-----------------------------------|----------------|
| DCA-PT-019E | |
| ASJ05-25 | (8/CTN) |
| Rated Power Input (W) | 550 |
| Rated Speed (r/min) | 9,000-26,700 |
| Max. Grinding Wheel Diameter (mm) | Ø 25 |
| Net Weight (kg) | 1.6 |


ELECTRIC DRILL


DCA-PT-010
AJZ02-6A (10/CTN)
 Rated Power Input (W) 230
 No-Load Speed (r/min) 0 - 3,800
 Max. Drilling Capacity
 Steel (mm) Ø 6.5
 Wood (mm) Ø 9
 Net Weight (kg) 1.2

D 6 SH (Hitachi)






DCA-PT-013
AJZ02-13 (8/CTN)
 Rated Power Input (W) 500
 No-Load Speed (r/min) 0 - 1,200
 Max. Drilling Capacity
 Steel (mm) Ø 13
 Wood (mm) Ø 20
 Net Weight (kg) 2.4

DU10 (Hitachi)






DCA-PT-011
AJZ10A (10/CTN)
 Rated Power Input (W) 300
 No-Load Speed (r/min) 0 - 3,000
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 18
 Net Weight (kg) 1.5







DCA-PT-014
AJZ03-13B (6/CTN)
 Rated Power Input (W) 800
 No-Load Speed (r/min) 850
 Max. Drilling Capacity
 Steel (mm) Ø 13
 Wood (mm) Ø 36
 Net Weight (kg) 2.9

6013 BR (Makita)






DCA-PT-011A
AJZ06-10 (10/CTN)
 Rated Power Input (W) 380
 No-Load Speed (r/min) 0 - 1,400
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 15
 Net Weight (kg) 1.9







DCA-PT-015
AJZ16A (6/CTN)
 Rated Power Input (W) 800
 No-Load Speed (r/min) 680
 Max. Drilling Capacity
 Steel (mm) Ø 16
 Wood (mm) Ø 36
 Net Weight (kg) 3.2

6013 BR (Makita)






DCA-PT-012
AJZ05-10A (6/CTN)
 Rated Power Input (W) 500
 No-Load Speed (r/min) 0 - 2,600
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 25
 Net Weight (kg) 1.7

GBM 500 RE (Bosch)






DCA-PT-015C
AJZ03-16A (6/CTN)
 Rated Power Input (W) 1,010
 No-Load Speed (r/min) 620
 Max. Drilling Capacity
 Steel (mm) Ø 16
 Wood (mm) Ø 36
 Net Weight (kg) 3.2







DCA-PT-012B
AJZ07-10 (KEYLESS) (10/CTN)
 Rated Power Input (W) 500
 No-Load Speed (r/min) 0 - 1,750
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 25
 Net Weight (kg) 1.5







DCA-PT-012A
AJZ08-10 (KEYLESS) (10/CTN)
 Rated Power Input (W) 250
 No-Load Speed (r/min) 0 - 850
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 20
 Net Weight (kg) 1.2






DCA-PT-012C
AJZ09-10 (8/CTN)
 Rated Power Input (W) 710
 No-Load Speed (r/min) 0 - 2,800
 Max. Drilling Capacity
 Steel (mm) Ø 10
 Wood (mm) Ø 20
 Net Weight (kg) 1.6







IMPACT SCREWDRIVER


DCA-PT-037B
APL6 (10/CTN)
 Rated Power Input (W) 710
 No-Load Speed (r/min) 0 - 4,300
 Max. Screw Dia (mm) 6
 Net Weight (kg) 1.6





DCA-PT-037ID
APL8 (8/CTN)
 Rated Power Input (W) 300
 No-Load Speed (r/min) 0 - 2,200
 Rated Impacting Frequency (.../min) 0 - 3,000
 Max. Fastening Torque (N.m) 98
 Net Weight (kg) 1.3





IMPACT DRILL



DCA-PT-017
AZJ13 (8/CTN)

| | |
|-------------------------------------|------------|
| Rated Power Input (W) | 500 |
| No-Load Speed (r/min) | 0 - 1,200 |
| Rated Impacting Frequency (.../min) | 0 - 15,600 |
| Max. Drilling Capacity (mm) | Ø 13 |
| Net Weight (kg) | 2.5 |






DCA-PT-017AA
AZJ02-13 (8/CTN)

| | |
|-------------------------------------|------------|
| Rated Power Input (W) | 500 |
| No-Load Speed (r/min) | 0 - 2,600 |
| Rated Impacting Frequency (.../min) | 0 - 41,600 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 10 |
| Concrete (mm) | Ø 13 |
| Wood (mm) | Ø 25 |
| Net Weight (kg) | 2.0 |



DCA-PT-017AB
AZJ16 (8/CTN)

| | |
|------------------------|-----------|
| Rated Power Input (W) | 710 |
| No-Load Speed (r/min) | 0 - 3,000 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 13 |
| Concrete (mm) | Ø 16 |
| Wood (mm) | Ø 30 |
| Net Weight (kg) | 2.0 |

DCA-PT-017AA-1
AZJ04-13 (4/CTN)



| | |
|-------------------------------------|------------|
| Rated Power Input (W) | 500 |
| No-Load Speed (r/min) | 0 - 2,600 |
| Rated Impacting Frequency (.../min) | 0 - 41,600 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 10 |
| Concrete (mm) | Ø 13 |
| Wood (mm) | Ø 25 |

MIXER



DCA-PT-016
AQU160 (B) (6/CTN)

| | |
|-----------------------|-----|
| Rated Power Input (W) | 800 |
| No-Load Speed (r/min) | 680 |
| Net Weight (kg) | 3.5 |

DCA-PT-016A
AQU02-160 (8/CTN)

| | |
|---------------------------|-------|
| Rated Power Input (W) | 1,010 |
| No-Load Speed (r/min) | 620 |
| Dia. of Mixing Wheel (mm) | Ø 160 |
| Net Weight (kg) | 3.5 |

DCA-PT-016B
AQU05-160 (3/CTN)

| | |
|-----------------------|-------|
| Rated Power Input (W) | 1,800 |
| No-Load Speed (r/min) | 2,000 |
| Net Weight (kg) | 5.5 |




ROTARY HAMMER

DCA-PT-017A
AZC38 (2/CTN)

| | |
|-----------------------------|------|
| Rated Power Input (W) | 800 |
| No-Load Speed (r/min) | 400 |
| Max. Drilling Capacity (mm) | Ø 38 |
| Net Weight (kg) | 7.6 |



PR 38E (Hitachi)
SDS-Hex 13mm




DCA-PT-017B
AZC03-26B (3/CTN)

| | |
|-------------------------------------|-------|
| Rated Power Input (W) | 750 |
| No-Load Speed (r/min) | 500 |
| Rated Impacting Frequency (.../min) | 3,200 |
| Max. Drilling Capacity (mm) | Ø 26 |
| Net Weight (kg) | 5.0 |

SDS-Plus
2 MODES : HAMMER & DEMOLITION

DCA-PT-017C
AZC03-38 (3/CTN)

| | |
|-------------------------------------|-------|
| Rated Power Input (W) | 1,100 |
| No-Load Speed (r/min) | 320 |
| Rated Impacting Frequency (.../min) | 2,900 |
| Max. Drilling Capacity (mm) | Ø 38 |
| Net Weight (kg) | 6.2 |



SDS-Max
2 MODES : HAMMER & DEMOLITION




AZC04-30 (3/CTN)

| | |
|-----------------------------|-------|
| Rated Power Input (W) | 960 |
| No-Load Speed (r/min) | 1,000 |
| Max. Drilling Capacity (mm) | Ø 30 |

SDS-Plus
2 MODES : HAMMER & DEMOLITION

HAMMER DRILL




DCA-PT-018
AZC02-20
 Rated Power Input (W)
 No-Load Speed (r/min)
 Max. Drilling Capacity (mm)
 Net Weight (kg)

(4/CTN)
 500
 0 - 850
 Ø 20
 2.9



DCA-PT-018C
AZC05-26B
 Rated Power Input (W)
 No-Load Speed (r/min)
 Rated Impacting Frequency (.../min)
 Max. Drilling Capacity (mm)
 Net Weight (kg)

(4/CTN)
 720
 0 - 1,200
 0 - 4,000
 Ø 26
 2.93



DEMOLITION HAMMER




DCA-PT-033
AZG6
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(2/CTN)
 1050
 2,900
 6.8



DCA-PT-034C
AZG04-15
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(1/CTN)
 1,520
 1,450
 14.3



DCA-PT-033C
AZG06-6
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(3/CTN)
 1,350
 3,900
 6.8



DCA-PT-034A
AZG15
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(1/CTN)
 1,240
 1,400
 16



DCA-PT-033B
AZG05-6
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(3/CTN)
 1,050
 3,000
 5.5



DCA-PT-034B
AZG10
 Rated Power Input (W)
 Rated Impacting Frequency (.../min)
 Net Weight (kg)

(1/CTN)
 1,500
 900 - 1,890
 10.4




PLANER



DCA-PT-023
AMB82
 Max. Planing Width (mm)
 Max. Planing Depth (mm)
 Rated Power Input (W)
 No-Load Speed (r/min)
 Net Weight (kg)

(3/CTN)
 82
 1
 500
 16,000
 2.9



DCA-PT-023A
AMB110
 Max. Planing Width (mm)
 Max. Planing Depth (mm)
 Rated Power Input (W)
 No-Load Speed (r/min)
 Net Weight (kg)

(4/CTN)
 110
 2
 840
 16,500
 4.2



DCA-PT-023B
AMB03-82
 Max. Planing Width (mm)
 Hole Planing Depth (mm)
 Rated Power Input (W)
 No-Load Speed (r/min)
 Net Weight (kg)

(4/CTN)
 82
 1
 500
 16,000
 2.9



ORBITAL SANDER



BO4510 (MAKITA)

DCA-PT-020
ASB100
Rated Power Input (W)
Orbits Frequency (.../min)
Pad Size (mm)
Net Weight (kg)

(16/CTN)
150
12,000
100 x 110
1.3



DCA-PT-021
ASB185
Rated Power Input (W)
Orbits Frequency (.../min)
Pad Size (mm)
Net Weight (kg)

(10/CTN)
160
10,000
93 x 185
1.7



DCA-PT-020A
ASB03-100
Rated Power Input (W)
Orbits Frequency (.../min)
Pad Size (mm)
Net Weight (kg)

(16/CTN)
240
14,000
100 x 110
1.2



DCA-PT-022
ASB234
Rated Power Input (W)
Orbits Frequency (.../min)
Pad Size (mm)
Net Weight (kg)

(8/CTN)
520
10,000
114 x 234
2.9

WOOD ROUTER



DCA-PT-024A
AMR02-12
Rated Power Input (W)
Max. Milling Cutter Dia. (mm)
No-Load Speed (r/min)
Net Weight (kg)

(2/CTN)
1,650
Ø12/12.7
22,000
6.0



DCA-PT-024B
AMR05-12
Rated Power Input (W)
Max. Milling Cutter Dia. (mm)
No-Load Speed (r/min)
Net Weight (kg)

(2/CTN)
1,240
Ø12/12.7
24,000
4.6



DCA-PT-024
AMR12
Rated Power Input (W)
Max. Milling Cutter Dia. (mm)
No-Load Speed (r/min)
Net Weight (kg)

(2/CTN)
1,600
Ø12/12.7
23,000
6.0

BELT SANDER



DCA-PT-025A
AST533
Rated Power Input (W)
Belt Speed (m/s)
Belt Size (mm)
Net Weight (kg)

(8/CTN)
550
3.3 - 16.6
30 x 533
2.1



DCA-PT-025B
AST610
Rated Power Input (W)
Belt Speed (m/min)
Belt Size (mm)
Net Weight (kg)

(3/CTN)
1,200
500
100 x 610
5.8

SANDER POLISHER



HITACHI SAT-180

DCA-PT-027
ASP180
Rated Power Input (W)
Rated Speed (r/min)
Wheel Size (mm)
Net Weight (kg)

(4/CTN)
750
2,500 - 3,400
Ø 180
3.6



MAKITA 92188

DCA-PT-028
ASP02-180
Rated Power Input (W)
Rated Speed (r/min)
Wheel Size (mm)
Net Weight (kg)

(4/CTN)
570
1,000 - 2,400
Ø 180
3.3



DCA-PT-027A
ASP03-180
Rated Power Input (W)
Rated Speed (r/min)
Wheel Size (mm)
Net Weight (kg)

(4/CTN)
1,020
1,000 - 3,600
Ø 180
3.6



DCA-PT-028A
ASP04-180
Rated Power Input (W)
Rated Speed (r/min)
Wheel Size (mm)
Net Weight (kg)

(4/CTN)
1,400
690 - 3,800
Ø 180
3.4

DISC SANDER



GV 6000 (Makita) 

| | |
|------------------------|-----------------|
| DCA-PT-026 | |
| ASA150 | (10/CTN) |
| Rated Power Input (W) | 405 |
| Rated Speed (r/min) | 4,700 |
| Grinding Disc Diameter | Ø 150 |
| Net Weight (kg) | 1.6 |

JIG SAW



GST 85 (Bosch) 

| | |
|----------------------------------|----------------|
| DCA-PT-025 | |
| AMQ85 | (6/CTN) |
| Rated Power Input (W) | 580 |
| No-Load Strokes (.../min) | 500 - 3,100 |
| Bevel Cutting Angle (Left/Right) | 0 - 45° |
| Max. Cutting Capacity | |
| Steel (mm) | 10 |
| Wood (mm) | 85 |
| Net Weight (kg) | 2.7 |





| | |
|----------------------------------|----------------|
| DCA-PT-025C | |
| AMQ65K | (6/CTN) |
| Rated Power Input (W) | 600 |
| No-Load Strokes (.../min) | 500 - 3,000 |
| Bevel Cutting Angle (Left/Right) | 0 - 45° |
| Max. Cutting Capacity | |
| Steel (mm) | 10 |
| Wood (mm) | 65 |
| Net Weight (kg) | 2.5 |

RECIPROCATING SAW





| | |
|---------------------------|----------------|
| DCA-PT-030 | |
| AJF30 | (3/CTN) |
| Rated Power Input (W) | 590 |
| No-Load Strokes (.../min) | 0 - 2,300 |
| Length of Strokes (mm) | 30 |
| Max. Cutting Capacity | |
| Steel (mm) | 90 |
| Wood (mm) | 90 |
| Net Weight (kg) | 3.2 |





| | |
|-------------------------------|----------------|
| DCA-PT-030A | |
| AML02-405 | (2/CTN) |
| No-Load Speed (m/min) | 400 |
| Rated Power Input (W) | 1,300 |
| Max. Length of Guide Bar (mm) | 405 |
| Net Weight (kg) | 5.6 |

TRIMMER



3703 (MAKITA) 

| | |
|-------------------------------|----------------|
| DCA-PT-029 | |
| AMP02-6 | (9/CTN) |
| Rated Power Input (W) | 350 |
| Rated Speed (r/min) | 30,000 |
| Max. Milling Cutter Dia. (mm) | 6/6.35 |
| Net Weight (kg) | 1.8 |






| | |
|-------------------------------|----------------|
| DCA-PT-029A | |
| AMP03-6 | (9/CTN) |
| Rated Power Input (W) | 530 |
| Rated Speed (r/min) | 30,000 |
| Max. Milling Cutter Dia. (mm) | 6/6.35 |
| Net Weight (kg) | 1.8 |

SHEAR




JS 3200 (Makita) 

| | |
|-------------------------------------|----------------|
| DCA-PT-035 | |
| AJJ32 | (6/CTN) |
| Rated Power Input (W) | 620 |
| Cutting Capacity | |
| Mild Steel (mm) | 3.2 |
| Stainless (mm) | 2.5 |
| Min. Cutting Radius (mm) | 50 |
| Rated Impacting Frequency (.../min) | 1,600 |
| Net Weight (kg) | 3.8 |

NIBBLER



JN 3200 (Makita) 

| | |
|---------------------------|----------------|
| DCA-PT-036 | |
| AJH32 | (6/CTN) |
| Rated Power Input (W) | 620 |
| No-Load Strokes (.../min) | 1,300 |
| Max. Cutting Capacity | |
| Mild Steel (mm) | 3.2 |
| Stainless (mm) | 2.5 |
| Min. Cutting Radius | |
| Inner Dia. (mm) | 120 |
| Outer Dia. (mm) | 128 |
| Net Weight (kg) | 3.8 |

HOT AIR GUN



| | |
|-------------------------------------|-----------------|
| DCA-PT-044 AQB2000 | (10/CTN) |
| Rated Output Voltage (V~) | 220 - 240 |
| Rated Power Input (W) | 2,000 |
| Temperature: | |
| Low Temperature (°C) | 50 - 480 |
| High Temperature (°C) | 50 - 600 |
| Air Flow: | |
| Low Temperature (L/min) | 210 - 250 |
| High Temperature (L/min) | 340 - 380 |
| Net Weight (kg) | 0.8 |

BLOWER VACUUM



| | |
|------------------------------------|----------------|
| DCA-PT-045A AQF32 | (6/CTN) |
| Rated Power Input (W) | 680 |
| No-Load Speed (r/min) | 8,300 - 16,300 |
| The Maximum Gas Volume (m³/min) | 1.6 - 3.2 |
| Net Weight (kg) | 1.8 |

CUT-OFF MACHINE



| | |
|---------------------------------------|----------------|
| DCA-PT-031 AJG02-355 | (1/CTN) |
| Wheel Size (mm) | 355 x 3 x 25.4 |
| Rated Power Input (W) | 2,000 |
| No-Load Speed (r/min) | 3,800 |
| Net Weight (kg) | 16.0 |



| | |
|--|----------------|
| DCA-PT-031A AJG04-355 | (1/CTN) |
| Wheel Size (mm) | 355 x 3 x 25.4 |
| Rated Power Input (W) | 2,000 |
| No-Load Speed (r/min) | 3,800 |
| Net Weight (kg) | 14.0 |

MITRE SAW



| | |
|------------------------------------|----------------|
| DCA-PT-043 AJX255 | (1/CTN) |
| Rated Power Input (W) | 1,650 |
| No-Load Speed (r/min) | 4,600 |
| Blade Diameter (mm) | 255 |
| Net Weight (kg) | 12.0 |

CIRCULAR SAW



5704 R (Makita)

| | |
|------------------------------------|----------------|
| DCA-PT-039 AMY185 | (2/CTN) |
| Rated Power Input (W) | 1,100 |
| No-Load Speed (r/min) | 4,900 |
| Max. Cutting Capacity (mm) | 64 |
| Max. Cutting Angle | 45° |
| Net Weight (kg) | 5.0 |



| | |
|--|----------------|
| DCA-PT-039A AMY02-185 | (2/CTN) |
| Rated Power Input (W) | 1,100 |
| No-Load Speed (r/min) | 5,600 |
| Max. Cutting Capacity (mm) | 64 |
| Max. Cutting Angle | 45° |
| Net Weight (kg) | 3.6 |



| | |
|--|----------------|
| DCA-PT-039B AMY03-185 | (2/CTN) |
| Rated Power Input (W) | 1,400 |
| No-Load Speed (r/min) | 5,300 |
| Max. Cutting Capacity (mm) | 64 |
| Max. Cutting Angle | 45° |
| Net Weight (kg) | 5.0 |



5900 BR (Makita)

| | |
|------------------------------------|----------------|
| DCA-PT-040 AMY235 | (2/CTN) |
| Rated Power Input (W) | 1,520 |
| No-Load Speed (r/min) | 4,100 |
| Max. Cutting Capacity (mm) | 84 |
| Max. Cutting Angle | 45° |
| Net Weight (kg) | 7.5 |



| | |
|--|----------------------|
| DCA-PT-040A AMY02-235 | (2/CTN) |
| Rated Power Input (W) | 2,000 |
| No-Load Speed (r/min) | 4,100 |
| Max. Cutting Capacity (mm) | (90°) 85 (45°) 60 |
| Max. Bevel Cutting Angle(°) | 50 |
| Net Weight (kg) | 6.5 |

DIAMOND CORE DRILL



DCA-PT-041A
AZZ90 (3/CTN)
 Rated Power Input (W) 1,350
 No-Load Speed (r/min) 0 - 2,300
 Max. Drilling Capacity (mm) Ø 90
 Net Weight (kg) 4.4



DCA-PT-042B
AZZ02-160 (3/CTN)
 Rated Power Input (W) 1,800
 No-Load Speed (r/min) 1,900
 Max. Drilling Capacity (mm) Ø 160
 Net Weight (kg) 5



DCA-PT-041
AZZ130 (1/CTN)
 Rated Power Input (W) 1,350
 No-Load Speed (r/min) 1,100
 Max. Drilling Capacity (mm) Ø 130
 Net Weight (kg) 12



DCA-PT-042C
AZZ02-200S (1/CTN)
 Rated Power Input (W) 3,500
 No-Load Speed (r/min) 700
 Max. Drilling Capacity (mm) Ø 200
 Net Weight (kg) 25



DCA-PT-042A
AZZ02-250 (1/CTN)
 Rated Power Input (W) 3,800
 No-Load Speed (r/min) 390/1110
 Max. Drilling Capacity (mm) Ø 250
 Net Weight (kg) 25

MAGNETIC DRILL



DCA-PT-050
AJC30 (1/CTN)
 Rated Power Input (W) 900
 Max. Drilling Capacity Ø 30
 Magnetism (N) 11,500
 No-Load Speed (r/min) 450
 Max. Stroke (mm) 140
 Connector Straight Shank (mm) Ø 19
 Net Weight (kg) 11.5



DCA-PT-050A
AJC23 (1/CTN)
 Rated Power Input(W) 1500
 Max. Drilling Capacity
 Twist Drill Bit(mm) Ø23
 Core Drill Bit(mm) Ø50
 Magnetism(N) 15,000
 No-Load Speed(r/min) 390
 Max. Stroke(mm) 220
 Connector Mt2 Shank
 Net Weight(kg) 21



DCA-PT-050B
AJC02-23 (1/CTN)
 Rated Power Input(W) 1,600
 Max. Drilling Capacity
 Twist Drill Bit(mm) Ø23
 Core Drill Bit(mm) Ø50
 Magnetism(N) 15,000
 No-Load Speed(r/min) 130-260/260-520
 Max. Stroke(mm) 220
 Connector Mt3 Shank
 Net Weight(kg) 24

WRENCH



DCA-PT-037A
APB12 (8/CTN)

| | |
|-------------------------------------|-------------|
| Rated Power Input (W) | 300 |
| No-Load Speed (r/min) | 1,800 |
| Rated Impacting Frequency (.../min) | 2,000 |
| Capacities (Bolt Size) (mm) | M8 - M12 |
| Square Drive (mm) | 12.7 x 12.7 |
| Max. Fastening Torque (N.m) | 188 |
| Net Weight (kg) | 2.1 |



DCA-PT-037
APB20C (4/CTN)

| | |
|-------------------------------------|-------------|
| Rated Power Input (W) | 340 |
| No-Load Speed (r/min) | 1,700 |
| Rated Impacting Frequency (.../min) | 2,000 |
| Capacities (Bolt Size) (mm) | M12 - M20 |
| Square Drive (mm) | 12.7 x 12.7 |
| Max. Fastening Torque (N.m) | 294 |
| Net Weight (kg) | 3.2 |



DCA-PT-038
APB22C (3/CTN)

| | |
|-------------------------------------|-----------|
| Rated Power Input (W) | 620 |
| No-Load Speed (r/min) | 1,700 |
| Rated Impacting Frequency (.../min) | 1,600 |
| Capacities (Bolt Size) (mm) | M16 - M22 |
| Square Drive (mm) | 19 x 19 |
| Max. Fastening Torque (N.m) | 588 |
| Net Weight (kg) | 5.0 |



DCA-PT-038A
APB30 (2/CTN)

| | |
|-------------------------------------|-------------|
| Rated Power Input (W) | 1050 |
| No-Load Speed (r/min) | 1,400 |
| Rated Impacting Frequency (.../min) | 1,500 |
| Capacities (Bolt Size) (mm) | M22 - M30 |
| Square Drive (mm) | 25.4 x 25.4 |
| Fastening Torque Range (N.m) | 400-900 |
| Net Weight (kg) | 10.0 |

AIR STAPLER



DCA-PT-054
A422J (16/CTN)

| | |
|--------------------------------|--------------------|
| Working Pressure(Bar) | 4-8 |
| Inner Diameter of Air Pipe(mm) | 8 |
| Capacity of Magazine(PCS) | 100 |
| Nail Type | Staple |
| Nail Size(mm) | 0.6 x 4 x 22 (max) |
| Net Weight(kg) | 1.1 |



DCA-PT-054A
A1022J (16/CTN)

| | |
|--------------------------------|--------------------|
| Working Pressure(Bar) | 4-8 |
| Inner Diameter of Air Pipe(mm) | 8 |
| Capacity of Magazine(PCS) | 100 |
| Nail Type | Staple |
| Nail Size(mm) | 0.6 x 4 x 22 (max) |
| Net Weight(kg) | 1.1 |

AIR BRAD NAILER



DCA-PT-055
AF30 (16/CTN)

| | |
|--------------------------------|------------------|
| Working Pressure(Bar) | 4-8 |
| Inner Diameter of Air Pipe(mm) | 8 |
| Capacity of Magazine(PCS) | 100 |
| Nail Type | Brad Nail |
| Nail Size(mm) | ∅ 1.05 x 30(Max) |
| Net Weight(kg) | 1.1 |



DCA-PT-055A
AT50DC (10/CTN)

| | |
|--------------------------------|---------------------|
| Working Pressure(Bar) | 4-8 |
| Inner Diameter of Air Pipe(mm) | 8 |
| Capacity of Magazine(PCS) | 100 |
| Nail Type | Brad Nail |
| Nail Size(mm) | 1.6 x 1.4 x 50(Max) |
| Net Weight(kg) | 2.1 |

AIR CONCRETE NAILER



DCA-PT-058
AST64C (6/CTN)

| | |
|--------------------------------|---------------|
| Working Pressure(Bar) | 4-8 |
| Inner Diameter of Air Pipe(mm) | 8 |
| Capacity of Magazine(PCS) | 75 |
| Nail Type | Steel Nail |
| Nail Size(mm) | ∅ 2.2 (18-64) |
| Net Weight(kg) | 3 |

VACUUM CLEANER



| | |
|-----------------------------------|---------|
| DCA-PT-056 AVC15 | (1/CTN) |
| Rated Power Input(W) | 1,200 |
| Capacity (L) | 15 |
| Cooling System | Recycle |
| Net Weight(kg) | 7.6 |



| | |
|------------------------------------|---------|
| DCA-PT-056A AVC30 | (1/CTN) |
| Rated Power Input(W) | 1,200 |
| Capacity (L) | 30 |
| Cooling System | Recycle |
| Net Weight(kg) | 8.8 |



DUST-FREE SAW



| | |
|---------------------------------------|---------|
| DCA-PT-057 AFF02-150 | (1/CTN) |
| Rated Power Input(W) | 1,400 |
| No-Load Speed (r/min) | 5,300 |
| Blade Diameter | 105-150 |
| Fan Rated Power (W) | 1,000 |
| Maximum Vacuum Degree (Pa) | 24,000 |
| Net Weight (kg) | 11.9 |

LASER LEVEL



| | |
|-----------------------------------|-----------------------|
| DCA-PT-047 AFF21 | (6/CTN) |
| Laser Diode (nm) | 635 |
| Centering Laser Diode (mm) | 650 |
| Vertical Accuracy | ± 1mmAT5m |
| Levelling Accuracy | ± 1mmAT5m |
| Auto-levelling Range | ± 3° |
| Width of Laser Line | 2mm at distance of 5m |
| Power Supply | 3 x 1.5VLR6 (AA) |
| Operating Temperature | -10°C ~ 45°C |
| Laser Class | 2 |



| | |
|-----------------------------------|-----------------------|
| DCA-PT-048 AFF41 | (6/CTN) |
| Laser Diode (nm) | 635 |
| Centering Laser Diode (mm) | 650 |
| Vertical Accuracy | ± 1mmAT5m |
| Levelling Accuracy | ± 1mmAT5m |
| Auto-levelling Range | ± 3° |
| Width of Laser Line | 2mm at distance of 5m |
| Power Supply | 3 x 1.5VLR6 (AA) |
| Operating Temperature | -10°C ~ 45°C |
| Laser Class | 2 |

GREEN LASER LEVEL



| | |
|---------------------------------------|-----------------------|
| DCA-PT-047A AFF04-21 | (6/CTN) |
| Laser Diode (nm) | 532 |
| Centering Laser Diode (mm) | 650 |
| Vertical Accuracy | ± 1mmAT5m |
| Levelling Accuracy | ± 1mmAT5m |
| Auto-levelling Range | ± 3° |
| Width of Laser Line | 2mm at distance of 5m |
| Power Supply | 3 x 1.5VLR6 (AA) |
| Operating Temperature | -0°C ~ 40°C |
| Laser Class | 3A |



| | |
|---------------------------------------|-----------------------|
| DCA-PT-048A AFF04-41 | (6/CTN) |
| Laser Diode (nm) | 532 |
| Centering Laser Diode (mm) | 650 |
| Vertical Accuracy | ± 1mmAT5m |
| Levelling Accuracy | ± 1mmAT5m |
| Auto-levelling Range | ± 3° |
| Width of Laser Line | 2mm at distance of 5m |
| Power Supply | 3 x 1.5VLR6 (AA) |
| Operating Temperature | -0°C ~ 40°C |
| Laser Class | 3A |

LI-ION BATTERY CORDLESS POWER TOOLS

DCA-PT-012CC-1
CORDLESS DRIVER DRILL
ADJZ10-10 (Type E)



| | | |
|-----------------------------|------|-----------------|
| | | (8/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| Max. Screw Dia. (mm) | | Ø 10 |
| No-Load Speed (r/min) | Low | 0 - 400 |
| | High | 0 - 1,500 |
| Max. Chucking Capacity (mm) | | 10 |
| Max. Drilling Capacity | | |
| Steel (mm) | | Ø 10 |
| Wood (mm) | | Ø 20 |
| Net Weight (kg) | | 1.1 |



DCA-PT-012CCA
CORDLESS DRIVER DRILL
ADJZ20-10 (TYPE E)



| | | |
|-----------------------------|------|-----------------|
| | | (8/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| Max. Screw Dia. (mm) | | Ø 7 |
| No-Load Speed (r/min) | Low | 0 - 400 |
| | High | 0 - 1,500 |
| Max. Chucking Capacity (mm) | | 10 |
| Max. Drilling Capacity | | |
| Steel (mm) | | Ø 10 |
| Wood (mm) | | Ø 20 |
| Net Weight (kg) | | 1.2 |



DCA-PT-0125C
CORDLESS ANGLE DRIVER DRILL
ADJZ14-10(Type E)



| | | |
|----------------------------|--|-----------------|
| | | (6/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| Max. Screw Dia.(mm) | | 6.5 |
| No-Load Speed (r/min) | | 0 - 800 |
| Max.Chucking Capacity (mm) | | 10 |
| Max Drilling Capacity | | |
| Steel(mm) | | Ø 10 |
| Wood (mm) | | Ø 25 |
| Net Weight (kg) | | 1.0 |



DCA-PT-012HC3
CORDLESS BRUSHLESS HAMMER DRILL
ADZC02-24E



| | | |
|----------------------------|--|-----------------|
| | | (3/CTN) |
| Battery | | 18V x 4.0Ah x 2 |
| No-Load Speed (r/min) | | 0 - 1,100 |
| Impact Frequency (.../min) | | 0 - 4,900 |
| Max. Drilling Capacity | | |
| Steel (mm) | | Ø12 |
| Wood (mm) | | Ø28 |
| Concrete (Kg) | | Ø24 |
| Net Weight (kg) | | 3.1 |



DCA-PT-012GC
CORDLESS SCREWDRIVER
ADPL02-5B



| | | |
|-----------------------|--|-----------------|
| | | (12/CTN) |
| Battery | | 4V / 1.5Ah |
| Max. Screw Dia. (mm) | | 5 |
| No-Load Speed (r/min) | | 200 |
| Net Weight (kg) | | 0.35 |



Bracket Charger

DCA-PT-012EC
CORDLESS SCREWDRIVER
ADPL8 (Type E)



| | | |
|-----------------------|------|-----------------|
| | | (8/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| Max. Screw Dia. (mm) | | 6 |
| No-Load Speed (r/min) | High | 0 - 1,060 |
| | Low | 0 - 270 |
| Net Weight (kg) | | 1.0 |



DCA-PT-012FC
CORDLESS IMPACT DRIVER
ADPL02-8 (Type E)



| | | |
|-----------------------------|--|-----------------|
| | | (8/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| No-Load Speed (RPM) | | 0 - 2,400 |
| Rated Impacts (.../min) | | 0 - 3,000 |
| Max. Fastening Torque (RPM) | | 100 |
| Net Weight (kg) | | 1.0 |



DCA-PT-012HC
CORDLESS IMPACT WRENCH
ADPB10A



| | | |
|-------------------------------------|--|-----------------|
| | | (8/CTN) |
| Battery | | 12V x 2.0Ah x 2 |
| No-Load Speed (RPM) | | 0 - 2,400 |
| Rated Impacting Frequency (.../min) | | 0 - 3,000 |
| Max. Fastening Torque (N.M) | | 100 |
| Net Weight (kg) | | 1.0 |



DCA-PT-012IC
CORDLESS IMPACT WRENCH
ADPB16E



| | | |
|-------------------------------------|--|-----------------|
| | | (4/CTN) |
| Battery | | 18V / 4.0Ah x 2 |
| No-Load Speed (RPM) | | 0 - 2,200 |
| Rated Impacting Frequency (.../min) | | 0 - 3,200 |
| Max. Fastening Torque (N.M) | | 230 |
| Net Weight (kg) | | 1.75 |



DCA-PT-012HC1
CORDLESS IMPACT WRENCH
ADPB20 (TYPE F)



| | | |
|------------------------------------|--|----------------|
| | | (4/CTN) |
| Battery | | 18V/5.0Ah x 2 |
| Applicable Screw Diameter(mm) | | M16-M20 |
| No-Load Speed(RPM) | | 0-1,700 |
| Rated Impacting Frequency(.../min) | | 0-2,000 |
| Max. Fastening Torque(N.M) | | 650 |
| Net Weight(Kg) | | 3.2 |



DCA-PT-012TC
CORDLESS DRIVER HAMMER DRILL
ADJZ13(Type E)



| | | |
|-----------------------------|--------|-----------------|
| | | (4/CTN) |
| Battery | | 18V x 4.0Ah x 2 |
| Max. Chucking Capacity (mm) | | 13 |
| Max. Screw Dia. (mm) | | Ø 10 |
| Blows per minute (BPM) | | 0-36,000 |
| No-Load Speed (r/min) | Step 1 | 0 - 400 |
| | Step 2 | 0 - 2,000 |
| Max. Drilling Diameter | | |
| Steel (mm) | | Ø 13 |
| Brick Wall (mm) | | Ø 14 |
| Wood (mm) | | Ø 38 |
| Torque Setting | | 25+2 |
| Max.Torque(N.m) | | 70 |
| Net Weight (kg) | | 2.2 |



DCA-PT-012GCA
CORDLESS DRIVER IMPACT DRIVER
ADPL02-14 (TYPE F)



| | | |
|------------------------|-----|-----------------|
| | | (4/CTN) |
| Battery | | 18V x 5.0Ah x 2 |
| Clamping Capacity | | 6.35mm Hex |
| Max. Screw Dia. (mm) | | Ø 14 |
| Torque Setting | | Smart-loosen |
| | | Low 140(N.m) |
| | | High 175(N.m) |
| No-Load Speed (r/min) | | 0 - 2,000 |
| | | 0 - 2,400 |
| Rated Impacts(.../min) | Low | 0 - 2,900 |
| | Hig | 0 - 3,200 |
| Net Weight (kg) | | 1.9 |



LI-ION BATTERY CORDLESS POWER TOOLS



DCA-PT-012HC2
CORDLESS BRUSHLESS IMPACT WRENCH
ADPB18 (TYPE F) (4/CTN)

| | |
|--------------------------------|--------------|
| Battery | 18V/5.0Ahx2 |
| Applicable Screw Diameter (MM) | M12-M18 |
| Square Drive Size (MM) | 12.7 (1/2") |
| Torque Setting | Smart-loosen |
| Step L (N.M) | 240 |
| Step H (N.M) | 300 |
| No-Load Speed | |
| Step L (R/MIN) | 0-2,000 |
| Step H (R/MIN) | 0-2,400 |
| Rated Impacting Frequency | |
| Step L (.../min) | 0-2,900 |
| Step H (.../min) | 0-3,200 |
| Net Weight (Kg) | 1.7 |



DCA-PT-012CCB
CORDLESS BRUSHLESS DRIVER DRILL
ADJZ16 (TYPE E) (4/CTN)

| | |
|-----------------------------|---------------|
| Battery | 18V/4.0Ah x 2 |
| Max. Chucking Capacity (mm) | 16 |
| No-Load Speed (r/min) | 0- 1,200 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 16 |
| Wood (mm) | Ø 38 |
| Max. Torque (N.m) | 45 |
| Net Weight (kg) | 2.2 |

DCA-PT-012PC
CORDLESS ANGLE GRINDER
ADSM100 (TYPE E) (4/CTN)

| | |
|-----------------------------|-----------------|
| Battery | 18V / 4.0Ah X 2 |
| Max. Wheel Diameter (mm) | Ø 100 |
| Hole Diameter of Wheel (mm) | Ø 16 |
| Rated Speed (r/min) | 10,000 |
| Spindle Thread | M10 |
| Net Weight (kg) | 2.1 |



DCA-PT-012PCA
CORDLESS ANGLE GRINDER
ADSM02-100 (TYPE E) (4/CTN)

| | |
|-----------------------------|-----------------|
| Battery | 18V / 4.0Ah X 2 |
| Max. Wheel Diameter (mm) | Ø 100 |
| Hole Diameter of Wheel (mm) | Ø 16 |
| Rated Speed (r/min) | 8,500 |
| Spindle Thread | M10 |
| Net Weight (kg) | 2.4 |



DCA-PT-012QC
CORDLESS DIE GRINDER
ADSJ10(TYPE E) (6/CTN)

| | |
|---------------------------------|-----------------|
| Battery | 12V x 2.0Ah x 2 |
| Rated Speed (r/min) | 5,000 - 32,000 |
| Speed Shifting Gears | 1-2-3-4-5-6 |
| Max.Grinding Wheel Diameter(mm) | 10 |
| Power Display | 3 |
| Net Weight (kg) | 0.61 |



DCA-PT-012MC
CORDLESS MULTI TOOLS
ADMD12 (Type E) (6/CTN)

| | |
|------------------------|-----------------|
| Battery | 12V x 2.0Ah x 2 |
| Oscillation(/min) | 5,000-20,000 |
| Speed Shifting Gears | 2-4-6-8-10-12 |
| Oscillation Angle (°) | 3 |
| Power Display | 3 |
| Net Weight (kg) | 0.95 |



DCA-PT-012OC
CORDLESS SABRE SAW
ADJF15(TYPE E) (6/CTN)

| | |
|-----------------------|-----------------|
| Battery | 12V x 2.0Ah x 2 |
| Stroke(mm) | 15 |
| Max Cutting Depth | |
| Metal (mm) | 8 |
| Wood (mm) | 65 |
| Pipe Diameter (mm) | Ø 50 |
| No-Load Speed (r/min) | 0 - 3,000 |
| Net Weight (kg) | 1.2 |



DCA-PT-012WC
CORDLESS RECIPROCATING SAW
ADJF28(Type A) (4/CTN)

| | |
|--------------------------|---------------|
| Battery | 18V/4.0Ah x 2 |
| No-Load Strokes(.../min) | 0-3,300 |
| Length Of Strokes(mm) | 28 |
| Max.Cutting Capacity | |
| Steel(mm) | 20 |
| Wood(mm) | 250 |
| Tube Diameter(mm) | 130 |
| Net Weight(kg) | 3.4 |



DCA-PT-012VC
CORDLESS CAULK GUN
ADPJ12 (3/CTN)

| | |
|----------------------|-----------------|
| Battery | 12V x 2.0Ah x 2 |
| Max.Pushing force(N) | 3,400 |
| Feed Spdd(mm/s) | 0-12.9 |
| Stroke(mm) | 213 |
| Sealant Type | 300ML |
| Net Weight(kg) | 1.85 |



DCA-PT-012VCA
CORDLESS CAULK GUN
ADPJ12(TYPE E) (3/CTN)

| | |
|----------------------|-----------------|
| Battery | 12V x 2.0Ah x 2 |
| Max.Pushing force(N) | 3,400 |
| Feed Spdd(mm/s) | 0-12.9 |
| Stroke(mm) | 213 |
| Sealant Type | 600ML |
| Net Weight(kg) | 1.85 |



DCA-PT-012UC
CORDLESS BLOWER
ADQF28(Type B) (6/CTN)

| | |
|-----------------------|---------------|
| Battery | 18V / 4.0Ahx1 |
| No-Load Speed (r/min) | |
| Step 1 | 11000±14% |
| Step 2 | 15000±11% |
| Step 3 | 19000±10% |
| Capacity(m³/min) | 1.6-2.8 |
| Net Weight (kg) | 1.9 |



DCA-PT-012XC
CORDLESS PRUNER
ADYD14 (TYPE B) (24/CTN)

| | |
|--------------------------------|----------------|
| Battery | 4V/2.0Ah |
| Max.Cutting Diameter(mm) | Ø14 New Branch |
| No-Load Shear Frequency(.../s) | 1.2 |
| Net Weight (kg) | 0.71 |



LI-ION BATTERY CORDLESS POWER TOOLS




DCA-PT-012DC
CORDLESS CLEANER
ADXC12

| | |
|---------------------------------|-------------|
| | (6/CTN) |
| Battery | 12V / 2.0Ah |
| Max. Air Flow. (m/min) | 1.2 |
| Air Pressure (Kpa) | 1.8 |
| Continuous Use (minutes,approx) | 20 |
| Net Weight (kg) | 0.9 |



DCA-PT-012IC & DCA-PT-012KC
CORDLESS WORK LIGHT
ADWL12(B) & (C)

| | |
|------------------------------|---------------------|
| | (12/CTN) / (30/CTN) |
| Battery | 12V / 2.0Ah |
| Continuous Lighting Time (h) | 10 |
| LED (pcs) | 16 |
| Lamp Adjusting Angle (°) | 110 |
| Net Weight (kg) | 0.32 |

 (Type C): Product come without battery and charger , which are sold separately



DCA-PT-012YC
CORDLESS BLIND RIVETING GUN
ADPM50 (TYPE E)

| | |
|---------------------------------------|-------------|
| | (6/CTN) |
| Battery | 12V / 2.0Ah |
| Stroke (mm) | 20 |
| Capacity | |
| Ø2.4 - 5.0mm for All Purpose | |
| Ø2.4 - 6.0mm for Aluminum Blind Rivet | |
| Max. Tension | 10,000(N) |
| Net Weight (kg) | 1.6 |

CORDLESS COMBO KIT ADKIT01(E) (ADPL02-8 + ADJZ10-10)

(6/CTN)



DCA-PT-012LC
CORDLESS IMPACT DRIVER
ADPL02-8 (Type E)

| | |
|-----------------------------|-------------|
| Battery | 12V x 2.0Ah |
| No-Load Speed (RPM) | 0 - 2,400 |
| Rated Impacts (.../min) | 0 - 3,000 |
| Max. Fastening Torque (RPM) | 100 |
| Net Weight (kg) | 1.0 |



CORDLESS DRIVER DRILL
ADJZ10-10 (Type E)

| | |
|-----------------------------|---------------|
| Battery | 12V x 2.0Ah |
| Max. Screw Dia. (mm) | Ø 10 |
| No-Load Speed (r/min) | High 0 - 1400 |
| | Low 0 - 350 |
| Max. Chucking Capacity (mm) | 10 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 10 |
| Wood (mm) | Ø 20 |
| Net Weight (kg) | 1.1 |

CORDLESS COMBO KIT ADKIT02(E) (ADJF15 + ADJZ10-10)

(4/CTN)



DCA-PT-012RC
CORDLESS SABRE SAW
ADJF15 (TYPE E)

| | |
|-----------------------|-------------|
| Battery | 12V x 2.0Ah |
| Stroke(mm) | 15 |
| Max Cutting Depth | |
| Metal (mm) | 8 |
| Wood (mm) | 65 |
| Pipe Diameter (mm) | Ø 50 |
| No-Load Speed (r/min) | 0 - 3,000 |
| Net Weight (kg) | 1.2 |



CORDLESS DRIVER DRILL
ADJZ10-10 (Type E)

| | |
|-----------------------------|----------------|
| Battery | 12V x 2.0Ah |
| Max. Screw Dia. (mm) | Ø 10 |
| No-Load Speed (r/min) | High 0 - 1,500 |
| | Low 0 - 400 |
| Max. Chucking Capacity (mm) | 10 |
| Max. Drilling Capacity | |
| Steel (mm) | Ø 10 |
| Wood (mm) | Ø 20 |
| Net Weight (kg) | 1.1 |