



DRI-GARD SP 101

Cleaning solvent for degreasing & surface preparation

DRI-GARD SP 101 is a cleaning solvent for metal degreasing, removal of paint remover residues and final cleaning prior to the application of any paints or coatings. It is compatible with a wide range of coatings, including acrylic, alkyd, epoxy, polyurethane, and so on. It is also fast evaporating, and is suitable to be used for the cleaning of brushes and spray equipment.

FEATURES/BENEFITS

- ✓ Cleans and degreases metal surfaces
- ✓ Removes any residues of paint removers
- ✓ Suitable to be used as a final cleaning agent prior to application of paint/coatings
- ✓ Fast evaporating
- ✓ Compatible with wide range of coatings
- ✓ May be used to clean brushes & spray equipment

APPLICATION AREAS

- ✓ Metal surfaces
- ✓ Compatible with coatings such as:
 - Acrylic
 - Alkyd
 - Epoxy
 - Polyurethane
 - Nitro-cellulose
 - Etc.



DRITECH CHEMICALS SDN. BHD. (1184082-K)

23-3A, Oval Damansara, 685, Jalan Damansara, 60000 Kuala Lumpur, Malaysia
TEL: +603 7735 6015, FAX: +603 7735 6016

Product Data

Storage	12 Months from date of production
Storage Condition	Dry conditions at temperature between 5 – 25 °C. Keep away from direct sunlight. Store in the original unopened containers.

Technical Data

Origin	Solvent-based
Flash Point	< 21 °C
Consumption	12 – 15 m ² per litre
	Practical coverage varies depending on the application method, temperature, profile & condition of the substrate

SUBSTRATE

DRI-GARD SP 101 does not affect usual metals such as iron, steel, aluminium, magnesium alloys, copper, zinc, etc. Do not use on acrylic windows.

APPLICATION

Cleaning of metal surfaces:

Rub the surface thoroughly with clean cloths soaked with **DRI-GARD SP 101** and wipe off with clean dry cloths. Do not allow the surface to dry, as contamination can be spread. The degreased surface should not be touched to avoid contamination prior to paint application.

Cleaning of spray equipment:

Remove paint residues with a brush. Do not immerse spray guns in **DRI-GARD SP 101** as this may affect non-metallic parts.

Cleaning of brushes:

Immerse the brushes in a tray with **DRI-GARD SP 101**. After a few minutes, the paint can be removed from the brush.

LIMITATIONS

- ❖ Do not apply to acrylic windows.
- ❖ Do not leave brushes immersed for too long in the product as this may affect the elasticity of the hairs.

HEALTH & SAFETY

For information and advice on the safe handling, storage and disposal of chemical products, users shall refer to the most recent Material Safety Data Sheet containing physical, ecological, toxicological and other safety-related data.

LEGAL NOTE

The information, and, in particular, the recommendations relating to the application and end-use of these products, are given in good faith based on current knowledge and experience of the products when properly stored, handled and applied under normal conditions in accordance to the manufacturer recommendations. In practice, the differences in materials, substrates and actual site conditions are such that no warranty in respect of merchantability or of fitness for a particular purpose, nor any liability arising out of any legal relationship whatsoever, can be inferred either from this information, or from any written recommendations, or from any other advice offered. The user of the product must test the product's suitability for the intended application and purpose. The manufacturer reserves the right to change the properties of its products. The proprietary rights of third parties must be observed. All orders are accepted subject to our current terms of sale and delivery. Users must always refer to the most recent issue of the local Product Data Sheet for the product concerned, copies of which will be supplied on request.