

MTY SOLUTIONS (M) SDN BHD^(1266640-U)

No.11-G, Jalan OP 1/6, Pusat Perdagangan One Puchong, 47160 Puchong, Selangor Darul Ehsan. Malaysia.
Tel: 012-300 5602 Fax: 03-8999 2120 Email: mty.solutions@gmail.com

HP1070 TIJ PRINTER

Easy ● Stable ● Economical ● No Maintenance

-Based on HP TIJ 2.5 Technology-



Splite Design
Suit for all kinds of installation



Economical
Stable and good performance



Online Editing
5 Inch touch screen for editing message



Multiple Fonts
Can install kinds of fonts

MODBUS

Support MODBUS
Communication Protocol

SDK
Support



JAVA

C++

C++

C#

C#

VB

Delphi

MTY SOLUTIONS (M) SDN BHD (1266640-U)

No.11-G, Jalan OP 1/6, Pusat Perdagangan One Puchong, 47160 Puchong, Selangor Darul Ehsan, Malaysia.
Tel: 012-300 5602 Fax: 03-8999 2120 Email: mty.solutions@gmail.com

Technical Parameters

Dimensions	Language
Conctroller: H*W*D: 151*93*32mm/ 5.9*3.7*1.3 inch Head: H*W*D: 175*52*33mm/ 6.9*2.0*1.3 inch	Chinese, English, Japanese, French, German, Spanish, Portuguese and Russian
Resolution	Printing Speed
50~600DPI	0~60m/min (300DPI) 0~30m/min (600DPI)
Line Speed	Barcode
Print speed can be set, auto-measuring or using external synchronize	UPCA, UPCE, EAN13, EAN8, INT25, CODE39, CODE128, EAN128, PDF417, DATAMATRIX, QR
Date Format	Interface
Variety of date modes available (Production Date, Use by Date, Expiration Date, etc)	5 inch 800*480 colour LCD touch screen
Ink management	Installation
1) Automatically recognize the ink types, and identify the optimum printing parameters; 2) Guarantee of using genuine original HP ink; 3) Automatic measuring system for the usage of the ink	Standard side, downside and anti-shock printing bracket
Adapter input power supply	Certificate
100-240V~50/60Hz	CE、FCC
Adapter output power supply	Environment
30V 1.5A	Working Environment: -10°-- +45°C; 10%-85%RH Storage Environment: -25°-- +55°C; 10%-90%RH

Printer and Sample Show



Barcode printing sample



Logo and barcode



MFG and EXP date printing