


## GUIDE LIFTER PIN SETS



Dimension: MM

Catalog No.		D Tolerance	① GLP			L												
Type	D	g6	e	W	D1													
GLS	4	-0.004	5	2.0	6	10	15	20	22	25	28	30	33	35	36	40	45	50
	6	-0.012		3.6	8	10	15	20	22	25	28	30	33	35	36	40	45	50
	8	-0.005	7	5.0	10	15	20	22	25	28	30	33	35	36	40	45	50	55
	10	-0.014		6.0	13	20	22	25	28	30	33	35	36	40	45	50	55	
GLP	13	-0.006	8	7.0	16	20	22	25	28	30	33	35	36	40	45	50	55	
	16	-0.017		8.0	19	30	33	35	36	40	45	50	55	60	70			
	20	-0.007 -0.020	12	10.0	23	33	35	36	40	45	50	55	60	70				

Catalog No.		③ MSW		A				② Spring	
Type	D	M x P	h					Type	FL
GLS	4	8 x 1.25	8	0.5	0.8	1.0		WR	20
	6	10 x 1.5		0.5	0.8	1.0	1.6		25
	8	12 x 1.5	10	1.0	1.6	2.0		WF	30
	10	16 x 1.5		1.6	2.0	2.5			35
GLP	13	20 x 1.5	12	2.0	2.5	3.6		WL	40
	16	22 x 1.5		2.0	2.5	4.0			45
	20	27 x 1.5	12	3.6			5.0	WT	50
									55
							WM	60	
							WH	65	
							WL . WT	70	
							WM . WH	80	
								90	
								100	

How to order: Type D – L – A - ② Type FL x Qty

Catalog No : GLS 6 – 30 – 1.0 – WH50 x 100pcs

Material : SK4

Hardness : HRC 53° - 58°