



## HCL6-60-Y-N-3/8x1/4

**Item Number 4687411**

The larger inner diameter allows a higher volume flow during evacuation and filling. This reduces valuable working time.

- High volume flow rate due to larger diameter
- Without core depressor
- Replaceable neoprene (CR) seal
- High-quality material for maximum durability, against hardening and embrittlement
- Serrated union nuts for better grip when tightening by hand

## Technical Data

<b>Material</b>	Brass   Rubber
<b>Colour</b>	yellow
<b>Number of Hoses</b>	1
<b>Length</b>	150 cm
<b>Sealing</b>	Neoprene (CR)
<b>System Connection</b>	1/4" SAE   Straight
<b>Device Connection</b>	3/8" SAE
<b>Valve Core Depressor</b>	No
<b>Ball Valve</b>	No
<b>Working Pressure</b>	32 bar
<b>Burst Pressure</b>	128 bar
<b>Diameter</b>	3/8"
<b>Packaging</b>	Blister

## Accessories

*Acknowledged globally*



9884813	A-40513/10	Core depressors 3/8", 10 pieces
---------	------------	---------------------------------

## Spare Parts

9880872	P-509/10	Neoprene gasket, 1/4" SAE, 10 pieces
---------	----------	--------------------------------------

9880870	P-510/10	Neoprene O-rings 3/8" SAE, 10 pieces
---------	----------	--------------------------------------

9883980	P-509/100	Neoprene gaskets, 100 pieces
---------	-----------	------------------------------