

Gas Tubing

Transfer of gas



TU 1596 - PVC Tubing



TU 1670 - PVC lined with Teflon (Tygon)

Calgaz supplies two types of tubing in a range of lengths including 2ft (0.6m), 3ft (1m), 10ft (3m), and 100ft (30m).

The PVC tubing is recommended for use with applications involving non-reactive gases.

For reactive gases, Tygon tubing performs better with reduced gas absorption due to the inner teflon coating.

Calgaz Global Standards			
Name	Description	Dimension	Application
TU -1596	PVC Tubing	Int Dia = 4.8mm Ext Dia = 6.4mm	Non-reactive mixtures only
TU -1670	PVC Tubing lined with Teflon (Tygon)	Int Dia = 4.8mm Ext Dia = 7.9 mm	Non-reactive and Reactive mixtures



Contact Details

Americas

Global Headquarters

Houston, TX, USA
+1 713 624 8000

Customer Service and Manufacturing Facility

Cambridge, MD, USA
+1 800 638 1197

Europe, Middle East & Africa

Customer Service, Sales and Manufacturing Facility

Stoke-on-Trent, United
Kingdom
+44 0808 164 8897

Middle East Sales

Dubai, UAE
+971 56 131 2346

South East Asia & Australia

Customer Service and Distribution

Singapore
+65 3163 9392

China

Customer Service and Distribution

Shanghai
+86 21 6090 3711

info@calgaz.com

www.calgaz.com