

MS-S

Magnetic Stirrer

MS7-S

7" Square Magnetic Stirrer

- Speed range of 0–1500rpm
- Maximum stirring quantity of H₂O up to 10L
- Ceramic work plate provides excellent corrosion resistance



MS7-S



MS-S



MS6-Pro

MS6-Pro

LCD Digital Magnetic Stirrer

- High resolution LCD displays actual stirring speed
- Brushless DC motor is maintenance free
- Aluminum covered ceramic coating, corrosion resistant and easy to clean
- Digital speed control up to 1500rpm
- Maximum stirring quantity of H₂O at 5L

| Specifications | MS7-S | MS-S | MS6-Pro |
|--|---------------------------|------------------------------------|-------------------------------------|
| Work plate Dimension [W x D] | 184x184mm (7 inch) | Ø135mm (5 inch) | 140x140mm |
| Work plate material | Glass ceramic | Stainless steel cover with ceramic | Aluminum cover with ceramic coating |
| Motor type | Shaded pole motor | Brushless DC motor | Brushless DC motor |
| Stirring positions | 1 | 1 | 1 |
| Max. stirring quantity[H ₂ O] | 10L | 20L | 5L |
| Max.magnetic bar[length] | 80mm | 80mm | 40mm |
| Speed range | 0–1500rpm | 0–1500rpm | 200–1500rpm |
| Speed display | Scale | Scale | LCD |
| Protection class | IP21 | IP21 | IP21 |
| Motor input Power | 15W | 18W | 2.4W |
| Motor output Power | 1.5W | 10W | 1.8W |
| Power | 30W | 30W | 10W |
| Voltage,Frequency | 100–120/200–240V, 50/60Hz | 100–240V, 50/60Hz | 100–240V, 50/60Hz |
| Dimension[WxDxH] | 215x360x112mm | 160x280x85mm | 320x180x108mm |
| Weight | 3.8kg | 2.8kg | 2.2kg |
| Permissible ambient temperature and humidity | 5–40°C, 80%RH | 5–40°C, 80%RH | 5–40°C, 80%RH |