

## **VC100**

## Vacuum Controller Reliable,robust,effcient and extremely durable

The vacuum controller serves as a device for labs to display, adjust and control the degree of vacuum in vacuum systems. It generally constitutes the vacuum control system of rotary evaporator along with vacuum pump, which enables repeatable distillation experiment and recovery of many kinds of solvents in an efficient and automatic manner.



## **Features**

- Wide range of measurement and control, 1–1,000mbar
- Two control modes available Single-point control and programmed control
- Stores up to 5 programs, each containing up to 5 steps of programming control
- Large TFT touch screen display control provides easy operation
- All parts in contact with vapor or liquid are made of PTFE, ceramics or other high-performance materials which effectively resists corrosion caused by organic solvents, water, acid and alkali
- Built-in vent valve can feed inert gas into system equipment
- One-click decompression allows easy
  installation and dismantling of vacuum system
- Can be connected with pump power control for temporary shutdown of pump power supply after reaching stable degree of vacuum for energy conservation and environmental protection.
- Can also be operated in the normally open status of pump
- Reliable and functional design to fulfill essential needs of precise vacuum regulation

Specifications	VC100
Vacuum setting range	1-1000mbar
Vacuum measurement range	1-1000mbar
Control mode	Single-point control mode, Programmed control mode
Control program	Can store up to 5 programs, each containing 5-step control (capable to set the degree of vacuum and time)
Setting method	Touch screen setting
Display	5" TFT
Sensor overload pressure	1,500mbar
Connector diameter	8mm
Materials in contact with vapor	PTFE, PP, silicone and ceramics
Power	600W
Compatible conditions with vacuum pump	Power of 50Hz vacuum pump ≤400W Power of 60Hz vacuum pump ≤500W
Overall dimensionsWxDxH	189x207x193mm
Weight	4.0kg
Voltage, Frequency	110 240V,50Hz/60Hz
Operating environment	10℃~40℃ ≤80%RH