

Specifications	H100-Pro	HB105-S1 HB105-S2	HB150-S1 HB150-S2	HB120-S	HB60-S
Temperature range[°C]	Room temp+5-100	Room temp+5-105	Room temp+5-150	Room temp+5-120	Room temp+5-60
Temperature Setting range [°C]	15-100	25-105	25-150	25-120	5 gears:25, 30, 37,45,60
Temperature control accuracy[°C]	± 0.5	25-90: ± 0.3 90-105: ± 0.6	25-90: ± 0.3 90-150: ± 0.6	± 0.5	± 0.5
Temperature uniformity@ 37°C[°C]	± 0.5	± 0.2	± 0.2	± 0.5	± 0.3
Power [W]	200	HB105-S1:100 HB105-S2:200	HB150-S1:100 HB150-S2:200	160	160
Time setting range	0min-99h30min	0min-99h59min	0min-99h59min	0min-99h30min	0min-99h30min
External sensor	-	Yes	Yes	-	-
Display	TFT	LED	LED	LED	LED
Voltage,Frequency	110/220V,50/60HZ	110/220V,50/60HZ	110/220V,50/60HZ	110/220V,50/60HZ	110/220V,50/60HZ
External Dimension[WxDxH]	200x235X120	290x210X120	290x210X120	175X290X85	175X290X85
Weight (kg)	7.3	3.2	3.2	3	2.5
Operating temperature[°C]	10-40	10-40	10-40	10-40	10-40
Operating humidity[% RH]	< 80	< 80	< 80	< 80	< 80

