

Malaysia

598G/599G DC DRIVE EXTERNAL STACK CONTROLLER

Email Print



Click for Larger View

The 598G/599G External Stack Controllers can be used with an external thyristor power stack to build a DC Drive with an output rating of up to 1440A.

Select attributes to refine your product search.

DRIVE TYPE:

FEEDBACK TECHNOLOGY:

[Reset Attributes](#)



GET A QUOTE

WHERE TO BUY

PRODUCT OVERVIEW

-

TECH SPECIFICATIONS

+

Print Tech Specifications

PERFORMANCE CHARACTERISTICS**BRAND**

Parker

PRODUCT TYPE

DC Drive

DRIVE FORMAT

Single Axis Technology

SERIES

DC598G

INPUT SUPPLY VOLTAGE

3*220-500VAC

CONTINUOUS OUTPUT CURRENT RATING

up to 1440A (supplied by external thyristor power stack)

OUTPUT RATING (HP)

-

SUPPORTED MOTOR TYPES

DC Brushed Servo

SUPPORTED FEEDBACK DEVICE

Armature Voltage

Tachometer

Encoder

MODES OF CONTROL

Regenerative

Non-Regenerative

COMMUNICATION INTERFACE

n/a

OPERATING TEMPERATURE (C)

0 - 55

OPERATING TEMPERATURE (F)

32 - 131

OPERATING ALTITUDE

n/a

OVERLOAD RATINGS

n/a

CERTIFICATES

-

[Print Tech Specifications](#)

CONTACT US

PARKER HANNIFIN INDUSTRIAL (M) SDN.BHD.

11, Persiaran Pasak Bumi,
Seksyen U8, Jelutong Ind Park,
40150 Shah Alam, Selangor
Malaysia

Phone

+60 3 7849 0800

Fax

+60 3 7842 4349



EMAIL PARKER

Parker Hannifin



Products

About Parker

Investors

Community

Careers

Global Operations



Divisions

Sales Companies

Worldwide Locations

Distribution Network

ParkerStore™ Network

Company Information



Newsroom

Event Calendar

Working with Parker

Product Brands

History

Global Support Center



Support

CAD

Where to Buy

Contact Parker

ENGINEERING YOUR SUCCESS.

[SITE MAP](#) | [SAFETY](#) | [PRIVACY POLICIES](#)

[TERMS AND CONDITIONS](#)

© PARKER HANNIFIN CORP 2017