

KCC paint™

KOREA No. 1

Good Colour Fastness /
Teknologi Anti-Pudar



Minimal Splattering /
Percikan Minimum



Quick Dry /
Cepat Kering



Anti-Fungus /
Anti-Kulat



KORETON PLUS COLOUR SELECTIONS





Azera Green
623



Blonde White **18** 588



Barley White **18** 628



Apple White **18** 629



Lime Light **18** 451



Merry White **18** 589



Honey Dew **18** 455



Orchid White **18** 627



Antique White **18** 630



Peach **18** 568



Summer Heat 606



Sunset Carol 607



Orange Bulb 608



Fair Lady 604



Purple Angel 615



Moonlight Sonata 617



Cabana Coral 611



Orange Bulb
608



Mandarin Orange
620+



5th Symphony 618



Mandarin Orange ★ 620+



Chili Red ★ 570+



Melon Red ★ 363+

The colours shown are as close to actual colours as modern printing techniques allow.
For new surface or walls where alkalinity is present, a coat of Classic / Professional Series Wall Sealer must be applied prior to 2 coats of Koreton Plus.

★ Premium Pricing

18 Also Available in 18 Litre



Ode to Joy
616



Raw Silk 605



Ode to Joy 616



100% Gold 309




Amber White 18 300




Incheon Yellow ★ 624+



Daffodil 18 353




Carmel 612



Mocha Woods 319



Banana Toffee 626




Zambesi Rock 459



Mandarin Field 469



Balinese Green 625



Vintage Army 631



Straw Yellow 632



Green Olive 633



Azera Green 623



Sea Breeze 582




Bluebells 346



Lime Fizz 603



Cool White 563



Tropic Green 622



Bright Jade 613




Sky Blue 399



Lakeland 565



Crystal White 636




Flirtation 601



Blue Beauty 602



Sonata Blue 621



Oyster Grey 634



Moonshadow 635

Warna-warna ini mendekati warna asli cat yang dapat dihasilkan oleh teknik percetakan moden. Untuk permukaan atau dinding yang beralkali, satu lapisan Classic / Professional Series Wall Sealer harus disapukan sebelum 2 lapisan Koreton Plus.

Also Available :
White 9145 in 1, 7 & 18 Litre
Black 9103 in 1 & 7 Litre



KORETON PLUS

Quality Latex Emulsion Paint

Koreton Plus is a specially formulated vinyl acetate emulsion paint for interior use with a good degree of durability and smooth matt finishing on walls, ceilings and hard boards. It is user-friendly, and is most suitable as an economical interior emulsion paint for housing projects.

Koreton Plus dirumus khas untuk kegunaan dalaman. Ia memberi sajian yang menarik, halus serta tahan lasak pada permukaan dinding, siling dan papan keras. Koreton Plus mudah disapu dan berkemampuan mencegah pertumbuhan kulat.

Surface Preparation :

New concrete is recommended to be allowed to cure for at least 28 days. Ensure surface to be painted is clean, dry and free from all defective or poorly adhering contaminants like dirt, mud and grease etc. For previously painted surfaces, remove all loose paint, powdery residue or chalky surfaces by brushing or scraping with a stiff fibre brush under running water or high pressure water jet cleaning. Apply a coat of recommended KCC Wall Sealer before painting Koreton Plus.

Application :

Roller, brush or spray applications are highly recommended.

Mixing :

Stir the content of the paint thoroughly and evenly before use.

Thinning :

For normal use, thinning is not necessary; however if necessary, dilute with 5% to 10% water for good workability.

Touch Dry :

Depending on temperature and humidity, usually 30 to 45 minutes. May apply topcoat / recoat after 1 to 2 hours.

No. of Coats :

2 to 3 coats are usually recommended depending on the conditions of the substrate and the choice of colour. Theoretical spreading rate is approximately between 10 - 12m² / litre per coat at 30 microns dry film thickness. (Usually 2 coats are sufficient however may require additional coat if tinted from Base 3 or 4).

Cleaning Up :

Clean all equipment and tools with water immediately after use.

Penyediaan Permukaan :

Konkrit baru mestilah dibiarkan kering sekurang-kurangnya 28 hari. Pastikan permukaan yang hendak dicat bersih, kering dan tiada kotoran lain seperti habuk, lumut, minyak dan sebagainya. Bagi permukaan yang telah dicat, tanggalkan lapisan tidak stabil, berhabuk atau berkapur, dengan mengikis atau memberus disertai aliran air ataupun menggunakan pancutan air deras. Gunakan satu lapisan KCC Wall Sealer yang disyorkan sebelum mengecat Koreton Plus.

Peralatan :

Berus, penggelek atau penyembur cat adalah disyorkan.

Adunan :

Kacaukan kandungan cat secara rata sebelum guna.

Pencairan :

Untuk kegunaan biasa, pencairan lazimnya tidak perlu. Jikalau perlu, tambahkan air bersih sebanyak 5% hingga 10% kandungan cat untuk hasil yang lebih baik.

Masa Kering :

Di antara 30 hingga 45 minit bergantung kepada suhu dan kelembapan, boleh ulang cat selepas 1 hingga 2 jam.

Bilangan Lapis :

Bergantung kepada keadaan permukaan substrat dan warna pilihan, 2 hingga 3 lapisan adalah disyorkan. Mengikut teori, kadar liputan dianggarkan di antara 10 - 12m² / liter pada ketebalan 30 mikron filem kering. (Kebiasaannya 2 lapisan adalah memadai, namun lapisan tambahan mungkin diperlukan sekiranya dibancuh dari Asas (Base) 3 atau 4).

Pencucian :

Cuci semua peralatan dengan air bersih sebaik saja selesai kerja.

GREEN CHOICE / MESRA ALAM

Low VOC / Rendah VOC	
100% Free from APEO / 100% Bebas Dari APEO	
100% Free from Heavy Metal / 100% Bebas dari Logam Berat	
100% Free from Formaldehyde / 100% Bebas dari Formaldehid	

FUNCTIONAL BENEFITS / KELEBIHAN FUNGSI

Fast Drying / Cepat Kering	
No Peeling & Flaking / Tidak Mengelupas	
Easy to Apply / Senang Digunakan	
Good Hiding / Menyembunyikan Kotoran	

FINISHING / KEMASAN

Matt

Available in / Tersedia dalam kemasan :

1 Litre, 7 Litres & 18 Litres



KCC Paints Sdn. Bhd. (323967-T)

No. 1, Jalan Anggerik Mokara 31/55, Seksyen 31, Kota Kemuning, 40460 Shah Alam, Selangor D.E.

T | 603-5122 2900 F | 603-5122 1900 W | www.kccpaint.com.my