

HydroWhirl™ Orbitor

High Impact Rotary Tank Cleaning Machine

DESIGN FEATURES


- Reduced operating costs
- Minimum moving parts = reduced life-cycle costs
- Self cleaning; self lubricating = no process contamination
- High-impact jets; orbital wash pattern = high efficiency cleaning process
- Compact design
- 2 or 4 nozzle configurations = wash pattern variable up to super intense
- Male or female connections

SPRAY CHARACTERISTICS

- 360° wash pattern
 - Variable cycle times
 - High impact cleaning
- Flow rates:** 80 - 600 L/min
Working Pressure: 3 - 10 bar
- Materials:**
 Housing: 316L
 Nozzle Head: SAF 2205
 Gears: PEEK + 316 SS
 Bushings/Seals: Carbon Filled PTFE

Max. Working Temp.: 95°C (203°F)
Max. Ambient Temp.: 140°C (284°F)

Weight: 6 kg



Orbitor 2 nozzle spray pattern



Orbitor 4 nozzle spray pattern

Jet lengths are effective cleaning lengths

Connection Size	4 X 4.2mm				4 x 5mm			4 x 6mm			4 x 7mm			4 x 8mm		
	1" and 1-1/2"				1" and 1-1/2"			1-1/2"			1-1/2"			1-1/2"		
Pressure (BAR)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	
3	80.0	2.9	11	112	4	13	138	5.3	15.5	217	6.5	20.1	250	7.2	15.5	
4	100	3	9.3	137	4.2	10.8	170	5.7	12.9	252	7.1	15.2	293	8	12.9	
5	115	3.5	7.9	155	4.7	9.4	200	6.2	11	283	7.7	14.9	333	9	11	
6	127	4	6.9	173	5.2	8	220	7	9.5	310	8.5	13	367	9.9	9.5	
7	138	5	6.3	185	6.3	7.3	240	8	8.4	333	9.4	11.7	395	10.6	8.5	
8	147	6.2	5.8	195	7.5	6.8	257	9.4	7.6	350	10.3	10.4	418	11.2	7.8	
9	153	7.1	5.6	202	8.5	6.5	270	10.3	7	367	11.2	9.3	438	12.2	7	
10	157	7.8	5.5	207	9	6.4	282	11.2	6.9	380	12	8.9	458	13	6.9	

Connection Size	2 x 6mm				2 x 7mm			2 x 8mm			*2 x 10mm			*2 x 12.5mm		
	1-1/2"				1-1/2"			1-1/2"			1-1/2"			1-1/2"		
Pressure (BAR)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	Flow (L/min)	Jet Length (m)	Cycle Time (min)	
3	80.0	5.5	33	93.3	6.5	37.5	117	7.2	25.7	217	9.8	41	330	10.1	26.8	
4	91.7	6	27.2	117	7.2	31.6	150	8	22.9	255	10.5	34.2	383	11.2	24	
5	108	6.3	24.7	137	7.9	28.2	172	8.7	20.5	290	11.5	30.5	433	12.1	21.7	
6	122	7	22.6	153	8.5	25.8	190	9.4	18.9	320	12.7	28	473	13.4	19.8	
7	130	8	21	168	9.2	24	203	10.3	17.5	347	13.9	26	512	14.8	18.4	
8	140	9	19.5	182	10.4	22.3	213	11.3	16.4	368	15.2	24.5	547	16.4	17.2	
9	148	10.2	18.4	192	11.3	21	223	12.4	15.6	390	17	23.2	572	18.3	16.3	
10	157	11.5	17.4	200	12.3	20	232	13.5	14.9	405	18.8	22	600	20.1	15.5	

*High Capacity Jet Machine