

GS EPOXY MORTAR

Solvent Free Adhesive And Repair Mortar

Description

GS Epoxy Mortar is 2 part solvent free, thixotropic adhesive and repair mortar. It is a combination of Epoxy resins and specially selected high strength fillers. Offers high strength, moisture – tolerant properties for structural purpose.

Applications:

- Reinstall structural bonding of concrete, masonry and metals
- As patching mortar for concrete, stone, ceramics and plasterworks
- Anchoring of grout bolts
- Repair of joint corners
- Brick and concrete surfaces

Advantages

- High strength
- High modulus of elasticity
- Application on dry or damp concrete surfaces
- Fast curing
- Non flammable
- Shrinkage free
- Excellent chemical resistance.

Packaging

5kg / set

Storage

12 months from date of production if in original packing and unopened and undamaged.

Store in a dry and cool place in air tight containers.

Disclaimer:

All representations and recommendations set forth are given in good faith and to the best of our knowledge. However due to varying conditions and applications, the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usages. The sale of this product shall be on terms and conditions set forth on GCS order acknowledgement.

Product Specifications

Appearance	Grey mortar (Resin)
Main Ingredients	Epoxy Resin Polyamide Hardener
Mixing ratio:	12:1 (by volume)
Working time at 25°C	~45minutes
100% Curing time at 25°C	7 hours
Application Temperature	20 - 40°C
Solid content:	100%

Directions To Use

- Surfaces must be clean and free from grease, dirt and oil
- Surface must be free of water ponding
- For metal surface it should be cleaned thoroughly by water jet.
- Mix component A and component B according to ratio to 2 : 1
- Mix thoroughly for 3 minutes using a low speed drill
- After mixing , apply mixture within 1 hour before curing

Caution:

- Since mixture contains epoxy resin and polyamide hardener may cause severe eye and skin irritation when in contact with eyes or skin.
- In case of contact with eyes flush with water immediately for 15 minutes. If irritation persists, seek medical attention.
- In case of skin contact wipe off and clean with soap water.



GOLDEN CHANNEL SERVICES
SDN BHD (162485-H)

HQ & Showroom : ☒ No. 17 & 17A, Jalan Wangsa 1/1, Taman Wangsa, Cheras, 43200 Selangor Darul Ehsan, Malaysia.
☎ (603) 9080 5762 ☎ (603) 9080 5764 @ Email: gcskl@yahoo.com/enquiry@goldenchannel.com.my

Penang Branch : ☒ 14, Gr. Floor, Jalan Prai Jaya 1, Bandar Prai Jaya, 13600 Perai, Pulau Pinang, Malaysia.
☎ (604) 390 5621 ☎ (604) 390 0216 @ Email: pugroutsb@yahoo.com

🌐 [Http://www.goldenchannel.com.my](http://www.goldenchannel.com.my)