

# GS POLYMER SEALANT

## One Component, High Performance Sealant

---

### Description

GS Polymer sealant is a one component high performance sealant. It is based on Hybrid Polymer Technology. It is non staining for natural stone applications. It cures to form a tough flexible coating with supreme waterproofing qualities.

### Uses

- Connections & Expansion joints
- Retaining walls
- Movement joints in precast concrete constructions.
- Subways
- Balcony parapets
- Wall / floor joints
- Skirtings
- Shutter housings

### Advantages

- 1 – part ready to use
- Non staining
- Good UV resistance
- Anti fungal / Mildew resistance
- Paintable
- Bonds to most surfaces
- Good weathering and aging properties

### Packaging

600ml sausages, 20 sausages / carton

### Colour

Available in White, Grey and Black

### Storage

9 months from date of production if in original packing and unopened and undamaged.

Store in a dry and cool place with temperature below +25°C.

#### Disclaimer:

*All representations and recommendations set forth are given in good faith and to the best of our knowledge. However due to varying conditions and applications, the buyer shall conduct its own tests of this product before use. Under no circumstances will the manufacturer be liable for any loss or damages caused by incorrect usages. The sale of this product shall be on terms and conditions set forth on GCS order acknowledgement.*

## Product Specifications

Curing System	Moisture curing
Skin over time	45 minutes
Elongation at Break ( ASTM D412 )	800 %
Shore A Hardness ( ASTM C661 )	25 – 35 ( Approx )
Density	1.55 – 1.57 g/ml
Application Temperature	5°C to 40°C
Service Temperature	-30°C to 100°C

### Limitation:

The GS Polymer sealant should not be:

- Used in areas subject to continuous chlorinated water emersion.
- Swimming pools, spas.
- Constantly immersed in salt water.
- Used for glazing applications.
- Used in heavy trafficable joints greater than 10mm width.

### Caution:

- Avoid contact with eyes, skin and mouth.
- Uncured adhesive / sealant causes skin and eyes irritation upon contact.
- In case of contact with eyes flush with eyes immediately for 15 minutes.  
If irritation persists, seek medical attention.



**GOLDEN CHANNEL SERVICES**  
**SDN BHD** (162485-H)

HQ & Showroom : ☒ No. 17 & 17A, Jalan Wangsa 1/1, Taman Wangsa, Cheras, 43200 Selangor Darul Ehsan, Malaysia.  
☎ (603) 9080 5762 ☎ (603) 9080 5764 @ Email: gcskl@yahoo.com/enquiry@goldenchannel.com.my

Penang Branch : ☒ 14, Gr. Floor, Jalan Prai Jaya 1, Bandar Prai Jaya, 13600 Perai, Pulau Pinang, Malaysia.  
☎ (604) 390 5621 ☎ (604) 390 0216 @ Email: pugroutsb@yahoo.com

🌐 [Http://www.goldenchannel.com.my](http://www.goldenchannel.com.my)