

5.0 Purity Single Stage Nickel Plated Brass Barstock Diaphragm Cylinder Regulator - Acetylene



The Lab Master LGS510 Series single stage diaphragm cylinder regulators are designed for primary pressure gas control of high purity Acetylene gas up to grade 5.0 purity (99.999%), on applications where slight pressure variation from decreasing cylinder pressure is acceptable.

 LGS510 Series | Single Stage Diaphragm Cylinder Regulator, EPDM Pressure Relief Valve



- Six port configuration
- Rear panel mounting capabilities
- Encapsulated seat design
- Low wetted surface area
- Full range of inlet and outlet fittings
- Side entry

MATERIAL

Nickel Plated Brass Barstock

Bonnet High Strength Alloy Diaphragm 316L Stainless Steel

PTFE ■ Bonnet Seal

Seat Polyamide (Nylon®)

Filter 10 Micron 316L Stainless Steel

SPECIFICATION

25 bar (360 PSI) Maximum Inlet Pressure ■ Delivery Pressure Range 0 to 1 bar (15 PSI)

0 to 1.5 bar (22 PSI)


Gauges 50mm (2") Diameter Ports 1/4" NPT Female

■ Temperature Range -20° C to +60° C (-4° F to +140° F)


■ Weight 1.2 kg (2.7 lb) **

** Cylinder connection not included

FLOW PERFORMANCE



(1) DRAWINGS



MODEL NO. SELECTOR GUIDE

Example for a Model No. for LGS510 Series

LGS510-	02-	02-	00-		00-		000-		00-		Α		
Product Type	Inlet Pressure Bar [PSI]	Outlet Pressurek Bar [PSI]			Outlet Pressure Gauge		ı	Inlet/Cylinder Connection		Outlet Connection		Options	
LGS510	01 25 [360]	01 0 to 1.0 [15]		No Gauge Fitted	00	No Gauge Fitted	000	1/4" NPT Female	00	1/4" NPT Female	Α	No Options Selected	
		02 0 to 1.5 [22]	01	bar/PSI	01	bar/PSI	001	1/8 Stainless Steel Compression	01	1/8 Stainless Steel Compression	В	Regulator Tee Purge FKM	
				Plugged Port	10	Plugged Port	002	1/4 Stainless Steel Compression	02	1/4 Stainless Steel Compression	С	Regulator Tee Purge EPDM	
							003	6mm Stainless Steel Compression	03	6mm Stainless Steel Compression	K	Certificate of Conformity (CoC)	
							004	1/4 NPT Male	04	1/4 NPT Male	Р	Calibration / Pressure Test Certificate	
							800	G3/8 BSP L/H Brass Male	08	G3/8 BSP L/H, Brass, Male	Х	Special Instruction	
							012	BS341 No.4	10	Isolation Valve, 1/4 NPT Female, EPDM Seal			
							027	DIN477 No.3	12	Isolation Valve, 1/8 Stainless Steel Compression, EPDM Seal			
							028	DIN477 No.3.1	14	Isolation Valve, 1/4 Stainless Steel Compression, EPDM Seal			
							050	CGA510	16	Isolation Valve, 6mm Stainless Steel Compression, EPDM Seal			
							conn	our complete range of cylinder nections refer to 'Cylinder nections Data'					