



DULUX AMBIANCE PEARL GLO

MID SHEEN-FINISH

WATERBASED

PRODUCT INFORMATION

PRODUCT NAME	Dulux Ambiance Pearl Glo
DESCRIPTION	Dulux Ambiance Pearl Glo is a premium quality, highly durable emulsion paint with an attractive mid-sheen luxurious pearlized finish.
USAGE	Dulux Ambiance Pearl Glo is suitable for all normal interior wall masonry surfaces including brickwork, plaster, cement and wallboards.
BENEFITS	<p>Gives an attractive luxurious mid sheen finish that exudes the shimmers and luxury of pearls.</p> <p>Colourguard Technology that locks in the colour.</p> <p>Low Odour Low VOC ^.</p> <p>Certified to Singapore Green Label & SIRIM Eco-label ^.</p> <p><small>^ Applicable to selected colours only.</small></p> <p>No added lead & mercury.</p>
PACK SIZE	1, 5 and 18 litres
COLOUR RANGE	Refer to Dulux Colour Catalogue.

PERFORMANCE GUIDE

FILM PROPERTIES	Will tolerate the levels of atmospheric humidity present in normal interior environments and able to withstand moderate washing. Not suitable where frequent heavy condensation is likely to occur, as in kitchens and bathrooms.
THEORETICAL COVERAGE	A guide to the theoretical coverage which can be achieved under normal conditions is 11 – 12m ² /L.

PRODUCT DATA

COMPOSITION	<p>Pigment : Lightfast non-lead pigments and mineral extenders.</p> <p>Binder : Acrylic copolymer.</p> <p>Solvent : Water</p>
VOLUME SOLIDS	White 38% (nominal), other colours will vary.

APPLICATION

THINNING	
Brush or Roller	For normal use thinning is not usually necessary, but if required add up to 1 part of clean water to 10 parts of paint (10%).
Conventional Spray	Add up to 1 part of clean water to 3 parts of paint (30%).
Airless Spray	Ready for use. Thinning is usually not required.
SPRAY RECOMMENDATIONS	
Conventional Spray	Satisfactory through most equipment.
Airless Spray	A typical set up for airless spray application would be a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a spray tip size 0.58mm (23 thou) and a spray tip angle 65°.
DRYING TIMES	
Touch Dry	Single coat at standard thickness: Dependant on temperature and humidity
Recoat	2-3 hours.
CLEANING EQUIPMENT	Clean all equipment with water immediately after use.



DULUX AMBIANCE PEARL GLO

MID SHEEN-FINISH

WATERBASED

PRODUCT INFORMATION

PRE-APPLICATION

SURFACE PREPARATION	Surface must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease or wax and be rubbed down using a suitable abrasive paper and dusted off. Treat areas affected by mould, fungi or algae with Dulux Fungicidal Wash (A980-19260). If after thorough preparation, surfaces remain powdery, seal with one coat of an appropriate primer/sealer (see below). It should not be applied on areas where moisture reading (as measured by Protimeter) exceeds 16%. These walls should be left to dry further.	
SYSTEM INFORMATION	<u>SEALER/PRIMER (1 COAT)</u>	<u>FINISH (MINIMUM 2 COATS)</u>
Powdery Surfaces	Dulux Weathershield Primer	
Alkali and New Surfaces	Dulux Exterior & Interior Wall Sealer	Dulux Ambiance Pearl Glo
Normal, Sound Surfaces	Dulux Exterior & Interior Wall Sealer	<i>(Colour enhancer is advisable for vibrant colour)</i>

PRECAUTION

HEALTH, SAFETY AND ENVIRONMENT INFORMATION	Product Safety Data Sheet available upon request
---------------------------------------------------	--------------------------------------------------

Any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints in relation to goods manufactured or marketed by it or their use or any application is given in good faith. However, any advice, recommendations, information, assistance or service provided by Akzo Nobel Paints is provided without expressed or implied warranties

APG: 140722

Akzo Nobel Paints (Malaysia) Sdn Bhd
(Formerly known as ICI Paints (Malaysia) Sdn Bhd)

For further details on Product Data Sheet, kindly contact:
Customer Care Department

Tel: 1-800-88-9338 Website: www.dulux.com.my Email: customer care.my@akzonobel.com

AkzoNobel