

KM-100

MICROPHONE



FEATURES

- + Streamlined appearance design, user-friendly operation interface, beautiful and generous.
- + High-definition LCD display, intuitive and clear.
- + The sound curve has been carefully tuned, and the sound is warm and transparent.
- + Lockable control function selection.
- + Features high-performance audio processing chip, ultra-low distortion sound processing circuit design.
- + The ultra-high frequency dynamic compression and shunt technology automatically shunts the high and low frequencies to show better dynamic performance.



KM-100

MICROPHONE

FEATURES

- + Streamlined appearance design, user-friendly operation interface, beautiful and generous.
- + High-definition LCD display, intuitive and clear.
- + The sound curve has been carefully tuned, and the sound is warm and transparent.
- + Lockable control function selection.
- + Features high-performance audio processing chip, ultra-low distortion sound processing circuit design.
- + The ultra-high frequency dynamic compression and shunt technology automatically shunts the high and low frequencies to show better dynamic performance.



Frequency Range	645 - 693 MHz
Receive Sensitivity	-95 - 60 dBm can be equipped with 100 private rooms without serial frequency
Receiving Method	Superheterodyne Secondary Frequency Conversion
Debug Mode	Frequency Modulation (FM)
Receiving Range	20-30 meters
Adjustable Channels	100*2
Power Specifications	220-230V, 50-60Hz, 12 VDC (switching power adapter)
Power Specifications	220 VDC, 50-60 Hz 12 (Linear power supply)
Battery	Two AA batteries