



FEIKEN PERFORM LUBE PLUS ENGINE OIL SAE 5W-30

Fully Synthetic | Engine Oil | SAE 5W-30 | SN PLUS

FEIKEN PERFORM LUBE PLUS Fully Synthetic Engine Oil SAE 5W-30 is a high-performance engine oil designed to meet the demands of the latest gasoline and diesel engines while delivering excellent all-around performance. The formulation establishes a protective barrier that extends the life of your engine and maintains its functionality like new. As a testament to its durability and reliability, this advanced engine oil offers extended protection up to 10,000 miles, underscoring its commitment to long-lasting performance. In essence, FEIKEN PERFORM LUBE PLUS Fully Synthetic Engine Oil SAE 5W-30 is more than just an engine oil; it's a comprehensive solution designed to enhance your driving experience by protecting your engine's health and efficiency over the long term.

FEATURES & BENEFITS

- Meets OEM standards for quality.
- Enhances protection against sludge, promoting overall engine cleanliness.
- Reduces fuel consumption and wear during start-up.
- Keeps your engine running like new.
- High oxidation stability and strong resistance to high- and low-temperature sludge formation.
- Turbo-friendly additives ensure durability.

PERFORMANCE LEVELS

- ACEA A3/B3, A3/B4
- API SN/CF, SN PLUS
- BMW Longlife-01
- MB-Approval 226.5/229.3/229.5
- Porsche A40
- Renault RN0700/RN0710
- Volkswagen 502.00/505.00

APPLICATIONS

Suitable for use in passenger cars, 4WDs, and light duty commercial vehicles fitted with gasoline engines.

TYPICAL SPECIFICATION

SAE Viscosity Grade	5W-30
Appearance, Visual	Bright & Clear
Colour, ASTM D1500	3
Density@15 °C, kg/l, ASTM D4052	0.854
Viscosity at 40°C, mm ² /s, ASTM D445	53.69
Viscosity at 100°C, mm ² /s, ASTM D445	10.10
Viscosity Index, ASTM D2270	179
Flash Point COC, °C, ASTM D92	Min 215
Total Base Number, mgKOH/g, ASTM D2896	8.08
Pour Point, °C, ASTM D5950	-45
Cold Crank Vis@-30°C, cP, ASTM D5293	6470

Note: FEIKEN PERFORM LUBE PLUS Fully Synthetic Engine Oil SAE 5W-30 may be unsuitable for use in some engines, always consult owners' manual if in doubt.



SAE 5W-30 Fully Synthetic
Pack Size: 4 Litre
Shipping Weight:

Health & Safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. The recommendations or suggestions made in this sheet are made without guarantee or representation as to results. The content of this sheet is correct to the best of our knowledge. We advise the reader to carefully evaluate the product choice for critical applications together with the supplier.