



FEIKEN PERFORM LUBE ECOSHIELD ENGINE OIL SAE 10W-40

Semi-Synthetic | Engine Oil | SAE 10W-40 | SN PLUS

FEIKEN PERFORM LUBE ECOSHIELD Semi-Synthetic Engine Oil SAE 10W-40 is an advanced engine oil designed to meet the demanding requirements of both gasoline and diesel engines, regardless of whether they are equipped with turbochargers. Due to the high viscosity range, the oil is ideal for all-season use. This formulation combines high-performance synthetic oil with hydrotreated base oil, integrating state-of-the-art additive technology to provide optimum protection for modern engines. Its versatility, all-season capability, and advanced technology make it a reliable choice for those seeking optimal engine protection and performance for their gasoline and diesel-powered vehicles.

FEATURES & BENEFITS

- Meets OEM standards for quality.
- Enhances protection against sludge, promoting overall engine cleanliness.
- Reduces fuel consumption and wear during start-up.
- Keeps your engine running like new.
- High oxidation stability and strong resistance to high- and low-temperature sludge formation.
- Turbo-friendly additives ensure durability.

PERFORMANCE LEVELS

- ACEA A3/B3, A3/B4
- API SN/CF, SN PLUS
- BMW Longlife-01
- MB-Approval 229.1/229.3
- Porsche A40
- Renault RN0700/RN0710
- Volkswagen 502.00/505.00

APPLICATIONS

Suitable for use in passenger cars, 4WDs, and light duty commercial vehicles fitted with gasoline engines.

TYPICAL SPECIFICATION

SAE Viscosity Grade	10W-40
Appearance, Visual	Bright & Clear
Colour, ASTM D1500	3
Density@15 °C, kg/l, ASTM D4052	0.873
Viscosity at 40°C, mm ² /s, ASTM D445	94.0
Viscosity at 100°C, mm ² /s, ASTM D445	13.8
Viscosity Index, ASTM D2270	149
Flash Point COC, °C, ASTM D92	Min 215
Total Base Number, mgKOH/g, ASTM D2896	10.2
Pour Point, °C, ASTM D5950	-45
Cold Crank Vis@-30°C, cP, ASTM D5293	6430



SAE 10W-40 Semi-Synthetic
Pack Size: 4 Litre
Shipping Weight:

Note: FEIKEN PERFORM LUBE ECOSHIELD Semi-Synthetic Engine Oil SAE 10W-40 may be unsuitable for use in some engines, always consult owners' manual if in doubt.

Health & Safety

This product should not cause any health problems when used in the applications suggested and when the guidance provided in the Safety Data Sheet (SDS) is followed. The recommendations or suggestions made in this sheet are made without guarantee or representation as to results. The content of this sheet is correct to the best of our knowledge. We advise the reader to carefully evaluate the product choice for critical applications together with the supplier.