

TEMPERATURE CONTROLLER TC-29



TECH SPECS

Model	TC-29
Dimension (HxWxD) mm	72 x 72 x 45
Panel Cutout	68 x 68
Input	J/K or PT-100 2W/3W (Factory Set)
Range	J: 400° C, K: 1200° C PT-100 2 Wire or 3 Wire (0° C to 400° C, -50.0° C to 200.0° C) (Any one factory set)
Output	1 Relay 1 C/O, 5A, 230V AC (Resistive Load) or SSR (Factory Set)
Control Action	TP / ON-OFF (Factory Set)
Power Supply	230V AC \pm 10%,50Hz

APPLICATIONS

Packaging Machinery

Extrusion Machinery

Furnace & Boilers

Ovens & Incubators

Food Industry

Technical Specifications

Input	
Input Type	Thermocouple : (J, K) PT-100 2 Wire or 3 Wire (Factory Set)
Display Range	Refer (Table 1)
Accuracy	± 1% of FSD
ADC Resolution	10 Bits
Display Resolution	Thermocouple : 1 °C RTD : 1 °C
Sample Rate	6 Sample / Sec
CJC Error	± 2 °C
Sensor Open	All Input
Sensor Burnout Current	1.10uA
RTD Excitation Current	0.2mA
CMRR	>120 db (Typical)
Input Impedance	>1M
Max Voltage	20V DC

Output	
Control Output	
Control Type	On-Off, TP
Relay Control Output	
Relay	1 Nos.
Rating	5A @230V AC / 28V DC Resistive Load
SSR Control Output	
Rating	12V DC @30mA

Display	
Process Value	4 Digit 7 seg 0.56", RED LED Display
Keys	SET, UP, DOWN
LED Indication	Relay

Environmental	
Operating Temperature	0 to 55 °C
Storage Temperature	0 to 70 °C
Humidity	95% RH Non-condensing
Protection	IP 54 (Front Side)

Physical	
	TC-29
Enclosure	Molded ABS
Color	Black
Front Bezel (mm)	72 x 72
Panel cutout (mm)	68 x 68
Depth behind panel	45 mm
Accessories	1 pair of Mounting clamp
Terminal Cable Size	Barrier Type terminal Cable Size (2.5 mm ²)


Table 1 (Sensor Range)	
J	0 to 400 °C
K	0 to 1200 °C
PT-100 2 Wire or 3 Wire	0 to 400 °C, -50.0 to 200.0 °C

Power Supply	
Standard	230V AC, ±10%,50Hz
Consumption	3VA

Mechanical Dimension

Outline Dimension (mm)	Panel Cutout Dimension (mm)
<p>72</p> <p>72</p> <p>45</p> <p>3</p>	<p>68</p> <p>68</p>

Connection Diagram



Multispan reserves the right to change specifications without prior notice. Printing and typographical errors reserved.
Product improvement and upgrade is a constant procedure. So for more updated operating information & support contact us.

Multispan Control Instruments Pvt. Ltd.

72/B, Phase 1, GIDC Estate, Vatva, Ahmedabad-382445, Gujarat, India.

+91-7575805463/7623001206

support@multispanindia.com

Follow us



www.multispanindia.com