

PVC Suction Hose (F-type)

APPLICATIONS

Widely used for conveying water, oil, powder, abrasive materials like sands, gravel, cement in construction, agriculture and industrial service applications.

FEATURE

- Economical & flexible
- Abrasion & corrosion resistant
- Impact & crush resistant
- Transparent visibility
- Smooth inner ideal for unrestricted flow of materials



MATERIAL

PVC reinforced with the rigid helix.

TEMPERATURE

-10°C to + 60°C

Code	Nominal Diameter (Inch)	I.D. (mm)	O.D. (mm)	Working / Burst Pressure (bar)	Length per roll (mt)
PSU - 1025	1"	25.0	30.0	6.0 / 18	20
PSU - 1032	1-1/4"	32.0	38.0	6.0 / 18	20
PSU - 1038	1-1/2"	38.0	44.0	5.0 / 15	20
PSU - 1049	2"	50.0	57.8	4.0 / 12	20
PSU - 1050	2"	50.0	60.0	6.0 / 18	20
PSU - 1065	2 1/2"	63.0	72.2	3.5 / 10	20
PSU - 1075	3"	76.0	85.1	3.5 / 10	20
PSU - 1076	3"	76.0	86.0	5.0 / 15	20
PSU - 1100	4"	101.0	113.0	3.5 / 10	20
PSU - 1125	5"	127.0	139.5	3.0 / 9	20
PSU - 1152	6"	152.0	166.5	2.5 / 8	20
PSU - 1200	8"	200.0	216.0	2.0 / 6	6