

# PVC SPRING HOSE



tel : 012-3868942 / 016-2285297 email : sales@lwgi.com.my website: www.lwgi.com.my

**LWG INDUSTRIAL SDN BHD**  
202301019617 (1513539-K)



## Applications

- Suitable for oil and chemical resistance applications.
- Ideal for pumping and transferring of liquid, powder and granular material.
- Exceptionally tough and durable for heavy-duty industrial applications.
- Extensively used for suction and discharge - public utilities, drainage, ships, silos and irrigation plants.

## Feature :

- \* Excellent Flexibility
- \* Corrosion & Abrasion Resistant
- \* Transparent Visibility
- \* Smooth inner construction for unrestricted flow of materials

## Material

Transparent soft PVC with wire helix

## Temperature

-10°C to +60°C

Nominal Size	I.D. (mm)	O.D. (mm)	Working / Burst Pressure (bar)	Weight (kg/m)	Length per roll (mt)
1/2"	12.0	18.0	6 / 15	0.22	100
5/8"	15.0	22.0	6 / 15	0.31	100
3/4"	19.0	26.0	5 / 12	0.38	50
7/8"	22.0	30.0	5 / 12	0.50	50
1"	25.0	33.0	5 / 12	0.55	50
1 1/4"	32.0	41.0	4 / 10	0.79	40
1 1/2"	38.0	48.0	4 / 10	1.03	40
1 5/8"	41.0	52.0	4 / 10	1.29	40
1 7/8"	48.0	59.0	4 / 10	1.40	40
2"	51.0	62.0	4 / 10	1.50	40
2 1/2"	63.0	80.0	3 / 8	2.75	20
3"	76.0	92.0	3 / 8	3.25	20
4"	102.0	120.0	3 / 8	5.00	20
6"	152.0	168.0	2 / 5	6.80	20