



AVG AVG GOLF PUTTING GREENS

Product / Description 10MM AVG Golf Putting Greens						
DTEX						
Pile Height	10mm - 15mm					
Gauge	3/16 inch					
Stitch Rate	220 - 270 s/m					
Packing Size	2m (W) x 10m (L) / 20m ² 2m (W) x 20m (L) / 40m ²					
Backing	PP 200g					
Roll Width	2m					
Roll Length	10m / 20m					
Colour	Bicolor					









Smooth and Soft

Abrasion Resistance

Excellent Sport Performance

AVG Golf Putting Greens are designed specifically for golf courses and ranges. It features high-intensity and rotational freedom, allowing for a realistic golf ball traction and roll.

AVG Golf Putting Greens also designed to be thick and solid, providing a durable surface that can withstand heavy foot traffic and weather conditions. Additionally, AVG Golf Putting Greens is a non-infill product, which means that it does not require any additional infill materials to be added to the surface.

AVG Golf Putting Greens has a natural look and feel due to its incorporation of golf standard grass curled fibers and evergreens. Its easy maintenance requirements make it an appealing choice for golf course and range managers who want to minimize upkeep time and expenses.



MP PLUS MARKETING (201803221711)

No. 14 & 16, Jalan Bayu 7/2, Taman Nusa Bayu, 79200, Iskandar Puteri, Johor Malaysia. Contact Person: Mr. Danny

Mobile: +60 168628368 Email: sales@mpplus.com.my







PREMIER TURF **ARTIFICIAL GRASS**

PREMIER TURF ARTIFICIAL GRASS							
Pile Height (+/-2mm)	20mm	25mm	30mm	35mm	40mm		
Gauge	3/8"	3/8"	3/8"	3/8"	3/8"		
Stitches	200S/M ±5%	200S/M ±5%	200S/M ±5%	200S/M ±5%	200S/M ±5%		
DTEX	11000 ±5%	11000 ±5%	11000 ±5%	11000 ±5%	11000 ±5%		
Packing Size	2m(W) X 25m(L) / Roll (50m²/ Roll)						
Fibre	100% Synthetic (Blend of Polypropylene & Polyetheylene with U/V Stablilizer)						
Cohesion Base	Draining Latex						
Roll Width	2 meter						
Roll Length	25 meter						
Colour	Straight (Field Green & Apple Green) ; Curved Yellow Base						



PREMIER TURF ARTIFICIAL GRASS IN MODERN LIVING

Warranties:

5-year Carpet Residential Wear Warranty & Lifetime Antishock Carpet Warranty.

Ideal for Swimming Pool Borders, Landscape Decoration, Exhibitions, Displays, Outdoors uses, Nautical uses.

The subfloor should be dry, smooth, flat, dust-free and resistant to comprassion and load-bearing. Where seaming is necessary, a seam sealant must be used for all such installations. Due to dyelot variations, actual material may vary slightly from the samples.

Performance:

100% Solution Dyed Synthetic: Extremely hardwearing, Waterproof and Abrasion Resistant Fibre.

Draining Latex: Mildew Proof, Rot Proof, Excellent Dimensional Stability, most suitable for outdoor use and for all types of weather.

U/V Stabilized : Chemically Treated to provide maximum protection against fading from ultra violet sunlight.

Solution Dyed: For Excellent Colourfastness.



MP PLUS MARKETING (201803221711)

No. 14 & 16, Jalan Bayu 7/2, Taman Nusa Bayu, 79200, Iskandar Puteri, Johor Malaysia.

Contact Person: Mr. Danny Mobile: +60 168628368 Email: sales@mpplus.com.my

