

Power Up Gear Oil GL5

Product Description:

Power Up GL5 is a multi purpose gear lubricant manufactured from selected, highly refined base oil and blended with field-proven additives. This combination creates a product with excellent chemical and thermal stability over a wide range of temperature.

Applications / Benefits:

- ▣ Proven gear protection in low and high-speed conditions.
- ▣ Reduces costs associated with seasonal oil changes.
- ▣ Improves fuel economy.
- ▣ Superior sulfur phosphorus additives.
- ▣ Easier low temperature starting.

Typical Characteristics:

Test Description	Method	90	140	80W90	85W90	85W140
SAE Viscosity Grade	SAE J 300					
Specific Gravity @ 15 °C	ASTM D 4052	0.894	0.907	0.885	0.896	0.907
Flash Point, °C	ASTM D 92	215	226	210	220	225
Pour Point, °C	ASTM D 97	-9	-6	-27	-18	-12
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	198	421	140.3	153.2	378
cSt @ 100°C	ASTM D 445	17	28.4	14.6	15.05	27.4
Viscosity Index	ASTM D 2270	95	94	103	98	98
Color	ASTM D 1500	<3.0	<3.5	<2.5	2.5	3.0

Specifications, Approvals & Recommendations:

- API GL-5
- MAN 342N
- ZF TE-ML05A/07A/12E
- ZF TE-ML C/D
- ZF TE-ML16B/17B/19B
- AISE 224
- AGMA 9005-EO2
- DIN 51517 Part 3
- David Brown S1.53.101