



Power Up Vacuum Pump Oil

Product Description:

Power Up Vacuum Pump Oils are formulated from highly refined hydro-treated Gp2 base stocks and specially selected additives designed to achieve premium performance that is suitable for each kind of mechanical vacuum pump, partocularly in areas of good-oil water seperation property, resistance to wear and oxidized stability, high viscousity index and long life service.

Applications / Benefits:

- Very low saturated steam pressure
- High viscosity index
- Rresistance to wear protect.
- Outstanding long-term oxidation stability
- Unsurpassed water separation properties

Typical Characteristics:

Test Description	Method					
ISO Viscosity Grade	-	32	46	68	100	150
Specific Gravity @ 15 °C	ASTM D 4052	0.873	0.882	0.886	0.885	0.893
Flash Point, °C	ASTM D 92	218	224	228	230	230
Pour Point, °C	ASTM D 97	-12	-12	-9	-9	-9
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	32	46.3	68.2	98.1	147.2
cSt @ 100°C	ASTM D 445	5.44	6.8	8.7	11.0	14.4
Viscosity Index	ASTM D 2270	103	100	98	97	95
Color	ASTM D 1500	<0.5	<0.5	<1.0	<1.5	<1.5
Color	ASTM D 1500	<0.5	<0.5	<1.0	<1.5	<1.5