





# ADV 2361 HIGH MOLECULAR WEIGHT POLYISOBUTYLENE SUCCINIMIDE ASHLESS DISPERSANT

#### PRODUCT DESCRIPTION

- Prepared from high-active polyisobutylene (Molecular weight 2300) by thermal adduction process.
- Has good detergency and sludge dispersancy at low temperature.
- Can inhibit the formation of carbon and paint film at engine piston.
- The thermal stability and detergency at high temperature is much better than traditional KTD1354 and KTD1355.

#### PRODUCT FEATURE

- Good dispersancy at low temperature.
- Good high temperature detergency.
- Good oil solubility.
- Good solubilization.
- Good alkaline reserve capability.
- Contains no chlorine.

#### PRODUCT APPLICATIONS

- Used for blending high quality engine oil.
- Dosage recommended (wt%): 1.0-10.0%.

### PRODUCT CHARACTERISTICS

ITEM	TYPICAL VALUE	TEST METHOD
Kinematic Viscosity (100°C), mm²/s	Report	GB/T 265
Flash Point (COC), °C	170 min	GB/T3536
Nitrogen, wt%	1.0-1.3	SH/T 0224
Water, wt%	0.10max	GB/T 260
TBN, mg KOH/g	15~30	SH/T0251

## PACKING, STORAGE AND TRANSPORTATION

 Packed in 200 liter steel drum, 170 kg net weight per drum. For the details of health and safety precautions, please see the related Material Safety Data Sheet.