

ADV 2038 ZINC PROPYL OCTYL SECONDARY-PRIMARY ALKYL DITHIOPHOSPHATE

PRODUCT DESCRIPTION

- The product has fine antioxidation, anti-corrosion, antiwear and thermal stability.

PRODUCT FEATURE

- Excellent antiwear performance.
- Antioxidation/corrosion performance.
- Good hydrolytic stability

PRODUCT APPLICATIONS

- Used primarily for blending high-grade gasoline engine oil.
- Dosage recommended (wt%): 0.5-2.5%.

PRODUCT CHARACTERISTICS

ITEM	TYPICAL VALUE	TEST METHOD
Flash Point (COC), °C	160 min	GB/T 3536
Kinematics Viscosity (100°C), mm ² /s	Report	GB/T 265
Sulfur, wt%	15-19.0	SH/T 0303
Phosphorus, wt%	7.5 min	SH/T 0296
Zinc, wt%	9.5 min	SH/T 0226
Thermo decomposition temperature °C	190 min	SH/T0561
PH value	5.5 min	SH/T0394

PACKING, STORAGE AND TRANSPORTATION

- Packed in 200 liter steel drum, 200 kg net weight per drum.
For the details of health and safety precautions, please see the related Material Safety Data Sheet.