

# ATF DEXRON II

ATF DEXRON II is an oil for automatic transmissions in older vehicles specifying the use of DEXRON® II quality fluids. High quality base oils and special additives provides resistance towards oxidation, provides and shows improved frictional properties. ATF DEXRON II is formulated on high quality re-refined mineral and virgin synthetic base stocks in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Very High Viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

Available in 18L and 200L

**Exceeds: DEXRON® II D, ZF TE-ML 02F, 03D, 04D, 09, 11B, 14A, 17C**

Property	Unit	Test Method	Typical Value
Color		Visual	Red
Density @15°C	kg/m <sup>3</sup>	ASTM D4052	853
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	38
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7.6
Viscosity Index		ASTM D2270	172
Viscosity Brookfield @-40°, typical	cP	ASTM D2983	18000
Flash Point COC	°C	ASTM D92	201
Pour Point	°C	ASTM D7346	-51