

# ATF DEXRON VI

ATF DX VI is a high quality universal fluid based on 100% synthetic base stocks to be used in automatic transmission, torque converters and powersteering of pas- senger car, light vans and commercial vehicles where a GM Dexron VI specification is required. This product is backwards compatible where DEXRON® III (H), DEX- RON® III(G), DEXRON®IIE and DEXRON®IID is been required. ATF DX VI is formulated on high refined synthetic base stock in combination with an unique additive package to reach the following properties.

- Excellent thermal- and oxidation stability.
- Special friction modifiers.
- Verry high viscosity Index.
- Low pour point.
- Excellent shifting at very low and high temperatures.
- Excellent protection against the forming corrosion, foam and wear.

Available in 18L and 200L

## Exceeds: DEXRON®VI

Property	Unit	Test Method	Typical Value
Colour		Visual	Red
Density @ 15°C	kg/m <sup>3</sup>	ASTM D4052	846
Kinematic Viscosity @ 40°C	mm <sup>2</sup> /s	ASTM D7042	29
Kinematic Viscosity @ 100°C	mm <sup>2</sup> /s	ASTM D7042	5.9
Viscosity Index		ASTM D2270	152
Flash Point (COC)	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-48