

# TRANSMISSION FLUID 10W T0-4

TRANSMISSION FLUID 10 W T0-4 is specifically designed for powershift transmissions, final drives and wet brakes on heavy duty off-highway equipment used in earthmoving, mining logging, road transport and agricultural applications. TRANSMISSION FLUID 10W T0-4 is formulated with a high refined solvent mineral base stock in combination with a special additive package to reach the following properties:

- Excellent thermal- and oxidation stability.
- Very good dispersancy and detergency.
- High anti-foam, anti-wear and anti-corrosion properties.
- Excellent protection against Bore Polishing.
- Extended drain intervals possible.

Available in 18L and 200L

**Exceeds: Caterpillar T0-4, Komatsu KES 07.868.1, Allison C-4, API CF-2/CF, Vickers 35VQ25, ZF TE-ML 03C, Komatsu Dresser, DANA Powershift transmissions**

Property	Unit	Test Method	Typical Value
SAE Viscosity Grade		SAE J300	10W
Density@15°C	kg/m <sup>3</sup>	ASTM D4052	869
Kin. Viscosity @40°C	mm <sup>2</sup> /s	ASTM D7042	43.8
Kin. Viscosity @100°C	mm <sup>2</sup> /s	ASTM D7042	7.0
Viscosity Index		ASTM D2270	117
Flash Point COC	°C	ASTM D92	>201
Pour Point	°C	ASTM D7346	-33
Total Base Number	mgKOH/g	ASTM D2896	9.1