



Scandinavian Design

Vintec products are designed in Denmark and Sweden, with sustainably-sourced premium white oak shelves, fingerprint-proof acid-etched and edge-to-edge glass doors, no protruding handles, minimal touch control panels, signature red bumpers on shelves, and diffused LED lighting throughout.

35 bottle single zone cellaring OR serving wine cabinet for red and white wines

Product Benefits & Features

Stable Temperature

Our wine cabinets maintain a stable temperature to keep your wine in perfect cellaring conditions. This is thanks to the Triple Glazed, UV treated, insulated side panels and interactions between a compressor and thermostat.

- LED Digital Display Panel
- Energy Efficient R600a Gas



Humidity above 50%

Our wine cabinets incorporate a Thermal Recycling Pump that ensures adequate humidity levels are maintained. The Thermal Recycling Pump works by heating condensed water, which is then introduced as humid air within the cabinet.



UV Protected Dark Storage Area

UV rays negatively impact the quality of your wine. Our cabinets eliminate this threat by incorporating UV treated tinted glass doors or solid doors, dark interiors and dimmed internal LED lights.



Vibration Reduction System

To protect the storage life and quality of your wine, our cabinets have been designed to create a vibration proof environment by including an externally housed compressor, rubber shock absorbers and vibration absorbing wooden shelves.

Quality Air Flow

Our cabinets include internal and external fans to ensure there is a slow reticulated air flow throughout the cabinet

Product Specification

RangeName	Classic	Door Type	Glass Door
Main Function	Cellar Reds & Whites	Door Construction	Triple Glazed, UV treated
Alternate Function	Serve Reds OR Whites	BodyFinish	Black
ZonesDenomination	Single-Zone	Finish	Classic Black
No of Zones	1	Hinge	Right
Temperature Range Zone 1 (deg)	6 - 18	Reversible	Yes
Temperature Range Zone 2 (deg)	N/A	OppositeHingingPC	N/A
Temperature Range Zone 3 (deg)	N/A	Product Installation	Freestanding Only
UVTreated	Yes	Installation Type	Cannot be placed underbench
Lock	No	Height (mm)	840
Alarm	None	Width (mm)	493
Display Panel	LED Digital Display	Depth (mm)	588
Internal Heater	No	Joinery cut out dimension- minimum h	Freestanding Only
CutOffThermostat	Yes	Joinery cut out dimension- minimum w	Freestanding Only
AirFilter	No	Joinery cut out dimension- minimum d	Freestanding Only
Easy Capacity (Bottles)	35	Air space above cabinet (mm)	200
Max Capacity (Bottles)	35	Air space at sides (mm)	200
Number of Shelves	4	Rear Spacer (mm)	30
Shelving Material	Wood	Ambient Temperature (deg)	5-43
Shelving Type	3 Full, 1 Half	Electricity Consumption (kWh/Day)	0.395
AdjustableShelves	Yes	Refrigerant	R600a
SlidingShelvesType	N/A		
Lighting	White LED		
LightPosition	Top		
Handle	Recessed		