



### Scandinavian Design

Vintec products are designed in Denmark and Sweden, with sustainably-sourced premium white oak shelves, fingerprint-proof acid-etched and edge-to-edge glass doors, no protruding handles, minimal touch control panels, signature red bumpers on shelves, and diffused LED lighting throughout.

50 bottle single zone cellaring OR serving wine cabinet for red or white wines

## Product Benefits & Features

### Stable Temperature

Our wine cabinets maintain a stable temperature to keep your wine in perfect cellaring conditions. This is thanks to the Triple Glazed, UV treated, insulated side panels and interactions between a compressor and thermostat.

- LED Digital Display Panel
- Energy Efficient R600a Gas



### Humidity above 50%

Our wine cabinets incorporate a Thermal Recycling Pump that ensures adequate humidity levels are maintained. The Thermal Recycling Pump works by heating condensed water, which is then introduced as humid air within the cabinet.



### UV Protected Dark Storage Area

UV rays negatively impact the quality of your wine. Our cabinets eliminate this threat by incorporating UV treated tinted glass doors or solid doors, dark interiors and dimmed internal LED lights.



### Vibration Reduction System

To protect the storage life and quality of your wine, our cabinets have been designed to create a vibration proof environment by including an externally housed compressor, rubber shock absorbers and vibration absorbing wooden shelves.

### Quality Air Flow

Our cabinets include internal and external fans to ensure there is a slow reticulated air flow throughout the cabinet

**Product Specification**

RangeName	Allure	Handle	Recessed
Main Function	Cellar Reds & Whites	Door Type	Glass Door
Alternate Function	Serve Reds OR Whites	Door Construction	Triple Glazed, UV treated
ZonesDenomination	Single-Zone	BodyFinish	Black
No of Zones	1	Finish	Brushed Aluminium
Temperature Range Zone 1 (deg)	5 - 18	Hinge	Right
Temperature Range Zone 2 (deg)	N/A	Reversible	Yes
Temperature Range Zone 3 (deg)	N/A	OppositeHingingPC	N/A
UVTreated	Yes	Product Installation	Built-In or Freestanding
Lock	No	Installation Type	Slot-in
Alarm	None	Height (mm)	820
Display Panel	LED Digital Display	Width (mm)	595
Internal Heater	No	Depth (mm)	573
CutOffThermostat	Yes	Joinery cut out dimension- minimum h	830
AirFilter	No	Joinery cut out dimension- minimum w	615
Easy Capacity (Bottles)	40	Joinery cut out dimension- minimum d	555
Max Capacity (Bottles)	50	Air space above cabinet (mm)	10
Number of Shelves	5	Air space at sides (mm)	20
Shelving Material	Wood	Rear Spacer (mm)	30
Shelving Type	4 Full, 1 Half	Ambient Temperature (deg)	5-43
AdjustableShelves	Yes	Electricity Consumption (kWh/Day)	0.397
SlidingShelvesType	Standard glide rails, partial extension	Refrigerant	R600a
Lighting	White LED		
LightPosition	Top		