



Scandinavian Design

Vintec products are designed in Denmark and Sweden, with sustainably-sourced premium white oak shelves, fingerprint-proof acid-etched and edge-to-edge glass doors, no protruding handles, minimal touch control panels, signature red bumpers on shelves, and diffused LED lighting throughout.

165 bottle* single zone cellaring cabinet for red and white wines. *Based on a Bordeaux shaped bottle

Product Benefits & Features

Stable Temperature

Our wine cabinets maintain a stable temperature to keep your wine in perfect cellaring conditions. This is thanks to the Double Glazed, UV treated, insulated side panels and interactions between a compressor and thermostat.

- No alert
- Security lock
- Energy Efficient R600a Gas



Humidity above 50%

Our wine cabinets incorporate a Thermal Recycling Pump that ensures adequate humidity levels are maintained. The Thermal Recycling Pump works by heating condensed water, which is then introduced as humid air within the cabinet.



UV Protected Dark Storage Area

UV rays negatively impact the quality of your wine. Our cabinets eliminate this threat by incorporating UV treated tinted glass doors or solid doors, dark interiors and dimmed internal LED lights.



Vibration Reduction System

To protect the storage life and quality of your wine, our cabinets have been designed to create a vibration proof environment by including an externally housed compressor, rubber shock absorbers and vibration absorbing wooden shelves.

Quality Air Flow

Our cabinets include internal and external fans to ensure there is a slow reticulated air flow throughout the cabinet

Product Specification

RangeName	Classic	Finish	Black
Main Function	Cellar Reds & Whites	Hinge	Recessed
Alternate Function	Serve Reds OR Whites	Reversible	Yes
ZonesDenomination	Single-Zone	OppositeHingingPC	N/A
No of Zones	1	Product Installation	Built-In or Freestanding
Temperature Range Zone 1 (deg)	5°C - 18°C	Installation Type	Slot-in
Temperature Range Zone 2 (deg)	N/A	Height (mm)	1770 mm
Temperature Range Zone 3 (deg)	N/A	Width (mm)	595 mm
UVTreated	Yes	Depth (mm)	680mm
Lock	Yes	Depth Door Open (mm)	730 mm
Alarm	No	Ambient Temperature (deg)	10C - 32C
Display Panel	Electronic-Digital	Weight Unloaded	105 Kg
Internal Heater	No	Electricity Consumption (kWh/Day)	N/A
AirFilter	No	Refrigerant	R600a
Easy Capacity (Bottles)	165		
Max Capacity (Bottles)	165		
Number of Shelves	14 + 1		
Shelving Material	Beech		
Shelving Type	Universal		
AdjustableShelves	Yes		
LightPosition	Top		
Handle	Recessed		
Door Type	Glass Door		
Door Construction	Double Glazed, UV treated		
BodyFinish	Black		